INTERNATIONAL STANDARD

ISO 16063-42

First edition
2014-07-15

Methods for the calibration of vibration and shock transducers —

Part 42: Calibration of seismometers with high accuracy using acceleration of gravity

Méthodes pour l'étalonnage des transducteurs de vibrations et de chocs —

Partie 42: Étalonnage des diomomètres de haute exactitude utilisant l'accélération due à la pesanteur



Reference number
ISO 16063-42:2014(E)

© ISO 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword ... **iv**

1 Scope ... **1**

2 Normative references ... **1**

3 Traceability of measurement ... **1**

4 Determination of local gravity ... **2**
4.1 Method using absolute gravimeter ... 2
4.2 Method using gravitational acceleration standardization network and relative gravimeter ... 2
4.3 Method using gravitational acceleration standardization network ... 2

5 Requirements for apparatus and environmental conditions ... **2**
5.1 Calibration environment ... 2
5.2 Base and vibration environment (seismic block for calibration apparatus) ... 2
5.3 Voltage-measuring instrumentation ... 2
5.4 Tuneable low-pass filter ... 3
5.5 Power supply ... 3
5.6 Tilt table ... 3

6 Method ... **3**
6.1 Calibration principle ... 3
6.2 Calibration procedure ... 5

7 Expression of results ... **6**

Annex A (normative) **Expression of uncertainty of measurement in calibration** ... **7**

Annex B (informative) **Traceability of calibration measurement of seismometer** ... **8**

Bibliography ... **9**

© ISO 2014 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information.

The committee responsible for this document is ISO/TC 108, *Mechanical vibration, shock and condition monitoring*, Subcommittee SC 3, *Use and calibration of vibration and shock measuring instruments*.

ISO 16063 consists of the following parts, under the general title *Methods for the calibration of vibration and shock transducers*:

— *Part 1: Basic concepts*

— *Part 11: Primary vibration calibration by laser interferometry*

— *Part 12: Primary vibration calibration by the reciprocity method*

— *Part 13: Primary shock calibration using laser interferometry*

— *Part 15: Primary angular vibration calibration by laser interferometry*

— *Part 16: Calibration by Earth's gravitation*

— *Part 21: Vibration calibration by comparison to a reference transducer*

— *Part 22: Shock calibration by comparison to a reference transducer*

— *Part 31: Testing of transverse vibration sensitivity*

— *Part 41: Calibration of laser vibrometers*

— *Part 42: Calibration of seismometers with high accuracy using acceleration of gravity*

The following parts are under preparation:

— *Part 17: Primary calibration by centrifuge*

— *Part 32: Resonance testing — Testing the frequency and the phase response of accelerometers by means of its excitation*

 © ISO 2014 – All rights reserved

— *Part 33: Testing of magnetic field sensitivity*

— *Part 43: Calibration of accelerometers by model-based parameter identification*

Angular vibration calibration by comparison to reference transducers, calibration of hand-held accelerometer calibrators, and calibration of vibration transducers with built-in calibration coils are to form the subjects of future parts 23, 44 and 45.

© ISO 2014 – All rights reserved

Methods for the calibration of vibration and shock transducers —

Part 42: Calibration of seismometers with high accuracy using acceleration of gravity

1 Scope

This part of ISO 16063 specifies the instrumentation and procedure to be used for the accurate calibration of seismometer sensitivity using local gravitational acceleration (local Earth's gravitation; local value for the acceleration due to the Earth's gravity) as a reference value.

It is intended generally to be applied to a servo-type accelerometer with/without a velocity output, which usually has a mass position output in the category of a wide-band seismometer with a bandwidth from 0,003 Hz to 100 Hz.

The method specified enables the user to obtain static sensitivity for the seismometers up to 10^{-5} m/s^2 (which corresponds to 1 mGal and approximately 1 ppm of the gravitational acceleration).

The combined and expanded (k = 2) uncertainty of applied acceleration achieved by this method is 10^{-6} m/s^2 (0,1 mGal). When the absolute gravimeter described in this part of ISO 16063 is used, the uncertainty of applied acceleration can be suppressed to 5×10^{-8} m/s^2 (5 μGal). The relative expanded uncertainty of calibration, excluding the uncertainty due to the device under test (DUT), is 0,5 %.

The intended end-usage of the seismometer to be applied is as follows:

a) measurement and observation for the earth science including geophysics usage;

b) measurement and observation for disaster prevention, such as detecting the precursor of a land slide;

c) diagnosis for the soundness of a building structure and foundation soil in civil engineering;

d) observation for nuclear-test detection.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IGSN-71, *International Gravity Standardization Network 1971*. (Morelli, 1974) Morelli, Carlo, ed., 1974, The International Gravity Standardization Net 1971: International Association of Geodesy Special Publication No. 4, 194p

3 Traceability of measurement

The traceability of measurement in this method is shown in Annex B.

© ISO 2014 – All rights reserved