INTERNATIONAL STANDARD

ISO 16787

Second edition
2017-12

Intelligent transport systems — Assisted parking system (APS) — Performance requirements and test procedures

Systèmes intelligents de transport — Système de stationnement assisté (APS) — Exigences de performance et modes opératoires d'essai

Reference number
ISO 16787:2017(E)

© ISO 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Definition of APS type and common requirements **3**
4.1 Basic system functionality 3
4.2 APS types 3
4.3 Common requirements 3
4.3.1 Maximum speed during operation 3
4.3.2 APS exit conditions 3
4.3.3 Advisory note 3

5 Functional and performance requirements of APS type 1 ..... **4**
5.1 Basic system functionality 4
5.1.1 General 4
5.1.2 Parking slot type 1 parallel 4
5.1.3 Parking slot type 1 perpendicular 5
5.1.4 APS operation sequence 5
5.1.5 Basic operation procedure of APS 5
5.1.6 Quiescent mode 6
5.1.7 Slot search 6
5.1.8 Slot found 6
5.1.9 Target parking slot recognition 6
5.1.10 Assisted parking mode 6
5.1.11 End of assisted parking mode 6
5.1.12 APS diagram of operating modes (APS type 1) 6
5.2 Driver interface and information strategy 7
5.2.1 General information presentation 7
5.2.2 Information in the slot search mode 7
5.2.3 Information during “slot found” until “start of assisted parking” 8
5.2.4 Driver request 8
5.2.5 Information during assisted parking 8
5.2.6 Information at “end of assisted parking” 8
5.3 Minimum performance requirements 8
5.3.1 Performance requirements during slot search mode 8
5.3.2 Performance requirements during assisted parking mode 8
5.4 Performance test requirements (APS type 1) 11
5.4.1 Test objects 11
5.4.2 Ambient conditions — General 11
5.4.3 Test criteria 11
5.4.4 Slot search tests 11
5.4.5 Test of supported speed during assisted parking 12
5.4.6 End position tests 12

6 Functional and performance requirements APS type 2 ..... **13**
6.1 Basic system functionality 13
6.1.1 Basic function 13
6.1.2 Geometric requirements 14
6.1.3 APS diagram of operating modes (APS type 2) 15
6.2 Driver interface and information strategy 16
6.2.1 Operation procedure 16
6.2.2 Basic operation procedure of APS 16
6.3 Minimum performance requirements 17

© ISO 2017 – All rights reserved

6.3.1 Defined parking slot 17
6.3.2 Target slot recognition 18
6.3.3 Maximum speed during operation 18
6.3.4 Performance requirements for the end position 18
6.4 Performance test requirements 21
6.4.1 Performance test conditions 21
6.4.2 Parking slot recognition test 21
6.4.3 Environmental conditions — General 23
6.4.4 Test criteria 23
6.4.5 End position tests 23
Annex A (informative) **Example of APS operation sequence** **25**
Bibliography **28**

 © ISO 2017 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 204, *Intelligent transport systems*.

This second edition cancels and replaces the first edition (ISO 16787:2016), of which it constitutes a minor revision.

The main changes compared to the previous edition are as follows:

— some editorial errors have been corrected, such as the term, “must”, replaced with the term, “shall”;

— the figures and keys have been updated for clarity.

© ISO 2017 – All rights reserved

Introduction

Assisted parking system (APS) consists of non-contact sensors and steering control which assist the driver in parking the vehicle. The assistance starts with searching a suitable parking area, getting information on the area around the vehicle (environmental map), calculating the trajectory and finishes with the lateral control of the vehicle. APS also assists the driver in recognizing obstacles while manoeuvring into the parking slot.

© ISO 2017 – All rights reserved

Intelligent transport systems — Assisted parking system (APS) — Performance requirements and test procedures

1 Scope

This document covers the assisted parking system (APS) for light-duty vehicles, e.g. passenger cars, pick-up trucks, light vans and sport utility vehicles (motorcycles excluded) equipped with such APS. This document establishes minimum functionality requirements that the driver can expect of the system, such as the detection of suitable parking spaces, calculation of trajectories and lateral control of the vehicle. Information on the presence of relevant obstacles in the driving path of the vehicle can also be included in the functionality of such systems. This document also sets minimum requirements for failure indication as well as performance test procedures. It includes rules for the general information strategy, but does not restrict the kind of information or display system.

APS is intended to provide automated parking assistance functionality to the driver. The APS searches the environment adjacent to the vehicle for suitable parking areas between other parked vehicles or markings on the road such as painted lines, evaluates the required information to calculate parking trajectories and sends steering commands to an electronic interface of the steering system for lateral control of the vehicle during the parking manoeuvre.

The basic APS function is to assist the driver with lateral control of the vehicle during parking manoeuvres. As an optional extension, APS can also offer limited longitudinal control of the vehicle movement, e.g. braking assistance while manoeuvring into the parking slot.

This document contains requirements for the lateral control capability of APS. It does not address longitudinal control.

During the parking manoeuvre, the driver can take over the control of the vehicle movement at any time and is also fully responsible for the parking manoeuvre.

APS uses object-detection devices for detection and ranging in order to search the environment for suitable parking areas. Such devices can be sensors with distance information or vision-based systems. In addition, sensors or counters, as well as relevant data available on the vehicle network (e.g. CAN), may be used to calculate the position of the vehicle relative to the parking area.

APS is an extension of systems which inform the driver about obstacles in parking manoeuvres (e.g. ISO 17386 and ISO 22840).

This document does not include assisted parking systems, reversing aids and obstacle-detection devices for use on heavy commercial vehicles or on vehicles with trailers.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— IEC Electropedia: available at https://www.electropedia.org/

— ISO Online browsing platform: available at https://www.iso.org/obp/

© ISO 2017 – All rights reserved

3.1
assisted parking system
APS
system capable of measuring the dimensions of a parking slot, calculating an applicable trajectory, performing lateral control of the vehicle while manoeuvring into the slot and giving needed instructions to the driver

3.2
slot search mode
operation mode in which the *APS* (3.1) searches the environment for suitable parking slots

3.3
assisted parking mode
automated lateral control (i.e. steering) of the vehicle by the *APS* (3.1) during the parking manoeuvre while the driver has control of the vehicle speed and driving direction

3.4
system activation
action of transitioning the system operation from a quiescent mode to an active one

3.5
driver assistance request
unique interaction between driver and user interface which is required to enable the *APS* (3.1) before each active parking manoeuvre

3.6
audible information and warning
acoustical signal (e.g. pulses, speech) which is used to present relevant information to the driver

3.7
visual information and warning
optical signal (e.g. a telltale or display) which is used to present relevant information to the driver

3.8
sensor system
component or set of components which detects objects in the monitoring range

3.9
test object
object with a specific material, geometry and surface for testing the monitoring range

3.10
searching range
minimum area in which *APS* (3.1) is able to search the environment for suitable parking slots

3.11
APS exit condition
condition after *system activation* (3.4) which causes the *APS* (3.1) to abort the manoeuvring support

3.12
APS end condition
assisted parking manoeuvre is finished and *APS* (3.1) gives the full control of the vehicle back to the drive

3.13
bordering vehicle
vehicle that limits the parking slot to the rear or the front

3.14
APS vehicle
vehicle which is equipped with *APS* (3.1)

© ISO 2017 – All rights reserved

3.15
V_{search_max}
requirement up to which maximum speed *APS* (3.1) shall be able to search the environment for suitable parking slots

3.16
parking slot defining line(s)
painted lines on the ground surface in a bright colour to identify the boundary of a defined parking slot

4 Definition of APS type and common requirements

4.1 Basic system functionality

The APS recognizes a parking slot where the vehicle can be parked, determines the target parking position and calculates the parking trajectory.

The APS guides the vehicle to the target parking position by automatically controlling the steering during a parking manoeuvre. Upon completion of control, the vehicle's position relative to the target parking position shall fulfil a certain accuracy requirement.

4.2 APS types

This document addresses the practical systems available in the market because the driver's parking behaviour and urban parking conditions are unique issues for each country or district. Two APS type definitions according to the system's target parking slot follow:

a) APS type 1: the APS whose target slot is the space between two vehicles;

b) APS type 2: the APS whose target slot is defined by markings such as painted lines.

For both types, parallel and perpendicular slots are possible.

4.3 Common requirements

4.3.1 Maximum speed during operation

It is recommended to limit the speed range during assisted parking and abort the assisted parking mode for safety when the driver exceeds this limit. The recommended range for the speed limit is (Forward: 10 km/h; Reverse: 7 km/h to 12 km/h). However, this speed limit shall conform to local regulatory requirements such as internal law, technical guidelines.

4.3.2 APS exit conditions

APS shall abort the assisted parking mode if one or more of the following conditions apply.

— The driver operates the steering to take over the control. Minimum torque to the steering wheel shall be defined by OEM. Typical value could be approximately 5 Nm.

— There is a system internal failure detected by the APS.

— The vehicle exceeds the speed limit for the assisted parking mode, as specified in 4.3.1.

The system shall cancel automatic steering control and give both audible and visual information to the driver upon detecting malfunctions.

4.3.3 Advisory note

The APS, as described in this document, is intended to detect suitable parking slots and steer the vehicle during the parking manoeuvre. It is recommended that the vehicle operator's handbook

© ISO 2017 – All rights reserved