INTERNATIONAL STANDARD

ISO 16842

Second edition
2021-07

Metallic materials — Sheet and strip — Biaxial tensile testing method using a cruciform test piece

Matériaux métalliques — Tôles et bandes — Méthode d'essai de traction biaxiale sur éprouvette cruciforme

Reference number
ISO 16842:2021(E)

© ISO 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Principle ... **2**
5 Test piece ... **2**
5.1 Shape and dimensions ... 2
5.2 Preparation of the test pieces ... 3
6 Testing method ... **4**
6.1 Testing machine ... 4
6.2 Measurement method of force and strain ... 5
6.2.1 General ... 5
6.2.2 Measurement method of force ... 5
6.2.3 Measurement method of strain ... 5
6.2.4 Strain measurement positions ... 5
6.3 Installation of the test piece to a biaxial tensile testing machine ... 6
6.4 Testing methods ... 7
7 Determination of biaxial stress-strain curves ... **7**
7.1 General ... 7
7.2 Determination of the original cross-sectional area of the test piece ... 7
7.3 Determination of true stress ... 7
7.4 Determination of true strain ... 8
7.5 Determination of true plastic strain ... 9
8 Test report ... **11**
8.1 Information in the report ... 11
8.2 Additional note ... 11
Annex A (informative) **Method for measuring a yield surface** ... **12**
Annex B (informative) **Factors affecting the maximum equivalent plastic strain applicable to the gauge area of the test piece** ... **16**
Annex C (informative) **Biaxial tensile testing machine** ... **19**
Bibliography ... **23**

© ISO 2021 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 164, *Mechanical testing of metals*, Subcommittee SC 2, *Ductility testing*.

This second edition cancels and replaces the first edition (ISO 16842:2014), of which it constitutes a minor revision. The changes compared to the previous edition are as follows:

— the font of "a" Figure 1 has been modified to "*a*";

— the description in 6.1 h) has been modified for clarity;

— the title of Figure 2 b) has been modified for clarity;

— ISO 10275 has been moved from Clause 2 (Normative references) to the Bibliography;

— ISO 7500-1 has been added to Clause 2 (Normative references);

— the font of "C" Figure C.2 has been modified to "*C*";

— general editorial corrections have been made.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2021 – All rights reserved

Introduction

This document specifies the testing method for measuring the biaxial stress-strain curves of sheet metals subject to biaxial tension at an arbitrary stress ratio using a cruciform test piece made of flat sheet metals. The document applies to the shape and strain measurement position for the cruciform test piece. The biaxial tensile testing machine is described in Annex C, only in terms of the typical example of the machine and the requirements with which the machine ought to conform.

The cruciform test piece recommended in this document has the following features:

a) the gauge area of the test piece ensures superior homogeneity of stress, enabling measurement of biaxial stress with satisfactory accuracy;

b) capability of measuring the elasto-plastic deformation behaviour of sheet metals at arbitrary stress or strain rate ratios;

c) free from the out-of-plane deformation as is encountered in the hydrostatic bulge testing method;

d) easy to fabricate from a flat metal sheet by laser cutting, water jet cutting, or other alternative manufacturing methods.

© ISO 2021 – All rights reserved

Metallic materials — Sheet and strip — Biaxial tensile testing method using a cruciform test piece

1 Scope

This document specifies the method for measuring the stress-strain curves of sheet metals subject to biaxial tension using a cruciform test piece fabricated from a sheet metal sample. The applicable thickness of the sheet is 0,1 mm or more and 0,08 times or less of the arm width of the cruciform test piece (see Figure 1). The test temperature ranges from 10 °C to 35 °C. The amount of plastic strain applicable to the gauge area of the cruciform test piece depends on the force ratio, slit width of the arms, work hardening exponent (n-value) (see Annex B) and anisotropy of a test material.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 80000-1, *Quantities and units — Part 1: General*

ISO 7500-1, *Metallic materials — Calibration and verification of static uniaxial testing machines — Part 1: Tension/compression testing machines —Calibration and verification of the force-measuring system*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
cruciform test piece
test piece which is recommended in the biaxial tensile test and whose geometry is specified in this document

Note 1 to entry: See Figure 1.

3.2
gauge area
square area which is located in the middle of the cruciform test piece and is enclosed by the four arms of the cruciform test piece

Note 1 to entry: See Figure 1.

3.3
arm
generic name for all areas other than the gauge area in the cruciform test piece

Note 1 to entry: The arms play a role of transmitting tensile forces in two orthogonal directions to the gauge area of the cruciform test piece (see Figure 1).

© ISO 2021 – All rights reserved

3.4
biaxial tensile testing machine
testing machine for applying biaxial tensile forces to a cruciform test piece in the orthogonal directions parallel to the arms of the test piece

Note 1 to entry: See Annex C.

3.5
yield surface
group of stress determined in a stress space, at which a metal starts plastic deformation when probing from the elastic region into the plastic range

Note 1 to entry: See Annex A and Reference [1].

3.6
yield function
mathematical function used to generate the conditional equation (yield criterion) to which the stress components ought to conform when the material subject to the stress is in the plastic deformation state

Note 1 to entry: See Annex A.

3.7
contour of plastic work
graphic figure derived by subjecting the material to plastic deformation along various linear stress paths and plotting the stress points in stress space at the instance when the plastic work consumed per unit volume along each stress path becomes identical and the plotted stress points are approximated into either a smooth curve or curved surface

Note 1 to entry: See Annex A.

4 Principle

Measurement is made at room temperature on the yield stress and the stress-strain curves of sheet metals under biaxial tensile stresses by measuring simultaneously and continuously the biaxial tensile forces and strain components applied to the gauge area of a cruciform test piece while applying biaxial tensile forces in the orthogonal directions parallel to the arms of the test piece. The test piece is made of a flat sheet metal and has a uniform thickness. The measured biaxial stress-strain curves are used to determine contours of plastic work of the sheet samples (see Annex A). According to the finite element analyses of the cruciform test piece (as recommended in Clause 5) and the strain measurement position (as specified in 6.2.4), the stress calculation error is estimated to be less than 2,0 %[2][3].

5 Test piece

5.1 Shape and dimensions

Figure 1 shows the shape and dimensions of the cruciform test piece recommended in document. The test piece shall be as described as follows:

a) In principle, the thickness of a test piece, a, shall be the same as that of the as-received sheet sample, without any work done in the thickness direction. See 5.1 b) for an exception to the rule.

b) The arm width, B, should be 30 mm or more, except where it is determined according to the agreement between parties involved in transaction. It shall satisfy $a \leq 0{,}08B$ and should be accurate to within ±0,1 mm for all four arms. The sheet thickness can be reduced to satisfy $a \leq 0{,}08B$ according to the agreement between the parties involved in transaction.

c) Seven slits per one arm shall be made. Specifically, one slit shall be made on the centreline (x-axis or y-axis) of the test piece with a positional accuracy of ±0,1 mm, and three slits shall be made at an interval of $B/8$ with a positional accuracy of ±0,1 mm on each side of the centreline. All slits shall

© ISO 2021 – All rights reserved