INTERNATIONAL STANDARD

ISO 17325-1

First edition
2014-06-15

Ships and marine technology — Marine environment protection — Oil booms —

Part 1: Design requirements

Navires et technologie maritime — Protection de l'environnement marin — Barrages de rétention de pétrole —

Partie 1: Exigences de conception

Reference number
ISO 17325-1:2014(E)

© ISO 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **iv**

Introduction ..... **v**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Boom design **2**
4.1 Application 2
4.2 Environmental considerations 2
4.3 Parts of booms 2
4.4 Types of booms 2

5 Boom functions and configurations **3**
5.1 General 3
5.2 Containment 3
5.3 Deflection 3
5.4 Protection 3
5.5 Configurations 3

6 Forces on boom assemblies **7**

7 Classification of booms by environmental conditions **7**

8 Data requirements for manufacturers **8**

9 Designation and marking **10**
9.1 General 10
9.2 Marking 10

Annex A (informative) **Forces on boom assemblies — Calculations** **11**

Bibliography **13**

© ISO 2014 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2. www.iso.org/directives

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received. www.iso.org/patents

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: Foreword - Supplementary information

The committee responsible for this document is ISO/TC 8, *Ships and marine technology*, Subcommittee SC 2, *Marine environment protection*.

ISO 17325 consists of the following parts, under the general title *Ships and marine technology — Marine environment protection — Oil booms*:

— *Part 1: Design requirements*

The following parts are under preparation:

— *Part 2: Strength and performance requirements*

— *Part 3: End connectors*

— *Part 4: Auxiliary equipment*

© ISO 2014 – All rights reserved

Introduction

Oil booms can be classified in two major types:

— fence booms typically provide a stiffened barrier designed to float vertically in the water; and

— curtain booms are provided with flexible material for the underwater portion of the membrane (called the skirt).

There are other types of booms, such as special purpose booms and sorbent booms, which are not the subject of this part of the International Standard.

All parts of ISO 17325 will give some general guidelines for manufacturers as well as users with regard to subjects associated with producing, purchasing, and using such types of equipment. It will not define any specific type and size of boom for a particular application, as many variables have to be taken into consideration.

This part of ISO 17325 specifies the basic design requirements, general function, designations and marking of oil booms. It further specifies minimum information regarding design, dimensions and materials of oil booms to be provided by the manufacturer.

This International Standard has been developed after considering the below standards and national legislative requirements.

The American Society for Testing and Materials (ASTM) Committee F-20 has prepared two standards relating to boom connectors. ASTM F1093 specifies static laboratory tests of the strength of an oil spill response boom under tensile loading. ASTM F1523 provides a guide on the selection of a containment boom that may be used to control spills of oil and other substances that float on the water.

The Japanese Industrial Standard JIS F 9900 (Parts 1 and 2) provides the necessary conditions and specifications for the design, manufacture, etc. of oil booms.

© ISO 2014 – All rights reserved

Ships and marine technology — Marine environment protection — Oil booms —

Part 1: Design requirements

1 Scope

This part of ISO 17325 specifies the basic design requirements, general function, designations and marking of oil booms. It further specifies minimum information regarding design, dimensions and materials of oil booms to be provided by the manufacturer.

The intent of this International Standard is to assist manufacturers and facilitate user selection of booms by technical criteria. It does not purport to address all aspects of booms or safety concerns associated with boom use, nor does it define boom operational procedures. It is the responsibility of the user of this International Standard to establish the appropriate safety and health practices, and determine applicability of regulatory limitations.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

International Maritime Organization, Manual on Oil Pollution, Section IV, Combating Oil Spills, IMO 596E, London, 2004

ISO 34-1:2010, *Rubber, vulcanized or thermoplastic — Determination of tear strength — Part 1: Trouser, angle and crescent test pieces*

ISO 505:1999, *Conveyor belts — Method for the determination of the tear propagation resistance of textile conveyor belts*

ISO 1817:2011, *Rubber, vulcanized or thermoplastic — Determination of the effect of liquids*

ISO 16165:2013, *Ships and marine technology — Marine environment protection — Terminology relating to oil spill response*

ISO 17325-2, *Ships and marine technology — Marine environment protection — Oil booms — Part 2: Strength and performance requirements*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 16165, ASTM F1093, and the following apply.

3.1
end connector
device attached to the boom used for joining boom sections to one another or to other accessory devices

3.2
gross buoyancy
weight of fresh water displaced by an entire boom section when totally submerged

© ISO 2014 – All rights reserved