International Standard

ISO 17507-2

First edition
2025-12

Natural gas — Calculation of methane number of gaseous fuels for reciprocating internal combustion engines —

Part 2: PKI method

Gaz naturel — Calcul de l'indice de méthane des combustibles gazeux pour les moteurs alternatifs à combustion interne —

Partie 2: Méthode PKI

Reference number
ISO 17507-2:2025(en)

© ISO 2025



COPYRIGHT PROTECTED DOCUMENT

© ISO 2025

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **iv**
Introduction ..... **v**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 Abbreviated terms **2**
5 PKI method **2**
5.1 Introduction 2
5.2 Applicability 2
5.2.1 Standard gaseous fuel composition range 2
5.2.2 Handling of other gaseous fuel components 3
5.3 Methodology to calculate the MN_{PKI} 4
5.3.1 General 4
5.3.2 Step 1: Calculation of the *PKI* 4
5.3.3 Step 2: Calculation of the MN_{PKI} 5
5.4 Expression of results 5
5.5 Uncertainty error and bias 5
6 Example calculations **6**
6.1 Example calculation 1 6
6.2 Example calculation 2 6
Annex A (normative) **Listing of coefficients used in Formula (1) and Formula (4)** **9**
Annex B (informative) ***PKI* and MN_{PKI} values for selected gaseous fuel compositions** **13**
Annex C (informative) **Tools for users of the MN_{PKI} method** **15**
Annex D (normative) **Uncertainty error and bias** **16**
Annex E (informative) **Natural gas-based fuels for reciprocating internal combustion engines** **18**
Annex F (informative) **Basis of the PKI method** **19**
Bibliography **22**

© ISO 2025 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 193, *Natural gas*, in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 408, *Biomethane and other renewable and low-carbon methane rich gases*, in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

A list of all parts in the ISO 17507 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2025 – All rights reserved

Introduction

The globalization of the natural gas market and the drive towards sustainability are increasing the diversity of the supply of gases to the natural gas infrastructure. For example, the introduction of regasified liquefied natural gas (LNG) can result in higher fractions of non-methane hydrocarbons in the natural gas grid than the traditionally distributed pipeline gases for which these hydrocarbons have been removed during processing. Also, the drive towards sustainable gaseous fuels, such as hydrogen and gases derived from biomass, results in the introduction of "new" gas compositions that contain components that do not occur in the traditional natural gas supply. Consequently, the increasing variations in gas composition affect the knock resistance of the gas when used as a fuel. This can affect the operational integrity of reciprocating internal combustion engines.

For the efficient and safe operation of gas engines, it is of great importance to characterize the knock resistance of gaseous fuels accurately. Engine knock is caused by the autoignition of unburned fuel mixture ahead of this mixture being consumed by the propagating flame. Mild engine knock increases pollutant emissions accompanied by gradual build-up of component damage and complete engine failure if not counteracted. Severe knock causes structural damage to critical engine parts, quickly leading to catastrophic engine failure. To ensure that gas engines are matched with the expected variations in fuel composition, the knock resistance of the fuel is to be characterized, and subsequently specified, unambiguously.

Traditional methods for characterizing the knock resistance of gaseous fuels, such as the methane number method developed by Anstalt für Verbrennungskraftmaschinen List (AVL) in the 1960s, relate the knock propensity of a given fuel with that of an equivalent methane/hydrogen mixture using a standardized test engine (see References [1], [2] and [3]). Several other methane number methods have since been developed, sometimes based on either the approach or data, or both from the original experimental work performed by AVL.

In recognition of the need to standardize a method for characterizing the knock resistance of gaseous fuels, several existing methods for calculating a methane number have been considered, including the propane knock index (PKI) method outlined in this document. ISO 17507-1 describes the MN_C method.

Methods to calculate a methane number are based on the input of the gas composition under investigation. While methods can be fundamentally different in their development approach, ideally the methods produce similar methane numbers for the range of gas compositions they are valid for. Yet, differences in outcome can be observed. Engine manufacturers typically determine the calculation method to be used when specifying a methane number value for their engines as part of their application and warranty statements. In all cases, when specifying a methane number based on either method, or any other method, the method used should be noted.

The PKI method was developed by Det Norske Veritas (DNV), headquartered in Oslo, Norway in a consortium of engine Original Equipment Manufacturers (OEMs) and natural gas fuel suppliers. The method is based on the physics and chemistry of the air-fuel mixture during the compression and combustion phases of the engine working cycle that determine engine knock, using an experimentally verified engine combustion model.

The PKI method uses two polynomial functions to compute the methane number from the gaseous fuel composition input. The development and experimental verification of the PKI method is documented in a series of publications (see References [5] to [18]). A more detailed history of the PKI method can be found in Annex F.

A version of the PKI method dedicated to LNG fuels is described in ISO 23306:2020, Annex A.

© ISO 2025 – All rights reserved

Natural gas — Calculation of methane number of gaseous fuels for reciprocating internal combustion engines —

Part 2:
PKI method

1 Scope

This document specifies the PKI method for the calculation of the methane number of a gaseous fuel, using the composition of the gas as sole input for the calculation.

This document applies to natural gas (and biomethane) and their admixtures with hydrogen.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 14532, *Natural gas — Vocabulary*

ISO 14912, *Gas analysis — Conversion of gas mixture composition data*

ISO/IEC Guide 98-3, *Uncertainty of measurement — Part 3: Guide to the expression of uncertainty in measurement (GUM:1995)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 14532 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
methane number
MN
numerical rating indicating the knock resistance of a gaseous fuel

Note 1 to entry: It is analogous to the octane number for petrol. The methane number is the volume fraction expressed as the percentage of methane in a methane-hydrogen mixture, that in a test engine under standard conditions has the same knock resistance as the gaseous fuel to be examined.

3.2
PKI methane number
MN_{PKI}
numerical rating index obtained by calculation, indicating the knock resistance of a gaseous fuel according to this document

Note 1 to entry: This analytical estimate of a methane number is based on using mole fraction gaseous fuel composition as input.

© ISO 2025 – All rights reserved