INTERNATIONAL STANDARD

ISO 18495-1

First edition
2016-09-01

Intelligent transport systems — Commercial freight — Automotive visibility in the distribution supply chain —

Part 1: Architecture and data definitions

Systèmes intelligents de transport — Fret commercial — Visibilité automobile dans la chaîne d'approvisionnement de la distribution —

Partie 1: Architecture et définitions des données

Reference number
ISO 18495-1:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword ..... **iv**
Introduction ..... **v**
1 Scope **1**
2 Conformance **1**
3 Normative references **1**
4 Terms and definitions **2**
5 Symbols and abbreviated terms **3**
6 General requirement **4**
6.1 Business modelling and core use cases 4
6.2 Business process overview 4
6.2.1 Distribution supply chains liable to “informal” movements of automotives 4
6.2.2 Business process for automotives in the distribution supply chain 6
6.3 High level system data architecture 8
6.4 Data architecture 9
6.4.1 Concept 9
6.5 Data concept definitions 10
6.5.1 Automotive Identifier 10
6.5.2 Automotive event 11
Annex A (informative) **ASN.1 modules for the data concepts defined in this part of ISO 18945** **13**
Annex B (informative) **Interpreting a VIN number** **15**
Annex C (informative) **Example business processes and work flows** **17**
Annex D (informative) **Sector descriptive information** **20**
Bibliography **25**

© ISO 2016 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html

The committee responsible for this document is ISO/TC 204, *Intelligent transport systems*.

ISO 18495-1 is the first of potentially several parts of this family of International Standards deliverables relating to automotive visibility in the distribution supply chain. Subsequent parts will provide specifications for particular aspects within this architecture.

© ISO 2016 – All rights reserved

Introduction

The automotive distribution supply chain, which includes newly manufactured vehicles, second hand vehicles, industrial machines, construction machines and agricultural equipment (but, particularly, that for the supply of newly manufactured vehicles and machines), can be defined as a logistics chain from point of origin to an intended destination. The related parties are many, consisting of automotive manufactures, dealers, truckers, terminal operators, shipping lines, tally body, customs authorities, automotive dealers and other logistic related companies such as labelling, forwarding, stevedoring among others and this complexity makes the distribution chain difficult to control and financially inefficient. Most of the logistics process occurs at land transport and parks of new manufactured and used automotive terminals, both prior to international shipping and post international shipping.

Most distribution supply chain operations that manage the movement of automobiles through the distribution supply chain are currently handled manually, on a company by company basis, and generate a very significant amount of paperwork, which is duplicated at each stage throughout the distribution chain, causing duplication of unharmonized data and difficulty in matching these different data concepts associated with a single item in shipment.

Transport movements are made by international shippers and forwarders, and not on a single company basis. Inconsistent availability and format of data creates problems in the management of the distribution chain.

The many parties involved in the distribution supply chain, and lack of data or inconsistency in its format and presentation, causes inefficient land transport and highly labour intensive and complicated operations in terminals and increases the required minimum stock levels required to ensure contingency of supply in order to avoid stock-out situations.

Further, it is very common for dealers to request changes of finished vehicle options and destination based on final customers request in an actual business environment. This is complex and difficult to achieve without visibility throughout the distribution supply chain.

Improving the efficiency of the automotive distribution supply chain will make a significant contribution to reducing pollution, reducing waste of finite resources and reduction of environmental problems.

Considerable work and effort has already been undertaken to formalize, harmonize and standardize the documentation and the formal business processes associated with the documentation management of the automotive supply chain for finished vehicles, and these processes and data concepts are acknowledged and accepted with regards to the formal documentation processing and management of such systems. The existing (and standardized) supply chain documentation and data processing are not affected by this part of ISO 18495, which is complementary to those processes, and designed mostly for use by logistics operators. However, unlike many items in supply chains, automotives can be, and are, informally physically moved around car parks and holding centres during the logistics of operations.

As there are many existing practices within the process of automotive fabrication, and very local practices within dealers, it is recognized that these aspects of vehicle build and delivery will have their own domestic architectures. Similarly, there are established practices and procedures on the maritime leg of the journey. However, if the manufacturer, dealer, shipper or dealer wishes, at their option, to extend this architecture and data definitions into their domains, this architecture enables them to do so, should they so elect to do.

This part of ISO 18495 establishes a framework and architecture for data collection of the physical movement of vehicles, construction machinery and agricultural equipment, in the distribution chain between a point of origin (start of logistics movement) and an intended destination, and provides a means to monitor their actual physical movement at and between various stages of the distribution supply chain, including informal movements within any of these stages/locations, and provides consistent data architecture, harmonized data concepts and presentation for such data.

© ISO 2016 – All rights reserved

Intelligent transport systems — Commercial freight — Automotive visibility in the distribution supply chain —

Part 1: Architecture and data definitions

1 Scope

This part of ISO 18495 establishes a framework and architecture for data collection and to provide data definitions for visibility of vehicles, self-propelled construction machinery and agricultural equipment (hereinafter referred to as "automotives" or "automobiles") in the distribution supply chain between a point of origin (start of logistics movement) and an intended destination.

This architecture is designed to cover any undocumented movements at any location. The scope of this part of ISO 18495 is to

a) enable dynamic location within a storage area/compound,

b) provide consistent use of the ISO 3779/ ISO 3780 VIN (where available) as the prime identifier, and

c) where a VIN is not available, provide consistent and standardized identification throughout the distribution chain movement.

NOTE 1 The scope of this part of ISO 18495 does not standardize the data carriers or their interrogation means.

NOTE 2 This part of ISO 18495 is expected to be the first part of multipart standard relating to this subject.

NOTE 3 This specification is complementary to, and does not replace any supply chain documentation standardized and in use by JAIF or ODETTE in the new vehicle supply chain, nor does it impose any specification or change on the representation, nor exchange of, their data concepts nor documentation.

NOTE 4 The movement of automobiles within containers is outside of the scope of this part of ISO 18495.

2 Conformance

No specific conformance requirements are specified in this part of ISO 18495.

3 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 3779, *Road vehicles — Vehicle identification number (VIN) — Content and structure*

ISO 3780, *Road vehicles — World manufacturer identifier (WMI) code*

ISO 14816, *Road transport and traffic telematics — Automatic vehicle and equipment identification — Numbering and data structure*

ISO 14817 (all parts), *Intelligent transport systems — ITS central data dictionaries*

ISO 17262, *Intelligent transport systems — Automatic vehicle and equipment identification — Numbering and data structures*

© ISO 2016 – All rights reserved

4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

4.1
architecture
fundamental concepts or properties of a system in its environment embodied in its elements, relationships and its *framework* (4.9)

4.2
automobile
automotive
any self-propelling motorized vehicle including cars, vans, trucks, self-propelling construction machinery and self-propelling agricultural equipment

Note 1 to entry: See also *vehicle* (4.14).

4.3
current location
physical position at the time of the enquiry

4.4
data concept
characterization which describes and defines the essential features of a distinct entity such as a *data element* (4.5), group of data entities or metadata, normally described by defining all or some of its object class, properties, value domain, data element concept, data element, data frame, message, interface dialogue, associations, but does not define the specific value domain

Note 1 to entry: *Data concepts* (4.4) can be classified into the following categories: object class, value domain, data element, aggregate domain, data frame, message, interface dialogue, dictionary document, term, symbol or module.

4.5
data element
union of a specific *data concept* (4.4) with a specific value domain creates a data element

Note 1 to entry: For example, the *Person-date of birth* can be combined with the *Date DDMMYYYY* value domain to create the *data element*: *Person-date of birth, DDMMYYYY*; alternatively, the *data element* could be formed using the *Date YYYY* value domain making a distinct *data element Person*.

4.6
destination
destination location
most recently updated end point of the journey

4.7
distribution chain
series of businesses or organizations that are involved in transporting, storing and selling goods to customers (Cambridge ED)

Note 1 to entry: See also *distribution supply chain* (4.8) and *supply chain* (4.13).

4.8
distribution supply chain
process of transportation and distribution, of *vehicles* (4.14) and mobile plant and equipment, through a *distribution chain* (4.7)

4.9
framework
particular set of beliefs or ideas referred to in order to describe a scenario or solve a problem

© ISO 2016 – All rights reserved

4.10
location type
function of the facility/point where the data was collected

4.11
point of origin
start point of a logistical movement of an *automotive* (4.2) to a *destination* (4.6)

4.12
status definition
identifier indicating whether the *automotive* (4.2) is “Not Ready” or “Ready” for the next function of the facility or the next READ POINT of the journey

4.13
supply chain
system of organizations, people, activities, information and resources involved in moving a (new) product or service from supplier to customer (OED)

Note 1 to entry: See also *distribution chain* (4.7) and *distribution supply chain* (4.8).

4.14
vehicle
automobile (4.2) such as automotive, van, truck, tractor unit, self-driven agricultural equipment, self-driven construction equipment

Note 1 to entry: The term vehicle within the context of this part of ISO 18495 embraces all forms of self-driven automotive.

4.15
VIN
structured combination of characters assigned to a *vehicle* (4.14) by the manufacturer for identification purposes as defined in ISO 3779 and ISO 3780

Note 1 to entry: See Annex B.

5 Symbols and abbreviated terms

ASN.1	Abstract Syntax Notation One
DD	Delivery to Destination
DFE	Destination Final Egress
DPT	Despatching Port Terminal
DVP	Dealer Vehicle Park
FVP	Finished Vehicle Park
M	Mandatory
MT	Marine Transport
O	Optional
PoO	Point of Origin
RPT	Receiving Port Terminal

© ISO 2016 – All rights reserved