International Standard

ISO 19426-4

Structures for mine shafts —

Part 4: Conveyances

Structures de puits de mine —

Partie 4: Moyens de transport

Second edition
2026-09

Reference number
ISO 19426-4:2026(en)

© ISO 2026



COPYRIGHT PROTECTED DOCUMENT

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **v**
Introduction ..... **vi**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 Symbols **2**
5 Materials **4**
5.1 Steel 4
5.1.1 High strength steel grades 4
5.1.2 Cold temperature operation 4
5.2 Aluminium alloys 4
5.3 Critical load bearing components 4
6 Nominal operating loads **5**
7 General operating loads **5**
7.1 Permanent loads 5
7.2 Vertical imposed loads due to holding devices 5
7.2.1 Holding device engagement load 5
7.2.2 Holding devices securing load 5
7.3 Lateral imposed loads 6
7.3.1 Fixed guide systems in vertical shafts 6
7.3.2 Rope guide systems 6
7.3.3 Decline shaft conveyance wheel loads 6
7.4 Winder system loads 7
7.4.1 Acceleration/deceleration load 7
7.4.2 Trip-out load 7
7.4.3 Tail-rope load 8
7.4.4 Vertical friction load 8
7.5 Roof loads 8
8 Personnel winding loads **8**
8.1 Standing personnel load 8
8.2 Seated personnel load 8
8.3 Loading of cages 8
8.4 Loading of cages in decline shafts 8
8.5 Dogging system load 8
9 Material and equipment winding loads **9**
9.1 Floor loads 9
9.1.1 Static load 9
9.1.2 Impact loads 9
9.2 Slung loads or trailing loads 11
10 Rock winding loads **11**
10.1 Skip loads 11
10.1.1 General 11
10.1.2 Static rock loads 11
10.1.3 Bridle and top transom loads during filling 11
10.1.4 Reference rock pressure 12
10.1.5 Pressure during filling or travelling in the shaft 12
10.1.6 Pressures during emptying 13
10.1.7 Load on tipping rollers 14
10.1.8 Skip return-stop loads 14
10.2 Kibble loads 14
10.2.1 Static rock or slurry loads 14

© ISO 2026 – All rights reserved

10.2.2 Reference rock or slurry pressure 14
10.2.3 Pressure during filling 14
10.2.4 Pressures during emptying 14
10.2.5 Heavy kibble payloads 15

11 Emergency loads 15
11.1 Rope emergency load 15
11.1.1 Permanent operating conveyances with fixed rope winders 15
11.1.2 Permanent operating conveyances with friction winders 15
11.1.3 Slung equipment and conveyances 15
11.1.4 Kibbles and kibble cross-heads 16
11.2 Emergency drop-back loads 16
11.2.1 General 16
11.2.2 All permanent conveyances 16
11.2.3 Kibbles and kibble cross-heads 16
11.3 Roof impact loads 16
11.4 Skip loads 16
11.4.1 General 16
11.4.2 Reference rock pressure 17
11.4.3 Pressure during filling or travelling in the shaft 17
11.5 Emergency stopping device loads 18
11.5.1 General 18
11.5.2 Overspeed device 18
11.6 Application of emergency loads 18

12 Design procedures 18
12.1 Design loads 18
12.2 Design codes 19
12.3 Design for emergency loads 19
12.3.1 Steel components 19
12.3.2 Aluminium components 19
12.3.3 Special considerations 19
12.4 Functional requirement 19
12.4.1 Aspect ratio 19
12.4.2 Ventilation requirements 19
12.5 Fatigue 19

13 Construction requirements 19
13.1 General 19
13.2 Confirmation of design by testing 20
13.2.1 Testing of operating mechanisms 20
13.3 Construction tolerances 20

Annex A (informative) **Load factors and load combinations 22**

Annex B (informative) **Examples of tipping roller and skip return-stop loads 24**

Annex C (informative) **Construction tolerances 28**

Bibliography 29

© ISO 2026 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 82, *Mining*.

This second edition cancels and replaces the first edition (ISO 19426-4:2018), which has been technically revised.

The main changes are as follows:

— in 11.4.3.3 a), paragraph below Formula (33), the wording and value have been corrected to read "but the rock size shall not be taken as less than 0,02 m^3.";

— emergency loads for friction winders included;

— conveyance function requirements;

— construction tolerances updated;

— Annex C on construction tolerances added.

A list of all parts in the ISO 19426 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2026 – All rights reserved

Introduction

Many mining companies, and many of the engineering companies which provide designs for mines, operate globally so ISO 19426 series was developed in response to a desire for a unified global approach to the safe and robust design of structures for mine shafts. The characteristics of ore bodies, such as their depth and shape, vary in different areas so different design approaches have been developed and proven with use over time in different countries. Bringing these approaches together in ISO 19426 series will facilitate improved safety and operational reliability.

The majority of the material in ISO 19426 series deals with the loads to be applied in the design of structures for mine shafts. Some principles for structural design are given, but for the most part it is assumed that local standards will be used for the structural design. It is also recognized that typical equipment varies from country to country, so the clauses in ISO 19426 series do not specify application of the principles to specific equipment. However, in some cases examples demonstrating the application of the principles to specific equipment are provided in informative annexes.

© ISO 2026 – All rights reserved

Structures for mine shafts —

Part 4:
Conveyances

1 Scope

This document specifies the loads, the load combinations and the design procedures for the design of the steel and aluminium alloy structural members of conveyances used for the transport of personnel, materials, equipment and rock in vertical and decline shafts. The conveyances covered by this document include personnel or material cages (or both), skips, kibbles, equipping skeleton cages, inspection cages, bridles, crossheads and counterweights.

This document is not intended to be used for the design of ropes, sheaves or attachments. Rope sizes are determined in accordance with other standards.

This document does not cover chairlifts.

This document does not cover matters of operational safety or layout of conveyances.

This document adopts a limit states design philosophy.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2394, *General principles on reliability for structures*

ISO 10721-1, *Steel structures — Part 1: Materials and design*

ISO 10721-2, *Steel structures — Part 2: Fabrication and erection*

ISO 19426-1, *Structures for mine shafts — Part 1: Vocabulary*

ISO 19426-2, *Structures for mine shafts — Part 2: Headgear structures*

ISO 19426-5, *Structures for mine shafts — Part 5: Shaft system structures*

ISO 22111, *Bases for design of structures — General requirements*

EN 1999-1-1, *Eurocode 9 — Part 1: Design of aluminium structures — Part 1: General structural rules*

EN 1999-1-3, *Eurocode 9 — Part 1: Design of aluminium structures — Part 3: Structures susceptible to fatigue*

EN 1999-1-4, *Eurocode 9 — Par 1: Design of aluminium structures — Part 4: Cold-formed structural sheeting*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 19426-1 apply.

© ISO 2026 – All rights reserved

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org

4 Symbols

A_o	operating winder system acceleration/deceleration load (N)
A_t	trip-out winder deceleration load (N)
a_D	maximum permitted deceleration of the conveyance when the dogging system activates (m/s^2)
a_o	operating winder system peak acceleration/deceleration (m/s^2)
a_t	trip-out winder system peak deceleration (m/s^2)
C	impact load during loading of the conveyance (N)
C_h	horizontal impact load from rolling stock (N)
C_v	vertical impact load from rolling stock (N)
C_y	conveyed load (P, ΣM, U or R, as appropriate) (N)
D	dogging system load (N)
d_i	deformation of the skip door (m)
E_j	emergency dropback load (N)
E_r	rope emergency load (N)
e	maximum moving beam misalignment of the guide (m); lateral flare dimension (see Figure 1)
F	design load, or load effect (N, Nm)
F_v	friction induced vertical load (N)
G_1 and G_2	are the permanent loads, including the self-weight of the structure and the structural components, in newtons (N)
G_c	conveyance self-weight load (N)
g	acceleration due to gravity (m/s^2)
H	lateral imposed load (N)
H_r	rubbing block load (N)
H_s	lateral slipper plate load (N)
h_d	length through which the rock falls (m)
h_h	height to which the skip is filled above the lowest point of the skip door (m)
K	holding device engagement load (N)
K_c	holding device securing load (N)

© ISO 2026 – All rights reserved