International Standard

ISO 19901-1

Third edition
2026-08

Specific requirements for offshore structures —

Part 1: Metocean design and operating considerations

Exigences spécifiques relatives aux structures en mer —

Partie 1: Dispositions océano-météorologiques pour la conception et l'exploitation

Reference number
ISO 19901-1:2026(en)

© ISO 2026



COPYRIGHT PROTECTED DOCUMENT

© ISO 2026

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **v**
Introduction ..... **vii**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **2**
4 Symbols and abbreviated terms **9**
4.1 Symbols 9
4.2 Abbreviated terms 12
5 Determining the relevant metocean parameters **12**
5.1 General 12
5.2 Expert development of metocean criteria 13
5.3 Selecting appropriate parameters for determining design actions and action effects 13
5.4 The metocean database 14
5.5 Storm types in a region 15
5.6 Directionality 15
5.7 Extrapolation to extreme and abnormal conditions 15
5.8 Metocean parameters for fatigue assessments 16
5.9 Metocean parameters for short-term activities 16
5.10 Metocean parameters for medium-term activities 18
6 Water depth, tides and storm surges **18**
6.1 General 18
6.2 Tides 18
6.3 Storm surges 19
6.4 Extreme water level 19
7 Wind **20**
7.1 General 20
7.2 Wind actions and action effects 21
7.3 Wind profile and time-averaged wind speed 22
7.4 Wind spectra 22
8 Waves **22**
8.1 General 22
8.2 Wave actions and action effects 23
8.3 Sea-states — spectral waves 24
8.3.1 Wave spectrum 24
8.3.2 Directional spreading 24
8.3.3 Wave periods 24
8.3.4 Wave kinematics — velocities and accelerations 24
8.4 Regular (periodic) waves 25
8.4.1 General 25
8.4.2 Wave period 25
8.4.3 Wave kinematics — velocities and accelerations 25
8.4.4 Intrinsic, apparent and encounter wave periods 26
8.5 Maximum height of an individual wave for long return periods 27
8.6 Linear and non-linear wave models 27
8.7 Wave crest elevation 27
9 Currents **28**
9.1 General 28
9.2 Current velocities 28
9.3 Current profile 29
9.4 Current profile stretching 29
9.5 Current blockage 29

© ISO 2026 – All rights reserved

9.6 Tidal currents 29
10 Other environmental factors 30
10.1 Marine growth 30
10.2 Tsunamis 30
10.3 Seiches 30
10.4 Sea ice and icebergs 31
10.5 Snow and ice accretion 31
10.6 Thunderstorms and lightning 31
10.7 Rainfall 31
10.8 Squalls and downbursts 31
10.9 Internal waves and solitons 32
10.10 Shelf waves and eddies 32
10.11 Infra-gravity waves 32
10.12 Seawater temperature 33
10.13 Miscellaneous 33
11 Collection of metocean data 33
11.1 General 33
11.2 Common requirements 34
11.2.1 General 34
11.2.2 Instrumentation 34
11.3 Meteorology 34
11.3.1 General 34
11.3.2 Weather observation and reporting for helicopter operations 34
11.3.3 Weather observation and reporting for weather forecasting services 35
11.3.4 Weather observations for design purposes 35
11.3.5 Weather observation and reporting for climatological purposes 36
11.4 Oceanography 36
11.4.1 General 36
11.4.2 Measurements and observations 36
11.5 Data quality control 36
12 Verification of weather forecast information 37
12.1 General 37
13 Information concerning the annexes 37
13.1 Information concerning Annex A 37
13.2 Information concerning the regional annexes 37
Annex A (informative) **Additional information and guidance 38**
Annex B (informative) **Northwest Europe 107**
Annex C (informative) **West Coast of Africa 117**
Annex D (informative) **Offshore Canada 128**
Annex E (informative) **Sakhalin/Sea of Okhotsk 154**
Annex F (informative) **Caspian Sea 178**
Annex G (informative) **South East Asian Sea 196**
Annex H (informative) **Mediterranean Sea 217**
Annex I (informative) **Brazil 243**
Annex J (informative) **US Gulf of Mexico 256**
Annex K (informative) **US Coast of California 307**
Annex L (informative) **Other US Waters 312**
Bibliography 316

© ISO 2026 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 67, *Oil and gas industries including lower carbon energy*, Subcommittee SC 7, *Offshore structures,* in collaboration with the European Committee for Standardization (CEN) Technical Committee CEN/TC 12, *Oil and gas industries including lower carbon energy,* in accordance with the Agreement on technical cooperation between ISO and CEN (Vienna Agreement).

This third edition cancels and replaces the second edition (ISO 19901-1:2015), which has been technically revised.

The main changes are as follows:

— clarification on the role of the metocean expert (5.2 and A.5.2);

— additional information related to the determination of associated criteria (5.3 and A.5.3);

— additional information related to the estimation of extreme or abnormal conditions (5.7 and A.5.7);

— alignment of the content related to wind with API RP 2MET (Clause 7 and Clause A.7);

— additional information related to breaking or non-breaking wave kinematic estimation (8.4.3 and A.8.4.3);

— expansion of the content related to additional environment factors to be considered (Clause 10 and Clause A.10);

— introduction of text related to the verification of weather forecast information (Clause 12 and Clause A.12);

— update to offshore Canada regional annex (Annex D);

— update to Sakhalin/Sea of Okhotsk regional annex (Annex E);

— update to Caspian Sea regional annex (Annex F);

— introduction of Mediterranean Sea regional annex (Annex H);

© ISO 2026 – All rights reserved

— introduction of Brazil regional annex (Annex I);

— re-introduction of US Gulf of Mexico regional annex (Annex J);

— re-introduction of coast of California regional annex (Annex K);

— re-introduction of the overview annex of regions excluding Gulf of Mexico and California (Annex L).

A list of all parts in the ISO 19901 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2026 – All rights reserved

Introduction

The International Standards on offshore structures prepared by TC 67 (i.e. ISO 19900, the ISO 19901 series, ISO 19902, ISO 19903, ISO 19904-1, the ISO 19905 series, ISO 19906) constitute a common basis covering those aspects that address design requirements and assessments of all offshore structures used by the oil and gas industries including lower carbon energy worldwide. Through their application the intention is to achieve reliability levels appropriate for manned and unmanned offshore structures, whatever the type of structure and the nature or combination of the materials used.

It is important to recognize that structural integrity is an overall concept comprising models for describing actions, structural analyses, design rules, safety elements, workmanship, quality control procedures and national requirements, all of which are mutually dependent. The modification of one aspect of design in isolation can disturb the balance of reliability inherent in the overall concept or structural system. The implications involved in modifications, therefore, should be considered in relation to the overall reliability of all offshore structural systems.

The International Standards on offshore structures prepared by TC 67 are intended to provide a wide latitude in the choice of structural configurations, materials and techniques without hindering innovation. Sound engineering judgement is therefore necessary in the use of these International Standards.

Some additional considerations apply for metocean design and operating conditions. The term “metocean” is short for “meteorological and oceanographic” and refers to the discipline concerned with the establishment of relevant environmental conditions for the design and operation of offshore structures. A major consideration in the design and operation of such a structure is the determination of actions on, and the behaviour of, the structure as a result of winds, waves and currents.

Environmental conditions vary widely around the world. For the majority of offshore locations there are little numerical data from historic conditions; comprehensive data often only start being collected when there is a specific need, for example, when exploration for hydrocarbons is being considered. Despite the usually short duration for which data are available, designers of offshore structures need estimates of extreme and abnormal environmental conditions (with an individual or joint probability of the order of 1×10^{-2}/year and 1×10^{-3} to 1×10^{-4}/year, respectively).

Even for areas like the Gulf of Mexico, offshore Indonesia and the North Sea, where there are over 40 years of fairly reliable measurements available, the data are insufficient for rigorous statistical determination of appropriate extreme and abnormal environmental conditions. The determination of relevant design parameters has therefore to rely on the interpretation of the available data by experts, together with an assessment of any other information, such as prevailing weather systems, ocean wave creation and regional and local bathymetry, coupled with consideration of data from comparable locations. In particular, due account should be taken of the uncertainties that arise from the analyses of limited datasets. It is hence important to employ experts from both the metocean and structural communities in the determination of design parameters for offshore structures, particularly since setting of appropriate environmental conditions depends on the chosen option for the offshore structure.

Requirements for the determination of the actions on, and the behaviour of, a structure in these environmental conditions are given in ISO 19901-3, ISO 19901-6, ISO 19901-7, ISO 19902, ISO 19903, ISO 19904-1, ISO 19905-1 and ISO 19906.

NOTE Specific metocean requirements for site-specific assessment of jack-ups are contained in ISO 19905-1, for arctic offshore structures in ISO 19906, for arctic offshore operations in ISO 35106 and for topside structures in ISO 19901-3.

Some background to, and guidance on, the use of this document is provided in Annex A. The clause numbering in Annex A is the same as in the main text to facilitate cross-referencing.

Regional information, where available, is provided in the Annexes B to L. This information has been developed by experts from the region or country concerned to supplement the guidance provided in this document. Each regional annex provides regional or national data on environmental conditions for the area concerned.

© ISO 2026 – All rights reserved

Specific requirements for offshore structures —

Part 1:
Metocean design and operating considerations

IMPORTANT — The electronic file of this document contains colours which are considered to be useful for the correct understanding of the document. Users should therefore consider printing this document using a colour printer.

1 Scope

This document provides two broad types of requirements for the determination and use of meteorological and oceanographic (metocean) conditions for the design, construction and operation of offshore structures:

— those related to the determination of environmental conditions in general, together with the metocean parameters that are required to adequately describe them;

— those related to the characterization and use of metocean parameters for the design, the construction activities or the operation of offshore structures.

This document covers the following environmental conditions and metocean parameters:

— extreme and abnormal values of metocean parameters that recur with given return periods that are considerably longer than the design service life of the structure;

— long-term distributions of metocean parameters in the form of cumulative, conditional, marginal or joint statistics of metocean parameters;

— normal environmental conditions that are expected to occur frequently during the design service life of the structure.

Metocean parameters specified in this document are applicable to:

— the determination of actions for the design of new structures;

— the determination of actions for the assessment of existing structures;

— the site-specific assessment of mobile offshore units;

— the determination of limiting environmental conditions, weather windows, actions and action effects for pre-service and post-service situations (i.e. fabrication, transportation and installation or decommissioning and removal of a structure);

— the operation of the platform, where appropriate.

It is beyond the scope of this document to provide detailed instructions that can be followed to produce reliable estimates of extreme or abnormal conditions in all areas and in all cases.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 19900, *Petroleum and natural gas industries — General requirements for offshore structures*

© ISO 2026 – All rights reserved

ISO 19906, *Petroleum and natural gas industries — Arctic offshore structures*

3 Terms and definitions

For the purpose of this document, the terms and definitions given in ISO 19900 and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

3.1
abnormal value
design value of a parameter of abnormal severity used in accidental limit state checks in which a structure is intended not to suffer complete loss of integrity

Note 1 to entry: Abnormal events are typically accidental and environmental (including seismic) events having probabilities of exceedance of the order of 10^{-3} to 10^{-4} per annum.

3.2
chart datum
local datum used to fix *water depths* (3.51) on a chart or tidal heights over an area

Note 1 to entry: Chart datum is usually an approximation to the level of the *lowest astronomical tide* (3.17).

Note 2 to entry: Chart datum can differ from one chart to another and care is required if cross referencing sites that are not on the same chart.

3.3
conditional probability
probability of the occurrence of a variable A, given that other variables B, C, … have certain assigned values

Note 1 to entry: The conditional probability of A given that B, C, … occur is written as $P(A|B,C,\ldots)$. The concept is applicable to metocean parameters, as well as to actions and action effects.

EXAMPLE When considering wave parameters, A can be the individual crest elevation, B the *water depth* (3.51) and C the *significant wave height* (3.36), and so on.

3.4
design crest elevation
extreme crest elevation measured relative to *still water level* (3.44)

Note 1 to entry: The design crest elevation is used in combination with information on astronomical tide, *storm surge* (3.45), platform settlement, reservoir subsidence and *water depth* (3.51) uncertainty and is derived using *extreme value* (3.7) analysis. Where simplified models are used to estimate the kinematics of the *design wave* (3.5), the design crest elevation can be different from (usually somewhat greater than) the crest elevation of the design wave used to calculate actions on the structure. In reality, the wave with the greatest trough-to-crest height and the wave with the highest crest are different waves.

3.5
design wave
deterministic wave used for the design of an offshore structure

Note 1 to entry: The design wave is an engineering abstraction. Most often it is a periodic wave with suitable characteristics (e.g. height H, period T, steepness, crest elevation). The choice of a design wave depends on:

— the design purpose(s) considered;

— the wave environment;

— the geometry of the structure;

— the type of action(s) or action effect(s) pursued.

© ISO 2026 – All rights reserved

Note 2 to entry: Normally, a design wave is only compatible with design situations in which the action effect(s) are quasi-statically related to the associated wave actions on the structure.

3.6
extreme water level
combination of *design crest elevation* (3.4), astronomical tide and *storm surge* (3.45) referenced to either *LAT* (3.17) or *MSL* (3.20)

3.7
extreme value
representative value of a parameter used in ultimate limit state checks

Note 1 to entry: Extreme events have probabilities of the order of 10^{-2} per annum.

3.8
gravity wave
wave in a fluid or in the interface between two fluids for which the predominant restoring forces are gravity and buoyancy

Note 1 to entry: Wind-generated surface waves.

3.9
gust
brief rise and fall in wind speed lasting less than 1 min

Note 1 to entry: In some countries, gusts are reported in meteorological observations if the maximum wind speed exceeds approximately 8 m/s.

3.10
gust wind speed
maximum value of the wind speed of a *gust* (3.9) averaged over a short (3 s to 60 s) specified duration within a longer (1 min to 1 h) specified duration, measured at a given elevation

Note 1 to entry: For design purposes, the specified duration depends on the dimensions and natural period of (part of) the structure being designed such that the structure is designed for the most onerous conditions; thus, a small part of a structure is designed for a shorter gust wind speed duration (and hence a higher gust wind speed) than a larger (part of a) structure.

3.11
highest astronomical tide
HAT
level of high tide when all harmonic components causing the tides are in phase

Note 1 to entry: The harmonic components are in phase approximately once every 19 years, but these conditions are approached several times each year.

3.12
hindcasting
method of simulating historical (metocean) data for a region through numerical modelling

3.13
infra-gravity wave
surface *gravity wave* (3.8) with a period in the range of approximately 25 s to 500 s

Note 1 to entry: In principle an infra-gravity wave is generated by different physical processes but is most commonly associated with waves generated by non-linear second-order difference frequency interactions between different *swell* (3.47) wave components.

3.14
internal wave
gravity wave (3.8) which propagates within a stratified water column

© ISO 2026 – All rights reserved

3.15
JONSWAP
Joint North Sea Project Spectrum
version of the Pierson-Moskowitz *spectrum* (3.42) which accounts for the continued development of the spectrum through non-linear wave-wave interaction over time and space

3.16
long-term distribution
probability distribution of a variable over a long time scale

Note 1 to entry: The time scale exceeds the duration of a *sea-state* (3.32), in which the statistics are assumed constant (see *short-term distribution* (3.35)). The time scale is hence comparable to a season or to the design service life of a structure.

EXAMPLE Long-term distributions of:

— *significant wave height* (3.36) (based on, for example, storm peaks or all sea-states);

— significant wave height in the months May to September;

— individual wave heights;

— current speeds (such as for use in assessing vortex-induced vibrations of drilling risers);

— *scatter diagrams* (3.30) with the joint distribution of significant wave height and wave period (such as for use in a fatigue analysis);

— a particular action effect;

— sea ice types and thickness;

— iceberg mass and velocity;

— storm maximum significant wave height.

3.17
lowest astronomical tide
LAT
level of low tide when all harmonic components causing the tides are in phase

Note 1 to entry: The harmonic components are in phase approximately once every 19 years, but these conditions are approached several times each year.

3.18
marginal distribution
marginal probability
statistical distribution (probability) of the occurrence of a variable A independent of any other variable

Note 1 to entry: The marginal distribution is obtained by integrating the full distribution over all values of the other variables B, C, ... and is written as $P(A)$. The concept is applicable to metocean parameters, as well as to actions and action effects.

EXAMPLE When considering wave conditions, A can be the individual crest elevation for all *mean zero-crossing periods* (3.22) B and all *significant wave heights* (3.36) C, occurring at a particular site.

3.19
marine growth
living organisms attached to an offshore structure

© ISO 2026 – All rights reserved

3.20
mean sea level
MSL
arithmetic mean of all sea levels measured over a long period, a minimum of 1 year

Note 1 to entry: Seasonal changes in mean level can be expected in some regions and over many years the mean sea level can change.

3.21
mean wind speed
time-averaged wind speed, averaged over a specified time interval and at a specified elevation

Note 1 to entry: The mean wind speed varies with elevation above *mean sea level* (3.20) and the averaging time interval; a standard reference elevation is 10 m and with an averaging time of 10 min. See also *gust wind speed* (3.10) and *sustained wind speed* (3.46).

3.22
mean zero-crossing period
average period between (up or down) zero-crossing waves in a *sea-state* (3.32)

Note 1 to entry: In practice the mean zero-crossing period is often estimated from the zeroth and second moments of the *wave spectrum* (3.52) as $T_z = T_2 = \sqrt{m_0(f)/m_2(f)} = 2\pi\sqrt{m_0(\omega)/m_2(\omega)}$.

3.23
monsoon
seasonally reversing wind pattern, with associated pattern of rainfall

Note 1 to entry: The term was first applied to the winds over the Arabian Sea which blow for six months from northeast and for six months from southwest, but it has been extended to similar winds in other parts of the world.

3.24
most probable maximum
value of the maximum of a variable with the highest probability of occurring

Note 1 to entry: The most probable maximum is the value for which the probability density function of the maxima of the variable has its peak. It is also called the mode or modus of the statistical distribution.

3.25
operating conditions
most severe combination of environmental conditions under which a given operation is permitted to proceed

Note 1 to entry: Operating conditions are determined for operations that exert a significant action on the structure. Operating conditions are usually a compromise: they are sufficiently severe that the operation can generally be performed without excessive downtime, but they are not so severe that they have an undue impact on design or safety.

3.26
polar low
depression that forms in polar air, often near a boundary between ice and sea

3.27
residual current
part of the total current that is not constituted from harmonic tidal components (i.e. the tidal stream)

Note 1 to entry: Residual currents are caused by a variety of physical mechanisms and comprise a large range of natural frequencies and magnitudes in different parts of the world.

3.28
residual water level
part of the total water level that is not constituted from harmonic tidal components (i.e. the tidal height)

© ISO 2026 – All rights reserved

3.29
return period
average period between occurrences of an event or of a particular value being exceeded

Note 1 to entry: The offshore industry commonly uses a return period measured in years for environmental events. For a rare event, the return period in years is equal to the reciprocal of the annual probability of exceedance of the event.

3.30
scatter diagram
joint probability of two or more (metocean) parameters

Note 1 to entry: A scatter diagram is especially used with wave parameters in the metocean context (for example in fatigue assessments). The wave scatter diagram is commonly understood to be the probability of the joint occurrence of the *significant wave height* (3.36) (H_s) and a representative period (T_z or T_p).

3.31
sea floor
interface between the sea and the *seabed* (3.33) and referring to the upper surface of all unconsolidated material

3.32
sea-state
condition of the sea during a period in which its statistics remain approximately stationary and egodic

Note 1 to entry: In a statistical sense the sea-state does not change markedly within the period. The period during which this condition exists depends on the particular weather condition at any given time, however it is often assumed to be 3 h in extra-tropical conditions, however it can be as short as 1 h in tropical cyclonic conditions.

3.33
seabed
materials below the sea in which a structure is founded, whether of soils such as sand, silt or clay, cemented material or of rock

3.34
seiche
oscillation of a body of water at its natural period

3.35
short-term distribution
probability distribution of a variable within a short interval of time during which conditions are assumed to be statistically stationary

Note 1 to entry: The interval chosen is most often the duration of a *sea-state* (3.32).

3.36
significant wave height
statistical measure of the height of waves in a *sea-state* (3.32)

Note 1 to entry: The significant wave height was originally defined as the mean height of the highest one-third of the zero up-crossing waves in a sea-state. In most offshore data acquisition systems the significant wave height is currently taken as $4\sqrt{m_0}$, (where m_0 is the zeroth *spectral moment* (3.40)) or 4σ, where σ is the standard deviation of the time series of water surface elevation over the duration of the measurement, typically a period of approximately 30 min.

3.37
site-averaging
averaging *extreme values* (3.7) from a number of individual sites

Note 1 to entry: It is used to take account of the localised extent of phenomena such as *tropical cyclones* (3.49) or meso-scale eddies e.g. warm core rings in the Gulf of Mexico.

© ISO 2026 – All rights reserved

3.38
site-pooling
concatenating datasets from several sites into a single dataset for extremal analysis, with the length of the dataset equating to the sum of the individual datasets.

Note 1 to entry: It is used to take account of the localised extent of phenomena such as *tropical cyclones* (3.49) or meso-scale eddies e.g. warm core rings in the Gulf of Mexico.

3.39
soliton
solitary wave or wave packet travelling on an internal density discontinuity which, as a result of the cancellation of non-linear and dispersive effects, maintains its shape and speed over extended distances

EXAMPLE Internal tides which form on the density gradient within the water column can interact with the continental slope and form internal solitary wave packets.

3.40
spectral moment
integral over frequency of the *spectral density function* (3.42) multiplied by the *n*th power of the frequency, either expressed in hertz (cycles per second) as $m_n(f) = \int_0^\infty f^n S(f)\,df$ or expressed in circular frequency (radians/second) as $m_n(\omega) = \int_0^\infty \omega^n S(\omega)\mathrm{d}\omega$

Note 1 to entry: As $\omega = 2\pi f$, the relationship between the two moment expressions is: $m_n(\omega) = (2\pi)^n m_n(f)$.

Note 2 to entry: The integration extends over the entire frequency range from zero to infinity. In practice the integration is often truncated at a frequency beyond which the contribution to the integral is negligible and/or the sensor no longer responds accurately. Care should be taken when utilizing moments of order higher than 2, as for standard spectral models, the 4th moment will not converge; the value is in effect determined by the choice of truncation.

3.41
spectral peak period
period of the maximum (peak) energy density in the *spectrum* (3.42)

Note 1 to entry: In practice there is often more than one peak in a spectrum.

3.42
spectral density function
measure of the variance associated with a time-varying variable per unit frequency band and per unit directional sector

Note 1 to entry: Energy density function is used synonymously with spectral density function.

Note 2 to entry: Spectrum is a shorter expression for the full and formal name of spectral density function or energy density function.

Note 3 to entry: Within this document, the concept of a spectrum applies to waves, wind turbulence and action effects (responses) that are caused by waves or wind turbulence. For waves, the spectrum is a measure of the energy traversing a given space.

3.43
squall
strong wind event characterized by a sudden onset, a duration of the order of minutes and often, a sudden decrease in speed

Note 1 to entry: A squall is often accompanied by a change in wind direction, a drop in barometric pressure, a drop in air temperature and heavy precipitation.

Note 2 to entry: The WMO classification of a squall requires the wind speed to increase by at least 8 m/s and attain a top speed of at least 11 m/s, lasting at least 1 min in duration.

© ISO 2026 – All rights reserved

3.44
still water level
abstract water level used in the calculation of elevations at which actions are applied

Note 1 to entry: Still water level is typically used for the calculation of:

— wave kinematics for global actions;

— wave crest elevation for minimum deck elevations;

— maximum elevation of ice actions.

Note 2 to entry: Still water level is an engineering abstraction calculated by adding the effects of tides and *storm surge* (3.45) to the *water depth* (3.51) but excluding variations due to waves (see Figure 1). It can be above or below *mean sea level* (3.20).

3.45
storm surge
change in sea level (either positive or negative) that is due to meteorological (rather than tidal) forcing

3.46
sustained wind speed
time-averaged wind speed with an averaging duration of 10 min or longer at a specified elevation

3.47
swell
wave that was wind-generated but has travelled out of its generation area and has no relationship with the local wind

3.48
track-shifting
method of perturbing the track (intensity, radius) of historical *tropical cyclones* (3.49) to increase the duration of the record artificially

3.49
tropical cyclone
closed atmospheric circulation around a zone of low pressure that originates over the tropical oceans

Note 1 to entry: The circulation is counter-clockwise in the northern hemisphere and clockwise in the southern hemisphere.

Note 2 to entry: At maturity, the tropical cyclone can be one of the most intense storms in the world, with wind speeds exceeding 90 m/s and accompanied by torrential rain.

Note 3 to entry: In some areas, local terms for tropical cyclones are used. For example, tropical cyclones are typically referred to as hurricanes in the Gulf of Mexico and North Atlantic, while in the East Asian Sea and NW Pacific they are called typhoons. In the South Pacific and South Indian Ocean, however, they are commonly referred to as cyclones.

Note 4 to entry: The term cyclone is also used to refer to a tropical storm with *sustained wind speeds* (3.46) in excess of 32 m/s (Beaufort Force 12).

Note 5 to entry: In the Australian region the term ‘tropical cyclone’ refers to a warm-cored, non-frontal low-pressure system of synoptic scale developing over warm waters, and having organised convection and a (10-min mean) wind speed of at least 34 knots (17,4 m/s), extending more than half way around near the centre and persisting for at least 6 h.

3.50
tsunami
long period surface waves caused by displacement of a large volume of a body of water, normally an ocean

Note 1 to entry: The vertical movement of the *sea floor* (3.31) is often associated with fault rupture during earthquakes or with *seabed* (3.33) mud slides.

© ISO 2026 – All rights reserved

3.51
water depth
vertical distance between the *sea floor* (3.31) and *still water level* (3.44)

Note 1 to entry: As there are several options for the still water level, there can be several water depth values. Generally, design water depth is determined to *LAT* (3.17) or to *mean sea level* (3.20).

Note 2 to entry: The water depth used for calculating wave kinematics varies between the maximum water depth of the *highest astronomical tide* (3.11) plus a positive *storm surge* (3.45), and the minimum water depth of the *lowest astronomical tide* (3.17) less a negative storm surge, where applicable. The same maximum and minimum water depths are applicable to bottom-founded and floating structures, although water depth is usually a much less important parameter for floating structures. Water depth is, however, important for the design and analysis of the mooring system and risers for floating structures.

3.52
wave spectrum
measure of the amount of energy associated with the fluctuation of the sea surface elevation per unit frequency band and per unit directional sector

Note 1 to entry: The wave frequency *spectrum* (3.42) (integrated over all directions) is often described by use of some parametric form such as the Pierson-Moskowitz or *JONSWAP* (3.15) wave spectrum.

Note 2 to entry: The area under the wave spectrum is the zeroth *spectral moment* (3.40)m_0, which is a measure of the total energy in the *sea-state* (3.32); m_0 is used in contemporary definitions of the *significant wave height* (3.36).

3.53
wave steepness
characteristic of individual waves defined as wave height divided by wave length

Note 1 to entry: For periodic waves, the concept is straightforward as H / λ. For random waves, the definition is normally used with the *significant wave height* (3.36) (H_s) and the wavelength that corresponds with the mean zero crossing period (T_z) of the *wave spectrum* (3.52) in deep water. The significant wave steepness is then defined as H_s / λ_z = H_s / [(g/2π) T_z^2].

3.54
wind spectrum
measure of the variance associated with the fluctuating wind speed per unit frequency band

Note 1 to entry: The wind spectrum is an expression of the dynamic properties of the wind (turbulence). It reflects the fluctuations about and in the same direction as a certain *mean wind speed* (3.21), usually the 1 h *sustained wind speed* (3.46). There is hence no direction variable associated with the wind spectrum within this document.

Note 2 to entry: As the sustained wind speed varies with elevation, the wind spectrum is a function of elevation.

4 Symbols and abbreviated terms

4.1 Symbols

$D(\theta)$	wave directional spreading function
$D(f,\theta)$	general form of the wave directional spreading function
d	water depth
$F_{coh}(f;P_1,P_2)$	coherence function between turbulence fluctuations at $P_1(x_1, y_1, z_1)$ and at $P_2(x_2, y_2, z_2)$
f	frequency in cycles per second (Hertz)
f_1	mean wave frequency of the wave spectrum ($f_1 = 1/T_1 = \omega_1 / (2\pi)$)
f_a	apparent wave frequency ($f_a = 1/T_a = \omega_a / (2\pi)$)

© ISO 2026 – All rights reserved