INTERNATIONAL STANDARD

ISO 20419

First edition
2018-10

Treated wastewater reuse for irrigation — Guidelines for the adaptation of irrigation systems and practices to treated wastewater

Réutilisation des eaux usées traitées en irrigation — Lignes directrices pour l'adaptation des systèmes et pratiques d'irrigation aux eaux usées traitées

Reference number
ISO 20419:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO 2018 – All rights reserved

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**
3.1 Treated wastewater (TWW) 2
3.2 Filtration 2

4 TWW quality monitoring for micro-irrigation **4**
4.1 General 4
4.2 TWW quality monitoring devices 4
4.2.1 Flushing counter for automated filters 4
4.2.2 pH level sensor 4
4.2.3 Clogging capacity meter 4
4.2.4 Chlorine demand sensor 5
4.3 TWW quality monitoring procedure 5

5 TWW reservoirs **5**
5.1 General 5
5.2 TWW reservoir safety 5
5.3 TWW reservoir design 5
5.4 Type of TWW stored in the reservoir 5
5.5 Quality of TWW stored in the reservoir 6
5.6 Reservoir processes affecting TWW quality and derived reservoir operation 6
5.7 Reservoir engineering data and design 6
5.8 Biological treatment in reservoirs 6

6 Filtration systems **7**
6.1 General 7
6.2 Filtration battery manifold structure 8
6.3 Filtration technology — Filtration media 12
6.4 Flow/filter area ratio 12
6.5 Filtration stations location in accordance with flow direction 12
6.6 Filtration grade 13
6.7 Manual filter cleaning 13

7 Pumping stations **13**
7.1 General 13
7.1.1 Bottom pumping chamber 13
7.1.2 Floating suction head 13
7.2 Reservoir stratification prevention 14

8 Adaptation of emitters to TWW **15**
8.1 General 15
8.2 Emitters classification 15
8.3 Drippers 15
8.3.1 General 15
8.3.2 On-surface dripper and sub-surface dripper 15
8.4 Durability and longevity of dripper 15
8.5 Functional features of the dripper 15
8.5.1 General 15
8.5.2 Functional features 16
8.6 Sprinkler/centre pivot/frontal pivot 20
8.6.1 General 20
8.6.2 Overhead sprinkler 20
8.6.3 Mini sprinklers 21

© ISO 2018 – All rights reserved

8.6.4 Micro sprinklers and sprayers 21
8.6.5 Center pivot sprinklers/sprayers 22

9 Design parameters for TWW irrigation 22
9.1 General 22
9.2 Design parameters for TWW irrigation systems (drippers, sprinkler irrigation machines) 22

10 Physical treatment 23
10.1 General 23
10.2 Flushing mains, sub-mains and tubes 23
10.3 Collector pipes 23

11 Chemical treatment 24

Annex A (informative) **Definition of TWW quality and treatment recommendations for micro-sprinkler irrigation or drip irrigation 25**

Annex B (informative) **TWW quality parameters and test methods 26**

Annex C (informative) **pH effect on Chlorine concentration 27**

Annex D (informative) **Clogging capacity meter 29**

Annex E (informative) **Sprinklers spacing according to wind conditions 33**

Annex F (informative) **Water stratification in reservoirs 34**

Annex G (informative) **Reservoir inspection and maintenance specification 36**

Annex H (informative) **Chemical treatments in a reservoir 38**

Annex I (informative) **Application of filtration systems to protect drip irrigation systems and spraying systems using TWW: the Israeli experience 39**

Bibliography 41

 © ISO 2018 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 282, *Water reuse*, Subcommittee SC 1, *Treated wastewater reuse for irrigation*.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2018 – All rights reserved

Introduction

Irrigation is gaining importance all over the world, and the lack of water available from surface or groundwater is driving the introduction of treated wastewater for this purpose. Accordingly, some adaptation is needed to the equipment included in the irrigation system to ensure its proper functioning.

The composition of treated wastewater (TWW) is different from that of freshwater. TWW contains more nutritional elements and microbial populations. It is also characterized by a higher salt concentration, anions and cations with a high precipitation potential of sediments of low solubility salts. These characteristics can severely disrupt the operation of the TWW irrigation systems, which can result in poor performance of the system, and potentially harmful to the environment.

Changes in water quality of reservoirs or secondary water resources can affect the water systems' efficiency, as all parts of the irrigation system, such as filters, pipes and emitters, can be adversely affected by low quality water.

The transport efficiency of irrigation equipment is dependent on the quality of the treated wastewater used, due to several factors such as:

— formation of biofilm on interior pipe walls,

— scale precipitation, organic material and fertilizers, and

— excess build-up of sediment.

Irrigation systems clogging types can be classified into three categories:

— organic and inorganic particles (minerals) sedimentation,

— chemical precipitation of low solubility salts, and

— biofouling -attachment/detachment of microorganism colonies on the irrigation system interior surface, which results in biofilm development.

This document provides guidelines on how to use TWW in or with irrigation systems and to protect them from clogging.

© ISO 2018 – All rights reserved

Treated wastewater reuse for irrigation — Guidelines for the adaptation of irrigation systems and practices to treated wastewater

1 Scope

This document provides guidelines to planners and practitioners on how to adjust irrigation equipment so as to allow direct utilization of treated wastewater (TWW) for irrigation. It deals with the adjustment of all components of irrigation systems to TWW quality in respect to physical, chemical and biological parameters.

This document provides guidelines on how to protect irrigation equipment so as to guarantee water systems functionality at high levels of efficiency.

This document includes recommendations for

a) pumping stations,

b) filtration,

c) water network systems,

d) irrigation equipment: emitters (drippers, sprinklers, mini sprinklers, micro sprinklers, sprayers and irrigation machine (sprinklers and sprayers),

e) physical treatment of irrigation equipment, and

f) chemical treatment of irrigation equipment.

This document defines TWW parameters at the irrigation system inlet after a wastewater treatment plant, in order to allow optimal and continual functioning of the irrigation systems and to allow uniformity of emitters' discharge.

2 Normative references

There are no normative references in this document.

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

© ISO 2018 – All rights reserved

3.1 Treated wastewater (TWW)

3.1.1
wastewater
water arising from any combination of domestic, industrial or commercial activities, which can include surface runoff and any accidental sewer inflow/infiltration water and which can include collected storm water, discharged to the environment or sewer

[SOURCE: ISO 20670:2018, 3.80]

3.1.2
treated wastewater
TWW
wastewater that has gone through physical, chemical and/or biological processes to remove contaminants

3.1.3
clogging capacity meter
device used for measuring the time to reach a specified pressure loss across a standard filter screen, at a constant flow rate

[SOURCE: ISO 18471:2015,3.2]

3.1.4
biofilm
attached/detached microorganism colonies on the irrigation systems' interior surface, which results in organic matter development

3.1.5
self-cleaning strainer
filter located in the reservoir that protects the pumping chamber from clogging and has continuous flushing capability

3.1.6
bottom pumping chamber
subsystem that pumps water from the bottom of a water source such as a reservoir or pond, which includes pumping equipment, motors, piping, valves and liquid level controls

3.1.7
floating suction head
unit pumping TWW from the upper level of the reservoir whose pumping point level can be adjusted according to the quality of TWW

3.2 Filtration

3.2.1
filtration
physical process that separates solid particles from water, by passing the water through a physical porous barrier to trap and separate suspended solids from the water

Note 1 to entry: Examples of barrier include media bed, surface or depth filter, screen, disc or membrane.

[SOURCE: ISO 20670:2018, 3.27, modified — Note 1 to entry, the word “disc” has been added.]

3.2.2
nominal flow rate of filtration
flow rate through a filter for proper filtration, as declared by manufacturer

[SOURCE: ISO 9912–1:2004, 2.37]

© ISO 2018 – All rights reserved

3.2.3
check filter
filter located before the irrigation emitters (drip, sprayers and micro sprinklers)

3.2.4
flushing differential pressure
differential pressure between two points, one upstream and one downstream of the filter media, which initiates the flushing cycle

3.2.5
emitter
dripper
device fitted to an irrigation lateral and intended to discharge water in the form of drops or recommended continuous flow at flow rates not exceeding 24 l/h except during flushing

Note 1 to entry: Other emitters flow at flow rates between 24 l/h and 60 l/h.

[SOURCE: ISO 16075–1:2015, 3.4.3]

3.2.6
on-line emitter
emitter intended for installation in the wall of an irrigation lateral, either directly or indirectly by means such as tubing

[SOURCE: ISO 16075–1:2015, 3.4.12]

3.2.7
in-line emitter
emitter intended for installation between two lengths of pipe in an irrigation lateral

[SOURCE: ISO 9261:2004, 3.2]

3.2.8
unregulated dripper
non-pressure compensating emitter/emitting pipe

Note 1 to entry: An unregulated dripper's flow rate varies with inlet water pressure.

[SOURCE: ISO 9261:2004, 3.10]

3.2.9
regulated dripper
pressure compensating emitter/emitting pipe

Note 1 to entry: A regulated dripper maintains a relatively constant flow rate at varying water pressures.

[SOURCE: ISO 9261:2004, 3.8]

3.2.10
sprinkler
water distribution device of a variety of sizes and types, for example, impact sprinkler, fixed nozzle, sprayer, irrigation gun

[SOURCE: ISO 16075-1:2015, 3.4.24]

3.2.11
rotating sprinkler
device which by its rotating motion around its vertical axis distributes water over a circular area or part of a circular area

[SOURCE: ISO 15886-1:2012, 2.38]

© ISO 2018 – All rights reserved

3.2.12
irrigation sprayer
device which discharges water in the form of fine jets or in a fan shape without rotation movements of its parts

[SOURCE: ISO 16075-1:2015, 3.4.7]

3.2.13
center pivot
automated irrigation machine consisting of a number of self-propelled towers supporting a pipeline rotating around a pivot point and through which water supplied at the pivot point flows radially outward for distribution by sprayers or sprinklers located along the pipeline

[SOURCE: ISO 16075-1:2015, 3.4.2]

4 TWW quality monitoring for micro-irrigation

4.1 General

4.1.1 Micro-irrigation equipment should be adapted to the quality of the given water.

4.1.2 Water quality parameters should fulfill the recommended values shown in Table A.1 and Table B.1.

4.1.3 Since TWW quality changes from season to season, from month to month, from week to week, from day to day or even during the course of one day, TWW users should closely monitor the TWW quality in the system at key points, to be able to respond to quality changes, which can otherwise quickly clog the entire micro-irrigation system.

4.1.4 Monitoring of TWW quality (see 4.2) can provide users with efficient real-time information.

4.1.5 Changes in TWW quality should be responded to by the adaptation of irrigation parameters, such as flow reduction, filters insertion and chemical treatments.

4.1.6 The quality of TWW should be monitored using the devices listed in 4.2, and according to the procedure described in 4.3.

4.2 TWW quality monitoring devices

4.2.1 Flushing counter for automated filters

A flushing counter for automated filters monitors changes that occur between one period of flushing and the next period of flushing.

A change in flushing frequency should indicate changes in water quality.

4.2.2 pH level sensor

A pH level sensor indicates calcium and calcium carbonate levels, as well as the expected efficiency of any injected chlorine (see Annex C).

4.2.3 Clogging capacity meter

A clogging capacity meter provides immediate information about changes in TWW and identifies the main material causing the clogging.

© ISO 2018 – All rights reserved