International Standard

ISO/CIE 10916

First edition
2024-11

Light and lighting — Energy performance of lighting in buildings — Calculation of the impact of daylight utilization

Lumière et éclairage — Performance énergétique de l'éclairage des bâtiments — Calcul de l'impact de l'utilisation de la lumière du jour

Reference number
ISO/CIE 10916:2024(en)

© ISO/CIE 2024



COPYRIGHT PROTECTED DOCUMENT

© ISO/CIE 2024

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11

Email: copyright@iso.org
Website: www.iso.org

CIE Central Bureau
Babenbergerstraße 9/9A • A-1010 Vienna

Phone: +43 1 714 3187
Fax: +41 22 749 09 47
Email: ciecb@cie.co.at
Website: www.cie.co.at

Published in Switzerland

Contents

Page

Foreword ... **iv**

Introduction ... **v**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **2**

4 Symbols, indices, and abbreviated terms ... **4**
4.1 Symbols ... 4
4.2 Indices and abbreviated terms ... 5

5 Proof calculation method ... **6**
5.1 Energy demand for lighting as function of daylight ... 6
5.2 Subdivision of a building into zones ... 8
5.3 Operating time ... 8
5.4 Electric lighting ... 8
5.5 Constant illuminance control ... 8
5.6 Daylight ... 8
5.7 Occupancy dependency factor $F_{O,n}$ ... 9

6 Daylight Performance Indicator ... **9**

Annex A (informative) **Simple calculation method** ... **10**

Annex B (informative) **Comprehensive hourly calculation** ... **54**

Annex C (informative) **Daylight performance indicator** ... **89**

Annex D (informative) **Examples** ... **90**

Bibliography ... **97**

© ISO/CIE 2024 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

ISO draws attention to the possibility that the implementation of this document may involve the use of (a) patent(s). ISO takes no position concerning the evidence, validity or applicability of any claimed patent rights in respect thereof. As of the date of publication of this document, ISO had not received notice of (a) patent(s) which may be required to implement this document. However, implementers are cautioned that this may not represent the latest information, which may be obtained from the patent database available at www.iso.org/patents. ISO shall not be held responsible for identifying any or all such patent rights.

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 274, *Light and lighting,* in collaboration with the International Commission on Illumination (CIE).

This first edition of ISO/CIE 10916 cancels and replaces ISO 10916:2014, which has been technically revised.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO/CIE 2024 – All rights reserved

Introduction

This document is part of a set of standards which allows users to rate the overall energetic performance of buildings. Facades and rooflights have a key impact on the building's energy balance. This document supports daylighting and lighting-energy-related analysis and optimization of facade and rooflight systems. It is specifically devised to establish conventions and procedures for the estimation of daylight penetrating buildings through vertical facades and rooflights, as well as on the energy consumption for electric lighting as a function of daylight provided in indoor spaces.

© ISO/CIE 2024 – All rights reserved

Light and lighting — Energy performance of lighting in buildings — Calculation of the impact of daylight utilization

1 Scope

This document defines the calculation methodology for determining the monthly and annual amount of usable daylight penetrating non-residential buildings through vertical facades and rooflights and the impact thereof on the energy demand for electric lighting. This document is applicable for existing buildings and the design of new and renovated buildings.

This document provides the overall lighting energy balance equation relating the installed power density of the electric lighting system with daylight supply and lighting controls (proof calculation method).

The determination of the installed power density is not in the scope of this method, neither are controls relating, for instance, to occupancy detection. Provided the determination of the installed power density and control parameters using external sources, the internal loads by lighting and the lighting energy demand itself can be calculated. The energy demand for lighting and internal loads by lighting can then be taken into account in the overall building energy balance calculations:

— heating;

— ventilation;

— climate regulation and control (including cooling and humidification);

— heating the domestic hot-water supply of buildings.

For estimating the daylight supply and rating daylight-dependent electric lighting control systems, a simple table-based calculation approach is provided. The simple method describes the division of a building into zones as required for daylight illumination-engineering purposes, as well as considerations on the way in which daylight supplied by vertical facade systems and rooflights is utilized and how daylight-dependent lighting control systems affect energy demand. Dynamic vertical facades with optional shading and light redirection properties are considered, i.e. allowing a separate optimization of facade solutions under direct insolation and under diffuse skies. For rooflighting systems, standard, static solutions like shed rooflights and continuous rooflights are considered. The method is applicable for different latitudes and climates. For standard building zones (utilizations), operation times are provided.

For detailed analysis, an approach to calculate the effect of daylight on the lighting energy demand on an hourly or sub-hourly basis is provided. Unlike the simple table-based annual calculation approach, which is regression based, this method relies on an emulation concept. Relevant quantities are modelled explicitly and are then interacting directly with sensors, actuators and functional elements of the building automation and control system (BACS) or are triggering user interaction. By this approach, model configuration and parametrization from the design stage can seamlessly be used in the BACS configuration.

To support overall building performance assessment, additional daylight performance indicators on the overall building level are provided.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

CIE S 017:2020, *ILV: International Lighting Vocabulary*

© ISO/CIE 2024 – All rights reserved

3 Terms and definitions

For the purposes of this document, the terms and definitions given in CIE S 017, and the following apply.

ISO and IEC maintain terminology databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at https://www.electropedia.org/

CIE maintains a terminology database for use in standardization at the following address:

— e-ILV: available at https://cie.co.at/e-ilv

3.1
control system
various types of electrical and electronic systems including the following:

— systems used to control and regulate;

— systems to protect against solar radiation and/or glare;

— electric lighting in relation to the currently available daylight;

— systems used to detect and record the presence of occupants

3.2
daylight factor
D
quotient of the illuminance at a point on a given plane due to the light received directly and indirectly from a sky of assumed or known luminance distribution and the illuminance on a horizontal plane due to an unobstructed hemisphere of this sky, where the contribution of direct sunlight to both illuminances is excluded

Note 1 to entry: Glazing, dirt effects, etc. are included.

Note 2 to entry: When calculating the lighting of interiors, the contribution of direct sunlight has to be considered separately.

Note 3 to entry: CIE S 017:2020 defines the unit as 1. However, daylight factor is in practice, usually presented in percent values.

Note 4 to entry: The term daylight factor is normally used when considering an overcast sky as sky type 1 or 16 in ISO 15469.

[SOURCE: CIE S 017:2020, 17-29-121, modified — Notes 3 to 5 deleted, new Notes to entry 3 and 4 added]

3.3
electrical power of electric lighting system
P
total electrical power consumption of the lighting system in the considered space

3.4
illuminance
E
density of incident luminous flux with respect to area at a point on a real or imaginary surface

$$E = \frac{d\Phi_v}{dA},$$

where

© ISO/CIE 2024 – All rights reserved