ISO/IEC 14543-3-10

Edition 2.0 2020-03

INTERNATIONAL STANDARD

colour inside

Information technology – Home electronic system (HES) architecture – Part 3-10: Amplitude modulated wireless short-packet (AMWSP) protocol optimized for energy harvesting – Architecture and lower layer protocols



ISO/IEC 14543-3-10:2020-03(en)

THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2020 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigendum or an amendment might have been published.

IEC publications search - webstore.iec.ch/advsearchform
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,...). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and once a month by email.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: sales@iec.ch.

Electropedia - www.electropedia.org
The world's leading online dictionary on electrotechnology, containing more than 22 000 terminological entries in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
67 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

ISO/IEC 14543-3-10

Edition 2.0 2020-03

INTERNATIONAL STANDARD

colour inside

Information technology – Home electronic system (HES) architecture – Part 3-10: Amplitude modulated wireless short-packet (AMWSP) protocol optimized for energy harvesting – Architecture and lower layer protocols

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.200

ISBN 978-2-8322-7979-3

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 4
INTRODUCTION 6
1 Scope 8
2 Normative references 8
3 Terms, definitions and abbreviated terms 8
3.1 Terms and definitions 8
3.2 Abbreviated terms 13
4 Conformance 13
5 Architecture 13
5.1 Generic protocol description 13
5.1.1 Overview 13
5.1.2 Physical layer 14
5.1.3 Data link layer 14
5.1.4 Network layer 14
5.1.5 Transport layer 15
5.1.6 Session layer 15
5.1.7 Presentation layer 15
5.1.8 Application layer 15
5.2 Data unit description 15
6 Layer 1 – Physical layer 16
6.1 Overview 16
6.2 General description 16
6.3 Requirements for the 315 MHz AMWSP protocol 18
6.4 Requirements for the 868,3 MHz AMWSP protocol 21
6.5 Frame structure 23
7 Layer 2 – Data link layer 25
7.1 Overview 25
7.2 Subtelegram timing 25
7.3 Data integrity 26
7.3.1 General 26
7.3.2 4 bit summation hash function algorithm 27
7.3.3 8 bit summation hash function algorithm 27
7.3.4 8 bit cyclic redundancy check (CRC) hash function algorithm 27
7.4 Listen before talk 28
8 Layer 3 – Network layer 28
8.1 Overview 28
8.2 Switch telegram 28
8.3 Repeater 29
8.3.1 General 29
8.3.2 Time response for collision avoidance 29
8.3.3 Bits of a repeater level in the STATUS byte 30
8.4 Addressing 30
8.4.1 General 30
8.4.2 Encapsulation 31
Annex A (informative) Examples of how to evaluate the hash values 32
Bibliography 34

Figure 1 – Structure of a subtelegram 15
Figure 2 – Illustration of an ASK envelope and various physical parameters 17
Figure 3 – Complete frame structure for the 868,3 MHz AMWSP protocol 23
Figure 4 – Encoded subframe 24
Figure 5 – TX maturity time divided into four 10 ms time ranges 25
Figure 6 – Conversion of a switch telegram to a normal telegram 29
Figure 7 – Example of an encapsulation 31
Figure A.1 – Example of a C code program of the 4 bit long summation hash value 32
Figure A.2 – Example of a C code program of the 8 bit long summation hash value 32
Figure A.3 – Efficient C code program for the evaluation of an 8 bit long CRC type hash value 33

Table 1 – AMWSP protocol stack structure (OSI) 14
Table 2 – Transmitter requirements for the 315 MHz AMWSP protocol 19
Table 3 – Receiver requirements for the 315 MHz AMWSP protocol 20
Table 4 – Minimum required link budget for the 315 MHz AMWSP protocol 20
Table 5 – Maximum RX power for the 315 MHz AMWSP protocol 21
Table 6 – Transmitter requirements for the 868,3 MHz AMWSP protocol 21
Table 7 – Receiver requirements for the 868,3 MHz AMWSP protocol 22
Table 8 – Minimum required link budget for the 868,3 MHz AMWSP protocol 22
Table 9 – Maximum RX power for the 868,3 MHz AMWSP protocol 23
Table 10 – Frame definition for the 315 MHz AMWSP protocol 24
Table 11 – Frame definition for the 868,3 MHz AMWSP protocol 24
Table 12 – Maturity time parameters 25
Table 13 – Allocation of time slots to the different subtelegrams 26
Table 14 – Identification of the hash function used in the telegram 27
Table 15 – Conversion of the telegram type and STATUS fields from a switch telegram to a telegram 29
Table 16 – STATUS byte with repeater level bits 30
Table 17 – Repeating bits in STATUS byte 30

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-10: Amplitude modulated wireless short-packet (AMWSP) protocol optimized for energy harvesting – Architecture and lower layer protocols

FOREWORD

1) ISO (International Organization for Standardization) and IEC (International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards. Their preparation is entrusted to technical committees; any ISO and IEC member body interested in the subject dealt with may participate in this preparatory work. International governmental and non-governmental organizations liaising with ISO and IEC also participate in this preparation.
2) In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.
3) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC and ISO member bodies.
4) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
5) In order to promote international uniformity, IEC and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.
6) ISO and IEC provide no marking procedure to indicate their approval and cannot be rendered responsible for any equipment declared to be in conformity with an ISO/IEC publication.
7) All users should ensure that they have the latest edition of this publication.
8) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.
9) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
10) Attention is drawn to the possibility that some of the elements of this International Standard may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

International Standard ISO/IEC 14543-3-10 was prepared by subcommittee 25: Interconnection of information technology equipment, of ISO/IEC joint technical committee 1: Information technology.

The list of all currently available parts of the ISO/IEC 14543 series, under the general title *Information technology – Home electronic system (HES) architecture*, can be found on the IEC and ISO websites.

This second edition cancels and replaces the first edition published in 2012. This edition constitutes a technical revision.

The text of this standard is based on the following documents:

CDV	Report on voting
JTC1-SC25/2842/CDV	JTC1-SC25/2864/RVC

Full information on the voting for the approval of this standard can be found in the report on voting indicated in the above table.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

Various electrically controlled sensors and switches are used in homes and similar environments for many different applications. Examples of such applications are lighting, heating, energy management, blinds control, different forms of security control and entertainment (audio and video).

In most cases the device, e.g. a switch initiating an action, and the device, e.g. a lamp, are installed at different places. The distance can be bridged by wires, infrared or radio transmission. Presently equipment at both ends of a wireless transmission link needs to be powered by line or battery.

While wireless transmissions are especially attractive to retrofit homes, power maintenance of battery-driven devices is a burden. In addition, these batteries require scarce materials. Since the command and control messages sent by control and sensor devices in homes are very short, they can be powered using new techniques for energy harvesting, provided they use a wireless protocol that operates on relatively low power. Energy available in the environment of a device is captured and stored (harvested) to power operation of the device. Examples of energy sources are mechanical actuation, solar radiation, temperature differences, etc. If this is executed, at least one device in the link neither needs a battery nor a wire. Energy harvesting devices need very limited power and use an energy efficient radio protocol to send data to other conventionally powered devices in the home. In order to ensure interoperability of such devices from different sources within a home, an International Standard for a protocol is required that uses the little power that energy harvesting devices can provide and at the same time spans distances to be bridged within a home environment.

Several such devices used within a home often come from different sources. They are required to interwork with each other using a common internal network (in this document called a home network) and supporting a home automation system. When a home automation system meets ISO/IEC HES Standards, it is called a home electronic system (HES).

Alternative transmission technologies are specified by ISO/IEC 14543 (all parts). ISO/IEC 14543-3-10 and ISO/IEC 14543-3-11 are optimized for energy harvesting based on similar techniques, but with different modulation schemes. ISO/IEC 14543-3-10 and ISO/IEC 14543-3-11 specify two lower layer wireless short-packet protocols: ISO/IEC 14543-3-10 uses an amplitude modulated (AM) signal and ISO/IEC 14543-3-11 a frequency modulated (FM) signal.

Amplitude modulated wireless communications are more energy efficient but less adapted to mobile devices. This is because the impedance of a mobile antenna is affected by the environment of the mobile device, for example, when the device is held in the hand or moved to metal surface. Changes in impedance affect the amplitude linearity of the radio frequency output amplifier, but have no impact on the frequency itself. Thus an AM wireless system is more sensitive to changes in environment than an FM wireless system. Also frequencies above 800 MHz are better suited for mobile devices, since they require smaller antennas. Thus the frequency 315 MHz is not used in the FM specification, which makes the FM wireless system more efficient for mobile devices.

Compared to the AM wireless system, the FM wireless system provides more flexibility in the size of various pieces of information that can be transmitted. This includes the possibility to have larger payloads, different lengths of the identifiers of originators and destinations, and greater variability of structures and lengths of the telegram types. The number of steps a telegram can be repeated is two for the AM wireless system and 15 for the FM wireless system.

They are both efficient enough to

- support energy harvesting products for sensors and switches that require neither cabling nor batteries, and
- extend the life of battery-operated devices.

Both an AM and an FM system can be active at the same time, since each system is so constructed that only permitted messages are accepted. Collisions can be avoided by listen-before-talk (LBT) technology or overcome by redundant transmissions.

INFORMATION TECHNOLOGY – HOME ELECTRONIC SYSTEM (HES) ARCHITECTURE –

Part 3-10: Amplitude modulated wireless short-packet (AMWSP) protocol optimized for energy harvesting – Architecture and lower layer protocols

1 Scope

This part of ISO/IEC 14543 specifies a wireless protocol for low-powered devices such as energy harvesting devices in a home environment. This wireless protocol is specifically designed to keep the energy consumption of such sensors and switches extremely low.

The design is characterized by

- keeping the communications very short, infrequent and mostly unidirectional, and
- using communication frequencies that provide a good range even at low transmit power and avoid collisions from disturbers.

This allows the use of small and low-cost energy harvesting devices that can compete with similar battery-powered devices. The messages sent by energy harvesting devices are received and processed mainly by line-powered devices such as relay switch actuators, repeaters or gateways. Together these form part of a home automation system, which, when conforming to ISO/IEC 14543 (all parts), is defined as a home electronic system.

This document specifies OSI Layers 1 to 3 of the amplitude modulated wireless short-packet (AMWSP) protocols.

The AMWSP protocol system consists of two and optionally three types of components that are specified in this document. These are the transmitter, the receiver and optionally the repeater. Repeaters are needed when the transmitter and the receiver are located in such a way that no good direct communication between them can be established.

Protection against malicious attacks is handled in the upper layers and thus not treated in this document.

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ETSI EN 300 220-1 V3.1.1, *Short Range Devices (SRD) operating in the frequency range 25 MHz to 1 000 MHz; Part 1: Technical characteristics and methods of measurement*

3 Terms, definitions and abbreviated terms

3.1 Terms and definitions

For the purposes of this document the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org/obp

3.1.1
amplitude shift keying envelope
ASK envelope
envelope of the modulated signal

3.1.2
bit duration
time between transitions of the mesial amplitude of an ASK envelope in an alternating sequence

Note 1 to entry Figure 2 shows this in detail.

3.1.3
bit duration error
deviation of bit duration from specified bit duration

3.1.4
byte
ordered set of eight binary digits, operated on as an entity

Note 1 to entry: The non-qualified term "byte" designates an 8-bit byte.

[SOURCE: IEC 60050-702:2016, 702-05-09]

3.1.5
collision
state which exists when two wireless transmitters use the same wireless channel and transmit data at the same time

3.1.6
cyclic redundancy check
CRC
integrity hash algorithm based on a polynomial division

3.1.7
DATA
application payload data transmitted in the telegram

3.1.8
energy harvesting device
device able to capture and store (harvest) energy from the environment to power its operations

Note 1 to entry Examples of energy sources are mechanical actuation, solar radiation, temperature differences, etc.

3.1.9
frame
set of data to be transmitted as a complete unit on the physical layer

Note 1 to entry A frame contains the necessary protocol control and synchronization data for transmission between network nodes.

3.1.10
HASH
field in which the hash value for the data integrity control of each transmitted telegram and subtelegram is specified

3.1.11
high nibble
upper four bits of the byte

Note 1 to entry The N value from the byte 0xNM.

3.1.12
high state amplitude
amplitude corresponding to the physical high state level

3.1.13
high state level
level of the ASK envelope that represents the high state amplitude

Note 1 to entry The definition aligns with IEEE 194-1977, 5.2.2.5, static levels. Figure 2 gives an illustration.

3.1.14
identity of the destination device
DESTID
unique identity of the destination device of an AMWSP telegram consisting of four bytes

3.1.15
identity of the transmitting device
TXID
unique identity of the AMWSP protocol transmitting device consisting of four bytes

3.1.16
inverse bits
INV
bits added by the encoding procedure into a subframe behind the third and the sixth bit to reduce the DC content of the data

3.1.17
listen before talk
LBT
technique of checking the occupancy of the wireless channel before transmitting any frames

3.1.18
low nibble
lower four bits of the byte

Note 1 to entry The M value from the byte 0xNM.

3.1.19
low state amplitude
amplitude corresponding to the physical low state level

3.1.20
low state level
level of the ASK envelope that represents the low state amplitude

Note 1 to entry The definition aligns with IEEE 194-1977, 5.2.2.5, static levels. Figure 2 gives an illustration.

3.1.21
mesial power level
median between high state level and low state level of an ASK envelope

Note 1 to entry Figure 2 gives an illustration.

3.1.22
negative overshoot
difference between minimum peak level and low state level of an ASK envelope after a transition from a high state to a low state has occurred

Note 1 to entry Figure 2 gives an illustration.

3.1.23
negative undershoot
difference between maximum peak level and low state level of an ASK envelope after a transition from a high state to a low state has occurred

Note 1 to entry Figure 2 gives an illustration.

3.1.24
nibble
four-bit aggregation or half a byte

3.1.25
positive overshoot
difference between maximum peak level and high state level of ASK envelope after a transition from a low state to a high state has occurred

Note 1 to entry Figure 2 gives an illustration.

3.1.26
positive undershoot
difference between minimum peak level and high state level of ASK envelope after a transition from a low state to a high state has occurred

Note 1 to entry Figure 2 gives an illustration.

3.1.27
receiving device maturity time
RX maturity time
maximum time, determined at the receiving device, between the end of the first subtelegram and the end of the last subtelegram belonging to the same telegram

3.1.28
repeated telegram
telegram transmitted by a repeater

3.1.29
repeater
device that receives telegrams and sends refreshed signals to any AMWSP receiver

3.1.30
subframe
subtelegram byte expanded by protocol control and synchronization information

3.1.31
subtelegram
smallest interpreted data unit containing the fields telegram type (RORG), payload (DATA), transmitter identity (TXID), STATUS and HASH

3.1.32
switch telegram
telegram with fields telegram type (RORG), payload (DATA), transmitter identity (TXID) and HASH

Note 1 to entry The switch telegram structure differs from the telegram in that the fields of RORG and HASH are only four bits long and that it does not contain a STATUS field.

3.1.33
synchronization bits
SYNC
bits inserted by an encoding procedure at the end of each subframe (except for the last subframe) to provide clock resynchronization

Note 1 to entry Synchronization bits also reduce the DC content of transmitted data and can be used to ensure data reliability and integrity.

3.1.34
telegram
data unit composed of one or more identical subtelegrams

Note 1 to entry A telegram has the same structure and contains the same information as a subtelegram.

3.1.35
telegram type
RORG
field that identifies the type of a telegram in the AMWSP protocol

Note 1 to entry This type of telegram is denoted CHOICE in ISO/IEC 8825-2.

Note 2 to entry There are several types of telegram; however, with the exception of the switch telegram, they are not defined in this document.

3.1.36
time slot
unit of 1 ms of RX maturity time or TX maturity time

3.1.37
transmitting device lead time
time between activation of transmitting device and the start of the transmission of second preamble bit

3.1.38
transmitting device maturity time
TX maturity time
maximum time for the transmission of one complete telegram as determined at the sending device

3.1.39
transmitting device overtravel time
time a signal is still emitted from the transmitter after the last '0' bit of end of frame (EOF) has been transmitted

3.2 Abbreviated terms

ASK	amplitude shift keying
CRC	cyclic redundancy check
DC	direct current
DESTID	destination device identity
EIRP	effective isotropic radiated power
ERP	effective radiated power
EOF	end of frame
INV	inverse bits
LBT	listen before talk
MSB	most significant bit
PRE	preamble
RX	receiver
RORG	telegram type
SOF	start of frame
SYNC	synchronization bits
TX	transmitter
TXID	transmitting device identity
AMWSP	amplitude modulated wireless short-packet

4 Conformance

The three components of the AMWSP protocol system that are specified in this document are the transmitter, the receiver and the repeaters. The repeaters shall be able both to transmit and to receive telegrams and thus shall support both the requirements for the transmitters and the receivers.

To conform to this document, the components shall support one of the two wireless frequencies specified unless another frequency is mandated by local regulations. For the frequency chosen, the transmitter shall support all the transmitter requirements that are not explicitly listed as optional, and the receiver shall support all the receiver requirements that are not explicitly listed as optional. These requirements are specified in 5.2 and Clauses 6, 7 and 8.

5 Architecture

5.1 Generic protocol description

5.1.1 Overview

Subclause 5.1.1 provides a comprehensive overview of the amplitude modulated wireless short-packet (AMWSP) protocol stack (see Table 1). The AMWSP is a lightweight layered protocol designed to minimize both energy demand and the probability of a transmission collision. The AMWSP protocol stack accommodates the structure of the OSI reference model (see ISO/IEC 7498-1).