INTERNATIONAL STANDARD

ISO/IEC 15693-2

Third edition
2019-04

Cards and security devices for personal identification — Contactless vicinity objects —

Part 2: Air interface and initialization

Cartes et dispositifs de sécurité pour l'identification personnelle — Objets sans contact de voisinage —

Partie 2: Interface et initialisation dans l'air



Reference number
ISO/IEC 15693-2:2019(E)

© ISO/IEC 2019



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2019

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ... **iv**
Introduction ... **v**
1 Scope ... **1**
2 Normative references ... **1**
3 Terms and definitions ... **1**
4 Symbols and abbreviated terms ... **2**
4.1 Abbreviated terms ... 2
4.2 Symbols ... 2
5 Initial dialogue for vicinity cards ... **2**
6 Power transfer ... **3**
6.1 General ... 3
6.2 Frequency ... 3
6.3 Operating field ... 3
7 Communications signal interface VCD to VICC ... **3**
7.1 General ... 3
7.2 Modulation ... 3
7.3 Data rate and data coding ... 5
7.3.1 General ... 5
7.3.2 Data coding mode: 1 out of 256 ... 6
7.3.3 Data coding mode: 1 out of 4 ... 7
7.4 VCD to VICC frames ... 8
7.4.1 General ... 8
7.4.2 SOF to select 1 out of 256 code ... 8
7.4.3 SOF to select 1 out of 4 code ... 8
7.4.4 EOF for either data coding mode ... 9
8 Communications signal interface VICC to VCD ... **9**
8.1 General ... 9
8.2 Load modulation ... 9
8.3 Subcarrier ... 9
8.4 Data rates ... 9
8.4.1 General ... 9
8.4.2 Low and high data rates ... 10
8.4.3 Fast response data rates ... 10
8.5 Bit representation and coding ... 10
8.5.1 General ... 10
8.5.2 Bit coding when using one subcarrier ... 10
8.5.3 Bit coding when using two subcarriers ... 11
8.6 VICC to VCD frames ... 12
8.6.1 General ... 12
8.6.2 SOF when using one subcarrier ... 12
8.6.3 SOF when using two subcarriers ... 13
8.6.4 EOF when using one subcarrier ... 13
8.6.5 EOF when using two subcarriers ... 13
Annex A (informative) **Standards compatibility** ... **15**
Annex B (normative) **Bit coding and frames for a fast response data** ... **16**
Bibliography ... **21**

© ISO/IEC 2019 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see http://patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC1, *Information technology*, Subcommittee SC 17, *Cards and security devices for personal identification*.

This third edition cancels and replaces the second edition (ISO/IEC 15693-2:2006), which has been technically revised.

The main changes compared to the previous edition are as follows:

— fast response data rates in 8.4.3 and Annex B have been added.

A list of all parts in the ISO/IEC 15693 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO/IEC 2019 – All rights reserved

Introduction

ISO/IEC 15693 (all parts) is one of a series of International Standards defining the parameters for identification cards as defined in ISO/IEC 7810 and the use of such cards for international interchange.

This document defines the electrical characteristics of the contactless interface between a vicinity card and a vicinity coupling device. The interface includes power and bi-directional communications.

Contactless card standards cover a variety of types as embodied in ISO/IEC 10536 (close-coupled cards), ISO/IEC 14443 (proximity cards) and ISO/IEC 15693 (vicinity cards). These are intended for operation when very near, nearby and at a longer distance from associated coupling devices, respectively.

© ISO/IEC 2019 – All rights reserved

Cards and security devices for personal identification — Contactless vicinity objects —

Part 2: Air interface and initialization

1 Scope

This document specifies the nature and characteristics of the fields to be provided for power and bi-directional communications between vicinity coupling devices (VCDs) and vicinity cards (VICCs).

This document is intended to be used in conjunction with other parts of the ISO/IEC 15693 series.

This document does not preclude the incorporation of other standard technologies on the card as described in Annex A.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 10373-7[1)], *Cards and security devices for personal identification — Test methods — Part 7: Contactless vicinity objects*

ISO/IEC 15693-1, *Cards and security devices for personal identification — Contactless vicinity objects — Part 1: Physical characteristics*

ISO/IEC 15693-3, *Cards and security devices for personal identification — Contactless vicinity objects — Part 3: Anticollision and transmission protocol*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 15693-1 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
modulation index
index equal to [a-b]/[a+b] where a and b are the peak and minimum signal amplitudes, respectively

Note 1 to entry: The value of the index may be expressed as a percentage.

3.2
subcarrier
signal of frequency f_s used to modulate the carrier of frequency f_c

1) Under preparation.

© ISO/IEC 2019 – All rights reserved

3.3
byte
string that consists of 8 bits of data designated b1 to b8, from the most significant bit (MSB,b8) to the least significant bit (LSB,b1)

4 Symbols and abbreviated terms

4.1 Abbreviated terms

ASK	amplitude shift keying
EOF	end of frame
LSB	least significant bit
MSB	most significant bit
PPM	pulse position modulation
RF	radio frequency
SOF	start of frame
VCD	vicinity coupling device
VICC	vicinity integrated circuit card

4.2 Symbols

a	carrier amplitude without modulation
b	carrier amplitude when modulated
f_c	frequency of the operating field (carrier frequency)
f_s	frequency of the subcarrier
H_{max}	maximum operating field
H_{min}	minimum operating field

5 Initial dialogue for vicinity cards

The dialogue between the VCD and the VICC (one or more VICCs may be present at the same time) is conducted through the following consecutive operations:

— activation of the VICC by the RF operating field of the VCD;

— VICC waits silently for a command from the VCD;

— transmission of a command by the VCD;

— transmission of a response by the VICC.

These operations use the RF power transfer and communication signal interface specified in the following clauses and shall be performed according to the protocol defined in ISO/IEC 15693-3.

© ISO/IEC 2019 – All rights reserved