INTERNATIONAL STANDARD

ISO/IEC 17991

Second edition
2021-01

Information technology — Office equipment — Method for measuring scanning productivity of digital scanning devices

Technologie de l'information — Équipement d'office — Méthode de mesure de la productivité du scanner des appareils de numérisation

Reference number
ISO/IEC 17991:2021(E)

© ISO/IEC 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Contents

Page

Foreword ..... **v**

Introduction ..... **vi**

1 Scope **1**

2 Normative references **1**

3 Terms and definitions **1**

4 Test parameters and conditions **4**
4.1 Scanning device setup 4
4.2 Scanning device connection 5
4.3 Scanning device condition 5
4.4 Sample size 5
4.5 Maintenance 5
4.6 Preparation of test targets (test charts) 5
4.7 Environment 6
4.8 Voltage 6

5 Test method **6**
5.1 Overview 6
5.2 Test measurement procedure 7
5.2.1 Test setup 7
5.2.2 "1 set" test from ready 8
5.2.3 "1 set + 30 seconds" test from ready 8
5.3 Test method process 9
5.3.1 Suggested flow chart 9
5.3.2 ±5 % consistency criteria 10
5.3.3 Estimating the set count 11
5.4 ADF productivity measurement 11
5.5 "Scan to network folder productivity measurement" and "scan to PC file productivity measurement" 11
5.5.1 Overview 11
5.5.2 Measurement of ***scEFTP*** 12
5.6 Feature performance test 12
5.6.1 Overview 12
5.6.2 Features setting conditions 12
5.6.3 Measurement of ***FSOT*** and ***ESAT*** 12

6 Calculations and treatment of data **13**
6.1 Overview 13
6.2 "1 set" test from ready 13
6.3 "1 set + 30 seconds" test ready 14

7 Presentation of results **15**
7.1 Sharing testing and reports 15
7.2 Minimum declaration 16
7.3 ADF productivity measurement 16
7.3.1 Overview 16
7.3.2 Summary report 16
7.3.3 Full report 17
7.4 "Scan to network folder productivity measurement" and "Scan to PC file productivity measurement" 18
7.4.1 Overview 18
7.4.2 Summary report 19
7.4.3 Full report 20
7.5 Feature performance test 21
7.5.1 Overview 21
7.5.2 Summary report 21

© ISO/IEC 2021 – All rights reserved

7.5.3 Full report 21
Annex A (informative) **Report presentation** **23**
Annex B (informative) **Full detailed report example** **27**
Annex C (normative) **Test targets for measurement of scanning productivity** **31**
Bibliography **32**

 © ISO/IEC 2021 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see https://patents.iec.c).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 28, *Office equipment*.

This second edition cancels and replaces the first edition (ISO/IEC 17991:2015), which has been technically revised.

The main changes compared to the previous edition are as follows:

— changed the document structure to be consistent with other productivity standards;

— added single function scanners to the Scope;

— updated reporting to include examples of minimum declarations;

— added “first page eject” test result to the “1 set” test from ready.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO/IEC 2021 – All rights reserved

Introduction

The actual productivity measurement methods of copying and printing were published as ISO/IEC 24735 and ISO/IEC 24734. However, ISO/IEC 25735 contains no measurement method for the scanning productivity of multifunctional devices to be used for comparison and procurement of these machines.

This document provides a general method for measuring “scanning productivity” of the scanning devices. This document also includes a test chart for scanning productivity measurement. It allows the manufacturers and the buyers of scanning devices to describe the productivity with respect to representative usage.

© ISO/IEC 2021 – All rights reserved

Information technology — Office equipment — Method for measuring scanning productivity of digital scanning devices

1 Scope

This document specifies a method for determining scanning productivity by measuring "scanning speed", "scan to network folder speed" and "scan to PC speed". It includes test files, test setup procedure, test procedure and the reporting requirements for the scanning productivity measurements. This document is applicable to scanning devices including but not limited to multi-function devices, networked scanners and single-function scanners of any underlying scanning technology.

This document is applicable to devices which are able to scan a media size of A4/8,5" × 11" and which have an automatic document feeder (ADF). It is also applicable to devices which have the ability to scan to network folder, or folder on PC and do not require, but can use, other application programs on a computer or another device to perform a scanning job.

This document does not apply to testing and measurement of scan to USB, scan to local hard drive or other storage medium that is part of or plugged into the scanner.

This document is not intended to be used for image quality measurement, document or record management of any scanned images.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 536, *Paper and board — Determination of grammage*

ISO 2470-1, *Paper, board and pulps — Measurement of diffuse blue reflectance factor — Part 1: Indoor daylight conditions (ISO brightness)*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
ADF speed
rate at which a device scans documents using an automatic document feeder (ADF) to demonstrate the productivity of the ADF and is represented with suffix A

EXAMPLE $scEFTP_{1setA}$ is the scanner *effective throughput* (3.3) of the ADF on the 1set test.

© ISO/IEC 2021 – All rights reserved

3.2
duplex
duplex scanning
use of a scanning device with the scanning being done for both sides of a sheet

Note 1 to entry: An equivalent term is “double sided scanning”.

3.3
scEFTP
effective throughput
rate at which a device scans pages measured from the initiation of the job through the full ejection of the last page of the scanning sets or through the complete creation of the file on the shared network folder or PC after the transfer of the last page of the last *test set* (3.16)

EXAMPLE *scEFTP*$_{1setA}$ means scanning effective throughput of “1 set test” for “ADF productivity measurement”.

Note 1 to entry: “sc” denotes that the measurement is taken on the scanner.

Note 2 to entry: There are suffixes such as “$_{1setA}$”, “$_{30secF}$” or “$_{30secP}$”. Each suffix is used to classify tests such as “1 set test” or “1 set + 30 second test” of the objects of tests for “ADF productivity measurement” (using suffix A), “scan to network folder productivity measurement”(using suffix F) or “scan to pc file productivity measurement” (using suffix P) test respectively.

Note 3 to entry: *scEFTP* is expressed in images per minute (ipm); it can be affected by scan time, digital processing time, maintenance and the run time of the test.

Note 4 to entry: A different term (“EFTP; effective throughput” for digital copying machines) is defined in ISO/IEC 24735.

Note 5 to entry: As for *scEFTP*$_{30secF}$, measurement parameters involving the measurement of file transmission to a network folder are dependent on other factors like the computer and network configuration and represent relative values and not absolute values.

Note 6 to entry: As for *scEFTP*$_{30secP}$, measurement parameters involving the measurement of file transmission to a file are dependent on other factors like the computer, IO connection, IO speed and represent relative values and not absolute values.

3.4
scESAT
estimated saturated throughput
rate at which a device scans pages measured from full ejection of the last page of the first *test set* (3.16) from ADF through the full ejection of the last page of the last test set (using suffix A)

Note 1 to entry: “sc” denotes that the measurement is taken on the scanner.

Note 2 to entry: There are suffixes such as “$_{1setA}$”, “$_{30secF}$” or “$_{30secP}$”. Each suffix is used to classify tests such as “1 set test” or “1 set + 30 second test” of the objects of tests for “ADF productivity measurement” (using suffix A), “scan to network folder productivity measurement”(using suffix F) or “scan to pc file productivity measurement” (using suffix P) test respectively. There is no measurement for “scan to network folder productivity measurement” or “scan to pc file productivity measurement” of *scESAT*, *scESAT*$_{30secF}$ and *scESAT*$_{30secP}$ defined, therefore *scESAT*$_{1setA}$, *scESAT*$_{1setF}$, and *scESAT*$_{1setP}$ are not used as classifications.

Note 3 to entry: *scESAT* is expressed in images per minute (ipm).

3.5
scFPE
first page eject
number of seconds between the initiation of the job to full ejection of the first page of the first *test set* (3.16) from the ADF

© ISO/IEC 2021 – All rights reserved

3.6
scFSOT
first set out time
number of seconds between the initiation of the job to full ejection of the last page of the first *test set* (3.16) from the ADF

Note 1 to entry: There are suffixes such as "$_{1setA}$", "$_{30secF}$" or "$_{30secP}$". Each suffix is used to classify tests such as "1 set test" or "1 set + 30 second test" of the objects of tests for "ADF productivity measurement" (using suffix A), "scan to network folder productivity measurement"(using suffix F) or "scan to pc file productivity measurement" (using suffix P) test respectively .

3.7
full detailed report
presentation of information including machine setup, summary and full measured test results

Note 1 to entry: An example of the full detailed report is shown in Annex B.

3.8
full report
presentation of results including the *scFSOT* (3.6), *scESAT* (3.4), and *scEFTP* (3.3) values in the *performance test* (3.10) as well as the calculated averages for each value

3.9
network folder speed
rate at which a device scans and stores the scanned image file in the network folder to demonstrate the overall productivity of the device when scanning documents

EXAMPLE A suffix such as "$_{30secF}$" means a test of "1 set + 30 second" test for "scan to network folder productivity".

Note 1 to entry: Suffix "$_{F}$" means "scan to network folder productivity measurement".

3.10
performance test
test used to evaluate productivity by providing *scFSOT* (3.6), *scESAT* (3.4), and *scEFTP* (3.3) without using any special feature or mode, and includes both the *simplex scanning* (3.12) mode and the *duplex scanning* (3.2) mode if available

3.11
scLSOT
scLSOT$_{Nsets}$
scanning last set out time
number of seconds between the initiation of the job to full ejection of the last page of the last *test set* (3.16) from ADF

Note 1 to entry: There are suffixes such as "$_{1setA}$", "$_{30secF}$" or "$_{30secP}$". Each suffix is used to classify tests such as "1 set test" or "1 set + 30 second test" of the objects of tests for "ADF productivity measurement" (using suffix A), "scan to network folder productivity measurement"(using suffix F) or "scan to pc file productivity measurement" (using suffix P) test respectively.

3.12
simplex
simplex scanning
use of a scanning device when only a single side of a sheet is scanned

Note 1 to entry: An equivalent term is "single sided scanning".

3.13
summary report
presentation of results including the average overall *scEFTP* (3.3) in the *performance test* (3.10) for the scanning device default base line performance

© ISO/IEC 2021 – All rights reserved

3.14
test file
digital file used for creating *test targets* (3.17)

3.15
test run
operation of scanning all pages of targets from a *test file* (3.14), in a particular system configuration, with a particular set and page count

Note 1 to entry: Scan times are recorded for each test run.

3.16
test set
all of the pages of targets from a *test file* (3.14)

3.17
test target
hardcopy document used for testing per the test method, and created from *test file* (3.14)

Note 1 to entry: An equivalent term is “test chart”.

3.18
time measurement
number of seconds measured by a timing device (stopwatch or other device) or by reading time display on the PC clock

EXAMPLE "t_{sw1A}" is the time measured via stopwatch or other device for completion of the first set out and "t_{pc1F}" is the time measured via PC clock for completion of the first set file written to the network folder or PC file.

Note 1 to entry: Suffixes such as "$_{SW}$" and "$_{PC}$" are used to show which time measurement is done; by timing device (stopwatch or other device) or by reading time display on the PC clock.

4 Test parameters and conditions

4.1 Scanning device setup

Place the scanning device on a horizontal surface and set up the scanning device according to the manufacturer's recommendations.

The scanning device shall be fully enclosed in its normal exterior cover. The machine shall be acclimated in the test environment prior to conducting the test(s) at least 8 h. All images and scanning modes should be at their factory preset configuration for the scanning device. It is assumed that the settings listed in Table 1 are common to all scanning devices. These listed settings shall be set to the manufacturer's default or preset condition for the device. If a device has settings not listed in Table 1, they too shall be set to default settings. All settings shall be explicitly stated in either case of default or non-default settings. For scanning devices that have additional scan quality and digital image processing features, those features shall be set to match their normal default condition and included in the result reporting. Disabling manufacturer default installed features, routines or applications, is not allowed. As listed in Table 1 the preset values in the test shall be noted in the full detailed report (see Annex B).

If the scanning device is setup with internal or external options such as memory as default, then these options shall be noted on the full detailed report format in the configuration options as shown in Annex B.

EXAMPLE Examples of configurations options to be captured:

— 160GB HDD installed.

Additional tests may be conducted using other non-default settings for the scanning device. The results of such additional tests shall be documented as having parameters that differ from the factory defaults and shown in comparison to the default system parameter results.

© ISO/IEC 2021 – All rights reserved