INTERNATIONAL STANDARD

ISO/IEC 29341-26-12

First edition
2017-09

Information technology — UPnP Device Architecture —

Part 26-12: Telephony device control protocol — Level 2 — Messaging service

Technologies de l'information — Architecture de dispositif UPnP —

Partie 26-12: Protocole de contrôle de dispositif de téléphonie — Niveau 2 — Service de messagerie

Reference number
ISO/IEC 29341-26-12:2017(E)

© ISO/IEC 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

CONTENTS

1 Scope vi
2 Normative references 1
3 Terms, definitions, symbols and abbreviated terms 2
4 Notations and conventions 4
4.1 Text conventions 4
4.2 Data Types 4
4.3 Vendor-defined Extensions 5
5 Service Modeling Definitions 5
5.1 Service Type 5
5.2 *Messaging* Service Architecture 5
5.3 State Variables 6
5.3.1 State Variable Overview 6
5.3.2 *A_ARG_TYPE_MessagingCapabilities* 7
5.3.3 *NewMessages* 8
5.3.4 *SessionUpdates* 9
5.3.5 *A_ARG_TYPE_TelephonyServerIdentity* 10
5.3.6 *A_ARG_TYPE_MessageID* 10
5.3.7 *A_ARG_TYPE_MessageClass* 11
5.3.8 *A_ARG_TYPE_MessageFolder* 11
5.3.9 *A_ARG_TYPE_MessageStatus* 12
5.3.10 *A_ARG_TYPE_Message* 12
5.3.11 *A_ARG_TYPE_MessageList* 15
5.3.12 *A_ARG_TYPE_SessionID* 16
5.3.13 *A_ARG_TYPE_SessionClass* 16
5.3.14 *A_ARG_TYPE_RecipientsList* 17
5.3.15 *A_ARG_TYPE_SessionInfo* 18
5.3.16 *A_ARG_TYPE_SessionsList* 20
5.3.17 *A_ARG_TYPE_SupportedContentType* 21
5.3.18 *A_ARG_TYPE_Subject* 22
5.3.19 *A_ARG_TYPE_SessionStatus* 22
5.3.20 *A_ARG_TYPE_FileInfoList* 22
5.4 Eventing and Moderation 24
5.4.1 Eventing of *NewMessages* 24
5.4.2 Eventing of *SessionUpdates* 24
5.5 Actions 25
5.5.1 *GetTelephonyIdentity()* 26
5.5.2 *GetMessagingCapabilities()* 27
5.5.3 *GetNewMessages()* 28
5.5.4 *SearchMessages()* 29
5.5.5 *ReadMessage()* 30
5.5.6 *SendMessage()* 31
5.5.7 *DeleteMessage()* 33
5.5.8 *CreateSession()* 34

© ISO/IEC 2017 – All rights reserved

5.5.9 *ModifySession()* 35
5.5.10 *AcceptSession()* 36
5.5.11 *GetSessionUpdates()* 37
5.5.12 *GetSessions()* 38
5.5.13 *JoinSession()* 39
5.5.14 *LeaveSession()* 40
5.5.15 *CloseSession()* 41
5.5.16 *StartFileTransfer()* 42
5.5.17 *CancelFileTransfer()* 43
5.5.18 *GetFileTransferSession()* 44
5.5.19 Error Code Summary 45
5.6 Service Behavioral Model 46
5.6.1 State Diagrams 46
6 XML Service Description 47
Annex A (normative) XML complex type *peerType* 56
Annex B (normative) XML Schema 60
Annex C (informative) Theory of Operation 64
Annex D (informative) Bibliography 69

Figure 1 — Architecture of the *Messaging* Service 5
Figure 2 — Lifecycle of Messages 46
Figure 3 — Lifecycle of Sessions 47
Figure C.1 — Message handling 64
Figure C.2 — Session handling in the Session Mode Messaging 66
Figure C.3 — Incoming Session handling in the Session Mode Messaging 66
Figure C.4 — File Transfer Session handling 67
Figure C.5 — File Transfer Session handling 68

Table 1 — State Variables 6
Table 2 — Allowed values for *sessionEvent* and the corresponding values of the *sessionStatus* 9
Table 3 — allowedValueList for the *A_ARG_TYPE_MessageClass* state variable 11
Table 4 — allowedValueList for the *A_ARG_TYPE_MessageFolder* state variable 12
Table 5 — allowedValueList for the *A_ARG_TYPE_MessageStatus* state variable 12
Table 6 — allowedValueList for the *A_ARG_TYPE_SessionClass* state variable 16
Table 7 — allowedValueList for the *A_ARG_TYPE_SessionStatus* state variable 22
Table 8 — Event Moderation 24
Table 9 — Actions 25
Table 10 — Arguments for *GetTelephonyIdentity()* 26
Table 11 — Error Codes for *GetTelephonyIdentity()* 27
Table 12 — Arguments for *GetMessagingCapabilities()* 27
Table 13 — Error Codes for *GetMessagingCapabilities()* 28
Table 14 — Arguments for *GetNewMessages()* 28
Table 15 — Error Codes for *GetNewMessages* 29

 © ISO/IEC 2017 – All rights reserved

Table 16 — Arguments for *SearchMessages()* 29
Table 17 — Error Codes for *SearchMessages()* 30
Table 18 — Arguments for *ReadMessage()* 31
Table 19 — Error Codes for *ReadMessage()* 31
Table 20 — Arguments for *SendMessage()* 32
Table 21 — Error Codes for *SendMessage()* 33
Table 22 — Arguments for *DeleteMessage()* 33
Table 23 — Error Codes for *DeleteMessage()* 34
Table 24 — Arguments for *CreateSession()* 34
Table 25 — Error Codes for *CreateSession()* 35
Table 26 — Arguments for *ModifySession()* 35
Table 27 — Error Codes for *ModifySession()* 36
Table 28 — Arguments for *AcceptSession()* 36
Table 29 — Error Codes for *AcceptSession()* 37
Table 30 — Arguments for *GetSessionUpdates()* 37
Table 31 — Error Codes for *GetSessionUpdates()* 38
Table 32 — Arguments for *GetSessions()* 38
Table 33 — Error Codes for *GetSessions()* 39
Table 34 — Arguments for *JoinSession()* 39
Table 35 — Error Codes for *JoinSession()* 40
Table 36 — Arguments for *LeaveSession()* 40
Table 37 — Error Codes for *LeaveSession()* 41
Table 38 — Arguments for *CloseSession()* 41
Table 39 — Error Codes for *CloseSession()* 42
Table 40 — Arguments for *StartFileTransfer()* 42
Table 41 — Error Codes for *StartFileTransfer()* 43
Table 42 — Arguments for *CancelFileTransfer()* 43
Table 43 — Error Codes for *CancelFileTransfer()* 44
Table 44 — Arguments for *GetFileTransferSession()* 44
Table 45 — Error Codes for *GetFileTransferSession()* 45
Table 46 — Error Code Summary 45

© ISO/IEC 2017 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see http://www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of Standard, the meaning of the ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword – Supplementary information

ISO/IEC 29341-26-12 was prepared by UPnP Forum and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of ISO/IEC 29341 series, under the general title *Information technology — UPnP Device Architecture*, can be found on the ISO web site.

 © ISO/IEC 2017 – All rights reserved

Introduction

ISO and IEC draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights. The holders of -these patent rights have assured ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

© ISO/IEC 2017 – All rights reserved

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Huawei Technologies Co., Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Huawei Technologies Co., Ltd.
Administration Building, Bantian Longgang District
Shenzhen – China 518129

Qualcomm Incorporated has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Qualcomm Incorporated
5775 Morehouse Drive
San Diego, CA – USA 92121

Telecom Italia S.p.A.has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Telecom Italia S.p.A.
Via Reiss Romoli, 274
Turin - Italy 10148

Cisco Systems informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA – USA 95134

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

 © ISO/IEC 2017 – All rights reserved

Original UPnP Document

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation and later by UPnP Forum. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1:2008
UPnP Device Architecture Version 1.0	ISO/IEC 29341-1:2011
UPnP Device Architecture 1.1	ISO/IEC 29341-1-1:2011
UPnP Device Architecture 2.0	ISO/IEC 29341-1-2
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2008
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2011
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaRenderer:2 Device	ISO/IEC 29341-3-2:2011
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2008
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2011
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2008
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2011
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2008
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2011
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP ScheduledRecording:2	ISO/IEC 29341-4-14:2011
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2008
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2011
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16

© ISO/IEC 2017 – All rights reserved

UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2
UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11
UPnP ContentDirectory:3 Service	ISO/IEC 29341-14-12:2011
UPnP MediaServer:3 Device	ISO/IEC 29341-14-3:2011

© ISO/IEC 2017 – All rights reserved

UPnP ContentSync:1	ISO/IEC 29341-15-10:2011
UPnP Low Power Architecture:1	ISO/IEC 29341-16-1:2011
UPnP LowPowerProxy:1 Service	ISO/IEC 29341-16-10:2011
UPnP LowPowerDevice:1 Service	ISO/IEC 29341-16-11:2011
UPnP QoS Architecture:3	ISO/IEC 29341-17-1:2011
UPnP QosDevice:3 Service	ISO/IEC 29341-17-10:2011
UPnP QosManager:3 Service	ISO/IEC 29341-17-11:2011
UPnP QosPolicyHolder:3 Service	ISO/IEC 29341-17-12:2011
UPnP QosDevice:3 Addendum	ISO/IEC 29341-17-13:2011
UPnP RemoteAccessArchitecture:1	ISO/IEC 29341-18-1:2011
UPnP InboundConnectionConfig:1 Service	ISO/IEC 29341-18-10:2011
UPnP RADAConfig:1 Service	ISO/IEC 29341-18-11:2011
UPnP RADASync:1 Service	ISO/IEC 29341-18-12:2011
UPnP RATAConfig:1 Service	ISO/IEC 29341-18-13:2011
UPnP RAClient:1 Device	ISO/IEC 29341-18-2:2011
UPnP RAServer:1 Device	ISO/IEC 29341-18-3:2011
UPnP RADiscoveryAgent:1 Device	ISO/IEC 29341-18-4:2011
UPnP SolarProtectionBlind:1 Device	ISO/IEC 29341-19-1:2011
UPnP TwoWayMotionMotor:1 Service	ISO/IEC 29341-19-10:2011
UPnP AV Architecture:2	ISO/IEC 29341-20-1
UPnP AVTransport:3 Service	ISO/IEC 29341-20-10
UPnP ConnectionManager:3 Service	ISO/IEC 29341-20-11
UPnP ContentDirectory:4 Device	ISO/IEC 29341-20-12
UPnP RenderingControl:3 Service	ISO/IEC 29341-20-13
UPnP ScheduledRecording:2 Service	ISO/IEC 29341-20-14
UPnP MediaRenderer:3 Service	ISO/IEC 29341-20-2
UPnP MediaServer:4 Device	ISO/IEC 29341-20-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-20-4
UPnP InternetGatewayDevice:2 Device	ISO/IEC 29341-24-1
UPnP WANIPConnection:2 Service	ISO/IEC 29341-24-10
UPnP WANIPv6FirewallControl:1 Service	ISO/IEC 29341-24-11
UPnP WANConnectionDevice:2 Service	ISO/IEC 29341-24-2
UPnP WANDevice:2 Device	ISO/IEC 29341-24-3
UPnP Telephony Architecture:2	ISO/IEC 29341-26-1
UPnP CallManagement:2 Service	ISO/IEC 29341-26-10
UPnP MediaManagement:2 Service	ISO/IEC 29341-26-11
UPnP Messaging:2 Service	ISO/IEC 29341-26-12
UPnP PhoneManagement:2 Service	ISO/IEC 29341-26-13
UPnP AddressBook:1 Service	ISO/IEC 29341-26-14
UPnP Calendar:1 Service	ISO/IEC 29341-26-15
UPnP Presense:1 Service	ISO/IEC 29341-26-16
UPnP TelephonyClient:2 Device	ISO/IEC 29341-26-2
UPnP TelephonyServer:2 Device	ISO/IEC 29341-26-3
UPnP Friendly Info Update:1 Service	ISO/IEC 29341-27-1
UPnP MultiScreen MultiScreen Architecture:1	ISO/IEC 29341-28-1
UPnP MultiScreen Application Management:1 Service	ISO/IEC 29341-28-10

© ISO/IEC 2017 – All rights reserved

UPnP MultiScreen Screen:1 Device	ISO/IEC 29341-28-2
UPnP MultiScreen Application Management:2 Service	ISO/IEC 29341-29-10
UPnP MultiScreen Screen:2 Device	ISO/IEC 29341-29-2
UPnP IoT Management and Control Architecture Overview:1	ISO/IEC 29341-30-1
UPnP DataStore:1 Service	ISO/IEC 29341-30-10
UPnP IoT Management and Control Data Model:1 Service	ISO/IEC 29341-30-11
UPnP IoT Management and Control Transport Generic:1 Service	ISO/IEC 29341-30-12
UPnP IoT Management and Control:1 Device	ISO/IEC 29341-30-2
UPnP Energy Management:1 Service	ISO/IEC 29341-31-1

 © ISO/IEC 2017 – All rights reserved

1 Scope

This service definition is compliant with [1]. It defines a service type referred to herein as *Messaging* service.

The *Messaging* service is a UPnP service that allows control points to use the messaging features provided by a Telephony Server (TS) or a Telephony Client (TC).

It provides in the UPnP network the overall set of messaging capabilities of a phone (e.g., smartphone, IP phone, VoIP gateway, etc.), as the role of a TS. Additionally, or as an alternative, a device with the role of a TC can provide the *Messaging* service via UPnP Telephony.

This service provides the control points with the following functionalities:

- Page Mode Messaging (e.g., e-Mail, SMS, MMS, etc.): notification of incoming messages, reading messages, sending a message, deleting a message.
- Session Mode Messaging (e.g., Instant Messaging, SMS, etc.): notification of incoming messages, retrieving and sending the messages within a session, creating, modifying or closing a messaging session.
- File transfer session, to transfer the files in near real time.

This service does not provide the following functionalities:

- Connection to a remote server for sending or receiving the messages (e.g., WAN side);
- Rendering of message notifications and messages to the end user;
- Configuring the *Messaging* service with account for connecting to remote servers;

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[1] – UPnP Device Architecture, version 1.0, UPnP Forum, October 15, 2008. Available at: http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0-20081015.pdf. Latest version available at: http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf.

[2] – Data elements and interchange formats – Information interchange -- Representation of dates and times, International Standards Organization, December 21, 2000. Available at: ISO 8601:2000.

[3] – IETF RFC 2046, Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types, N. Freed, Innosoft, N. Borenstein, First Virtual, November 1996. Available at: http://www.ietf.org/rfc/rfc2046.txt.

[4] – IETF RFC 2396, Uniform Resource Identifiers (URI): Generic Syntax, T. Berners-Lee, MIT/LCS, R. Fielding, U.C. Irvine, L. Masinter, Xerox Corporation, August 1998. Available at: http://www.ietf.org/rfc/rfc2396.txt.

[5] – IETF RFC 3261SIP: Session Initiation Protocol, J. Rosenberg, dynamicsoft, H. Schulzrinne, Columbia U., G. Camarillo, Ericsson, A. Johnston, WorldCom, J. Peterson,

© ISO/IEC 2017 – All rights reserved

Neustar, R. Sparks, dynamicsoft, M. Handley, ICIR, E. Schooler, AT&T June 2002. Available at: http://www.ietf.org/rfc/rfc3261.txt.

[6] – IETF RFC 3339, Date and Time on the Internet: Timestamps, G. Klyne, Clearswift Corporation, C. Newman, Sun Microsystems, July 2002. Available at: http://www.ietf.org/rfc/rfc3339.txt.

[7] – IETF RFC 3966, The tel URI for Telephone Numbers, H. Schulzrinne, Columbia University, December 2004. Available at: http://www.ietf.org/rfc/rfc3966.txt.

[8] – Extensible Markup Language (XML) 1.0 (Third Edition), François Yergeau, Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, eds., W3C Recommendation, February 4, 2004. Available at: http://www.w3.org/TR/2004/REC-xml-20040204.

[9] – XML Schema Part 2: Data Types, Second Edition, Paul V. Biron, Ashok Malhotra, W3C Recommendation, 28 October 2004. Available at: http://www.w3.org/TR/2004/REC-xmlschema-2-20041028.

3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in [1] and the following apply.

3.1 Provisioning terms

3.1.1

conditionally allowed
CA
The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is allowed, otherwise it is not allowed.

3.1.2

conditionally required
CR
The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is required, otherwise it is not allowed.

3.1.3

not allowed
The definition or behavior is prohibited by this specification. Opposite of required.

3.2 Symbols

3.2.1

::
signifies a hierarchical parent-child (parent::child) relationship between the two objects separated by the double colon. This delimiter is used in multiple contexts, for example: Service::Action(), Action()::Argument, parentProperty::childProperty.

3.3 General terms

3.3.1

Message
an information unit (e.g., e-Mail, SMS, MMS, Instant Message, etc.) that is exchanged between two or more entities (e.g., UPnP TelCP and TS/TC).

 © ISO/IEC 2017 – All rights reserved

3.3.2

Messaging Session
a logical connection established between two or more recipients before starting to exchange Messages. The Messages are then orderly managed within the Messaging Session.

The Messaging Sessions are also referred to as “Sessions” in this specification.

3.3.3

Page Mode Messaging
a mode of sending and receiving messages from any recipients without establishing a session between the recipients.

The typical Messages exchanged under the Page Mode Messaging are e-Mail, SMS, and MMS.

3.3.4

Session Mode Messaging
the mode of sending and receiving Messages within a Messaging Session.

The typical Messages exchanged under the Session Mode Messaging are Instant Messages (IM) or chat. SMS, MMS, etc. can also be managed under the concept of Session Mode Messaging and can be used to logically group the Messages into an one conversation. It is also possible to have a Messaging Session with different Message classes.

3.3.5

Peer
a recipient for a Message or a participant in a Messaging Session.

3.4 Abbreviated terms

3.4.1

GUI
Graphical User Interface

3.4.2

ID
Identifier

3.4.3

IM
Instant Messaging

3.4.4

ISDN
Integrated Services Digital Network

3.4.5

MMS
Multimedia Messaging Service

3.4.6

PLMN
Public Land Mobile Network

© ISO/IEC 2017 – All rights reserved

3.4.7

PSTN
Public Switched Telephone Network

3.4.8

SMS
Short Message Service

3.4.9

TC
Telephony Client

3.4.10

TelCP
Telephony Control Point

3.4.11

TS
Telephony Server

3.4.12

VoIP
Voice over IP

3.4.13

WAN
Wide Area Network

4 Notations and conventions

4.1 Text conventions

- Strings that are to be taken literally are enclosed in “double quotes”.
- Words that are emphasized are printed in *italic*.
- Keywords that are defined by the UPnP Working Committee are printed using the *forum* character style.
- Keywords that are defined by [1] are printed using the **arch** character style.

4.2 Data Types

This specification uses data type definitions from two different sources. Data types from [1] are used to define state variable and action argument data types [1]. The XML Schema namespace is used to define property data types [9].

For Boolean data types from [1], it is strongly recommended to use the value “**0**” for false, and the value “**1**” for true. The values “**true**”, “**yes**”, “**false**”, or “**no**” may also be used but are not recommended. The values “**yes**” and “**no**” are deprecated and shall not be sent out by devices but shall be accepted on input.

For XML Schema defined Boolean data types, it is strongly recommended to use the value “*0*” for false, and the value “*1*” for true. The values “*true*”, “*yes*”, “*false*”, or “*no*” may also be used

 © ISO/IEC 2017 – All rights reserved