INTERNATIONAL STANDARD

**ISO/IEC 29341-26-15**

First edition
2017-09

# Information technology — UPnP Device Architecture —

## Part 26-15: Telephony device control protocol — Level 2 — Calendar service

*Technologies de l'information — Architecture de dispositif UPnP —*

*Partie 26-15: Protocole de contrôle de dispositif de téléphonie — Niveau 2 — Service de calendrier*

Reference number
ISO/IEC 29341-26-15:2017(E)

© ISO/IEC 2017



**COPYRIGHT PROTECTED DOCUMENT**

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

# CONTENTS


1 Scope ..... 1
2 Normative references ..... 1
3 Terms, definitions, symbols and abbreviated terms ..... 2
4 Notations and conventions ..... 3
4.1 Text conventions ..... 3
4.1.1 Data Types ..... 3
4.2 Vendor-defined Extensions ..... 4
5 Service Modeling Definitions ..... 4
5.1 Service Type ..... 4
5.2 *Calendar* Service Architecture ..... 4
5.3 State Variables ..... 5
5.3.1 State Variable Overview ..... 5
5.3.2 *CalendarItem* ..... 6
5.3.3 *TriggeredItem* ..... 6
5.3.4 *MemoInfo* ..... 7
5.3.5 *A_ARG_TYPE_TriggeredItems* ..... 8
5.3.6 *A_ARG_TYPE_CalItems* ..... 8
5.3.7 *A_ARG_TYPE_ItemIDs* ..... 9
5.3.8 *A_ARG_TYPE_Memo* ..... 10
5.3.9 *A_ARG_TYPE_MemoID* ..... 10
5.3.10 *A_ARG_TYPE_ItemDeliveryMethod* ..... 10
5.3.11 *A_ARG_TYPE_MemoInfoList* ..... 11
5.3.12 *A_ARG_TYPE_TelCPName* ..... 12
5.3.13 *A_ARG_TYPE_TelCPNameList* ..... 12
5.3.14 *A_ARG_TYPE_Expires* ..... 12
5.4 Eventing and Moderation ..... 12
5.4.1 Eventing of *CalendarItem* ..... 13
5.4.2 Eventing of *TriggeredItem* ..... 13
5.4.3 Eventing of *MemoInfo* ..... 13
5.5 Actions ..... 13
5.5.1 *AddCalendarItems()* ..... 14
5.5.2 *DeleteCalendarItems()* ..... 15
5.5.3 *UpdateCalendarItems()* ..... 15
5.5.4 *GetCalendarItems()* ..... 16
5.5.5 *GetTriggeredItems()* ..... 17
5.5.6 *PostMemo()* ..... 18
5.5.7 *RegisterItemDelivery()* ..... 19
5.5.8 *GetMemo()* ..... 20
5.5.9 *RegisterTelCPName()* ..... 21
5.5.10 *UnregisterTelCPName()* ..... 22
5.5.11 *GetTelCPNameList()* ..... 23
5.5.12 Error Code Summary ..... 24
5.6 Service Behavioral Model ..... 24


© ISO/IEC 2017 – All rights reserved 

6 XML Service Description....24
Annex A (normative) XML Schema....29
Annex B (informative) Theory of Operation....32
Annex C (informative) Bibliography....36

Figure 1 — *Calendar* Service Architecture....4
Figure B.1 — Memo handling....32
Figure B.2 — Logical flows for calendar service....34
Figure B.3 — Multiple TelCP handling for Alarm use case....35

Table 1 — State Variables....5
Table 2 — Event Moderation....12
Table 3 — Actions....13
Table 4 — Arguments for *AddCalendarItems()*....14
Table 5 — Error Codes for *AddCalendarItems()*....14
Table 6 — Arguments for *DeleteCalendarItems()*....15
Table 7 — Error Codes for *DeleteCalendarItems()*....15
Table 8 — Arguments for *UpdateCalendarItems()*....15
Table 9 — Error Codes for *UpdateCalendarItems()*....16
Table 10 — Arguments for *GetCalendarItems()*....16
Table 11 — Error Codes for *GetCalendarItems()*....17
Table 12 — Arguments for *GetTriggeredItems()*....17
Table 13 — Error Codes for *GetTriggeredItems()*....18
Table 14 — Arguments for *PostMemo()*....18
Table 15 — Error Codes for *PostMemo()*....19
Table 16 — Arguments for *RegisterItemDelivery()*....19
Table 17 — Error Codes for *RegisterItemDelivery()*....20
Table 18 — Arguments for *GetMemo()*....20
Table 19 — Error Codes for *GetMemo()*....21
Table 20 — Arguments for *RegisterTelCPName()*....21
Table 21 — Error Codes for *RegisterTelCPName()*....22
Table 22 — Arguments for *UnregisterTelCPName()*....22
Table 23 — Error Codes for *UnregisterTelCPName()*....23
Table 24 — Arguments for *GetTelCPNameList()*....23
Table 25 — Error Codes for *GetTelCPNameList()*....23
Table 26 — Error Code Summary....24

 © ISO/IEC 2017 – All rights reserved

# Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see http://www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of Standard, the meaning of the ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword – Supplementary information

ISO/IEC 29341-26-15 was prepared by UPnP Forum and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of ISO/IEC 29341 series, under the general title *Information technology — UPnP Device Architecture*, can be found on the ISO web site.

© ISO/IEC 2017 – All rights reserved

# Introduction

ISO and IEC draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights. The holders of -these patent rights have assured ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

 © ISO/IEC 2017 – All rights reserved

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Huawei Technologies Co., Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Huawei Technologies Co., Ltd.
Administration Building, Bantian Longgang District
Shenzhen – China 518129

Qualcomm Incorporated has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Qualcomm Incorporated
5775 Morehouse Drive
San Diego, CA – USA 92121

Telecom Italia S.p.A.has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Telecom Italia S.p.A.
Via Reiss Romoli, 274
Turin - Italy 10148

Cisco Systems informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA – USA 95134

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

© ISO/IEC 2017 – All rights reserved

### Original UPnP Document

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation and later by UPnP Forum. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

| UPnP Document Title | ISO/IEC 29341 Part |
|---|---|
| UPnP Device Architecture 1.0 | ISO/IEC 29341-1:2008 |
| UPnP Device Architecture Version 1.0 | ISO/IEC 29341-1:2011 |
| UPnP Device Architecture 1.1 | ISO/IEC 29341-1-1:2011 |
| UPnP Device Architecture 2.0 | ISO/IEC 29341-1-2 |
| UPnP Basic:1 Device | ISO/IEC 29341-2 |
| UPnP AV Architecture:1 | ISO/IEC 29341-3-1:2008 |
| UPnP AV Architecture:1 | ISO/IEC 29341-3-1:2011 |
| UPnP AVTransport:1 Service | ISO/IEC 29341-3-10 |
| UPnP ConnectionManager:1 Service | ISO/IEC 29341-3-11 |
| UPnP ContentDirectory:1 Service | ISO/IEC 29341-3-12 |
| UPnP RenderingControl:1 Service | ISO/IEC 29341-3-13 |
| UPnP MediaRenderer:1 Device | ISO/IEC 29341-3-2 |
| UPnP MediaRenderer:2 Device | ISO/IEC 29341-3-2:2011 |
| UPnP MediaServer:1 Device | ISO/IEC 29341-3-3 |
| UPnP AVTransport:2 Service | ISO/IEC 29341-4-10:2008 |
| UPnP AVTransport:2 Service | ISO/IEC 29341-4-10:2011 |
| UPnP ConnectionManager:2 Service | ISO/IEC 29341-4-11:2008 |
| UPnP ConnectionManager:2 Service | ISO/IEC 29341-4-11:2011 |
| UPnP ContentDirectory:2 Service | ISO/IEC 29341-4-12 |
| UPnP RenderingControl:2 Service | ISO/IEC 29341-4-13:2008 |
| UPnP RenderingControl:2 Service | ISO/IEC 29341-4-13:2011 |
| UPnP ScheduledRecording:1 | ISO/IEC 29341-4-14 |
| UPnP ScheduledRecording:2 | ISO/IEC 29341-4-14:2011 |
| UPnP MediaRenderer:2 Device | ISO/IEC 29341-4-2 |
| UPnP MediaServer:2 Device | ISO/IEC 29341-4-3 |
| UPnP AV Datastructure Template:1 | ISO/IEC 29341-4-4:2008 |
| UPnP AV Datastructure Template:1 | ISO/IEC 29341-4-4:2011 |
| UPnP DigitalSecurityCamera:1 Device | ISO/IEC 29341-5-1 |
| UPnP DigitalSecurityCameraMotionImage:1 Service | ISO/IEC 29341-5-10 |
| UPnP DigitalSecurityCameraSettings:1 Service | ISO/IEC 29341-5-11 |
| UPnP DigitalSecurityCameraStillImage:1 Service | ISO/IEC 29341-5-12 |
| UPnP HVAC_System:1 Device | ISO/IEC 29341-6-1 |
| UPnP ControlValve:1 Service | ISO/IEC 29341-6-10 |
| UPnP HVAC_FanOperatingMode:1 Service | ISO/IEC 29341-6-11 |
| UPnP FanSpeed:1 Service | ISO/IEC 29341-6-12 |
| UPnP HouseStatus:1 Service | ISO/IEC 29341-6-13 |
| UPnP HVAC_SetpointSchedule:1 Service | ISO/IEC 29341-6-14 |
| UPnP TemperatureSensor:1 Service | ISO/IEC 29341-6-15 |
| UPnP TemperatureSetpoint:1 Service | ISO/IEC 29341-6-16 |

 © ISO/IEC 2017 – All rights reserved

| | |
|---|---|
| UPnP HVAC_UserOperatingMode:1 Service | ISO/IEC 29341-6-17 |
| UPnP HVAC_ZoneThermostat:1 Device | ISO/IEC 29341-6-2 |
| UPnP BinaryLight:1 Device | ISO/IEC 29341-7-1 |
| UPnP Dimming:1 Service | ISO/IEC 29341-7-10 |
| UPnP SwitchPower:1 Service | ISO/IEC 29341-7-11 |
| UPnP DimmableLight:1 Device | ISO/IEC 29341-7-2 |
| UPnP InternetGatewayDevice:1 Device | ISO/IEC 29341-8-1 |
| UPnP LANHostConfigManagement:1 Service | ISO/IEC 29341-8-10 |
| UPnP Layer3Forwarding:1 Service | ISO/IEC 29341-8-11 |
| UPnP LinkAuthentication:1 Service | ISO/IEC 29341-8-12 |
| UPnP RadiusClient:1 Service | ISO/IEC 29341-8-13 |
| UPnP WANCableLinkConfig:1 Service | ISO/IEC 29341-8-14 |
| UPnP WANCommonInterfaceConfig:1 Service | ISO/IEC 29341-8-15 |
| UPnP WANDSLLinkConfig:1 Service | ISO/IEC 29341-8-16 |
| UPnP WANEthernetLinkConfig:1 Service | ISO/IEC 29341-8-17 |
| UPnP WANIPConnection:1 Service | ISO/IEC 29341-8-18 |
| UPnP WANPOTSLinkConfig:1 Service | ISO/IEC 29341-8-19 |
| UPnP LANDevice:1 Device | ISO/IEC 29341-8-2 |
| UPnP WANPPPConnection:1 Service | ISO/IEC 29341-8-20 |
| UPnP WLANConfiguration:1 Service | ISO/IEC 29341-8-21 |
| UPnP WANDevice:1 Device | ISO/IEC 29341-8-3 |
| UPnP WANConnectionDevice:1 Device | ISO/IEC 29341-8-4 |
| UPnP WLANAccessPointDevice:1 Device | ISO/IEC 29341-8-5 |
| UPnP Printer:1 Device | ISO/IEC 29341-9-1 |
| UPnP ExternalActivity:1 Service | ISO/IEC 29341-9-10 |
| UPnP Feeder:1.0 Service | ISO/IEC 29341-9-11 |
| UPnP PrintBasic:1 Service | ISO/IEC 29341-9-12 |
| UPnP Scan:1 Service | ISO/IEC 29341-9-13 |
| UPnP Scanner:1.0 Device | ISO/IEC 29341-9-2 |
| UPnP QoS Architecture:1.0 | ISO/IEC 29341-10-1 |
| UPnP QosDevice:1 Service | ISO/IEC 29341-10-10 |
| UPnP QosManager:1 Service | ISO/IEC 29341-10-11 |
| UPnP QosPolicyHolder:1 Service | ISO/IEC 29341-10-12 |
| UPnP QoS Architecture:2 | ISO/IEC 29341-11-1 |
| UPnP QosDevice:2 Service | ISO/IEC 29341-11-10 |
| UPnP QosManager:2 Service | ISO/IEC 29341-11-11 |
| UPnP QosPolicyHolder:2 Service | ISO/IEC 29341-11-12 |
| UPnP QOS v2 Schema Files | ISO/IEC 29341-11-2 |
| UPnP RemoteUIClientDevice:1 Device | ISO/IEC 29341-12-1 |
| UPnP RemoteUIClient:1 Service | ISO/IEC 29341-12-10 |
| UPnP RemoteUIServer:1 Service | ISO/IEC 29341-12-11 |
| UPnP RemoteUIServerDevice:1 Device | ISO/IEC 29341-12-2 |
| UPnP DeviceSecurity:1 Service | ISO/IEC 29341-13-10 |
| UPnP SecurityConsole:1 Service | ISO/IEC 29341-13-11 |
| UPnP ContentDirectory:3 Service | ISO/IEC 29341-14-12:2011 |
| UPnP MediaServer:3 Device | ISO/IEC 29341-14-3:2011 |

© ISO/IEC 2017 – All rights reserved

| | |
|---|---|
| UPnP ContentSync:1 | ISO/IEC 29341-15-10:2011 |
| UPnP Low Power Architecture:1 | ISO/IEC 29341-16-1:2011 |
| UPnP LowPowerProxy:1 Service | ISO/IEC 29341-16-10:2011 |
| UPnP LowPowerDevice:1 Service | ISO/IEC 29341-16-11:2011 |
| UPnP QoS Architecture:3 | ISO/IEC 29341-17-1:2011 |
| UPnP QosDevice:3 Service | ISO/IEC 29341-17-10:2011 |
| UPnP QosManager:3 Service | ISO/IEC 29341-17-11:2011 |
| UPnP QosPolicyHolder:3 Service | ISO/IEC 29341-17-12:2011 |
| UPnP QosDevice:3 Addendum | ISO/IEC 29341-17-13:2011 |
| UPnP RemoteAccessArchitecture:1 | ISO/IEC 29341-18-1:2011 |
| UPnP InboundConnectionConfig:1 Service | ISO/IEC 29341-18-10:2011 |
| UPnP RADAConfig:1 Service | ISO/IEC 29341-18-11:2011 |
| UPnP RADASync:1 Service | ISO/IEC 29341-18-12:2011 |
| UPnP RATAConfig:1 Service | ISO/IEC 29341-18-13:2011 |
| UPnP RAClient:1 Device | ISO/IEC 29341-18-2:2011 |
| UPnP RAServer:1 Device | ISO/IEC 29341-18-3:2011 |
| UPnP RADiscoveryAgent:1 Device | ISO/IEC 29341-18-4:2011 |
| UPnP SolarProtectionBlind:1 Device | ISO/IEC 29341-19-1:2011 |
| UPnP TwoWayMotionMotor:1 Service | ISO/IEC 29341-19-10:2011 |
| UPnP AV Architecture:2 | ISO/IEC 29341-20-1 |
| UPnP AVTransport:3 Service | ISO/IEC 29341-20-10 |
| UPnP ConnectionManager:3 Service | ISO/IEC 29341-20-11 |
| UPnP ContentDirectory:4 Device | ISO/IEC 29341-20-12 |
| UPnP RenderingControl:3 Service | ISO/IEC 29341-20-13 |
| UPnP ScheduledRecording:2 Service | ISO/IEC 29341-20-14 |
| UPnP MediaRenderer:3 Service | ISO/IEC 29341-20-2 |
| UPnP MediaServer:4 Device | ISO/IEC 29341-20-3 |
| UPnP AV Datastructure Template:1 | ISO/IEC 29341-20-4 |
| UPnP InternetGatewayDevice:2 Device | ISO/IEC 29341-24-1 |
| UPnP WANIPConnection:2 Service | ISO/IEC 29341-24-10 |
| UPnP WANIPv6FirewallControl:1 Service | ISO/IEC 29341-24-11 |
| UPnP WANConnectionDevice:2 Service | ISO/IEC 29341-24-2 |
| UPnP WANDevice:2 Device | ISO/IEC 29341-24-3 |
| UPnP Telephony Architecture:2 | ISO/IEC 29341-26-1 |
| UPnP CallManagement:2 Service | ISO/IEC 29341-26-10 |
| UPnP MediaManagement:2 Service | ISO/IEC 29341-26-11 |
| UPnP Messaging:2 Service | ISO/IEC 29341-26-12 |
| UPnP PhoneManagement:2 Service | ISO/IEC 29341-26-13 |
| UPnP AddressBook:1 Service | ISO/IEC 29341-26-14 |
| UPnP Calendar:1 Service | ISO/IEC 29341-26-15 |
| UPnP Presense:1 Service | ISO/IEC 29341-26-16 |
| UPnP TelephonyClient:2 Device | ISO/IEC 29341-26-2 |
| UPnP TelephonyServer:2 Device | ISO/IEC 29341-26-3 |
| UPnP Friendly Info Update:1 Service | ISO/IEC 29341-27-1 |
| UPnP MultiScreen MultiScreen Architecture:1 | ISO/IEC 29341-28-1 |
| UPnP MultiScreen Application Management:1 Service | ISO/IEC 29341-28-10 |


© ISO/IEC 2017 – All rights reserved

| | |
|---|---|
| UPnP MultiScreen Screen:1 Device | ISO/IEC 29341-28-2 |
| UPnP MultiScreen Application Management:2 Service | ISO/IEC 29341-29-10 |
| UPnP MultiScreen Screen:2 Device | ISO/IEC 29341-29-2 |
| UPnP IoT Management and Control Architecture Overview:1 | ISO/IEC 29341-30-1 |
| UPnP DataStore:1 Service | ISO/IEC 29341-30-10 |
| UPnP IoT Management and Control Data Model:1 Service | ISO/IEC 29341-30-11 |
| UPnP IoT Management and Control Transport Generic:1 Service | ISO/IEC 29341-30-12 |
| UPnP IoT Management and Control:1 Device | ISO/IEC 29341-30-2 |
| UPnP Energy Management:1 Service | ISO/IEC 29341-31-1 |

© ISO/IEC 2017 – All rights reserved

## 1 Scope

This service definition is compliant with [1]. It defines a service type referred to herein as *Calendar*.

This service provides the following functionalities:

- Manage the family calendar events and share calendar events between the family members.
- Calendar events includes Reminders/Alarms/Free-BusyTime.
- Synchronizing the local calendar events with family calendar.
- Registrating for receiving the events notification on WAN side using any kinds of messaging service mechanism.
- Memo handling : Posting simple memos, retrieveing memos.
- Registrating for receiving the memo notifications on the WAN side using any kind of messaging service.

This service does not provide the following functionalities:

- Interaction between Telephony Server and network side calendar service

## 2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[1] – UPnP Device Architecture, version 1.0, UPnP Forum, October 15, 2008. Available at: http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0-20081015.pdf. Latest version available at: http://www.upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf.

[2] – Data elements and interchange formats – Information interchange -- Representation of dates and times, International Standards Organization, December 21, 2000. Available at: ISO 8601:2000.

[3] – IETF RFC 2119, Key words for use in RFCs to Indicate Requirement Levels, S. Bradner, 1997. Available at: http://www.faqs.org/rfcs/rfc2119.html.

[4] – IETF RFC 2396, Uniform Resource Identifiers (URI): Generic Syntax, T. Berners-Lee, MIT/LCS, R. Fielding, U.C. Irvine, L. Masinter, Xerox Corporation, August 1998. Available at: http://www.ietf.org/rfc/rfc2396.txt.

[5] – IETF RFC 3339, Date and Time on the Internet: Timestamps, G. Klyne, Clearswift Corporation, C. Newman, Sun Microsystems, July 2002. Available at: http://www.ietf.org/rfc/rfc3339.txt.

[6] – IETF RFC 3966, The tel URI for Telephone Numbers, H. Schulzrinne, Columbia University, December 2004. Available at: http://www.ietf.org/rfc/rfc3966.txt.

© ISO/IEC 2017 – All rights reserved 

[7] – IETF RFC 5545, Internet Calendaring and Scheduling Core Object Specification (iCalendar), B. Desruisseaux, Sept 2009. Available at: http://tools.ietf.org/html/rfc5545.

[8] – Extensible Markup Language (XML) 1.0 (Third Edition), François Yergeau, Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, eds., W3C Recommendation, February 4, 2004. Available at: http://www.w3.org/TR/2004/REC-xml-20040204.

[9] – XML Schema Part 2: Data Types, Second Edition, Paul V. Biron, Ashok Malhotra, W3C Recommendation, 28 October 2004. Available at: http://www.w3.org/TR/2004/REC-xmlschema-2-20041028.

[10] – *PhoneManagement:2*, UPnP Forum, December 10, 2012. Available at: http://upnp.org/specs/phone/UPnP-phone-PhoneManagement-v2-Service-20121210.pdf. Latest version available at: http://upnp.org/specs/phone/UPnP-phone-PhoneManagement-Service.pdf.

## 3 Terms, definitions, symbols and abbreviated terms

For the purposes of this document, the terms and definitions given in [1] and the following apply.

### 3.1 Provisioning terms

#### 3.1.1

**conditionally allowed**
**CA**
The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is allowed, otherwise it is not allowed.

#### 3.1.2

**conditionally required**
**CR**
The definition or behavior depends on a condition. If the specified condition is met, then the definition or behavior is required, otherwise it is not allowed.

#### 3.1.3

**not allowed**
The definition or behavior is prohibited by this specification. Opposite of required.

### 3.2 Symbols

#### 3.2.1

**::**
signifies a hierarchical parent-child (parent::child) relationship between the two objects separated by the double colon. This delimiter is used in multiple contexts, for example: Service::Action(), Action()::Argument, parentProperty::childProperty.

### 3.3 Abbreviated terms

#### 3.3.1

**GUI**
Graphical User Interface

 © ISO/IEC 2017 – All rights reserved

**3.3.2**

**ID**
Identifier

**3.3.3**

**TC**
Telephony Client

**3.3.4**

**TelCP**
Telephony Control Point

**3.3.5**

**TS**
Telephony Server

**3.3.6**

**VoIP**
Voice over IP

**3.3.7**

**WAN**
Wide Area Network

# 4 Notations and conventions

## 4.1 Text conventions

- Strings that are to be taken literally are enclosed in “double quotes”.
- Words that are emphasized are printed in *italic*.
- Keywords that are defined by the UPnP Working Committee are printed using the *forum* character style.
- Keywords that are defined by [1] are printed using the **arch** character style.

### 4.1.1 Data Types

This specification uses data type definitions from two different sources. Data types from [1] are used to define state variable and action argument data types [1]. The XML Schema namespace is used to define property data types [9].

For Boolean data types from [1], it is strongly recommended to use the value “**0**” for false, and the value “**1**” for true. The values “**true**”, “**yes**”, “**false**”, or “**no**” may also be used but are not recommended. The values “**yes**” and “**no**” are deprecated and shall not be sent out by devices but shall be accepted on input.

For XML Schema defined Boolean data types, it is strongly recommended to use the value “*0*” for false, and the value “*1*” for true. The values “*true*”, “*yes*”, “*false*”, or “*no*” may also be used but are not recommended. The values “*yes*” and “*no*” are deprecated and shall not be sent out by devices but shall be accepted on input.

© ISO/IEC 2017 – All rights reserved