INTERNATIONAL STANDARD

ISO/IEC 29341-30-1

First edition
2017-06

Information technology — UPnP Device Architecture —

Part 30-1: IoT management and control device control protocol — IoT management and control architecture overview

Technologies de l'information — Architecture de dispositif UPnP —

Partie 30-1: Protocole de contrôle de dispositif de gestion et de contrôle de l'Internet des objets — Aperçu général de l'architecture de gestion et de contrôle de l'Internet des objets



Reference number
ISO/IEC 29341-30-1:2017(E)

© ISO/IEC 2017



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

CONTENTS

1 Scope 1
1.1 Introduction 1
1.2 Goals 1
1.3 Non-Goals 1
1.4 IoTManagementAndControl and DataStore Specification Map 2
2 Normative references 3
3 Terms, definitions and abbreviations 4
3.1 IoTManagementAndControl terms and definitions 4
3.2 DataStore terms and definitions 5
3.3 Configuration Management terms and definitions 6
3.4 Device Protection terms and definitions 7
4 Architectural Overview 8
4.1 UPnP IoTManagementAndControl Device 8
4.1.1 Sensor Data Model 9
4.1.2 Sensor Collections 9
4.1.3 Sensor Control 9
4.1.4 Sensors DataItem(s) 9
4.1.5 Sensor DataItem Description Document 10
4.1.6 Sensors DataRecord(s) 10
4.1.7 Sensors Data Transport 10
4.1.8 Sensors Groups 10
4.1.9 Sensor Protection Model 10
4.2 UPnP DataStore Service 12
4.2.1 DataTable(s) 13
4.2.2 DataTable DataRecord(s) 13
4.2.3 DataTable Dictionary 13
4.2.4 DataItem types 13
4.2.5 DataTable Operations 14
4.2.6 DataStore Protection Model 14
4.3 DataItem Semantics 15
4.3.1 DataItem Name 15
4.3.2 DataItem Prefix 16
4.3.3 DataItem Type 16
4.3.4 DataItem Encoding 17
4.3.5 DataItem Description Document 17
4.4 DataItem Description XML Document 18
4.4.1 Introduction 18
4.4.2 DataItem Categories 18
4.4.3 DataItem Description Document Elements 18
4.5 DataItem Description Units of Measurement 26
4.5.1 SI Prefixes 26
4.5.2 SI Base Units 26
4.5.3 SI Derived Units 26
4.5.4 Non-SI in common use 27
4.5.5 British units in common use 27

© ISO/IEC 2017 – All rights reserved

4.5.6 Coordinates 27
4.5.7 Duration 28
4.5.8 Encoding 28
4.6 Theory of Operation (informative) 29
4.6.1 IoTManagementAndControl Device 29
4.6.2 Configuring the DataStore service 36
Annex A Sample Device Illustration (informative) 44

Figure 1 — IoTManagementAndControl Architectural Components 8
Figure 2 — IoTManagementAndControl Device services 9
Figure 3 — DataStore service 12
Figure 4 — DataStore service - DataTable Components 13
Figure A.1 — Sample Device 44

Table 1 — Sensor Permissions 10
Table 2 — `access=` attribute allowed values 20
Table 3 — `treatment=` attribute allowed values (measurement) 20
Table 4 — `accumulation=` attribute allowed values (measurement) 21
Table 6 — `relationtype=` attribute (alarm) 22
Table 7 — `limittype=` attribute (limit) 23
Table 8 — `relationtype=` attribute allowed values (limit) 23
Table 9 — `relationtype=` attribute allowed values (setting) 24
Table 10 — `units=` attribute allowed values (interval) 24
Table 11 — `relationtype=` attribute allowed values (interval) 25

 © ISO/IEC 2017 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of Standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT), see the following URL: www.iso.org/iso/foreword.html.

ISO/IEC 29341-30-1 was prepared by UPnP Forum and adopted, under the PAS procedure, by joint technical committee ISO/IEC JTC 1, *Information technology*, in parallel with its approval by national bodies of ISO and IEC.

The list of all currently available parts of ISO/IEC 29341 series, under the general title *Information technology — UPnP Device Architecture*, can be found on the ISO web site.

© ISO/IEC 2017 – All rights reserved

Introduction

ISO and IEC draw attention to the fact that it is claimed that compliance with this document may involve the use of patents as indicated below.

ISO and IEC take no position concerning the evidence, validity and scope of these patent rights. The holders of -these patent rights have assured ISO and IEC that they are willing to negotiate licenses under reasonable and non-discriminatory terms and conditions with applicants throughout the world. In this respect, the statements of the holders of these patent rights are registered with ISO and IEC.

Intel Corporation has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Intel Corporation
Standards Licensing Department
5200 NE Elam Young Parkway
MS: JFS-98
USA – Hillsboro, Oregon 97124

Microsoft Corporation has informed IEC and ISO that it has patent applications or granted patents as listed below:

6101499 / US; 6687755 / US; 6910068 / US; 7130895 / US; 6725281 / US; 7089307 / US; 7069312 / US; 10/783 524 /US

Information may be obtained from:

Microsoft Corporation
One Microsoft Way
USA – Redmond WA 98052

Philips International B.V. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Philips International B.V. – IP&S
High Tech campus, building 44 3A21
NL – 5656 Eindhoven

NXP B.V. (NL) has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

NXP B.V. (NL)
High Tech campus 60
NL – 5656 AG Eindhoven

Matsushita Electric Industrial Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Matsushita Electric Industrial Co. Ltd.
1-3-7 Shiromi, Chuoh-ku
JP – Osaka 540-6139

 © ISO/IEC 2017 – All rights reserved

Hewlett Packard Company has informed IEC and ISO that it has patent applications or granted patents as listed below:

5 956 487 / US; 6 170 007 / US; 6 139 177 / US; 6 529 936 / US; 6 470 339 / US; 6 571 388 / US; 6 205 466 / US

Information may be obtained from:

Hewlett Packard Company
1501 Page Mill Road
USA – Palo Alto, CA 94304

Samsung Electronics Co. Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Digital Media Business, Samsung Electronics Co. Ltd.
416 Maetan-3 Dong, Yeongtang-Gu,
KR – Suwon City 443-742

Huawei Technologies Co., Ltd. has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Huawei Technologies Co., Ltd.
Administration Building, Bantian Longgang District
Shenzhen – China 518129

Qualcomm Incorporated has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Qualcomm Incorporated
5775 Morehouse Drive
San Diego, CA – USA 92121

Telecom Italia S.p.A.has informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Telecom Italia S.p.A.
Via Reiss Romoli, 274
Turin - Italy 10148

Cisco Systems informed IEC and ISO that it has patent applications or granted patents.

Information may be obtained from:

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA – USA 95134

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights other than those identified above. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

© ISO/IEC 2017 – All rights reserved

Original UPnP Document

Reference may be made in this document to original UPnP documents. These references are retained in order to maintain consistency between the specifications as published by ISO/IEC and by UPnP Implementers Corporation and later by UPnP Forum. The following table indicates the original UPnP document titles and the corresponding part of ISO/IEC 29341:

UPnP Document Title	ISO/IEC 29341 Part
UPnP Device Architecture 1.0	ISO/IEC 29341-1:2008
UPnP Device Architecture Version 1.0	ISO/IEC 29341-1:2011
UPnP Device Architecture 1.1	ISO/IEC 29341-1-1:2011
UPnP Device Architecture 2.0	ISO/IEC 29341-1-2
UPnP Basic:1 Device	ISO/IEC 29341-2
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2008
UPnP AV Architecture:1	ISO/IEC 29341-3-1:2011
UPnP AVTransport:1 Service	ISO/IEC 29341-3-10
UPnP ConnectionManager:1 Service	ISO/IEC 29341-3-11
UPnP ContentDirectory:1 Service	ISO/IEC 29341-3-12
UPnP RenderingControl:1 Service	ISO/IEC 29341-3-13
UPnP MediaRenderer:1 Device	ISO/IEC 29341-3-2
UPnP MediaRenderer:2 Device	ISO/IEC 29341-3-2:2011
UPnP MediaServer:1 Device	ISO/IEC 29341-3-3
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2008
UPnP AVTransport:2 Service	ISO/IEC 29341-4-10:2011
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2008
UPnP ConnectionManager:2 Service	ISO/IEC 29341-4-11:2011
UPnP ContentDirectory:2 Service	ISO/IEC 29341-4-12
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2008
UPnP RenderingControl:2 Service	ISO/IEC 29341-4-13:2011
UPnP ScheduledRecording:1	ISO/IEC 29341-4-14
UPnP ScheduledRecording:2	ISO/IEC 29341-4-14:2011
UPnP MediaRenderer:2 Device	ISO/IEC 29341-4-2
UPnP MediaServer:2 Device	ISO/IEC 29341-4-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2008
UPnP AV Datastructure Template:1	ISO/IEC 29341-4-4:2011
UPnP DigitalSecurityCamera:1 Device	ISO/IEC 29341-5-1
UPnP DigitalSecurityCameraMotionImage:1 Service	ISO/IEC 29341-5-10
UPnP DigitalSecurityCameraSettings:1 Service	ISO/IEC 29341-5-11
UPnP DigitalSecurityCameraStillImage:1 Service	ISO/IEC 29341-5-12
UPnP HVAC_System:1 Device	ISO/IEC 29341-6-1
UPnP ControlValve:1 Service	ISO/IEC 29341-6-10
UPnP HVAC_FanOperatingMode:1 Service	ISO/IEC 29341-6-11
UPnP FanSpeed:1 Service	ISO/IEC 29341-6-12
UPnP HouseStatus:1 Service	ISO/IEC 29341-6-13
UPnP HVAC_SetpointSchedule:1 Service	ISO/IEC 29341-6-14
UPnP TemperatureSensor:1 Service	ISO/IEC 29341-6-15
UPnP TemperatureSetpoint:1 Service	ISO/IEC 29341-6-16
UPnP HVAC_UserOperatingMode:1 Service	ISO/IEC 29341-6-17
UPnP HVAC_ZoneThermostat:1 Device	ISO/IEC 29341-6-2

 © ISO/IEC 2017 – All rights reserved

UPnP BinaryLight:1 Device	ISO/IEC 29341-7-1
UPnP Dimming:1 Service	ISO/IEC 29341-7-10
UPnP SwitchPower:1 Service	ISO/IEC 29341-7-11
UPnP DimmableLight:1 Device	ISO/IEC 29341-7-2
UPnP InternetGatewayDevice:1 Device	ISO/IEC 29341-8-1
UPnP LANHostConfigManagement:1 Service	ISO/IEC 29341-8-10
UPnP Layer3Forwarding:1 Service	ISO/IEC 29341-8-11
UPnP LinkAuthentication:1 Service	ISO/IEC 29341-8-12
UPnP RadiusClient:1 Service	ISO/IEC 29341-8-13
UPnP WANCableLinkConfig:1 Service	ISO/IEC 29341-8-14
UPnP WANCommonInterfaceConfig:1 Service	ISO/IEC 29341-8-15
UPnP WANDSLLinkConfig:1 Service	ISO/IEC 29341-8-16
UPnP WANEthernetLinkConfig:1 Service	ISO/IEC 29341-8-17
UPnP WANIPConnection:1 Service	ISO/IEC 29341-8-18
UPnP WANPOTSLinkConfig:1 Service	ISO/IEC 29341-8-19
UPnP LANDevice:1 Device	ISO/IEC 29341-8-2
UPnP WANPPPConnection:1 Service	ISO/IEC 29341-8-20
UPnP WLANConfiguration:1 Service	ISO/IEC 29341-8-21
UPnP WANDevice:1 Device	ISO/IEC 29341-8-3
UPnP WANConnectionDevice:1 Device	ISO/IEC 29341-8-4
UPnP WLANAccessPointDevice:1 Device	ISO/IEC 29341-8-5
UPnP Printer:1 Device	ISO/IEC 29341-9-1
UPnP ExternalActivity:1 Service	ISO/IEC 29341-9-10
UPnP Feeder:1.0 Service	ISO/IEC 29341-9-11
UPnP PrintBasic:1 Service	ISO/IEC 29341-9-12
UPnP Scan:1 Service	ISO/IEC 29341-9-13
UPnP Scanner:1.0 Device	ISO/IEC 29341-9-2
UPnP QoS Architecture:1.0	ISO/IEC 29341-10-1
UPnP QosDevice:1 Service	ISO/IEC 29341-10-10
UPnP QosManager:1 Service	ISO/IEC 29341-10-11
UPnP QosPolicyHolder:1 Service	ISO/IEC 29341-10-12
UPnP QoS Architecture:2	ISO/IEC 29341-11-1
UPnP QosDevice:2 Service	ISO/IEC 29341-11-10
UPnP QosManager:2 Service	ISO/IEC 29341-11-11
UPnP QosPolicyHolder:2 Service	ISO/IEC 29341-11-12
UPnP QOS v2 Schema Files	ISO/IEC 29341-11-2
UPnP RemoteUIClientDevice:1 Device	ISO/IEC 29341-12-1
UPnP RemoteUIClient:1 Service	ISO/IEC 29341-12-10
UPnP RemoteUIServer:1 Service	ISO/IEC 29341-12-11
UPnP RemoteUIServerDevice:1 Device	ISO/IEC 29341-12-2
UPnP DeviceSecurity:1 Service	ISO/IEC 29341-13-10
UPnP SecurityConsole:1 Service	ISO/IEC 29341-13-11
UPnP ContentDirectory:3 Service	ISO/IEC 29341-14-12:2011
UPnP MediaServer:3 Device	ISO/IEC 29341-14-3:2011
UPnP ContentSync:1	ISO/IEC 29341-15-10:2011
UPnP Low Power Architecture:1	ISO/IEC 29341-16-1:2011
UPnP LowPowerProxy:1 Service	ISO/IEC 29341-16-10:2011

© ISO/IEC 2017 – All rights reserved

UPnP LowPowerDevice:1 Service	ISO/IEC 29341-16-11:2011
UPnP QoS Architecture:3	ISO/IEC 29341-17-1:2011
UPnP QosDevice:3 Service	ISO/IEC 29341-17-10:2011
UPnP QosManager:3 Service	ISO/IEC 29341-17-11:2011
UPnP QosPolicyHolder:3 Service	ISO/IEC 29341-17-12:2011
UPnP QosDevice:3 Addendum	ISO/IEC 29341-17-13:2011
UPnP RemoteAccessArchitecture:1	ISO/IEC 29341-18-1:2011
UPnP InboundConnectionConfig:1 Service	ISO/IEC 29341-18-10:2011
UPnP RADAConfig:1 Service	ISO/IEC 29341-18-11:2011
UPnP RADASync:1 Service	ISO/IEC 29341-18-12:2011
UPnP RATAConfig:1 Service	ISO/IEC 29341-18-13:2011
UPnP RAClient:1 Device	ISO/IEC 29341-18-2:2011
UPnP RAServer:1 Device	ISO/IEC 29341-18-3:2011
UPnP RADiscoveryAgent:1 Device	ISO/IEC 29341-18-4:2011
UPnP SolarProtectionBlind:1 Device	ISO/IEC 29341-19-1:2011
UPnP TwoWayMotionMotor:1 Service	ISO/IEC 29341-19-10:2011
UPnP AV Architecture:2	ISO/IEC 29341-20-1
UPnP AVTransport:3 Service	ISO/IEC 29341-20-10
UPnP ConnectionManager:3 Service	ISO/IEC 29341-20-11
UPnP ContentDirectory:4 Device	ISO/IEC 29341-20-12
UPnP RenderingControl:3 Service	ISO/IEC 29341-20-13
UPnP ScheduledRecording:2 Service	ISO/IEC 29341-20-14
UPnP MediaRenderer:3 Service	ISO/IEC 29341-20-2
UPnP MediaServer:4 Device	ISO/IEC 29341-20-3
UPnP AV Datastructure Template:1	ISO/IEC 29341-20-4
UPnP InternetGatewayDevice:2 Device	ISO/IEC 29341-24-1
UPnP WANIPConnection:2 Service	ISO/IEC 29341-24-10
UPnP WANIPv6FirewallControl:1 Service	ISO/IEC 29341-24-11
UPnP WANConnectionDevice:2 Service	ISO/IEC 29341-24-2
UPnP WANDevice:2 Device	ISO/IEC 29341-24-3
UPnP Telephony Architecture:2	ISO/IEC 29341-26-1
UPnP CallManagement:2 Service	ISO/IEC 29341-26-10
UPnP MediaManagement:2 Service	ISO/IEC 29341-26-11
UPnP Messaging:2 Service	ISO/IEC 29341-26-12
UPnP PhoneManagement:2 Service	ISO/IEC 29341-26-13
UPnP AddressBook:1 Service	ISO/IEC 29341-26-14
UPnP Calendar:1 Service	ISO/IEC 29341-26-15
UPnP Presense:1 Service	ISO/IEC 29341-26-16
UPnP TelephonyClient:2 Device	ISO/IEC 29341-26-2
UPnP TelephonyServer:2 Device	ISO/IEC 29341-26-3
UPnP Friendly Info Update:1 Service	ISO/IEC 29341-27-1
UPnP MultiScreen MultiScreen Architecture:1	ISO/IEC 29341-28-1
UPnP MultiScreen Application Management:1 Service	ISO/IEC 29341-28-10
UPnP MultiScreen Screen:1 Device	ISO/IEC 29341-28-2
UPnP MultiScreen Application Management:2 Service	ISO/IEC 29341-29-10
UPnP MultiScreen Screen:2 Device	ISO/IEC 29341-29-2
UPnP IoT Management and Control Architecture Overview:1	ISO/IEC 29341-30-1

 © ISO/IEC 2017 – All rights reserved

UPnP DataStore:1 Service	ISO/IEC 29341-30-10
UPnP IoT Management and Control Data Model:1 Service	ISO/IEC 29341-30-11
UPnP IoT Management and Control Transport Generic:1 Service	ISO/IEC 29341-30-12
UPnP IoT Management and Control:1 Device	ISO/IEC 29341-30-2
UPnP Energy Management:1 Service	ISO/IEC 29341-31-1

© ISO/IEC 2017 – All rights reserved

1 Scope

1.1 Introduction

This document describes the overall UPnP IoTManagementAndControl Architecture, which forms the foundation for the UPnP IoTManagementAndControl device [11] and UPnP DataStore service [13] specifications. The IoTManagementAndControl device hosts services to bridge sensor devices connected to both UPnP networks as well as non-UPnP based networks. The DataStore service provides persistent retention and distribution of both sensor data as well as data from mobile devices which may leave the UPnP network at any time. This service can be hosted within the UPnP IoTManagementAndControl device as well as within other UPnP compliant devices.

1.2 Goals

The UPnP IoTManagementAndControl Architecture was explicitly defined to meet the following goals:

- Describe sensors and actuators residing on both UPnP and non-UPnP networks.
- Provide data transport services for sensors and actuators to UPnP network clients.
- Define a service to describe, retain and distribute data received from sensors as well as other non-persistent data sources.
- Define an allowed device protection model for both the sensor and data retention components.

1.3 Non-Goals

The following are not initial goals of the IoTManagementAndControl architecture:

- Low-level control of bridged networks

  The initial version of UPnP IoTManagementAndControl treats Sensors and Actuators as abstract data sources and sinks and does not expose details or provide direct access to bridging network protocols. Low-level control of selected bridged network protocols will be considered in subsequent versions of the architecture.

- Low-latency control of sensors and actuators

  The initial version of UPnP IoTManagementAndControl treats sensors and actuators as autonomous objects requiring relatively infrequent supervision from home-network clients. Closed loop control of sensor and actuator pairs is better accomplished directly within the internal vendor-device sensor/actuator architecture with UPnP home-network clients providing overall supervision. However, UPnP IoTManagementAndControl does support sensors which have substantial throughput requirements using transport connections.

© ISO/IEC 2017 – All rights reserved

1.4 IoTManagementAndControl and DataStore Specification Map

IoTManagementAndControl Architecture Overview [10]

- Sensor Discovery and Description
  - IoTManagementAndControl Detail Overview
  - Sensor Protection Model
  - DataStore Detail Overview
  - DataStore Protection Model
  - DataItem Description and Semantics
  - Sample Implementation Theory of Operation

IoTManagementAndControl Device

IoTManagementAndControl Device Specification [11]

- Sensor Components High-Level Overview
- IoTManagementAndControl Required/Allowed Services

IoTManagementAndControl Sensor DataModel Service Specification [14]

- Sensor Discovery and Description
  - Sensor URN Description
  - Sensor Event Model Description
  - ConfigurationManagement service action(s)
  - Mandatory DataItem(s)
  - Common Sensor Collection types
  - Sensor Data Model
  - IEEE-11073 Medical Device Data Model

SensorTransportGeneric Service Specification [12]

- Sensor Transport (SOAP/HTTP)
  - Sensor Transport action(s)
  - Sensor Data Record(s)

DataStore Service Specification [13]

- Persistent Data Retention
  - DataStore URN Description
  - DataStore (LastChange) Event Model
  - DataStore action(s)
  - DataTable schema(s)

Device Protection Service Specification [15]

- Device Protection
  - Device Protection action(s)

© ISO/IEC 2017 – All rights reserved

2 Normative references

The following documents, in whole or in part, are normatively referenced in this document and are indispensable for its application. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

[1] UPnP Device Architecture, version 1.0, UPnP Forum, June 13, 2000. Available at: http://upnp.org/specs/arch/UPnPDA10_20000613.pdf. Latest version available at: http://upnp.org/specs/arch/UPnP-arch-DeviceArchitecture-v1.0.pdf.

[2] ISO 8601 Data elements and interchange formats – Information interchange -- Representation of dates and times, International Standards Organization, December 21, 2000. Available at: ISO 8601:2000.

[3] IETF RFC 2119, Key words for use in RFCs to Indicate Requirement Levels, S. Bradner, 1997. Available at: http://www.faqs.org/rfcs/rfc2119.html.

[4] HyperText Transport Protocol – HTTP/1.1, R. Fielding, J. Gettys, J. Mogul, H. Frystyk, L. Masinter, P. Leach, T. Berners-Lee, June 1999. Available at: http://www.ietf.org/rfc/rfc2616.txt.

[5] IETF RFC 3339, Date and Time on the Internet: Timestamps, G. Klyne, Clearswift Corporation, C. Newman, Sun Microsystems, July 2002. Available at: http://www.ietf.org/rfc/rfc3339.txt.

[6] Extensible Markup Language (XML) 1.0 (Third Edition), François Yergeau, Tim Bray, Jean Paoli, C. M. Sperberg-McQueen, Eve Maler, eds., W3C Recommendation, February 4, 2004. Available at: http://www.w3.org/TR/2004/REC-xml-20040204.

[7] XML Schema Part 2: Data Types, Second Edition, Paul V. Biron, Ashok Malhotra, W3C Recommendation, 28 October 2004. Available at: http://www.w3.org/TR/2004/REC-xmlschema-2-20041028.

[8] XML Path Language (XPATH) Version 1.0. James Clark, Steve DeRose, W3C Recommendation 16 November 1999. Available from: http://www.w3.org/TR/1999/REC-xpath-19991116.

[9] ISO/IEEE-11073-20601 Health informatics - Personal health device communication - Part 20601: Application Profile - Optimized exchange protocol, 2010. Available at: http://www.iso.org/iso/search.htm?qt=11073&searchSubmit=Search&sort=rel&type=simple&published=true

[10] UPnP Sensor and DataStore Architecture Overview, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/specs/smgt/UPnP-smgt-IoTManagementAndControlArchitectureOverview-v1-20130701.pdf. Latest version available at: http://www.upnp.org/specs/smgt/UPnP-smgt-IoTManagementAndControlArchitectureOverview-v1.pdf.

[11] UPnP IoTManagementAndControl:1 Device, UPnP Forum July 1, 2013. Available at: http://www.upnp.org/specs/smgt/UPnP-smgt-IoTManagementAndControl-v1-Device-20130701.pdf. Latest version available at: http://www.upnp.org/specs/smgt/UPnP-smgt-IoTManagementAndControl-v1-Device.pdf.

[12] UPnP SensorTransportGeneric:1 Service, UPnP Forum July 1, 2013. Available at: http://www.upnp.org/specs/smgt/UPnP-smgt-SensorTransportGeneric-v1-Service-20130701.pdf. Latest version available at: http://www.upnp.org/specs/smgt/UPnP-smgt-SensorTransportGeneric-v1-Service.pdf.

[13] UPnP DataStore:1 Service, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/specs/smgt/UPnP-smgt-DataStore-v1-Service-20130701.pdf. Latest version available at: http://www.upnp.org/specs/smgt/UPnP-smgt-DataStore-v1-Service.pdf.

© ISO/IEC 2017 – All rights reserved

[14] UPnP IoTManagementAndControl Sensor DataModel Service, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/specs/smgt/UPnP-smgt-SensorDataModel-v1-Service-20130701.pdf. Latest version available at: http://www.upnp.org/specs/smgt/UPnP-smgt-SensorDataModel-v1-Service.pdf.

[15] UPnP DeviceProtection:1 Service, UPnP Forum, February 24, 2011. Available at: http://www.upnp.org/specs/gw/UPnP-gw-DeviceProtection-v1-Service-20110224.pdf. Latest version available at: http://www.upnp.org/specs/gw/UPnP-gw-DeviceProtection-v1-Service.pdf.

[16] UPnP ConfigurationManagement:2 Service, UPnP Forum, February 16, 2012. Available at: http://www.upnp.org/specs/dm/UPnP-dm-ConfigurationManagement-v2-Service-20120216.pdf. Latest version available at: http://www.upnp.org/specs/dm/UPnP-dm-ConfigurationManagement-v2-Service.pdf.

[17] XML Schema DataStore LastChange Eventing, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/dsevent-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/dsevent.xsd.

[18] XML Schema UPnP DataStore DataStoreInfo, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/dsinfo-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/dsinfo.xsd.

[19] XML Schema UPnP DataStore DataTableInfo, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/dtinfo-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/dtinfo.xsd.

[20] XML Schema UPnP DataStore DataStoreGroups, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/dsgroups-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/dsgroups.xsd.

[21] XML Schema UPnP DataStore DataRecord, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/drecs-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/drecs.xsd.

[22] XML Schema UPnP DataStore DataRecordFilter, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/drecfilter-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/drecfilter.xsd.

[23] XML Schema UPnP DataStore DataRecord Status, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/ds/drecstatus-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/ds/drecstatus.xsd.

[24] XML Schema UPnP IoTManagementAndControl DataRecord Information, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/smgt/srecinfo-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/smgt/srecinfo.xsd.

[25] XML Schema UPnP IoTManagementAndControl Sensor DataModel DataItem Description, UPnP Forum, July 1, 2013. Available at: http://www.upnp.org/schemas/smgt/sdmdid-v1-20130701.xsd. Latest version available at: http://www.upnp.org/schemas/smgt/sdmdid.xsd.

3 Terms, definitions and abbreviations

For initial readers of this document, it may be helpful to proceed to subclause 4, "Architectural Overview" and refer to this section for terms and definitions as needed.

3.1 IoTManagementAndControl terms and definitions

The following terms apply to the IoTManagementAndControl Device [11], IoTManagementAndControl Sensor DataModel Service [14], and IoTManagementAndControl SensorTransportGeneric Service [12] specifications.

 © ISO/IEC 2017 – All rights reserved

3.1.1
Sensor
A Sensor defines sets of named DataItem(s) (see subclause 3.2) which can be read and/or written via the SensorTransportGeneric service [12]. Access to Sensor DataItem(s) is provided by UPnP SOAP actions or via HTTP sensor transport connections. Discovery, control and status of Sensor(s) are provided through parameter(s) defined by the IoTManagementAndControl Sensor DataModel service [14]. Depending on the type of Sensor, additional sensor control and status parameters may also be defined by additional sensor ecosystem specific specifications.

3.1.2
SensorCollection
A SensorCollection contains zero or more Sensors. The Sensors enumerated within a SensorCollection typically relate to a real world device. In some instances the Sensors may be directly related to the operation of the device such as an IEEE-11073 Medical Device System [9], while in other instances, Sensors may indirectly assist in performing monitoring and possibly control operations on the device; such as sensors within a refrigerator or home thermostat. SensorCollections may identify other UPnP Devices which can provide additional command and control functionality.

3.1.3
SensorGroup
Sensors can be grouped using SensorGroup(s). An individual Sensor may participate (be a member of) zero or more SensorGroup(s). SensorGroup(s) may include Sensors from multiple SensorCollection(s). In addition to identifying related Sensors, SensorGroup(s) also can be assigned DeviceProtection permissions which can then be used as DeviceProtection Roles.

3.1.4
SensorID
A SensorID is an identifier which uniquely identifies a Sensor to SOAP actions implemented by the SensorTransportGeneric service [12]. SensorID values are provided by the IoTManagementAndControl Sensor DataModel service [14] *SensorID* parameter node.

3.1.5
SensorNode
A SensorNode is a set of IoTManagementAndControl Sensor DataModel [14] nodes which describe a Sensor and the DataItem(s) it supports. The required and allowed SensorNode parameters and corresponding syntax and semantics are detailed by IoTManagementAndControl Sensor DataModel service specification.

3.1.6
SensorPath
A PartialPath (see subclause 3.3) to a SensorNode.

3.1.7
SensorURN
A SensorURN(s) identifies sets of required and allowed DataItem(s) that a Sensor provides. The syntax and semantics of SensorURN(s) is detailed in the IoTManagementAndControl Sensor DataModel service specification [14], and subclause 5.2.6, "Sensor Normative Type Identifiers".

3.2 DataStore terms and definitions

The following terms apply to the DataStore Service specification [13],

3.2.1
DataItem
A DataItem identifies an output from a Sensor (or input to an Actuator). A DataItem is defined by a name, data type and encoding. See subclause 4.3, "DataItem Semantics" for a detailed description of DataItem(s).

© ISO/IEC 2017 – All rights reserved

3.2.2
DataRecord
A DataRecord consists of a defined set of DataItem(s). DataRecord(s) may contain DataItem(s) from multiple sensor types as well as containing DataItem(s) from multiple sensors of the same type.

3.2.3
DataStore
A DataStore is a collection of DataTable(s).

3.2.4
DataStore Group
DataTable(s) within a DataStore shall be a member of one or more groups. Membership in a group indicates the participating DataTable(s) are related in some way. A given DataTable may participate in multiple groups. The DataStore service however, only defines membership in a group and access rights to a group. Additional ecosystem specific requirements may provide further rules and meaning attached to group membership.

3.2.5
DataTable
A DataTable consists of a collection of DataRecord(s) and a key/value Dictionary managed by a DataStore service. All DataRecord(s) in a DataTable share a common DataRecord format.

3.2.6
DataTable Dictionary
A DataTable provides a key/value data structure containing information about the DataTable. DataItem(s) stored in the DataTable records may refer to entries stored in the DataTable's Dictionary.

3.2.7
DataTable GUID
A globally unique identifier of a DataTable.

3.2.8
DataTableID
A UPnP action argument identifying a specific DataTable (see DataTable GUID).

3.2.9
DataTable URN
A uniform resource name (URN) which identifies the contents stored in a DataTable. See DataStore service [13], subclause 5.3.4, "DataTable URN" for further information.

3.3 Configuration Management terms and definitions

The following terms apply to the ConfigurationManagement Service [16]. The IoTManagementAndControl Sensor DataModel service [14] defines a profile of ConfigurationManagement service.

3.3.1
Leaf
A leaf element in the data model’s logical tree.

3.3.2
Node
An element in the logical tree that represents the hierarchical structure of the data model.

3.3.3
Path
A string representation of the sequence of Node(s) starting with a Root Node and ending at the Node of interest. Specifically it’s the concatenation of the Node names.

 © ISO/IEC 2017 – All rights reserved

3.3.4
PartialPath
A Path from the Root to a Node in the data model tree which is not a Leaf.

3.3.5
ParameterInitializationPath
A sequence of Node(s) starting from SingleInstance Node and ending to the Leaf Node.

3.3.6
Root
The root element of the data model's logical tree.

3.4 Device Protection terms and definitions

The following terms apply to the DeviceProtection service [15].

3.4.1
Device Protection Roles
The UPnP DeviceProtection service associates control points with device protection roles which define allowable operations a control point may perform on a UPnP service. UPnP DeviceProtection service roles are a union of basic roles defined by the UPnP DeviceProtection service and device protection roles defined by the UPnP service subject to device protection. See UPnP DeviceProtection service [15] and subclause 4.1.9, "Sensor Collection Protection Model" and subclause 4.2.6, "DataStore Protection Model" for further details.

3.4.2
Control Point Identity
The UPnP DeviceProtection service associates control point identities with device protection roles. A UPnP control point may have its own assigned roles as well as roles resulting from particular end-users being associated with the control point.

© ISO/IEC 2017 – All rights reserved