INTERNATIONAL STANDARD

ISO/IEC 8825-2

Sixth edition
2021-06

Information technology — ASN.1 encoding rules —

Part 2: Specification of Packed Encoding Rules (PER)

Technologies de l'information — Règles de codage ASN.1 — Partie 2: Spécification des règles de codage compact (PER)

Reference number
ISO/IEC 8825-2:2021(E)

© ISO/IEC 2021



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2021

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives or www.iec.ch/members_experts/refdocs)

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems,* in collaboration with ITU-T. The identical text is published as ITU-T X.691 (02/2021).

This sixth edition cancels and replaces the fifth edition (ISO/IEC 8825-2:2015), which has been technically revised. It also incorporates ISO/IEC 8825-2:2015/Cor 1:2017.

A list of all parts in the ISO/IEC 8825 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

© ISO/IEC 2021 – All rights reserved

CONTENTS

Page

Introduction vi

1 Scope 1

2 Normative references 1
- 2.1 Identical Recommendations | International Standards 1
- 2.2 Additional references 1

3 Definitions 2
- 3.1 Specification of Basic Notation 2
- 3.2 Information Object Specification 2
- 3.3 Constraint Specification 2
- 3.4 Parameterization of ASN.1 Specification 2
- 3.5 Basic Encoding Rules 2
- 3.6 PER Encoding Instructions 2
- 3.7 Additional definitions 2

4 Abbreviations 5

5 Notation 5

6 Convention 5

7 Encoding rules defined in this Recommendation | International Standard 5

8 Conformance 6

9 PER encoding instructions 6

10 The approach to encoding used for PER 7
- 10.1 Use of the type notation 7
- 10.2 Use of tags to provide a canonical order 7
- 10.3 PER-visible constraints 7
- 10.4 Type and value model used for encoding 9
- 10.5 Structure of an encoding 9
- 10.6 Types to be encoded 10

11 Encoding procedures 10
- 11.1 Production of the complete encoding 10
- 11.2 Open type fields 11
- 11.3 Encoding as a non-negative-binary-integer 11
- 11.4 Encoding as a 2's-complement-binary-integer 12
- 11.5 Encoding of a constrained whole number 12
- 11.6 Encoding of a normally small non-negative whole number 13
- 11.7 Encoding of a semi-constrained whole number 13
- 11.8 Encoding of an unconstrained whole number 13
- 11.9 General rules for encoding a length determinant 14

12 Encoding the boolean type 16

13 Encoding the integer type 16

14 Encoding the enumerated type 17

15 Encoding the real type 18

16 Encoding the bitstring type 18

17 Encoding the octetstring type 19

18 Encoding the null type 19

19 Encoding the sequence type 19

20 Encoding the sequence-of type 20

21 Encoding the set type 21

22 Encoding the set-of type 21

23 Encoding the choice type 21

© ISO/IEC 2021 – All rights reserved

24 Encoding the object identifier type 22
25 Encoding the relative object identifier type 22
26 Encoding the internationalized resource reference type 22
27 Encoding the relative internationalized resource reference type 23
28 Encoding the embedded-pdv type 23
29 Encoding of a value of the external type 23
30 Encoding the restricted character string types 24
31 Encoding the unrestricted character string type 26
32 Encoding the time type, the useful time types, the defined time types and the additional time types 26
32.1 General 26
32.2 Encoding subtypes with the "Basic=Date" property setting 30
32.3 Encoding subtypes with the "Basic=Time" property setting 32
32.4 Encoding subtypes with the "Basic=Date-Time" property setting 35
32.5 Encoding subtypes with the "Basic=Interval Interval-type=SE" property setting 35
32.6 Encoding subtypes with the "Basic=Interval Interval-type=D" property setting 36
32.7 Encoding subtypes with the "Basic=Interval Interval-type=SD" or "Basic=Interval Interval-type=DE" property setting 37
32.8 Encoding subtypes with the "Basic=Rec-Interval Interval-type=SE" property setting 38
32.9 Encoding subtypes with the "Basic=Rec-Interval Interval-type=D" property setting 38
32.10 Encoding subtypes with the "Basic=Rec-Interval Interval-type=SD" or "Basic=Rec-Interval Interval-type=DE" property setting 39
32.11 Encoding subtypes with mixed settings of the Basic property 40
33 Object identifiers for transfer syntaxes 42
Annex A – Example of encodings 43
A.1 Record that does not use subtype constraints 43
A.1.1 ASN.1 description of the record structure 43
A.1.2 ASN.1 description of a record value 43
A.1.3 ALIGNED PER representation of this record value 43
A.1.4 UNALIGNED PER representation of this record value 44
A.2 Record that uses subtype constraints 46
A.2.1 ASN.1 description of the record structure 46
A.2.2 ASN.1 description of a record value 46
A.2.3 ALIGNED PER representation of this record value 46
A.2.4 UNALIGNED PER representation of this record value 47
A.3 Record that uses extension markers 48
A.3.1 ASN.1 description of the record structure 48
A.3.2 ASN.1 description of a record value 49
A.3.3 ALIGNED PER representation of this record value 49
A.3.4 UNALIGNED PER representation of this record value 50
A.4 Record that uses extension addition groups 52
A.4.1 ASN.1 description of the record structure 52
A.4.2 ASN.1 description of a record value 52
A.4.3 ALIGNED PER representation of this record value 52
A.4.4 UNALIGNED PER representation of this record value 53
Annex B – Combining PER-visible and non-PER-visible constraints 54
B.1 General 54
B.2 Extensibility and visibility of constraints in PER 54
B.2.1 General 54
B.2.2 PER-visibility of constraints 55
B.2.3 Effective constraints 56
B.3 Examples 57

© ISO/IEC 2021 – All rights reserved

Annex C – Support for the PER algorithms 59
Annex D – Support for the ASN.1 rules of extensibility 60
Annex E – Tutorial annex on concatenation of PER encodings 61
Annex F – Identification of Encoding Rules 62

© ISO/IEC 2021 – All rights reserved

Introduction

Specifications Rec. ITU-T X.680 | ISO/IEC 8824-1, Rec. ITU-T X.681 | ISO/IEC 8824-2, Rec. ITU-T X.682 | ISO/IEC 8824-3, Rec. ITU-T X.683 | ISO/IEC 8824-4 together describe Abstract Syntax Notation One (ASN.1), a notation for the definition of messages to be exchanged between peer applications.

This Recommendation | International Standard defines encoding rules that may be applied to values of types defined using the notation specified in Rec. ITU-T X.680 | ISO/IEC 8824-1. Application of these encoding rules produces a transfer syntax for such values. It is implicit in the specification of these encoding rules that they are also to be used for decoding.

There are more than one set of encoding rules that can be applied to values of ASN.1 types. This Recommendation | International Standard defines a set of Packed Encoding Rules (PER), so called because they achieve a much more compact representation than that achieved by the Basic Encoding Rules (BER) and its derivatives described in Rec. ITU-T X.690 | ISO/IEC 8825-1 which is referenced for some parts of the specification of these Packed Encoding Rules.

© ISO/IEC 2021 – All rights reserved

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)

1 Scope

This Recommendation | International Standard specifies a set of Packed Encoding Rules that may be used to derive a transfer syntax for values of types defined in Rec. ITU-T X.680 | ISO/IEC 8824-1. These Packed Encoding Rules are also to be applied for decoding such a transfer syntax in order to identify the data values being transferred.

The encoding rules specified in this Recommendation | International Standard:

- are used at the time of communication;
- are intended for use in circumstances where minimizing the size of the representation of values is the major concern in the choice of encoding rules;
- allow the extension of an abstract syntax by addition of extra values, preserving the encodings of the existing values, for all forms of extension described in Rec. ITU-T X.680 | ISO/IEC 8824-1;
- can be modified in accordance with the provisions of Rec. ITU-T X.695 | ISO/IEC 8825-6.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

NOTE – This Recommendation | International Standard is based on ISO/IEC 10646:2003. It cannot be applied using later versions of this standard.

2.1 Identical Recommendations | International Standards

- Recommendation ITU-T X.680 (2021) | ISO/IEC 8824-1:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*.
- Recommendation ITU-T X.681 (2021) | ISO/IEC 8824-2:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification*.
- Recommendation ITU-T X.682 (2021) | ISO/IEC 8824-3:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification.*
- Recommendation ITU-T X.683 (2021) | ISO/IEC 8824-4:2021, *Information technology – Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications*.
- Recommendation ITU-T X.690 (2021) | ISO/IEC 8825-1:2021, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER).*
- Recommendation ITU-T X.695 (2021) | ISO/IEC 8825-6:2021, *Information technology – ASN.1 encoding rules: Registration and application of PER encoding instructions.*

NOTE – The references above shall be interpreted as references to the identified Recommendations | International Standards together with all their published amendments and technical corrigenda.

2.2 Additional references

- ISO/IEC 646:1991, *Information technology – ISO 7-bit coded character set for information interchange.*
- ISO/IEC 2022:1994, *Information technology – Character code structure and extension techniques*.
- ISO/IEC 2375:2003, *Information technology – Procedure for registration of escape sequences and coded character sets.*

© ISO/IEC 2021 – All rights reserved

- ISO 6093:1985, *Information processing – Representation of numerical values in character strings for information interchange.*
- *ISO International Register of Coded Character Sets to be Used with Escape Sequences.*
- ISO/IEC 10646:2003, *Information technology – Universal Multiple-Octet Coded Character Set (UCS).*

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.1 Specification of Basic Notation

For the purposes of this Recommendation | International Standard, all the definitions in Rec. ITU-T X.680 | ISO/IEC 8824-1 apply.

3.2 Information Object Specification

For the purposes of this Recommendation | International Standard, all the definitions in Rec. ITU-T X.681 | ISO/IEC 8824-2 apply.

3.3 Constraint Specification

This Recommendation | International Standard makes use of the following terms defined in Rec. ITU-T X.682 | ISO/IEC 8824-3:

a) component relation constraint;

b) table constraint.

3.4 Parameterization of ASN.1 Specification

This Recommendation | International Standard makes use of the following term defined in Rec. ITU-T X.683 | ISO/IEC 8824-4:

- variable constraint.

3.5 Basic Encoding Rules

This Recommendation | International Standard makes use of the following terms defined in Rec. ITU-T X.690 | ISO/IEC 8825-1:

a) data value;

b) dynamic conformance;

c) encoding (of a data value);

d) receiver;

e) sender;

f) static conformance.

3.6 PER Encoding Instructions

This Recommendation | International Standard makes use of the following term defined in Rec. ITU-T X.695 | ISO/IEC 8825-6:

- identifying keyword.

3.7 Additional definitions

For the purposes of this Recommendation | International Standard, the following definitions apply.

3.7.1 2's-complement-binary-integer encoding: The encoding of a whole number into a bit-field (octet-aligned in the ALIGNED variant) of a specified length, or into the minimum number of octets that will accommodate that whole number encoded as a 2's-complement-integer, which provides representations for whole numbers that are equal to, greater than, or less than zero, as specified in 11.4.

© ISO/IEC 2021 – All rights reserved

NOTE 1 – The value of a two's complement binary number is derived by numbering the bits in the contents octets, starting with bit 1 of the last octet as bit zero and ending the numbering with bit 8 of the first octet. Each bit is assigned a numerical value of 2^N, where N is its position in the above numbering sequence. The value of the two's complement binary number is obtained by summing the numerical values assigned to each bit for those bits which are set to one, excluding bit 8 of the first octet, and then reducing this value by the numerical value assigned to bit 8 of the first octet if that bit is set to one.

NOTE 2 – *Whole number* is a synonym for the mathematical term *integer*. It is used here to avoid confusion with the ASN.1 type *integer*.

3.7.2 abstract syntax value: A value of an abstract syntax (defined as the set of values of a single ASN.1 type), which is to be encoded by PER, or which is to be generated by PER decoding.

NOTE – The single ASN.1 type associated with an abstract syntax is formally identified by an object of class **ABSTRACT-SYNTAX**.

3.7.3 bit-field: The product of some part of the encoding mechanism that consists of an ordered set of bits that are not necessarily a multiple of eight.

NOTE – If the use of this term is followed by "octet-aligned in the ALIGNED variant", this means that the bit-field is required to begin on an octet boundary in the complete encoding for the aligned variant of PER.

3.7.4 canonical encoding: A complete encoding of an abstract syntax value obtained by the application of encoding rules that have no implementation-dependent options; such rules result in the definition of a 1-1 mapping between unambiguous and unique bitstrings in the transfer syntax and values in the abstract syntax.

3.7.5 composite type: A set, sequence, set-of, sequence-of, choice, embedded-pdv, external or unrestricted character string type.

3.7.6 composite value: The value of a composite type.

3.7.7 constrained whole number: A whole number which is constrained by PER-visible constraints to lie within a range from "lb" to "ub" with the value "lb" less than or equal to "ub", and the values of "lb" and "ub" as permitted values.

NOTE – Constrained whole numbers occur in the encoding which identifies the chosen alternative of a choice type, the length of character, octet and bit string types whose length has been restricted by PER-visible constraints to a maximum length, the count of the number of components in a sequence-of or set-of type that has been restricted by PER-visible constraints to a maximum number of components, the value of an integer type that has been constrained by PER-visible constraints to lie within finite minimum and maximum values, and the value that denotes an enumeration in an enumerated type.

3.7.8 effective size constraint (for a constrained string type): A single finite size constraint that could be applied to a built-in string type and whose effect would be to permit all and only those lengths that can be present in the constrained string type.

NOTE 1 – For example, the following has an effective size constraint:

```
A ::= IA5String (SIZE(1..4) | SIZE(10..15))
```

since it can be rewritten with a single size constraint that applies to all values:

```
A ::= IA5String (SIZE(1..4 | 10..15))
```

whereas the following has no effective size constraint since the string can be arbitrarily long if it does not contain any characters other than 'a', 'b' and 'c':

```
B ::= IA5String (SIZE(1..4) | FROM("abc"))
```

NOTE 2 – The effective size constraint is used only to determine the encoding of lengths.

3.7.9 effective permitted-alphabet constraint (for a constrained restricted character string type): A single permitted-alphabet constraint that could be applied to a built-in known-multiplier character string type and whose effect would be to permit all and only those characters that can be present in at least one character position of any one of the values in the constrained restricted character string type.

NOTE 1 – For example, in:

```
Ax ::= IA5String (FROM("AB") | FROM("CD"))
Bx ::= IA5String (SIZE(1..4) | FROM("abc"))
```

Ax has an effective permitted-alphabet constraint of **"ABCD"**. **Bx** has an effective permitted-alphabet constraint that consists of the entire **IA5String** alphabet since there is no smaller permitted-alphabet constraint that applies to all values of **Bx**.

NOTE 2 – The effective permitted-alphabet constraint is used only to determine the encoding of characters.

3.7.10 enumeration index: The non-negative whole number associated with an "EnumerationItem" in an enumerated type. The enumeration indices are determined by sorting the "EnumerationItem"s into ascending order by their enumeration value, then by assigning an enumeration index starting with zero for the first "EnumerationItem", one for the second, and so on up to the last "EnumerationItem" in the sorted list.

NOTE – "EnumerationItem"s in the "RootEnumeration" are sorted separately from those in the "AdditionalEnumeration".

3.7.11 extensible for PER encoding: A property of a type which requires that PER identifies an encoding of a value as that of a root value or as that of an extension addition.

NOTE – Root values are normally encoded more efficiently than extension additions.

© ISO/IEC 2021 – All rights reserved