INTERNATIONAL STANDARD

ISO/IEC/IEEE 8802-3

Third edition
2021-02

AMENDMENT 8
2021-10

Telecommunications and exchange between information technology systems — Requirements for local and metropolitan area networks —

Part 3: **Standard for Ethernet**

AMENDMENT 8: Physical layer specifications and management parameters for 2.5 Gb/s, 5 Gb/s, and 10 Gb/s automotive electrical ethernet

Télécommunications et échange entre systèmes informatiques — Exigences pour les réseaux locaux et métropolitains —

Partie 3: Norme pour Ethernet

AMENDEMENT 8: Spécifications des couches physiques et paramètres de gestion pour l'ethernet électrique automobile à 2,5 Gb/s, 5Gb/s et 10 Gb/s

Reference number
ISO/IEC/IEEE 8802-3:2021/Amd.8:2021(E)

© IEEE 2020



COPYRIGHT PROTECTED DOCUMENT

© IEEE 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from IEEE at the address below.

Institute of Electrical and Electronics Engineers, Inc
3 Park Avenue, New York
NY 10016-5997, USA

Email: stds.ipr@ieee.org
Website: www.ieee.org

Published in Switzerland

© IEEE 2020 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO/IEC documents should be noted (see www.iso.org/directives or www.iec.ch/members_experts/refdocs).

IEEE Standards documents are developed within the IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association (IEEE-SA) Standards Board. The IEEE develops its standards through a consensus development process, approved by the American National Standards Institute, which brings together volunteers representing varied viewpoints and interests to achieve the final product. Volunteers are not necessarily members of the Institute and serve without compensation. While the IEEE administers the process and establishes rules to promote fairness in the consensus development process, the IEEE does not independently evaluate, test, or verify the accuracy of any of the information contained in its standards.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT), see www.iso.org/iso/foreword.html. In the IEC, see www.iec.ch/understanding-standards.

ISO/IEC/IEEE 8802-3:2021/Amd 8 was prepared by the LAN/MAN of the IEEE Computer Society (as IEEE Std 802.3ch-2020) and drafted in accordance with its editorial rules. It was adopted, under the "fast-track procedure" defined in the Partner Standards Development Organization cooperation agreement between ISO and IEEE, by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 6, *Telecommunications and information exchange between systems*.

A list of all parts in the ISO/IEC/IEEE 8802 series can be found on the ISO and IEC websites.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html and www.iec.ch/national-committees.

Copyright © 2020 IEEE. All rights reserved.

IEEE Std 802.3ch™-2020
(Amendment to IEEE Std 802.3™-2018
as amended by IEEE Std 802.3cb™-2018,
IEEE Std 802.3bt™-2018,
IEEE Std 802.3cd™-2018,
IEEE Std 802.3cn™-2019,
IEEE Std 802.3cg™-2019,
IEEE Std 802.3cq™-2020,
and IEEE Std 802.3cm™-2020)

IEEE Standard for Ethernet

Amendment 8: Physical Layer Specifications and Management Parameters for 2.5 Gb/s, 5 Gb/s, and 10 Gb/s Automotive Electrical Ethernet

Developed by the

LAN/MAN Standards Committee
of the
IEEE Computer Society

Approved 4 June 2020

IEEE SA Standards Board

Abstract: This amendment to IEEE Std 802.3-2018 adds physical layer specifications and management parameters for 2.5 Gb/s, 5 Gb/s, and 10 Gb/s operation on a single balanced pair of conductors suitable for automotive applications.

Keywords: 2.5GBASE-T1, 5GBASE-T1, 10GBASE-T1, Ethernet, IEEE 802.3ch™, MASTER-SLAVE, Medium Dependent Interface, Physical Coding Sublayer, Physical Layer, Physical Medium Attachment

The Institute of Electrical and Electronics Engineers, Inc.
3 Park Avenue, New York, NY 10016-5997, USA

Copyright © 2020 by The Institute of Electrical and Electronics Engineers, Inc.
All rights reserved. Published 30 June 2020. Printed in the United States of America.

IEEE and 802 are registered trademarks in the U.S. Patent & Trademark Office, owned by The Institute of Electrical and Electronics Engineers, Incorporated.

PDF: ISBN 978-1-5044-6770-4 STD24222
Print: ISBN 978-1-5044-6771-1 STDPD24222

IEEE prohibits discrimination, harassment and bullying.

For more information, visit http://www.ieee.org/web/aboutus/whatis/policies/p9-26.html.

No part of this publication may be reproduced in any form, in an electronic retrieval system or otherwise, without the prior written permission of the publisher.

Important Notices and Disclaimers Concerning IEEE Standards Documents

IEEE documents are made available for use subject to important notices and legal disclaimers. These notices and disclaimers, or a reference to this page, appear in all standards and may be found under the heading "Important Notices and Disclaimers Concerning IEEE Standards Documents." They can also be obtained on request from IEEE or viewed at https://standards.ieee.org/ipr/disclaimers.html.

Notice and Disclaimer of Liability Concerning the Use of IEEE Standards Documents

IEEE Standards documents (standards, recommended practices, and guides), both full-use and trial-use, are developed within IEEE Societies and the Standards Coordinating Committees of the IEEE Standards Association ("IEEE SA") Standards Board. IEEE ("the Institute") develops its standards through a consensus development process, approved by the American National Standards Institute ("ANSI"), which brings together volunteers representing varied viewpoints and interests to achieve the final product. IEEE Standards are documents developed through scientific, academic, and industry-based technical working groups. Volunteers in IEEE working groups are not necessarily members of the Institute and participate without compensation from IEEE. While IEEE administers the process and establishes rules to promote fairness in the consensus development process, IEEE does not independently evaluate, test, or verify the accuracy of any of the information or the soundness of any judgments contained in its standards.

IEEE Standards do not guarantee or ensure safety, security, health, or environmental protection, or ensure against interference with or from other devices or networks. Implementers and users of IEEE Standards documents are responsible for determining and complying with all appropriate safety, security, environmental, health, and interference protection practices and all applicable laws and regulations.

IEEE does not warrant or represent the accuracy or content of the material contained in its standards, and expressly disclaims all warranties (express, implied and statutory) not included in this or any other document relating to the standard, including, but not limited to, the warranties of: merchantability; fitness for a particular purpose; non-infringement; and quality, accuracy, effectiveness, currency, or completeness of material. In addition, IEEE disclaims any and all conditions relating to: results; and workmanlike effort. IEEE standards documents are supplied "AS IS" and "WITH ALL FAULTS."

Use of an IEEE standard is wholly voluntary. The existence of an IEEE standard does not imply that there are no other ways to produce, test, measure, purchase, market, or provide other goods and services related to the scope of the IEEE standard. Furthermore, the viewpoint expressed at the time a standard is approved and issued is subject to change brought about through developments in the state of the art and comments received from users of the standard.

In publishing and making its standards available, IEEE is not suggesting or rendering professional or other services for, or on behalf of, any person or entity nor is IEEE undertaking to perform any duty owed by any other person or entity to another. Any person utilizing any IEEE Standards document, should rely upon his or her own independent judgment in the exercise of reasonable care in any given circumstances or, as appropriate, seek the advice of a competent professional in determining the appropriateness of a given IEEE standard.

IN NO EVENT SHALL IEEE BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO: PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE PUBLICATION, USE OF, OR RELIANCE UPON ANY STANDARD, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE AND REGARDLESS OF WHETHER SUCH DAMAGE WAS FORESEEABLE.

Translations

The IEEE consensus development process involves the review of documents in English only. In the event that an IEEE standard is translated, only the English version published by IEEE should be considered the approved IEEE standard.

Copyright © 2020 IEEE. All rights reserved.

Official statements

A statement, written or oral, that is not processed in accordance with the IEEE SA Standards Board Operations Manual shall not be considered or inferred to be the official position of IEEE or any of its committees and shall not be considered to be, or be relied upon as, a formal position of IEEE. At lectures, symposia, seminars, or educational courses, an individual presenting information on IEEE standards shall make it clear that his or her views should be considered the personal views of that individual rather than the formal position of IEEE.

Comments on standards

Comments for revision of IEEE Standards documents are welcome from any interested party, regardless of membership affiliation with IEEE. However, IEEE does not provide consulting information or advice pertaining to IEEE Standards documents. Suggestions for changes in documents should be in the form of a proposed change of text, together with appropriate supporting comments. Since IEEE standards represent a consensus of concerned interests, it is important that any responses to comments and questions also receive the concurrence of a balance of interests. For this reason, IEEE and the members of its societies and Standards Coordinating Committees are not able to provide an instant response to comments or questions except in those cases where the matter has previously been addressed. For the same reason, IEEE does not respond to interpretation requests. Any person who would like to participate in revisions to an IEEE standard is welcome to join the relevant IEEE working group.

Comments on standards should be submitted to the following address:

Secretary, IEEE SA Standards Board
445 Hoes Lane
Piscataway, NJ 08854 USA

Laws and regulations

Users of IEEE Standards documents should consult all applicable laws and regulations. Compliance with the provisions of any IEEE Standards document does not imply compliance to any applicable regulatory requirements. Implementers of the standard are responsible for observing or referring to the applicable regulatory requirements. IEEE does not, by the publication of its standards, intend to urge action that is not in compliance with applicable laws, and these documents may not be construed as doing so.

Copyrights

IEEE draft and approved standards are copyrighted by IEEE under U.S. and international copyright laws. They are made available by IEEE and are adopted for a wide variety of both public and private uses. These include both use, by reference, in laws and regulations, and use in private self-regulation, standardization, and the promotion of engineering practices and methods. By making these documents available for use and adoption by public authorities and private users, IEEE does not waive any rights in copyright to the documents.

Photocopies

Subject to payment of the appropriate fee, IEEE will grant users a limited, non-exclusive license to photocopy portions of any individual standard for company or organizational internal use or individual, non-commercial use only. To arrange for payment of licensing fees, please contact Copyright Clearance Center, Customer Service, 222 Rosewood Drive, Danvers, MA 01923 USA; +1 978 750 8400. Permission to photocopy portions of any individual standard for educational classroom use can also be obtained through the Copyright Clearance Center.

Copyright © 2020 IEEE. All rights reserved.

Updating of IEEE Standards documents

Users of IEEE Standards documents should be aware that these documents may be superseded at any time by the issuance of new editions or may be amended from time to time through the issuance of amendments, corrigenda, or errata. A current IEEE document at any point in time consists of the current edition of the document together with any amendments, corrigenda, or errata then in effect.

Every IEEE standard is subjected to review at least every ten years. When a document is more than ten years old and has not undergone a revision process, it is reasonable to conclude that its contents, although still of some value, do not wholly reflect the present state of the art. Users are cautioned to check to determine that they have the latest edition of any IEEE standard.

In order to determine whether a given document is the current edition and whether it has been amended through the issuance of amendments, corrigenda, or errata, visit the IEEE SA Website at https://ieeexplore.ieee.org or contact IEEE at the address listed previously. For more information about the IEEE SA or IEEE's standards development process, visit the IEEE SA Website at https://standards.ieee.org.

Errata

Errata, if any, for all IEEE standards can be accessed on the IEEE SA Website at the following URL: https://standards.ieee.org/findstds/errata/index.html. Users are encouraged to check this URL for errata periodically.

Patents

Attention is called to the possibility that implementation of this standard may require use of subject matter covered by patent rights. By publication of this standard, no position is taken by the IEEE with respect to the existence or validity of any patent rights in connection therewith. If a patent holder or patent applicant has filed a statement of assurance via an Accepted Letter of Assurance, then the statement is listed on the IEEE SA Website at https://standards.ieee.org/about/sasb/patcom/patents.html. Letters of Assurance may indicate whether the Submitter is willing or unwilling to grant licenses under patent rights without compensation or under reasonable rates, with reasonable terms and conditions that are demonstrably free of any unfair discrimination to applicants desiring to obtain such licenses.

Essential Patent Claims may exist for which a Letter of Assurance has not been received. The IEEE is not responsible for identifying Essential Patent Claims for which a license may be required, for conducting inquiries into the legal validity or scope of Patents Claims, or determining whether any licensing terms or conditions provided in connection with submission of a Letter of Assurance, if any, or in any licensing agreements are reasonable or non-discriminatory. Users of this standard are expressly advised that determination of the validity of any patent rights, and the risk of infringement of such rights, is entirely their own responsibility. Further information may be obtained from the IEEE Standards Association.

Copyright © 2020 IEEE. All rights reserved.

Participants

The following individuals were officers and members of the IEEE 802.3 Working Group at the beginning of the IEEE P802.3ch Working Group ballot.

David J. Law, *IEEE 802.3 Working Group Chair*
Adam Healey, *IEEE 802.3 Working Group Vice-Chair*
Pete Anslow, *IEEE 802.3 Working Group Secretary, Phase 1*
Jon Lewis, *IEEE 802.3 Working Group Secretary, Phase 2*
Steven B. Carlson, *IEEE 802.3 Working Group Executive Secretary*
Valerie Maguire, *IEEE 802.3 Working Group Treasurer*

Steven B. Carlson, *IEEE P802.3ch Multi-Gig Automotive Ethernet PHY Task Force Chair*
Natalie Wienckowski, *IEEE P802.3ch Multi-Gig Automotive Ethernet PHY Task Force Editor-in-Chief*

John Abbott
David Abramson
Andrea Agnes
Dale Amason
Hongming An
Jes Asmussen
Richard Baca
Tim Baggett
Amrik Bains
Thananya Baldwin
Steven Baumgartner
Denis Beaudoin
Liav Ben-Artsi
Piergiorgio Beruto
Vipul Bhatt
Gao Bo
Martin Bouda
David Brandt
Ralf-Peter Braun
Paul Brooks
Alan Brown
Matthew Brown
Michal Brychta
Gary Burrell
Jairo Bustos Heredia
Adrian Butter
John Calvin
Clark Carty
Craig Chabot
David Chalupsky
Frank Chang
Xin Chang
Golam Choudhury
Keng Hua Chuang
Kamal Dalmia
John D'Ambrosia
Piers Dawe
Fred Dawson
John Deandrea
Gerrit den Besten
Claudio DeSanti
Chris Diminico
Hormoz Djahanshahi
Curtis Donahue
Liang Du
Kathryn Dube
Mike Dudek
Marc Dupuis
Frank Effenberger
David Estes
John Ewen
Borhan Fathi Moghadam
Vincent Ferretti
Brian Franchuk
Matthias Fritsche
Richard Frosch
Shiyong Fu
Mike Gardner
Claude Gauthier
Ali Ghiasi
Joel Goergen
Zhigang Gong
Steven Gorshe
Jens Gottron
Steffen Graber
Olaf Grau
Robert Grow
Mark Gustlin
Marek Hajduczenia
Hayden Haynes
Xiang He
Howard Heck
Brian Holden
Rita Horner
Bernd Horrmeyer
Gergely Huszak
Yasuhiro Hyakutake
Jonathan Ingham
Kazuhiko Ishibe
Hideki Isono
Tom Issenhuth
Kenneth Jackson
Andrew Jimenez
John Johnson
Chad Jones
Peter Jones
Lokesh Kabra
Manabu Kagami
Upen Kareti
Yasuaki Kawatsu
Yong Kim
Mark Kimber
Jonathan King
Michael Klempa
Curtis Knittle
Elizabeth Kochuparambil
Wojciech Koczwara
Paul Kolesar
Taiji Kondo
Glen Kramer
Olaf Krieger
Hans Lackner
Jeffrey Lapak
Mark Laubach
Han Hyub Lee
June Hee Lee
Alex Levin
David Li
Mike-Peng Li
Jane Lim
Alex Lin
Dekun Liu
Hai-Feng Liu
Karen Liu
Zhenyu Liu
William Lo
Yuchun Lu
Miklos Lukacs
Kent Lusted
Ilya Lyubomirsky
Jeffery Maki
David Malicoat
Flavio Marques
Arthur Marris
Chris Mash
Takeo Masuda
Kirsten Matheus
Erdem Matoglu
Marco Mazzini
Mick McCarthy

Copyright © 2020 IEEE. All rights reserved.

Brett McClellan
Larry McMillan
Greg McSorley
Richard Mellitz
Martin Miller
Toshiyuki Moritake
Thomas Mueller
Edward Nakamoto
Paul Neveux
Gary Nicholl
Shawn Nicholl
John Nolan
Kevin Noll
Mark Nowell
David Ofelt
Josef Ohni
Tom Palkert
Sujan Pandey
Carlos Pardo
Earl Parsons
Gerald Pepper
Phong Pham
David Piehler
Rick Pimpinella
Christopher Pohl
William Powell
Dino Pozzebon
Rick Rabinovich
Zvi Rechtman
Alon Regev
Duane Remein
Victor Renteria
Salvatore Rotolo
Alexander Rysin
Toshiaki Sakai
Hamid Salehi
Sam Sambasivan
Edward Sayre
James Schuessler
Steve Sekel
Masood Shariff
Mizuki Shirao
Jialong Shuai
Jeff Slavick
Daniel Smith
Scott Sommers
Tom Souvignier
Bryan Sparrowhawk
Edward Sprague
Peter Stassar
Heath Stewart
David Stover
Junqing Sun
Liyang Sun
Steve Swanson
Bharat Tailor
Tomoo Takahara
Kohichi Tamura
Mehmet Tazebay
Ronald Tellas
Geoffrey Thompson
Pirooz Tooyserkani
Nathan Tracy
David Tremblay
Stephen Trowbridge
Ta Chin Tseng
Ed Ulrichs
Alexander Umnov
Ricky Vernickel
Marco Vitali
Robert Voss
Dylan Walker
Haifei Wang
Roy Wang
Tongtong Wang
Xinyuan Wang
Xuehuan Wang
Christoph Wechsler
Brian Welch
Matthias Wendt
James Withey
Mau-Lin Wu
Peter Wu
Markus Wucher
Dayin Xu
Yu Xu
Shuto Yamamoto
Adrian Young
James Young
Lennart Yseboodt
Andrew Zambell
Conrad Zerna
Richard (Yujia) Zhou
Yan Zhuang
Martin Zielinski
George Zimmerman
Pavel Zivny
Harald Zweck

The following members of the individual balloting committee voted on this standard. Balloters may have voted for approval, disapproval, or abstention.

Shadi Abughazaleh
Thomas Alexander
Dale Amason
Butch Anton
Stefan Aust
Gitesh Bhagwat
Rich Boyer
Ralf-Peter Braun
Theodore Brillhart
Matthew Brown
Demetrio Bucaneg, Jr.
Jairo Bustos Heredia
William Byrd
John Calvin
Radhakrishna Canchi
Steven B. Carlson
Juan Carreon
Clark Carty
Pin Chang
Chan Chen
Eunmin Choi
James Cloos
Charles Cook
Rodney Cummings
John D'Ambrosia
John Deandrea
Christopher Diminico
Marc Dupuis
Avraham Freedman
Matthias Fritsche
Claude Gauthier
Devon Gayle
James Gilb
Joel Goergen
Zhigang Gong
James Graba
Randall Groves
Robert Grow
Martin Gubow
Marek Hajduczenia
Adam Healey
Marco Hernandez
Werner Hoelzl
Oliver Holland
Rita Horner
Atsushi Ito
Raj Jain
SangKwon Jeong
Ragnar Jonsson
Lokesh Kabra
Manabu Kagami
Piotr Karocki
Stuart Kerry
Yongbum Kim
Taiji Kondo
Peter Kroeplin
Mark Laubach
David J. Law
Hyeong Ho Lee
Yeou Song Lee
Jon Lewis
Robert Lingle
Javier Luiso
Michael Lynch
Jeffery Maki
David Malicoat
Michael Maytum
Stephen McCann
Brett McClellan
Larry McMillan
Richard Mellitz
Tremont Miao

Copyright © 2020 IEEE. All rights reserved.

Jose Morales
James Nadolny
Paul Neveux
Nick S. A. Nikjoo
Paul Nikolich
Satoshi Obara
Josef Ohni
Bansi Patel
Harsh Patel
Dev Paul
Arumugam Paventhan
Walter Pienciak
Rick Pimpinella
Adee Ran
R. K. Rannow
Alon Regev
Maximilian Riegel
Robert Robinson
Toshiaki Sakai
Olindo Savi
Dieter Schicketanz
James Schuessler
Hossein Sedarat
Thomas Starai
Heath Stewart
Walter Struppler
Mitsutoshi Sugawara
Geoffrey Thompson
Michael Thompson
Nathan Tracy
David Tremblay
Mark-Rene Uchida
Alexander Umnov
Paul Vanderlaan
Dmitri Varsanofiev
George Vlantis
Lisa Ward
Natalie Wienckowski
Scott Willy
Andreas Wolf
Peter Wu
Yu Yuan
Oren Yuen
Zhen Zhou
George Zimmerman

When the IEEE SA Standards Board approved this standard on 4 June 2020, it had the following membership:

Gary Hoffman, *Chair*
Jon Walter Rosdahl, *Vice Chair*
Jean-Philippe Faure, *Past Chair*
Konstantinos Karachalios, *Secretary*

Ted Burse
J. Travis Griffith
Grace Gu
Guido R. Hiertz
Joseph L. Koepfinger*
John D. Kulick
David J. Law
Howard Li
Dong Liu
Kevin Lu
Paul Nikolich
Damir Novosel
Dorothy Stanley
Mehmet Ulema
Lei Wang
Sha Wei
Philip B. Winston
Daidi Zhong
Jingyi Zhou

*Member Emeritus

Copyright © 2020 IEEE. All rights reserved.

Introduction

This introduction is not part of IEEE Std 802.3ch-2020, IEEE Standard for Ethernet. Amendment 8: Physical Layer Specifications and Management Parameters for 2.5 Gb/s, 5 Gb/s, and 10 Gb/s Automotive Electrical Ethernet.

IEEE Std 802.3™ was first published in 1985. Since the initial publication, many projects have added functionality or provided maintenance updates to the specifications and text included in the standard. Each IEEE 802.3 project/amendment is identified with a suffix (e.g., IEEE Std 802.3ba™-2010).

The half duplex Media Access Control (MAC) protocol specified in IEEE Std 802.3-1985 is Carrier Sense Multiple Access with Collision Detection (CSMA/CD). This MAC protocol was key to the experimental Ethernet developed at Xerox Palo Alto Research Center, which had a 2.94 Mb/s data rate. Ethernet at 10 Mb/s was jointly released as a public specification by Digital Equipment Corporation (DEC), Intel and Xerox in 1980. Ethernet at 10 Mb/s was approved as an IEEE standard by the IEEE Standards Board in 1983 and subsequently published in 1985 as IEEE Std 802.3-1985. Since 1985, new media options, new speeds of operation, and new capabilities have been added to IEEE Std 802.3. A full duplex MAC protocol was added in 1997.

Some of the major additions to IEEE Std 802.3 are identified in the marketplace with their project number. This is most common for projects adding higher speeds of operation or new protocols. For example, IEEE Std 802.3u™ added 100 Mb/s operation (also called Fast Ethernet), IEEE Std 802.3z added 1000 Mb/s operation (also called Gigabit Ethernet), IEEE Std 802.3ae added 10 Gb/s operation (also called 10 Gigabit Ethernet), IEEE Std 802.3ah™ specified access network Ethernet (also called Ethernet in the First Mile) and IEEE Std 802.3ba added 40 Gb/s operation (also called 40 Gigabit Ethernet) and 100 Gb/s operation (also called 100 Gigabit Ethernet). These major additions are all now included in and are superseded by IEEE Std 802.3-2018 and are not maintained as separate documents.

At the date of IEEE Std 802.3ch-2020 publication, IEEE Std 802.3 was composed of the following documents:

IEEE Std 802.3-2018

Section One—Includes Clause 1 through Clause 20 and Annex A through Annex H and Annex 4A. Section One includes the specifications for 10 Mb/s operation and the MAC, frame formats and service interfaces used for all speeds of operation.

Section Two—Includes Clause 21 through Clause 33 and Annex 22A through Annex 33E. Section Two includes management attributes for multiple protocols and speed of operation as well as specifications for providing power over twisted pair cabling for multiple operational speeds. It also includes general information on 100 Mb/s operation as well as most of the 100 Mb/s Physical Layer specifications.

Section Three—Includes Clause 34 through Clause 43 and Annex 36A through Annex 43C. Section Three includes general information on 1000 Mb/s operation as well as most of the 1000 Mb/s Physical Layer specifications.

Section Four—Includes Clause 44 through Clause 55 and Annex 44A through Annex 55B. Section Four includes general information on 10 Gb/s operation as well as most of the 10 Gb/s Physical Layer specifications.

Section Five—Includes Clause 56 through Clause 77 and Annex 57A through Annex 76A. Clause 56 through Clause 67 and Clause 75 through Clause 77, as well as associated annexes, specify subscriber access and other Physical Layers and sublayers for operation from 512 kb/s to 10 Gb/s, and defines

Copyright © 2020 IEEE. All rights reserved.

services and protocol elements that enable the exchange of IEEE Std 802.3 format frames between stations in a subscriber access network. Clause 68 specifies a 10 Gb/s Physical Layer specification. Clause 69 through Clause 74 and associated annexes specify Ethernet operation over electrical backplanes at speeds of 1000 Mb/s and 10 Gb/s.

Section Six—Includes Clause 78 through Clause 95 and Annex 83A through Annex 93C. Clause 78 specifies Energy-Efficient Ethernet. Clause 79 specifies IEEE 802.3 Organizationally Specific Link Layer Discovery Protocol (LLDP) type, length, and value (TLV) information elements. Clause 80 through Clause 95 and associated annexes include general information on 40 Gb/s and 100 Gb/s operation as well the 40 Gb/s and 100 Gb/s Physical Layer specifications. Clause 90 specifies Ethernet support for time synchronization protocols.

Section Seven—Includes Clause 96 through Clause 115 and Annex 97A through Annex 115A. Clause 96 through Clause 98, Clause 104, and associated annexes, specify Physical Layers and optional features for 100 Mb/s and 1000 Mb/s operation over a single twisted pair. Clause 100 through Clause 103, as well as associated annexes, specify Physical Layers for the operation of the EPON protocol over coaxial distribution networks. Clause 105 through Clause 114 and associated annexes include general information on 25 Gb/s operation as well as 25 Gb/s Physical Layer specifications. Clause 99 specifies a MAC merge sublayer for the interspersing of express traffic. Clause 115 and its associated annex specify a Physical Layer for 1000 Mb/s operation over plastic optical fiber.

Section Eight—Includes Clause 116 through Clause 126 and Annex 119A through Annex 120E. Clause 116 through Clause 124 and associated annexes include general information on 200 Gb/s and 400 Gb/s operation as well the 200 Gb/s and 400 Gb/s Physical Layer specifications. Clause 125 and Clause 126 include general information on 2.5 Gb/s and 5 Gb/s operation as well as 2.5 Gb/s and 5 Gb/s Physical Layer specifications.

IEEE Std 802.3cb™-2018

Amendment 1—This amendment includes changes to IEEE Std 802.3-2018 and its amendments, and adds Clause 127 through Clause 130, Annex 127A, Annex 128A, Annex 128B, and Annex 130A. This amendment adds new Physical Layers for operation at 2.5 Gb/s and 5 Gb/s over electrical backplanes.

IEEE Std 802.3bt™-2018

Amendment 2—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 145, Annex 145A, Annex 145B, and Annex 145C. This amendment adds power delivery using all four pairs in the structured wiring plant, resulting in greater power being available to end devices. This amendment also allows for lower standby power consumption in end devices and adds a mechanism to better manage the available power budget.

IEEE Std 802.3cd™-2018

Amendment 3—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 131 through Clause 140 and Annex 135A through Annex 136D. This amendment adds MAC parameters, Physical Layers, and management parameters for the transfer of IEEE 802.3 format frames at 50 Gb/s, 100 Gb/s, and 200 Gb/s.

IEEE Std 802.3cn™-2019

Amendment 4—This amendment includes changes to IEEE Std 802.3-2018 and adds 50 Gb/s, 200 Gb/s, and 400 Gb/s Physical Layer specifications and management parameters for operation over single-mode fiber with reaches of at least 40 km.

Copyright © 2020 IEEE. All rights reserved.

IEEE Std 802.3cg™-2019

Amendment 5—This amendment includes changes to IEEE Std 802.3-2018 and its amendments and adds Clause 146 through Clause 148 and Annex 146A and Annex 146B. This amendment adds 10 Mb/s Physical Layer specifications and management parameters for operation on a single balanced pair of conductors.

IEEE Std 802.3cq™-2020

Amendment 6—This amendment includes editorial and technical corrections, refinements, and clarifications to Clause 33 and related portions of the standard.

IEEE Std 802.3cm™-2020

Amendment 7—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 150. This amendment adds Physical Layer (PHY) specifications and management parameters for 400 Gb/s operation on four pairs (400GBASE-SR4.2) and eight pairs (400GBASE-SR8) of multimode fiber, over reaches of at least 100 m.

IEEE Std 802.3ch™-2020

Amendment 8—This amendment includes changes to IEEE Std 802.3-2018 and adds Clause 149, Annex 149A, Annex 149B, and Annex 149C. This amendment adds physical layer specifications and management parameters for operation at 2.5 Gb/s, 5 Gb/s, and 10 Gb/s over a single balanced pair of conductors.

Two companion documents exist, IEEE Std 802.3.1 and IEEE Std 802.3.2. IEEE Std 802.3.1 describes Ethernet management information base (MIB) modules for use with the Simple Network Management Protocol (SNMP). IEEE Std 802.3.2 describes YANG data models for Ethernet. IEEE Std 802.3.1 and IEEE Std 802.3.2 are updated to add management capability for enhancements to IEEE Std 802.3 after approval of those enhancements.

IEEE Std 802.3 will continue to evolve. New Ethernet capabilities are anticipated to be added within the next few years as amendments to this standard.

Copyright © 2020 IEEE. All rights reserved.

Contents

1. Introduction ... 23

1.3 Normative references ... 23
1.4 Definitions ... 23
1.5 Abbreviations ... 24

30. Management ... 25

30.3 Layer management for DTEs ... 25
30.3.2 PHY device managed object class ... 25
30.3.2.1 PHY device attributes ... 25
30.3.2.1.2 aPhyType ... 25
30.3.2.1.3 aPhyTypeList ... 25
30.5 Layer management for medium attachment units (MAUs) ... 26
30.5.1 MAU managed object class ... 26
30.5.1.1 MAU attributes ... 26
30.5.1.1.2 aMAUType ... 26
30.5.1.1.4 aMediaAvailable ... 26
30.6 Management for link Auto-Negotiation ... 26
30.6.1 Auto-Negotiation managed object class ... 26
30.6.1.1 Auto-Negotiation attributes ... 26
30.6.1.1.5 aAutoNegLocalTechnologyAbility ... 26
30.15 Layer management for Power over Data Lines (PoDL) of Single Balanced Twisted-Pair Ethernet ... 27
30.15.1 PoDL PSE managed object class ... 27
30.15.1.1 PoDL PSE attributes ... 27
30.15.1.1.4 aPoDLPSEType ... 27
30.15.1.1.5 aPoDLPSEDetectedPDType ... 27

44. Introduction to 10 Gb/s baseband network ... 28

44.1 Overview ... 28
44.1.1 Scope ... 28
44.1.2 Objectives ... 28
44.1.3 Relationship of 10 Gigabit Ethernet to the ISO OSI reference model ... 29
44.1.4 Summary of 10 Gigabit Ethernet sublayers ... 30
44.1.4.1 Reconciliation Sublayer (RS) and 10 Gigabit Media Independent Interface (XGMII) ... 30
44.1.4.4 Physical Layer signaling systems ... 30
44.3 Delay constraints ... 31
44.4 Protocol implementation conformance statement (PICS) proforma ... 31

45. Management Data Input/Output (MDIO) Interface ... 32

45.2 MDIO Interface Registers ... 32
45.2.1 PMA/PMD registers ... 32
45.2.1.7 PMA/PMD status 2 register (Register 1.8) ... 32
45.2.1.7.4 Transmit fault (1.8.11) ... 32
45.2.1.7.5 Receive fault (1.8.10) ... 33
45.2.1.16 BASE-T1 PMA/PMD extended ability register (1.18) ... 33
45.2.1.16.1 10GBASE-T1 ability (1.18.6) ... 33

Copyright © 2020 IEEE. All rights reserved.

45.2.1.16.2 5GBASE-T1 ability (1.18.5) ... 33
45.2.1.16.3 2.5GBASE-T1 ability (1.18.4) ... 34
45.2.1.18 2.5G/5G PMA/PMD extended ability register (Register 1.21) ... 34
45.2.1.185 BASE-T1 PMA/PMD control register (1.2100) ... 34
45.2.1.185.2 Type selection (1.2100.3:0) ... 34
45.2.1.192 MultiGBASE-T1 PMA control register (Register 1.2309) ... 34
45.2.1.192.1 PMA/PMD reset (1.2309.15) ... 35
45.2.1.192.2 Transmit disable (1.2309.14) ... 35
45.2.1.192.3 Low power (1.2309.11) ... 35
45.2.1.193 MultiGBASE-T1 PMA status register (1.2310) ... 36
45.2.1.193.1 MultiGBASE-T1 OAM ability (1.2310.11) ... 37
45.2.1.193.2 EEE ability (1.2310.10) ... 37
45.2.1.193.3 Receive fault ability (1.2310.9) ... 37
45.2.1.193.4 Low-power ability (1.2310.8) ... 37
45.2.1.193.5 PrecodeSel (1.2310.4:3) ... 37
45.2.1.193.6 Receive polarity (1.2310.2) ... 37
45.2.1.193.7 Receive fault (1.2310.1) ... 37
45.2.1.193.8 Receive link status (1.2310.0) ... 37
45.2.1.194 MultiGBASE-T1 training register (1.2311) ... 37
45.2.1.194.1 Interleave request (1.2311.12:11) ... 38
45.2.1.194.2 Precoder selection (1.2311.5) ... 38
45.2.1.194.3 Slow Wake request (1.2311.4) ... 39
45.2.1.194.4 User precoder selection (1.2311.3:2) ... 39
45.2.1.194.5 MultiGBASE-T1 OAM advertisement (1.2311.1) ... 39
45.2.1.194.6 EEE advertisement (1.2311.0) ... 39
45.2.1.195 MultiGBASE-T1 link partner training register (1.2312) ... 39
45.2.1.195.1 Link partner interleave request (1.2312.12:11) ... 40
45.2.1.195.2 Link partner Slow Wake requested (1.2312.4) ... 40
45.2.1.195.3 Link partner precoder requested (1.2312.3:2) ... 40
45.2.1.195.4 Link partner MultiGBASE-T1 OAM advertisement (1.2312.1) ... 40
45.2.1.195.5 Link partner EEE advertisement (1.2312.0) ... 40
45.2.1.196 MultiGBASE-T1 test mode control register (1.2313) ... 40
45.2.1.196.1 Test mode control (1.2313.15:13) ... 41
45.2.1.196.2 Local transmitter precoder override (1.2313.11) ... 41
45.2.1.196.3 Local transmit precoder setting (1.2313.10:9) ... 41
45.2.1.196.4 Jitter test control (1.2313.1:0) ... 41
45.2.1.197 MultiGBASE-T1 SNR operating margin register (Register 1.2314) ... 42
45.2.1.198 MultiGBASE-T1 minimum SNR margin register (Register 1.2315) ... 42
45.2.1.199 MultiGBASE-T1 user defined data (Register 1.2316) ... 42
45.2.1.199.1 MultiGBASE-T1 user defined data (1.2316.15:0) ... 43
45.2.1.200 MultiGBASE-T1 link partner user defined data register (Register 1.2317) ... 43
45.2.1.200.1 MultiGBASE-T1 link partner user defined data register (1.2317.15:0) ... 43
45.2.3 PCS registers ... 44
45.2.3.72 1000BASE-T1 OAM transmit register (Register 3.2308) ... 44
45.2.3.72.1 1000BASE-T1 OAM message valid (3.2308.15) ... 45
45.2.3.72.2 Toggle value (3.2308.14) ... 45
45.2.3.72.3 1000BASE-T1 OAM message received (3.2308.13) ... 45
45.2.3.72.4 Received message toggle value (3.2308.12) ... 45
45.2.3.72.5 Message number (3.2308.11:8) ... 45
45.2.3.72.6 Ping received (3.2308.3) ... 46
45.2.3.72.7 Ping transmit (3.2308.2) ... 46
45.2.3.72.8 Local SNR (3.2308.1:0) ... 46
45.2.3.73 1000BASE-T1 OAM message register (Registers 3.2309 to 3.2312) ... 46
45.2.3.74 1000BASE-T1 OAM receive register (Register 3.2313) ... 47

Copyright © 2020 IEEE. All rights reserved.

45.2.3.74.1 Link partner 1000BASE-T1 OAM message valid (3.2313.15) 47
45.2.3.74.2 Link partner toggle value (3.2313.14) 47
45.2.3.74.3 Link partner message number (3.2313.11:8) 47
45.2.3.74.4 Link partner SNR (3.2313.1:0) 47
45.2.3.75 Link partner 1000BASE-T1 OAM message register (Registers 3.2314 to 3.2317) 48
45.2.3.76 MultiGBASE-T1 OAM status message register (Register 3.2318 and 3.2319) 48
45.2.3.77 Link partner MultiGBASE-T1 OAM status message register (Register 3.2320 and 3.2321) 49
45.2.3.78 MultiGBASE-T1 PCS control register (Register 3.2322) 49
45.2.3.78.1 PCS reset (3.2322.15) 49
45.2.3.78.2 Loopback (3.2322.14) 50
45.2.3.79 MultiGBASE-T1 PCS status 1 register (Register 3.2323) 50
45.2.3.79.1 Tx LPI received (3.2323.11) 51
45.2.3.79.2 Rx LPI received (3.2323.10) 51
45.2.3.79.3 Tx LPI indication (3.2323.9) 51
45.2.3.79.4 Rx LPI indication (3.2323.8) 51
45.2.3.79.5 Fault (3.2323.7) 51
45.2.3.79.6 PCS receive link status (3.2323.2) 51
45.2.3.80 MultiGBASE-T1 PCS status 2 register (Register 3.2324) 51
45.2.3.80.1 Receive link status (3.2324.10) 51
45.2.3.80.2 PCS high RFER (3.2324.9) 52
45.2.3.80.3 PCS block lock (3.2324.8) 52
45.2.3.80.4 Latched high BER (3.2324.7) 52
45.2.3.80.5 Latched block lock (3.2324.6) 52
45.2.3.80.6 BER count (3.2324.5:0) 53
45.2.9 Power Unit Registers 53
45.2.9.2 PoDL PSE Status 1 register (Register 13.1) 53
45.2.9.2.7 PSE Type (13.1.9:7) 53
45.2.9.3 PoDL PSE Status 2 register (Register 13.2) 54
45.2.9.3.2 PD Type (13.2.2:0) 54
45.5 Protocol implementation conformance statement (PICS) proforma for Clause 45, Management Data Input/Output (MDIO) interface 55
45.5.3 PICS proforma tables for the Management Data Input Output (MDIO) interface. 55
45.5.3.3 PMA/PMD management functions 55
45.5.3.7 PCS management functions 57

78. Energy-Efficient Ethernet (EEE) 59

78.1 Overview 59
78.1.4 PHY types optionally supporting EEE 59
78.2 LPI mode timing parameters description 59
78.3 Capabilities Negotiation 60
78.5 Communication link access latency 60

97. Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, type 1000BASE-T1 62

97.3 Physical Coding Sublayer (PCS) 62
97.3.8 1000BASE-T1 Operations, Administration, and Maintenance (OAM) 62
97.3.8.3 State diagram variable to 1000BASE-T1 OAM register mapping 62

98. Auto-Negotiation for single differential-pair media 64

Copyright © 2020 IEEE. All rights reserved.

98.5 Detailed functions and state diagrams ... 64
98.5.1 State diagram variables ... 64

104. Power over Data Lines (PoDL) of Single-Pair Ethernet ... 65

104.1 Overview ... 65
104.1.3 PoDL system types ... 65
104.4 Power Sourcing Equipment (PSE) ... 65
104.4.1 PSE types ... 65
104.4.6 PSE output requirements ... 65
104.4.6.3 Power feeding ripple and transients ... 66
104.5 Powered Device (PD) ... 66
104.5.1 PD types ... 66
104.5.6 PD power ... 66
104.5.6.4 PD ripple and transients ... 66
104.6 Additional electrical specifications ... 67
104.6.2 Fault tolerance ... 67
104.7 Serial communication classification protocol (SCCP) ... 67
104.7.2 Serial communication classification protocols ... 67
104.7.2.4 Read_Scratchpad function command [0xAA] ... 67
104.9 Protocol implementation conformance statement (PICS) proforma for Clause 104, Power over Data Lines (PoDL) of Single-Pair Ethernet ... 69
104.9.3 Major capabilities/options ... 69
104.9.4 PICS proforma tables for Clause 104, Power over Data Lines (PoDL) of Single-Pair Ethernet ... 69
104.9.4.3 Powered Device (PD) ... 69
104.9.4.4 Common Electrical ... 70

125. Introduction to 2.5 Gb/s and 5 Gb/s networks ... 71

125.1 Overview ... 71
125.1.2 Relationship of 2.5 Gigabit and 5 Gigabit Ethernet to the ISO OSI reference model ... 71
125.1.3 Nomenclature ... 71
125.1.4 Physical Layer signaling systems ... 73
125.2 Summary of 2.5 Gigabit and 5 Gigabit Ethernet sublayers ... 74
125.2.2 Physical coding sublayer (PCS) ... 74
125.2.3 Physical Medium Attachment sublayer (PMA) ... 74
125.2.4 Auto-Negotiation ... 74
125.2.4.3 Auto-Negotiation, type single differential-pair media ... 74
125.3 Delay Constraints ... 74

149. Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, type 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 ... 76

149.1 Overview ... 76
149.1.1 Nomenclature ... 76
149.1.2 Relationship of 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 to other standards ... 76
149.1.3 Operation of 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 ... 77
149.1.3.1 Physical Coding Sublayer (PCS) ... 78
149.1.3.2 Physical Medium Attachment (PMA) sublayer ... 80
149.1.3.3 EEE Capability ... 80
149.1.3.4 Link Synchronization ... 80
149.1.4 Signaling ... 80

Copyright © 2020 IEEE. All rights reserved.

149.1.5 Interfaces 81
149.1.6 Conventions in this clause 81
149.2 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 service primitives and interfaces 81
149.2.1 Technology Dependent Interface 82
149.2.1.1 PMA_LINK.request 82
149.2.1.1.1 Semantics of the primitive 82
149.2.1.1.2 When generated 82
149.2.1.1.3 Effect of receipt 82
149.2.1.2 PMA_LINK.indication 82
149.2.1.2.1 Semantics of the primitive 82
149.2.1.2.2 When generated 82
149.2.1.2.3 Effect of receipt 83
149.2.2 PMA service interface 83
149.2.2.1 PMA_TXMODE.indication 83
149.2.2.1.1 Semantics of the primitive 83
149.2.2.1.2 When generated 84
149.2.2.1.3 Effect of receipt 84
149.2.2.2 PMA_CONFIG.indication 85
149.2.2.2.1 Semantics of the primitive 85
149.2.2.2.2 When generated 85
149.2.2.2.3 Effect of receipt 85
149.2.2.3 PMA_UNITDATA.request 85
149.2.2.3.1 Semantics of the primitive 85
149.2.2.3.2 When generated 85
149.2.2.3.3 Effect of receipt 86
149.2.2.4 PMA_UNITDATA.indication 86
149.2.2.4.1 Semantics of the primitive 86
149.2.2.4.2 When generated 86
149.2.2.4.3 Effect of receipt 86
149.2.2.5 PMA_SCRSTATUS.request 86
149.2.2.5.1 Semantics of the primitive 86
149.2.2.5.2 When generated 86
149.2.2.5.3 Effect of receipt 86
149.2.2.6 PMA_PCSSTATUS.request 87
149.2.2.6.1 Semantics of the primitive 87
149.2.2.6.2 When generated 87
149.2.2.6.3 Effect of receipt 87
149.2.2.7 PMA_RXSTATUS.indication 87
149.2.2.7.1 Semantics of the primitive 87
149.2.2.7.2 When generated 87
149.2.2.7.3 Effect of receipt 87
149.2.2.8 PMA_REMRXSTATUS.request 88
149.2.2.8.1 Semantics of the primitive 88
149.2.2.8.2 When generated 88
149.2.2.8.3 Effect of receipt 88
149.2.2.9 PMA_PCSDATAMODE.indication 88
149.2.2.9.1 Semantics of the primitive 88
149.2.2.9.2 When generated 88
149.2.2.9.3 Effect of receipt 88
149.2.2.10 PMA_PCS_RX_LPI_STATUS.request 88
149.2.2.10.1 Semantics of the primitive 89
149.2.2.10.2 When generated 89
149.2.2.10.3 Effect of receipt 89
149.2.2.11 PMA_PCS_TX_LPI_STATUS.request 89

Copyright © 2020 IEEE. All rights reserved.

149.2.2.11.1 Semantics of the primitive ... 89
149.2.2.11.2 When generated ... 89
149.2.2.11.3 Effect of receipt ... 89
149.2.2.12 PMA_ALERTDETECT.indication ... 89
149.2.2.12.1 Semantics of the primitive ... 90
149.2.2.12.2 When generated ... 90
149.2.2.12.3 Effect of receipt ... 90
149.3 Physical Coding Sublayer (PCS) functions ... 90
149.3.1 PCS service interface (XGMII) ... 90
149.3.2 PCS functions ... 90
149.3.2.1 PCS Reset function ... 91
149.3.2.2 PCS Transmit function ... 91
149.3.2.2.1 Use of blocks ... 93
149.3.2.2.2 65B RS-FEC transmission code ... 93
149.3.2.2.3 Notation conventions ... 94
149.3.2.2.4 Block structure ... 96
149.3.2.2.5 Control codes ... 97
149.3.2.2.6 Ordered sets ... 97
149.3.2.2.7 Idle (/I/) ... 97
149.3.2.2.8 LPI (/LI/) ... 97
149.3.2.2.9 Start (/S/) ... 97
149.3.2.2.10 Terminate (/T/) ... 98
149.3.2.2.11 Ordered set (/O/) ... 98
149.3.2.2.12 Error (/E/) ... 99
149.3.2.2.13 Transmit process ... 99
149.3.2.2.14 RS-FEC framing and RS-FEC encoder ... 99
149.3.2.2.15 RS-FEC superframe and round-robin interleaving ... 99
149.3.2.2.16 RS-FEC recombine ... 100
149.3.2.2.17 Reed-Solomon encoder ... 100
149.3.2.2.18 PCS scrambler ... 102
149.3.2.2.19 Gray mapping for PAM4 encoding ... 102
149.3.2.2.20 Selectable precoder ... 103
149.3.2.2.21 PAM4 encoding ... 103
149.3.2.2.22 EEE capability ... 104
149.3.2.3 PCS Receive function ... 105
149.3.2.3.1 Frame and block synchronization ... 106
149.3.2.3.2 PCS descrambler ... 106
149.3.2.3.3 Invalid blocks ... 106
149.3.3 Test-pattern generators ... 106
149.3.4 Side-stream scrambler polynomials ... 107
149.3.5 PMA training frame ... 108
149.3.5.1 Generation of symbol Tn ... 108
149.3.5.2 PMA training mode descrambler polynomials ... 108
149.3.6 LPI signaling ... 108
149.3.6.1 LPI synchronization ... 109
149.3.6.2 Quiet period signaling ... 110
149.3.6.3 Refresh period signaling ... 111
149.3.7 Detailed functions and state diagrams ... 111
149.3.7.1 State diagram conventions ... 111
149.3.7.2 State diagram parameters ... 111
149.3.7.2.1 Constants ... 111
149.3.7.2.2 Variables ... 112
149.3.7.2.3 Timers ... 114
149.3.7.2.4 Functions ... 114

Copyright © 2020 IEEE. All rights reserved.

149.3.7.2.5 Counters ... 116
149.3.7.2.6 Messages ... 116
149.3.7.3 State diagrams ... 117
149.3.8 PCS management ... 124
149.3.8.1 Status ... 124
149.3.8.2 Counter ... 124
149.3.8.3 Loopback ... 124
149.3.9 MultiGBASE-T1 operations, administration, and maintenance (OAM) ... 125
149.3.9.1 Definitions ... 125
149.3.9.2 Functional specifications ... 125
149.3.9.2.1 MultiGBASE-T1 OAM frame structure ... 125
149.3.9.2.2 OAM frame data ... 126
149.3.9.2.3 Ping RX ... 127
149.3.9.2.4 Ping TX ... 127
149.3.9.2.5 PHY health ... 127
149.3.9.2.6 OAM message valid ... 128
149.3.9.2.7 OAM message toggle ... 128
149.3.9.2.8 OAM message acknowledge ... 128
149.3.9.2.9 OAM message toggle acknowledge ... 128
149.3.9.2.10 OAM message number ... 128
149.3.9.2.11 OAM message data ... 128
149.3.9.2.12 OAM status ... 129
149.3.9.2.13 OAM Reed-Solomon ... 129
149.3.9.2.14 MultiGBASE-T1 OAM frame acceptance criteria ... 130
149.3.9.2.15 PHY health indicator ... 130
149.3.9.2.16 Ping ... 130
149.3.9.2.17 OAM message exchange ... 130
149.3.9.3 State diagram variable to OAM register mapping ... 132
149.3.9.4 Detailed functions and state diagrams ... 132
149.3.9.4.1 State diagram conventions ... 132
149.3.9.4.2 State diagram parameters ... 133
149.3.9.4.3 Variables ... 133
149.3.9.4.4 Counters ... 137
149.3.9.4.5 Functions ... 137
149.3.9.4.6 State diagrams ... 138
149.4 Physical Medium Attachment (PMA) sublayer ... 140
149.4.1 PMA functional specifications ... 140
149.4.2 PMA functions ... 140
149.4.2.1 PMA Reset function ... 141
149.4.2.2 PMA Transmit function ... 141
149.4.2.2.1 Global PMA transmit disable ... 141
149.4.2.3 PMA Receive function ... 141
149.4.2.4 PHY Control function ... 142
149.4.2.4.1 Infofield notation ... 143
149.4.2.4.2 Start of Frame Delimiter ... 143
149.4.2.4.3 Partial PHY frame count (PFC24) ... 143
149.4.2.4.4 Message Field ... 143
149.4.2.4.5 PHY capability bits ... 144
149.4.2.4.6 Data switch partial PHY frame count ... 144
149.4.2.4.7 Reserved fields ... 145
149.4.2.4.8 CRC16 ... 145
149.4.2.4.9 PMA MDIO function mapping ... 145
149.4.2.4.10 Startup sequence ... 146
149.4.2.5 Link Monitor function ... 146

Copyright © 2020 IEEE. All rights reserved.

149.4.2.6 PHY Link Synchronization 147
149.4.2.6.1 State diagram variables 148
149.4.2.6.2 State diagram timers 149
149.4.2.6.3 Messages 149
149.4.2.6.4 State diagrams 150
149.4.2.7 Refresh monitor function 151
149.4.2.8 Clock Recovery function 151
149.4.3 MDI 151
149.4.3.1 MDI signals transmitted by the PHY 151
149.4.3.2 Signals received at the MDI 151
149.4.4 State variables 151
149.4.4.1 State diagram variables 151
149.4.4.2 Timers 153
149.4.5 State diagrams 154
149.5 PMA electrical specifications 156
149.5.1 Test modes 156
149.5.1.1 Test fixtures 157
149.5.2 Transmitter electrical specifications 158
149.5.2.1 Maximum output droop 158
149.5.2.2 Transmitter linearity 158
149.5.2.3 Transmitter timing jitter 158
149.5.2.3.1 Transmit MDI random jitter in MASTER mode 159
149.5.2.3.2 Transmit MDI deterministic jitter in MASTER mode 159
149.5.2.4 Transmitter power spectral density (PSD) and power level 160
149.5.2.5 Transmitter peak differential output 161
149.5.2.6 Transmitter clock frequency 161
149.5.3 Receiver electrical specifications 161
149.5.3.1 Receiver differential input signals 161
149.5.3.2 Alien crosstalk noise rejection 161
149.6 Management interface 162
149.6.1 Optional Support for Auto-Negotiation 162
149.7 Link segment characteristics 162
149.7.1 Link transmission parameters 162
149.7.1.1 Insertion loss 163
149.7.1.2 Differential characteristic impedance 163
149.7.1.3 Return loss 163
149.7.1.3.1 2.5GBASE-T1 link segment return loss 163
149.7.1.3.2 5GBASE-T1 link segment return loss 164
149.7.1.3.3 10GBASE-T1 link segment return loss 165
149.7.1.4 Coupling attenuation 166
149.7.1.5 Screening attenuation 167
149.7.1.6 Maximum link delay 167
149.7.2 Coupling parameters between link segments 167
149.7.2.1 Power sum alien near-end crosstalk (PSANEXT) 167
149.7.2.2 Power sum alien attenuation to crosstalk ratio far-end (PSAACRF) 168
149.8 MDI specification 169
149.8.1 MDI connectors 169
149.8.2 MDI electrical specification 169
149.8.2.1 MDI return loss 169
149.8.3 MDI fault tolerance 170
149.9 Environmental specifications 170
149.9.1 General safety 170
149.9.2 Network safety 171
149.9.2.1 Environmental safety 171

Copyright © 2020 IEEE. All rights reserved.

149.9.2.2 Electromagnetic compatibility ... 171
149.10 Delay constraints ... 171
149.11 Protocol implementation conformance statement (PICS) proforma for Clause 149, Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, type 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 ... 173
149.11.1 Introduction ... 173
149.11.2 Identification ... 173
149.11.2.1 Implementation identification ... 173
149.11.2.2 Protocol summary ... 173
149.11.3 Major capabilities/options ... 174
149.11.4 PICS proforma tables for Physical Coding Sublayer (PCS), Physical Medium Attachment (PMA) sublayer, and baseband medium, type 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1 ... 174
149.11.4.1 General ... 174
149.11.4.2 Physical Coding Sublayer (PCS) ... 175
149.11.4.2.1 PCS Transmit ... 175
149.11.4.2.2 PCS Receive ... 177
149.11.4.2.3 Test-pattern generators ... 177
149.11.4.2.4 Side-stream scrambler ... 178
149.11.4.2.5 LPI signaling ... 178
149.11.4.2.6 Functions and state diagrams ... 179
149.11.4.2.7 PCS loopback ... 179
149.11.4.2.8 OAM ... 180
149.11.4.3 Physical Medium Attachment (PMA) ... 180
149.11.4.3.1 PMA Reset function ... 180
149.11.4.3.2 PMA Transmit function ... 181
149.11.4.3.3 PMA Receive function ... 182
149.11.4.3.4 PHY Control function ... 182
149.11.4.3.5 Link Monitor function ... 183
149.11.4.3.6 PHY Link Synchronization ... 184
149.11.4.3.7 Refresh monitor function ... 185
149.11.4.3.8 Clock Recovery function ... 185
149.11.4.3.9 MDI ... 185
149.11.4.3.10 PMA State variables ... 185
149.11.4.4 PMA electrical specifications ... 186
149.11.4.4.1 Test modes ... 186
149.11.4.4.2 Transmitter electrical specifications ... 186
149.11.4.4.3 Receiver electrical specifications ... 187
149.11.4.5 Link segment characteristics ... 188
149.11.4.6 MDI specifications ... 188
149.11.4.7 Delay constraints ... 188

Annex 98B (normative) IEEE 802.3 Selector Base Page definition ... 189

98B.3 Technology Ability Field bit assignments ... 189
98B.4 Priority Resolution ... 189

Annex 149A (normative) Coupling and screening attenuation test methodology ... 190

149A.1 Introduction ... 190
149A.2 General test conditions ... 190
149A.3 Reference cable assembly ... 190
149A.4 Measurement setup ... 191

Copyright © 2020 IEEE. All rights reserved.

149A.5 Protocol implementation conformance statement (PICS) proforma for Annex 149A, Coupling and screening attenuation test methodology 193
149A.5.1 Introduction 193
149A.5.2 Identification 193
149A.5.2.1 Implementation identification 193
149A.5.2.2 Protocol summary 193
149A.5.3 Major capabilities/options 194
149A.5.4 PICS proforma tables for Coupling and screening attenuation test methodology 194

Annex 149B (informative) OAM status 196

149B.1 Purpose 196
149B.2 MultiGBASE-T1 OAM status structure 196
149B.3 MultiGBASE-T1 status message data 196
149B.3.1 MultiGBASE-T1 status valid 197
149B.3.2 Power supply warning 197
149B.3.3 Internal temperature warning 197
149B.3.4 No MAC messages warning 197
149B.3.5 Degraded link segment 197
149B.3.6 Polarity inversion 197
149B.3.7 Vendor-specific field 198
149B.3.8 Clear REC 198
149B.3.9 REC cleared 198
149B.3.10 Receive error counter (REC) 198
149B.4 Detailed functions and state diagrams 198
149B.4.1 State diagram conventions 198
149B.4.2 State diagram parameters 198
149B.4.2.1 Variables 198
149B.4.2.2 Counters 199
149B.4.2.3 Messages 199
149B.4.2.4 State diagrams 200

Annex 149C (informative) Tx Function to Rx function channel characteristics 201

149C.1 Overview 201
149C.2 Differential printed circuit board trace loss 201
149C.3 Channel insertion loss 202
149C.4 Channel return loss 202
149C.4.1 Tx/Rx function to MDI return loss 202
149C.4.2 Link segment return loss 204
149C.4.3 Channel return loss concatenation 205
149C.5 Coupling between ports on multiport designs 205

Copyright © 2020 IEEE. All rights reserved.

IEEE Standard for Ethernet

Amendment 8: Physical Layer Specifications and Management Parameters for 2.5 Gb/s, 5 Gb/s, and 10 Gb/s Automotive Electrical Ethernet

(This amendment is based on IEEE Std 802.3™-2018 as amended by IEEE Std 802.3cb™-2018, IEEE Std 802.3bt™-2018, IEEE Std 802.3cd™-2018, IEEE Std 802.3cn™-2019, IEEE Std 802.3cg™-2019, IEEE Std 802.3cq™-2020, and IEEE Std 802.3cm™-2020.)

NOTE—The editing instructions contained in this amendment define how to merge the material contained therein into the existing base standard and its amendments to form the comprehensive standard.

The editing instructions are shown in ***bold italic***. Four editing instructions are used: change, delete, insert, and replace. ***Change*** is used to make corrections in existing text or tables. The editing instruction specifies the location of the change and describes what is being changed by using ~~strikethrough~~ (to remove old material) and underscore (to add new material). ***Delete*** removes existing material. ***Insert*** adds new material without disturbing the existing material. Deletions and insertions may require renumbering. If so, renumbering instructions are given in the editing instruction. ***Replace*** is used to make changes in figures or equations by removing the existing figure or equation and replacing it with a new one. Editing instructions, change markings, and this NOTE will not be carried over into future editions because the changes will be incorporated into the base standard.

Cross references that refer to clauses, tables, equations, or figures not covered by this amendment are highlighted in green.[1]

[1] Notes in text, tables, and figures are given for information only and do not contain requirements needed to implement the standard.

Copyright © 2020 IEEE. All rights reserved.

1. Introduction

1.3 Normative references

Insert the following references in 1.3 in alphanumeric order as follows:

IEC 62153-4-7, Metallic communication cable test methods—Part 4-7: Electromagnetic compatibility (EMC)—Test method for measuring of transfer impedance Z_T and screening attenuation a_S or coupling attenuation a_C of connectors and assemblies up to and above 3 GHz—Triaxial tube in tube method.[2]

1.4 Definitions

Insert a new definition for 10GBASE-T1 after 1.4.69 10GBASE-T as follows:

1.4.69a 10GBASE-T1: IEEE 802.3 Physical Layer specification for a 10 Gb/s Ethernet full duplex local area network over a single balanced pair of conductors. (See IEEE Std 802.3, Clause 149.)

Insert a new definition for 2.5GBASE-T1 after 1.4.82 2.5GBASE-T and before 1.4.82a 2.5GBASE-X (as inserted by IEEE Std 802.3cb-2018) as follows:

1.4.82aa 2.5GBASE-T1: IEEE 802.3 Physical Layer specification for a 2.5 Gb/s Ethernet full duplex local area network over a single balanced pair of conductors. (See IEEE Std 802.3, Clause 149.)

Insert a new definition for 5GBASE-T1 after 1.4.129 5GBASE-T and before 1.4.129a 5GSEI (as inserted by IEEE Std 802.3cb-2018) as follows:

1.4.129aa 5GBASE-T1: IEEE 802.3 Physical Layer specification for a 5 Gb/s Ethernet full duplex local area network over a single balanced pair of conductors. (See IEEE Std 802.3, Clause 149.)

Change the definition of Infofield in 1.4.289 as follows:

1.4.289 Infofield: A 16 octet frame transmitted at regular intervals containing messages for startup operation by certain PHYs. (See IEEE Std 802.3, Clause 55, Clause 113, and Clause 126.) Also a 12-octet frame transmitted at regular intervals containing messages for startup operation by certain PHYs. (See IEEE Std 802.3, Clause 97 and Clause 149.)

Insert a new definition for MultiGBASE-T1 after 1.4.333 MultiGBASE-T (re-numbered from 1.4.334 due to the deletion of 1.4.294 by IEEE Std 802.3bt-2018) as follows:

1.4.333a MultiGBASE-T1: PHYs that belong to the set of specific BASE-T1 PHYs at speeds in excess of 1000 Mb/s, including 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1. (See IEEE Std 802.3, Clause 149.)

Insert a new definition for Type F PoDL System after 1.4.494a Type E PoDL System (as inserted by IEEE Std 802.3cg-2019) as follows:

1.4.494b Type F PoDL System: A system comprising a PoDL PSE, link section, and PD that are compatible with 2.5GBASE-T1, 5GBASE-T1, and 10GBASE-T1.

[2]IEC publications are available from the International Electrotechnical Commission (https://www.iec.ch/) and the American National Standards Institute (https://www.ansi.org).

Copyright © 2020 IEEE. All rights reserved.