ISO/IEC TR 22560

Edition 1.0 2017-10

TECHNICAL REPORT

colour inside

Information technology – Sensor network – Guidelines for design in the aeronautics industry: active air-flow control



ISO/IEC TR 22560:2017-10(en)



THIS PUBLICATION IS COPYRIGHT PROTECTED
Copyright © 2017 ISO/IEC, Geneva, Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either IEC or IEC's member National Committee in the country of the requester. If you have any questions about ISO/IEC copyright or have an enquiry about obtaining additional rights to this publication, please contact the address below or your local IEC member National Committee for further information.

IEC Central Office
3, rue de Varembé
CH-1211 Geneva 20
Switzerland

Tel.: +41 22 919 02 11
Fax: +41 22 919 03 00
info@iec.ch
www.iec.ch

About the IEC
The International Electrotechnical Commission (IEC) is the leading global organization that prepares and publishes International Standards for all electrical, electronic and related technologies.

About IEC publications
The technical content of IEC publications is kept under constant review by the IEC. Please make sure that you have the latest edition, a corrigenda or an amendment might have been published.

IEC Catalogue - webstore.iec.ch/catalogue
The stand-alone application for consulting the entire bibliographical information on IEC International Standards, Technical Specifications, Technical Reports and other documents. Available for PC, Mac OS, Android Tablets and iPad.

IEC publications search - www.iec.ch/searchpub
The advanced search enables to find IEC publications by a variety of criteria (reference number, text, technical committee,…). It also gives information on projects, replaced and withdrawn publications.

IEC Just Published - webstore.iec.ch/justpublished
Stay up to date on all new IEC publications. Just Published details all new publications released. Available online and also once a month by email.

Electropedia - www.electropedia.org
The world's leading online dictionary of electronic and electrical terms containing 20 000 terms and definitions in English and French, with equivalent terms in 16 additional languages. Also known as the International Electrotechnical Vocabulary (IEV) online.

IEC Glossary - std.iec.ch/glossary
65 000 electrotechnical terminology entries in English and French extracted from the Terms and Definitions clause of IEC publications issued since 2002. Some entries have been collected from earlier publications of IEC TC 37, 77, 86 and CISPR.

IEC Customer Service Centre - webstore.iec.ch/csc
If you wish to give us your feedback on this publication or need further assistance, please contact the Customer Service Centre: csc@iec.ch.

ISO/IEC TR 22560

Edition 1.0 2017-10

TECHNICAL REPORT

colour inside

Information technology – Sensor network – Guidelines for design in the aeronautics industry: active air-flow control

INTERNATIONAL
ELECTROTECHNICAL
COMMISSION

ICS 35.110; 49.060

ISBN 978-2-8322-4920-8

Warning! Make sure that you obtained this publication from an authorized distributor.

CONTENTS

FOREWORD 5
INTRODUCTION 6
1 Scope 7
2 Normative references 7
3 Terms and definitions 7
4 Symbols (and abbreviated terms) 9
5 Motivations for active air-flow control (AFC) 11
5.1 Skin drag 11
5.2 Approaches for Aircraft Skin Drag Reduction 12
6 Objectives 13
6.1 General 13
6.2 Fuel efficiency 13
6.3 Hybrid dense wired-wireless sensor and actuator networks 13
6.4 Standardized and service oriented wireless sensor architecture 13
6.5 Re/auto/self- configuration 13
6.6 Communication protocols and scalability 13
6.7 Smart actuation profiles and policies 14
6.8 High rate sensor measurement, synchronous operation and data compression 14
6.9 Troubleshooting and fail safe operation 14
6.10 Enabling of wireless communication technologies in aeronautics industry 14
6.11 Integration of wireless technologies with the internal aeronautical communication systems 14
6.12 Design of bidirectional wireless transmission protocols for relaying of aeronautical bus communication traffic 14
6.13 Matching of criticality levels of aeronautics industry 14
6.14 Internetworking and protocol translation between wireless and wireline aeronautical networks 14
7 System description 15
7.1 Overview of system operation 15
7.2 Patch design 16
7.3 Internal aeronautics network 17
8 Micro-sensors and actuators 18
8.1 Micro-sensors 18
8.2 Actuators 19
9 High level architecture for aeronautical WSANs 21
9.1 Bubble concept 21
9.2 Layered model 21
9.3 Mapping to ISO/IEC 29182 Sensor Networks Reference Architecture (SNRA) 23
10 Requirements for AFC design 28
10.1 Sensing and actuation 28
10.1.1 BL position detection and space-time resolution 28
10.1.2 Efficient flow control actuation 28
10.1.3 Patch intra and inter-communication 29
10.1.4 Patch sensor data pre-processing, fusion, management and storage. 29
10.1.5 Patch configuration, redundancy, and organization 29
10.1.6 Sensors synchronicity 30

10.1.7 Low power sensor-actuator (patch) consumption 30
10.1.8 Patch data rate and traffic constraints 30
10.1.9 Patch low complexity 30
10.2 Sensor Network Communications 31
10.2.1 Interference 31
10.2.2 Wireless range and connectivity 31
10.3 Aeronautical Network and On-Board Systems 31
10.3.1 Full-duplex communications 31
10.3.2 Compatibility with avionics internal network (ARINC 664) 31
10.3.3 AFC interface 32
10.3.4 GS interface 32
11 Testing platform and prototype development 32
12 Scalability 33
Annex A (informative) System level simulation 36
A.1 Architecture of the simulator and module description 36
A.1.1 Fluid modelling domain 36
A.1.2 Sensor and actuators configuration: patches 36
A.1.3 Wing design, aircraft configuration, and propagation modelling 36
A.1.4 Radio resource management 37
A.2 Simulation metrics 38
A.2.1 AFC metrics 38
A.2.2 WSN metrics 39
Annex B (informative) Turbulent flow modeling 40
Bibliography 44

Figure 1 – Drag breakdown in commercial aircraft 11
Figure 2 – Boundary layer (BL) transition exemplified with a wing profile 12
Figure 3 – Operation mode of the AFC system 15
Figure 4 – Architecture of the AFC system 16
Figure 5 – Array(s) of patches of sensors/actuators 17
Figure 6 – Interaction with internal avionics networks 18
Figure 7 – Flow control actuators classified by function [22] 20
Figure 8 – Flow control actuators: a) SJA; b) Fliperon 21
Figure 9 – HLA mapping AFC system 22
Figure 10 – Mapping AFC system to the ISO domain reference architecture view 24
Figure 11 – Mapping AFC system to the ISO layered reference architecture view 25
Figure 12 – Mapping AFC system to the ISO sensor node reference architecture 25
Figure 13 – Mapping AFC system to the ISO physical reference architecture 26
Figure 14 – Prototype implementation AFC system 33
Figure 15 – Data rate vs patch size 35
Figure A.1 – Simulator architecture 38
Figure B.1 – Characteristics of turbulent flow with different Reynolds numbers (reproduced from [31]) 41

Table 1 – Mapping of AFC system to the HLA layered model 23
Table 2 – Mapping of AFC architecture to ISO architecture entity and functional models..... 27
Table 3 – Mapping of AFC system to ISO architecture interface model 28

INFORMATION TECHNOLOGY – SENSOR NETWORK – GUIDELINES FOR DESIGN IN THE AERONAUTICS INDUSTRY: ACTIVE AIR-FLOW CONTROL

FOREWORD

1) ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

2) The formal decisions or agreements of IEC and ISO on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees and ISO member bodies.

3) IEC, ISO and ISO/IEC publications have the form of recommendations for international use and are accepted by IEC National Committees and ISO member bodies in that sense. While all reasonable efforts are made to ensure that the technical content of IEC, ISO and ISO/IEC publications is accurate, IEC or ISO cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.

4) In order to promote international uniformity, IEC National Committees and ISO member bodies undertake to apply IEC, ISO and ISO/IEC publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any ISO, IEC or ISO/IEC publication and the corresponding national or regional publication should be clearly indicated in the latter.

5) ISO and IEC do not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. ISO or IEC are not responsible for any services carried out by independent certification bodies.

6) All users should ensure that they have the latest edition of this publication.

7) No liability shall attach to IEC or ISO or its directors, employees, servants or agents including individual experts and members of their technical committees and IEC National Committees or ISO member bodies for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication of, use of, or reliance upon, this ISO/IEC publication or any other IEC, ISO or ISO/IEC publications.

8) Attention is drawn to the normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.

9) Attention is drawn to the possibility that some of the elements of this ISO/IEC publication may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

The main task of the joint technical committee is to prepare International Standards. However, the joint technical committee may propose the publication of a Technical Report when it has collected data of a different kind from that which is normally published as an International Standard, for example "state of the art".

ISO/IEC TR 22560, which is a Technical Report, has been prepared by subcommittee 41: Internet of Things and related technologies, of ISO/IEC joint technical committee 1: Information technology.

This Technical Report has been approved by vote of the member bodies, and the voting results may be obtained from the address given on the second title page.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.

INTRODUCTION

The number of wireless connections is growing exponentially around the world. Wireless communications are expanding to areas previously reluctant to use this type of technology. In the field of aeronautics, wireless intra-avionics applications are just recently gaining acceptance both in industrial and academic arenas. This late adoption is mainly because wireless transmissions have been conventionally associated with reliability and interference issues. Aeronautics applications on board aircraft are highly critical and therefore the inherent randomness of wireless technologies created lots of skepticism, particularly for sensing, monitoring and control of critical aeronautical subsystems. In addition, uncontrolled wireless transmissions can potentially create interference to other aeronautical subsystems, thus leading to malfunctions and unsafe operation. However, recent interference and reliability studies with state-of-the-art wireless standards suggest safe operation and thus the feasibility of a relatively new research area called wireless avionics intra-communications (WAICs). In the last few years, wireless technology has started to be used on board for systems that conventionally used only wire-line infrastructure (i.e., as replacement of cables). It is also being used for applications which are now only possible thanks to the wireless component (e.g., indoor localization, tracking and wireless power transfer). Examples of potential applications of wireless avionics intra-communications are the following: structure health monitoring, avionics bus communications, smoke sensors, interference monitoring, logistics, identification, replacing of cables, fuel tank sensors, automatic route control based on optimized fuel consumption and weather monitoring, automatic turbulence reduction or active air-flow control, EMI (electromagnetic interference) monitoring, and flexible wiring redundancy design.

The avionics industry will experience a wireless revolution in the years to come. The concept of “fly-by-wireless” opens several issues in design, configuration, security, spectrum management, and interference control. There are several advantages in the use of wireless technologies for the aeronautics industry. They permit reduction of cables in aircraft design, thus reducing weight. Reduction of weight also leads to increased payload capacity, longer ranges, faster speeds, and mainly savings in fuel consumption. The reduction of cables can also improve the flexibility of aircraft design (less manpower for designing complex cabling infrastructure). Additionally, wireless technologies can reach places of aircraft that are difficult to reach by cables, while being relatively immune to electrical cable malfunctions. Wireless technology also provides improved configuration and troubleshooting with over-the-air functionalities of modern radio standards.

This document presents the application of wireless sensor and actuator networks for the dynamic tracking and compensation of turbulent flows across the surface of aircraft. Turbulent flow formation and the associated skin drag effect are responsible for the inefficiency of airplane design and thus act as major factors in increased fuel consumption. The area of active air-flow control represents the convergence of several scientific fields such as: fluid mechanics, sensor networks, control theory, computational fluid dynamics, and actuator design. Due to the high speeds experienced by modern commercial aircraft, dense networks of sensors and actuators are necessary to accurately track the formation of turbulent flows and for counteracting their effects by convenient actuation policies. The use of wireless technologies in this field aims to facilitate the management of the information generated by the large number of sensors, and reduce the need for cables to interconnect all the nodes or groups of nodes (patches) in the network. Additionally, the use of the wireless components opens new issues in joint propagation and turbulence flow modelling. This document presents the design principles of active air-flow control systems using dense wireless/wired sensor networks compliant with the ISO sensor network reference architecture (SNRA). Standardized interfaces will help developers create smart cloud avionics applications that will improve fleet management, optimized route traffic, and computation of actuation profiles for different moments of an aircraft mission. This also lies within the context of future technological concepts such as Internet of things, Big Data, and cloud computing.

INFORMATION TECHNOLOGY – SENSOR NETWORK – GUIDELINES FOR DESIGN IN THE AERONAUTICS INDUSTRY: ACTIVE AIR-FLOW CONTROL

1 Scope

This document describes the concepts, issues, objectives, and requirements for the design of an active air-flow control (AFC) system for commercial aircraft based on a dense deployment of wired/wireless sensor and actuator networks. The objective of this AFC system is to track gradients of pressure across the surface of the fuselage of aircraft. This collected information will be used to activate a set of actuators that will attempt to reduce the skin drag effect produced by the separation between laminar and turbulent flows. This will be translated into increased lift-off forces, higher vehicle speeds, longer ranges, and reduced fuel consumption. The document focuses on the architecture design, module definition, statement of objectives, scalability analysis, system-level simulation, as well as networking and implementation issues using standardized interfaces and service-oriented middleware architectures. This document aims to serve as guideline on how to design wireless sensor and actuator networks compliant with ISO/IEC 29182.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 29182-2:2013, *Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 2: Vocabulary and terminology*

ISO/IEC 29182-3:2014, *Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 3: Reference architecture views*

ISO/IEC 29182-4:2013, *Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 4: Entity models*

ISO/IEC 29182-5:2013, *Information technology – Sensor networks: Sensor Network Reference Architecture (SNRA) – Part 5: Interface definitions*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 29182-2:2013 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at http://www.electropedia.org/
- ISO Online browsing platform: available at http://www.iso.org.obp

3.1
active air-flow control
AFC
ability to manipulate a flow field to improve efficiency or performance adding energy to the flow by an actuator and using a sensor or sensors to adjust, optimize, and turn on/off the actuation policy

3.2
ARINC 664
A664
standard that defines the electrical and protocol specifications (IEEE 802.3 and ARINC 664, Part 7) for the exchange of data between avionics subsystems [1][1]

3.3
boundary layer
BL
region in the immediate vicinity of a bounding surface in which the velocity of a flowing fluid increases rapidly from zero and approaches the velocity of the main stream [2]

3.4
boundary layer separation
detachment of a boundary layer from the surface into a broader wake [3], [4]

3.5
bubble
higher level abstraction of a heterogeneous wireless sensor network with different underlying technologies that enables semantic interoperability between them and with the external world using standardized interfaces and flexible middleware application program interfaces

3.6
computational fluid dynamics
CFD
art of using a computer to predict how gases and liquids flow [5]

3.7
drag
force acting opposite to the relative motion of any object moving with respect to a surrounding fluid [29]

3.8
fly-by-wireless
paradigm where avionics subsystems usually controlled or linked by means of cables will use now a wireless connection

3.9
fuselage
aircraft's main body section that holds crew and passengers or cargo [6]

3.10
laminar flow
flow regime that typically occurs at the lower velocities where the particles of fluid move entirely in straight lines even though the velocity with which the particles move along one line is not necessarily the same as along another line [7]

---

1 Numbers in square brackets refer to the Bibliography.

3.11
patch
array of sensors and actuators wired together with a central or distributed control scheme

3.12
Reynolds number
number that characterizes the relative importance of inertial and viscous forces in a flow

Note 1 to entry: It is important in determining the state of the flow, whether it is laminar or turbulent [7].

3.13
shear force
force acting on a substance in a direction perpendicular to the extension of the substance, acting in a direction to a planar cross section of a body [8]

3.14
skin friction drag
effect that arises from the friction of the fluid against the "skin" of the object that is moving through it [30]

3.15
synthetic jet actuator
type of actuator whose main effect is produced by the interactions of a train of vortices that are typically formed by alternating momentary ejection and suction of fluid across an orifice such that the net mass flux is zero [8]

3.16
turbulence
type of flow where the paths of individual particles of fluid are no longer everywhere straight (as in laminar flow) but are sinuous, intertwining and crossing one another in a disorderly manner so that a thorough mixing of fluid takes place [2]

3.17
viscosity
resistance of a fluid to a change in shape, or to the movement of neighbouring portions relative to one another [9]

3.18
wireless avionics intra-communications
type of wireless communications within an aircraft [10]

4 Symbols and abbreviated terms

4.1 Abbreviated terms

AFC	Active air-Flow Control
A664	ARINC 664
AGP	Accelerated Graphics Port
AOC	Airline Operation Control
ARINC	Aeronautical Radio INC.
BL	Boundary Layer
CAD	Computer Aided Design
CFD	Computational Fluid Dynamics
GS	Ground Systems
HLA	High-Level Architecture