TECHNICAL REPORT

ISO/IEC TR 23008-13

Third edition
2020-12

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 13: MMT implementation guidance

Reference number
ISO/IEC TR 23008-13:2020(E)

© ISO/IEC 2020



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2020

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

© ISO/IEC 2020 – All rights reserved

Contents

Page

Foreword ... **vii**

Introduction ... **ix**

1 Scope ... **1**

2 Normative references ... **1**

3 Terms and definitions ... **1**

4 General overview of MPEG media transport ... **1**
4.1 System overview ... 1
4.2 Tools specified in ISO/IEC 23008-1 ... 2

5 MMT function deployments ... **3**
5.1 General ... 3
5.2 Object reconstruction ... 3
5.2.1 General ... 3
5.2.2 Recovery in MPU mode ... 4
5.2.3 Recovery in GFD mode ... 6
5.3 Default assets ... 6
5.4 Low-delay live streaming ... 7
5.5 Parallel processing in MMT sending and receiving entities ... 9
5.5.1 Processing in MMT sending entity ... 9
5.5.2 Processing in MMT receiving entity ... 11
5.6 MPU streaming for live services ... 13
5.6.1 MPU packetization ... 13
5.6.2 Sending of MPU and signalling message ... 16
5.6.3 MPU generation for SHVC-encoded video in real-time streaming ... 17
5.7 Fast MMT session acquisition ... 19
5.8 Referencing and processing non-timed data ... 20
5.8.1 General ... 20
5.8.2 Resource grouping and referencing ... 20
5.8.3 Receiver handling ... 21
5.9 Media adaptation for quality control in MMTP ... 21
5.9.1 General ... 21
5.9.2 Parameters for media adaptation ... 21
5.9.3 Adaptation operation of MMT entity ... 21
5.10 Hybrid delivery in MMT ... 22
5.10.1 General ... 22
5.10.2 Classification of hybrid delivery ... 22
5.10.3 Technical elements for hybrid delivery ... 23
5.11 Example of detailed implementation of MMT ... 24
5.11.1 Use case: Combination of MMT and MPEG-2 TS for synchronized presentation ... 24
5.11.2 Use case: Combination of MMT and HTTP streaming for synchronized decoding ... 24
5.11.3 Use case: Content request in advance for synchronized play-out ... 25
5.12 HRBM signalling for hybrid delivery ... 26
5.12.1 Hybrid delivery from the single MMT sending entity ... 26
5.12.2 Hybrid delivery from the multiple MMT sending entities ... 27
5.13 Error resilience in MMT protocol ... 29
5.14 Delay constrained ARQ ... 30
5.14.1 General ... 30
5.14.2 Delivery-time constrained ARQ ... 30
5.14.3 Arrival-deadline constrained ARQ ... 31
5.15 Delivery of encrypted MPUs ... 33
5.16 HRBM message updating ... 33
5.16.1 General ... 33

© ISO/IEC 2020 – All rights reserved

5.16.2 HRBM message sending schedule 34
5.16.3 Use case 34
5.16.4 HRBM buffer operation in unicast environment 35
5.17 MMTP packet with padded data 37
5.18 Constraints on signalling splicing points 39
5.18.1 General 39
5.18.2 Constraints on Case 1 – Asset change at the start of MPU 39
5.18.3 Constraints on Case 2 – Asset change at a point in MPU 39
5.18.4 Signal the splicing point for target assets in Case 1 and Case 2 40

6 Use cases for MMT deployment 40
6.1 General 40
6.2 Delivery of DASH presentations using MMT 40
6.2.1 General 40
6.2.2 Delivery of the MPD 41
6.2.3 Delivery of the data segments 41
6.3 Client operation for DASH service delivered through MMT protocol 42
6.3.1 Delivery of MPD with MMTP 42
6.3.2 Delivery and consumption of DASH segments with MMTP 42
6.4 Hybrid of MMT and DASH over heterogeneous network 44
6.5 MMT caching for effective bandwidth utilization 45
6.5.1 Overview of MMT caching middlebox architecture 45
6.5.2 Content-based caching of MMT media 46
6.5.3 MPU sync protocol between server and caching middlebox 48
6.5.4 MMT cache manifest 53
6.6 Usage of ADC signalling message 55
6.6.1 General 55
6.6.2 Operation in MMT sending entity 55
6.6.3 Operation in MANE router 55
6.6.4 Example operation in MMT-receiving entities 55
6.6.5 QoE multiplexing gain and bottleneck coordination 55
6.7 MMT deployment in Japanese broadcasting systems 58
6.7.1 General 58
6.7.2 Broadcasting systems using MMT 59
6.7.3 Media transport protocol 61
6.7.4 Signalling information 66
6.7.5 Start-up procedure of broadcasting service 74
6.7.6 Actual packet structure 77
6.8 MMT deployment in ATSC 3.0 systems 79
6.9 Implementation of MMT based on D-TMB in China 81
6.9.1 Background 81
6.9.2 MMT over legacy DTMB infrastructure 81
6.9.3 Use cases 81
6.10 Conversion of MMTP stream to MPEG-2 TS 83
6.10.1 Overview of conversion operation 83
6.10.2 Restrictions to MMTP packets 83
6.10.3 Calculation of PTS, DTS 83
6.10.4 Restriction related to MPEG-2 T-STD 84
6.10.5 Packet field conversion rule 85
6.10.6 PSI Conversion rule 86
6.11 MMT service provisioning at conventional broadcast environment 87
6.12 Usage of multimedia configuration for interface switching management 89
6.13 MMT signalling for multiple timed text assets 89
6.13.1 Multiple timed text assets within an MMT presentation 89
6.13.2 Selective spatial assignment for multiple timed text assets 90
6.13.3 Example of multiple timed text assets signalling in MMT 92
6.13.4 Carriage of TTML based timed text in MMT 92
6.14 Viewport-dependent baseline media profile with packed streaming for VR 94

 © ISO/IEC 2020 – All rights reserved

7 Application layer forward error correction (AL-FEC) 97
7.1 FEC decoding method for ssbg_mode2 97
7.1.1 General 97
7.1.2 Source symbol block format for ssbg_mode2 97
7.1.3 Regionalization of source symbol Block for FEC decoding 98
7.1.4 How to choose a proper unit of data for FEC decoding 102
7.2 Usage of two stage FEC coding structure 102
7.2.1 General 102
7.2.2 Use case: Hybrid content delivery 103
7.2.3 Use case: Streaming multicasting (or broadcasting) to two different end-user groups which is under two different channel conditions each other 104
7.3 Usage of layer-aware FEC coding structure 104
7.3.1 General 104
7.3.2 Use case 1: Layered multicast streaming 105
7.3.3 Use case 2: Hybrid delivery 106
7.3.4 Use case 3: Fast zapping with long time interleaving (LA-FEC UI) 107
7.3.5 Use case 4: Prioritized transmission 107
7.4 MPU mapping to source packet block 108
7.4.1 General 108
7.4.2 Aligned MPU mapping method to source packet block 108
7.5 FEC for hybrid service 109
7.6 Usage of rate-adaptive AL-FEC 111
7.6.1 General 111
7.6.2 AL-FEC rate control 112
7.7 FEC scheme for interleaved source symbol block 115
7.7.1 General 115
7.7.2 Re-order buffer for interleaved source symbol block 115

8 MMT developments in mobile environments 115
8.1 True realtime video streaming over a lossy channel 115
8.1.1 General 115
8.1.2 Main features 115
8.1.3 Ring buffer in the client 116
8.1.4 FEC/deFEC performance and delay 116
8.1.5 Characteristics of UDP based multi-path and multi-session transmitting for true real-time video streaming 116
8.2 Dynamic asset change 119
8.3 Media adaptation for quality control 121
8.3.1 Use cases of QoS management for adaptive video service 121
8.3.2 Advanced adaptation operation of MMT entity: selective transmission 125
8.4 Transition time decision using MTR and MTN 129
8.5 Usage of DRI and DSI message 130
8.5.1 Overview 130
8.5.2 Operation in MMT sending entity or MANE 130
8.5.3 Operation in MMT receiving entity 131
8.6 Usage of dynamic media resource identification information update 131
8.6.1 General 131
8.6.2 Classification of dynamic media resource allocation 131
8.6.3 Operation in MMT sending entity 131
8.6.4 Operation in MMT receiving entity 132
8.6.5 Example operation in MANE proxy 132
8.7 MMT service list 134
8.8 Usage of DNS message for MMT URL resolution 135
8.8.1 General 135
8.8.2 Example on DNS resolution procedure 135
8.9 Usage of guide information for dynamic media resource allocation 137
8.9.1 General 137
8.9.2 Classification of guide information 137
8.9.3 Classification of dynamic media resource allocation 137

© ISO/IEC 2020 – All rights reserved

8.9.4 Operation in MANEs 138
8.9.5 Operation in MMT sending entity 138
8.9.6 Example of dynamic media resource allocation using guide information 138
8.10 Usage of DARI for supporting DNS in MMT 139
8.10.1 General 139
8.10.2 Classification of DARI proxy 139
8.10.3 Operation in MANE DNS or DNS 140
8.10.4 Operation in DARI proxy 140
8.10.5 Relation between the media resource identification in MMT and DNS message 140
Bibliography **142**

© ISO/IEC 2020 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of document should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents) or the IEC list of patent declarations received (see http://patents.iec.ch).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation of the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by Joint Technical Committee ISO/IEC JTC 1, *Information technology*, Subcommittee SC 29, *Coding of audio, picture, multimedia and hypermedia information*.

This third edition cancels and replaces the second edition (ISO/IEC 23008-13:2017), which has been technically revised. The main changes compared to the previous edition are as follows:

— Guidance added to show how the MMT protocol can transmit media streams adaptively to environment changes such as network congestions, while also minimizing service quality degradation.

— Guidance added to describe the scenario in which MMT and MPEG-2 TS are used as transport schemes in broadband networks and broadcast channels, respectively.

— Guidance added for constraints on signalling splicing points that are specified for changing points or splicing points on MMT assets.

— Application Layer Forward Error Correction (AL-FEC) guidance added to describe the usage of Rate-Adaptive AL-FEC, Layer-Aware (LA) FEC coding structure and FEC scheme for interleaved source symbol block.

— Broadcasting MMT deployment guidance added to describe the implementation of MMT based on D-TMB in China and MMT Deployment in ATSC 3.0 systems.

— MMT deployment guidance added to show the usage of MMT signalling for multiple timed text assets and for the viewport-dependent baseline media profile with packed streaming for VR.

— MMT developments in mobile environments guidance added to describe the usage of true real time video streaming over lossy channels, dynamic asset change, and media adaptation for quality control.

— MMT developments in mobile environments guidance added to describe the usage of signalling messages for supporting Package retransmission and dynamic media resource allocation.

© ISO/IEC 2020 – All rights reserved

A list of all parts in the ISO/IEC 23008 series can be found on the ISO website.

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO/IEC 2020 – All rights reserved

Introduction

This document provides guidance for implementation and deployment of multimedia systems based on ISO/IEC 23008-1. These document include the following:

— Guidance on usage of MMT functions;

— Guidance on deployment use cases designed based on ISO/IEC 23008-1.

© ISO/IEC 2020 – All rights reserved

Information technology — High efficiency coding and media delivery in heterogeneous environments —

Part 13: MMT implementation guidance

1 Scope

This document provides guidance for implementing and deploying systems based on ISO/IEC 23008-1.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO/IEC 23008-1:2017, *Information technology — High efficiency coding and media delivery in heterogeneous environments — Part 1: MPEG media transport (MMT)*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO/IEC 23008-1 apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

4 General overview of MPEG media transport

4.1 System overview

This clause describes the exemplary but typical system overview of MPEG media transport (MMT) as shown in Figure 1.

The media origin provides A/V media or generic files to MMT sending entity in the form of packages or assets which are defined in ISO/IEC 23008-1. A package is comprised of assets, presentation information and transparent characteristics, etc. physically, an asset is a group of MPUs or generic files.

The MMT sending entity fragments MPU/generic files and generates MMTP packets to deliver A/V media data itself. Concurrently, it also generates signalling message for the successful delivery and presentation of A/V media included on that MMTP packet flow.

© ISO/IEC 2020 – All rights reserved