TECHNICAL SPECIFICATION

ISO/IEC TS 30135-6

First edition
2014-11-15

Information technology — Digital publishing — EPUB3 —

Part 6: EPUB Canonical Fragment Identifier

Technologies de l'information — Publications numériques — EPUB3 —

Partie 6: Identificateurs de fragment canoniques EPUB

Reference number
ISO/IEC TS 30135-6:2014(E)

© ISO/IEC 2014



COPYRIGHT PROTECTED DOCUMENT

© ISO/IEC 2014

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

© ISO/IEC 2014 – All rights reserved

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of the joint technical committee is to prepare International Standards. Draft International Standards adopted by the joint technical committee are circulated to national bodies for voting. Publication as an International Standard requires approval by at least 75 % of the national bodies casting a vote.

In other circumstances, particularly when there is an urgent market requirement for such documents, the joint technical committee may decide to publish an ISO/IEC Technical Specification (ISO/IEC TS), which represents an agreement between the members of the joint technical committee and is accepted for publication if it is approved by 2/3 of the members of the committee casting a vote.

An ISO/IEC TS is reviewed after three years in order to decide whether it will be confirmed for a further three years, revised to become an International Standard, or withdrawn. If the ISO/IEC TS is confirmed, it is reviewed again after a further three years, at which time it must either be transformed into an International Standard or be withdrawn.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO and IEC shall not be held responsible for identifying any or all such patent rights.

ISO/IEC TS 30135 series were prepared by Korean Agency for Technology and Standards (as KS X 6070 series) with International Digital Publishing Forum and were adopted, under a special “fast-track procedure”, by Joint Technical Committee ISO/IEC JTC 1, Information technology, in parallel with its approval by the national bodies of ISO and IEC.

ISO/IEC TS 30135 consists of the following parts, under the general title *Information technology — Document description and processing languages — EPUB 3:*

- *Part 1: Overview*
- *Part 2: Publications*
- *Part 3: Content Documents*
- *Part 4: Open Container Format*
- *Part 5: Media Overlay*
- *Part 6: Canonical Fragment Identifier*
- *Part 7: Fixed-Layout Documents*

EPUB Canonical Fragment Identifier (epubcfi) Specification

Recommended Specification 11 October 2011

This version

http://www.idpf.org/epub/linking/cfi/epub-cfi-20111011.html

Latest version

http://www.idpf.org/epub/linking/cfi/epub-cfi.html

Previous version

http://www.idpf.org/epub/linking/cfi/epub-cfi-20110908.html

A diff of changes from the previous draft is available at this link.

Please refer to the errata for this document, which may include some normative corrections.

Copyright © 2011 International Digital Publishing Forum™

All rights reserved. This work is protected under Title 17 of the United States Code. Reproduction and dissemination of this work with changes is prohibited except with the written permission of the International Digital Publishing Forum (IDPF).

EPUB is a registered trademark of the International Digital Publishing Forum.

Editors

Peter Sorotokin, Adobe

Garth Conboy, Google Inc.

Brady Duga, Google Inc.

John Rivlin, Google Inc.

Don Beaver, Apple Inc.

Kevin Ballard, Apple Inc.

Alastair Fettes, Apple Inc.

Daniel Weck, DAISY Consortium

Table of Contents

1. Overview
    - 1.1. Purpose and Scope
    - 1.2. Terminology
    - 1.3. Conformance Statements
2. EPUB CFI Definition
    - 2.1. Introduction
    - 2.2. Syntax
    - 2.3. Character Escaping
3. EPUB CFI Processing
    - 3.1. Path Resolution
        - 3.1.1. Step Reference to Child Node (/)
        - 3.1.2. XML ID Assertion ([)
        - 3.1.3. Step Indirection (!)

3.1.4. Terminating Step – Character Offset (:)
3.1.5. Terminating Step – Temporal Offset (~)
3.1.6. Terminating Step – Spatial Offset (@)
3.1.7. Terminating Step – Temporal-Spatial Offset (~ + @)
3.1.8. Text Location Assertion ([)
3.1.9. Side Bias ([+ ;s=)
3.1.10. Examples
3.2. Sorting Rules
3.3. Intra-Publication CFIs
3.4. Simple Ranges
3.5. Intended Target Location Correction
4. Extending EPUB CFIs
References

1 Overview

1.1 Purpose and Scope

This specification, EPUB Canonical Fragment Identifier (epubcfi), defines a standardized method for referencing arbitrary content within an EPUB® Publication through the use of fragment identifiers.

The Web has proven that the concept of hyperlinking is tremendously powerful, but EPUB Publications have been denied much of the benefit that hyperlinking makes possible because of the lack of a standardized scheme to link into them. Although proprietary schemes have been developed and implemented for individual Reading Systems, without a commonly-understood syntax there has been no way to achieve cross-platform interoperability. The functionality that can see significant benefit from breaking down this barrier, however, is varied: from reading location maintenance to annotation attachment to navigation, the ability to point into any Publication opens a whole new dimension not previously available to developers and Authors.

This specification attempts to rectify this situation by defining an arbitrary structural reference that can uniquely identify any location, or simple range of locations, in a Publication: the EPUB CFI. The following considerations have strongly influenced the design and scope of this scheme:

- The mechanism used to reference content should be interoperable: references to a reading position created by one Reading System should be usable by another.
- Document references to EPUB content should be enabled in the same way that existing hyperlinks enable references throughout the Web.
- Each location in an EPUB file should be able to be identified without the need to modify the document.
- All fragment identifiers that reference the same logical location should be equal when compared.
- Comparison operations, including tests for sorting and comparison, should be able to be performed without accessing the referenced files.
- Simple manipulations should be possible without access to the original files (e.g., given a reference deep in a file, it should be possible to generate a reference to the start of the file).
- Identifier resolution should be reasonably efficient (e.g., processing of the first chapter is not required to resolve a fragment identifier that points to the last chapter).
- References should be able to recover their target locations through parser variations and document revisions.
- Expression of simple, contiguous ranges should be supported.

- An extensible mechanism to accommodate future reference recovery heuristics should be provided.

› 1.2 Terminology

Please refer to the EPUB Specifications for definitions of EPUB-specific terminology used in this document.

Standard EPUB CFI

A Publication-level EPUB CFI links into an EPUB Publication. The path preceding the EPUB CFI references the location of the Publication.

Intra-Publication EPUB CFI

An intra-Publication EPUB CFI allows one Content Document to reference another within the same Publication. The path preceding the EPUB CFI references the current Publication's Package Document.

Refer to Intra-Publication CFIs for more information.

› 1.3 Conformance Statements

The keywords "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119].

All sections of this specification are normative except where identified by the informative status label "This section is informative". The application of informative status to sections and appendices applies to all child content and subsections they may contain.

All examples in this specification are informative.

› 2 EPUB CFI Definition

› 2.1 Introduction

This section is informative

A fragment identifier is the part of an IRI [RFC3987] that defines a location within a resource. Syntactically, it is the segment attached to the of end the resource IRI starting with a hash (`#`). For HTML documents, IDs and named anchors are used as fragment identifiers, while for XML documents the Shorthand XPointer [XPTRSH] notation is used to refer to a given ID.

A Canonical Fragment Identifier (CFI) is a similar construct to these, but expresses a location within an EPUB Publication. For example:

```
book.epub#epubcfi(/6/4[chap01ref]!/4[body01]/10[para05]/3:10)
```

The function-like string immediately following the hash (`epubcfi(…)`) indicates that this fragment identifier conforms to the scheme defined by this specification, and the value contained in the parentheses is the

syntax used to reference the location within the specified Publication (`demo.epub`). Using the processing rules defined in Path Resolution, any Reading System can parse this syntax, open the corresponding Content Document in the Publication and load the specified location for the User.

A complete definition of the EPUB CFI syntax is provided in the next section.

> NOTE
>
> `epub` has been prepended to the name of the scheme as a more generic CFI-like scheme may be defined in the future for all XML+ZIP-based file formats.

› 2.2 Syntax

(EBNF productions ISO/IEC 14977)

fragment	=	"epubcfi(" , (path | range) , ")" ;
path	=	step , local_path ;
range	=	path , "," , local_path , "," , local_path ;
local_path	=	{ step | "!" } , [termstep] ;
step	=	"/" , integer , ["[" , assertion , "]"] ;
termstep	=	terminus , ["[" , assertion , "]"] ;
terminus	=	(":" , integer) | ("@" , number , ":" , number) | ("~" , number) | ("~" , number , "@" , number , ":" , number) ;
number	=	(digit-non-zero , { digit } , ["." , { digit } , digit-non-zero]) | (zero , "." , { digit } , digit-non-zero) ;
integer	=	zero | (digit-non-zero , { digit }) ;
assertion	=	[csv] , { parameter } ;
parameter	=	";" , value-no-space , "=" , csv ;
csv	=	value , { "," , value } ;
value	=	string-escaped-special-chars ;
value-no-space	=	value - ([value] , space , [value]) ;
special-chars	=	circumflex | square-brackets | parentheses | comma | semicolon | equal ;
escaped-special-chars	=	(circumflex , circumflex) | (circumflex , square-brackets) | (circumflex , parentheses) | (circumflex , comma) | (circumflex , semicolon) | (circumflex , equal) ;
character-escaped-special	=	(character - special-chars) | escaped-special-chars ;
string-escaped-special-chars	=	character-escaped-special , { character-escaped-special } ;
	=	

string		character , { character } ;
digit	=	zero | digit-non-zero ;
digit-non-zero	=	"1" | "2" | "3" | "4" | "5" | "6" | "7" | "8" | "9" ;
zero	=	"0" ;
space	=	" " ;
circumflex	=	"^" ;
double-quote	=	"" ;
square-brackets	=	"[" | "]" ;
parentheses	=	"(" | ")" ;
comma	=	"," ;
semicolon	=	";" ;
equal	=	"=" ;
character	=	? Unicode Characters ? ;

› Unicode Characters

The definition of allowed Unicode characters is the same as [XML 1.0]. This excludes the surrogate blocks, FFFE, and FFFF:

```
#x9 | #xA | #xD | [#x20-#xD7FF] | [#xE000-#xFFFD] | [#x10000-#x10FFFF]
```

Document authors are encouraged to avoid "compatibility characters", as defined in section 2.3 of [Unicode]. The characters defined in the following ranges are also discouraged. They are either control characters or permanently undefined Unicode characters:

```
[#x7F-#x84], [#x86-#x9F], [#xFDD0-#xFDEF],
[#x1FFFE-#x1FFFF], [#x2FFFE-#x2FFFF], [#x3FFFE-#x3FFFF],
[#x4FFFE-#x4FFFF], [#x5FFFE-#x5FFFF], [#x6FFFE-#x6FFFF],
[#x7FFFE-#x7FFFF], [#x8FFFE-#x8FFFF], [#x9FFFE-#x9FFFF],
[#xAFFFE-#xAFFFF], [#xBFFFE-#xBFFFF], [#xCFFFE-#xCFFFF],
[#xDFFFE-#xDFFFF], [#xEFFFE-#xEFFFF], [#xFFFFE-#xFFFFF],
[#x10FFFE-#x10FFFF].
```

A Canonical Fragment Identifier (CFI) consists of an initial sequence `epubcfi` that identifies this particular reference method, and a parenthesized path or range. A path is built up as a sequence of structural steps to reference a location. A range is a path followed by two local (or relative) paths that identify the start and end of the range.

Steps can either be navigational or terminating. Navigational steps may be repeated as necessary (e.g., to count elements, to process children or to follow references). There may be only one terminating step, which, if present, must be the last step in the sequence.

Substrings in brackets are extensible assertions that improve the robustness of traversing paths and migrating them from one revision of the document to another. These assertions preserve additional

information about traversed elements of the document, which makes it possible to recover intended location even after some modifications are made to the Publication.

Although the `value` definition in the syntax above allows any a sequence of characters, a circumflex (`^`) must be used to escape the following characters to ensure their presence does not interfere with parsing:

- brackets (`[`,`]`)
- circumflex (`^`)
- comma (`,`)
- parentheses (`(`,`)`)
- semicolon (`;`)

Example of an EPUB CFI that points to a location after the text `2[1]`.

```
epubcfi(/6/7[chap05ref]!/4[body01]/10/2/1:3[2^[1^]])
```

The following rules apply to the use of numbers and integers within the path or range:

- leading zeros are not allowed for numbers or integers (to ensure uniqueness);
- trailing zeros are not allowed in the fractional part of a number;
- zero must be represented as the integer `0`;
- numbers in the range `1 > N > 0` must have a leading `0.`;
- integral numbers must be represented as integers.

› 2.3 Character Escaping

As described in Syntax, the EPUB CFI grammar contains characters that have a special purpose as delimiters within a fragment identifier expression. These characters must be escaped using the circumflex '^' character when *not* used as delimiters, so that they can appear within the EPUB CFI data without being mistaken for delimiters. . Depending on the usage context of such EPUB CFI, further character escaping may be required in order to ensure that all potentially-conflicting text tokens are encoded correctly.

- IRI and URI references:
    - The EPUB CFI (fragment identifier) scheme is designed to be used within URI and IRI references. The [RFC3986] specification defines a number of "reserved" characters that have a specific purpose as delimiters, and which may need to be escaped in cases when they would otherwise conflict with the syntactical structure of the URI/IRI reference. The character used for escaping is the percent sign '`%`', and escapable characters get percent-encoded. For example, the percent character itself becomes "`%25`" when it gets escaped (note the difference with EPUB CFI's circumflex '^', which gets escaped using a double character '`^^`').
    - Unlike IRI references, URI references require unicode characters to be ASCII-encoded. Although the EPUB specification itself is based on IRIs (i.e. authors and production tools are expected to use IRIs), some systems or APIs may only support URIs. As a result, implementors may still need too handle the conversion of IRI to URI references, as defined in [RFC3987]. Disallowed characters are escaped as follows:
        - Each disallowed character is converted to UTF-8 [RFC2279] as one or more bytes. The disallowed characters in URI references include all non-ASCII characters, plus