TECHNICAL REPORT

ISO/TR 10093

Second edition
2018-10

Plastics — Fire tests — Standard ignition sources

Plastiques — Essais au feu — Sources d'allumage normalisées

Reference number
ISO/TR 10093:2018(E)

© ISO 2018



COPYRIGHT PROTECTED DOCUMENT

© ISO 2018

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
CP 401 • Ch. de Blandonnet 8
CH-1214 Vernier, Geneva
Phone: +41 22 749 01 11
Fax: +41 22 749 09 47
Email: copyright@iso.org
Website: www.iso.org

Published in Switzerland

 © ISO 2018 – All rights reserved

Contents

Page

Foreword ..... **v**
Introduction ..... **vi**
1 Scope **1**
2 Normative references **1**
3 Terms and definitions **1**
4 Ignition processes **4**
5 Characteristics of ignition sources **4**
6 General principles **5**
6.1 Flaming ignition sources 5
6.1.1 Diffusion flame ignition source 5
6.1.2 Premixed flame source 5
6.1.3 Issues associated with flaming ignition sources 5
6.2 Non-flaming ignition sources 6
7 Smouldering (cigarette) ignition sources **7**
7.1 Traditional cigarettes 7
7.2 Non-reduced ignition propensity cigarettes 8
8 Non-flaming electrical ignition sources **8**
8.1 Glow-wire ignition 8
8.2 Hot-wire ignition 9
9 Radiant ignition sources **10**
9.1 Conical radiant ignition sources 10
9.1.1 General 10
9.1.2 Cone calorimeter ignition source 11
9.1.3 Smoke chamber conical heater 14
9.1.4 Ignition source from periodic flaming ignition test 17
9.2 Other radiant ignition sources 18
9.2.1 Glowbars ignition source 18
9.2.2 Lateral ignition and flame spread test (LIFT) radiant panel heater. 19
9.2.3 Setchkin ignition 20
10 Infrared heating system **21**
11 Diffusion flame ignition **22**
11.1 Needle flame ignition 22
11.2 Burning match 23
11.3 Burners generating 50 W or 500 W flames 25
12 Premixed burners **28**
12.1 Premixed burner for 1 kW flame 28
12.2 Burners for vertical cable tray tests 29
12.2.1 Venturi burners for 20 kW vertical cable tray tests 29
12.2.2 Burner for vertical riser cable tests 31
12.3 Burner for large scale horizontal tests 31
12.4 Burners for room corner tests 32
12.4.1 Burner for ISO 9705-1 32
12.4.2 Alternate burner for room corner test 33
12.5 Burners for individual product heat release tests 34
12.5.1 Burner for single fuel package calorimeter 34
12.5.2 Square tube propane burner 34
12.5.3 T-shaped propane burner 35
12.5.4 Dual T-shaped propane burner 35
13 Other ignition sources **36**

© ISO 2018 – All rights reserved

13.1 Wood cribs 36
13.2 Paper bags 37
Bibliography **38**

© ISO 2018 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular, the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see the following URL: www.iso.org/iso/foreword.html.

This document was prepared by Technical Committee ISO/TC 61, *Plastics*, Subcommittee SC 4, *Burning behaviour*.

This second edition cancels and replaces the first edition (ISO/TR 10093:2017), which has been technically revised. The main changes compared to the previous edition are as follows:

— general changes and updates have been made following early publication of the previous edition;

— Clause 3: terms and definitions have been updated to align and with the definitions in ISO 13943:2017;

— Table 1 has been corrected: Column 2 for “Premixed burner for 1 kW flame” has been corrected to show IEC 60332-1-1 and IEC 60332-1-2;

— Figure 9: reference in note has been corrected to IEC 60695-11-5:2016, Figure 1;

— 11.3.1 has been updated with correct references to IEC standards;

— 12.1.1: “Premixed burner for 1 kW flame” has been corrected to show IEC 60332-1-1 and IEC 60332-1-2;

— 12.1.2 has been updated to state that the flow rates are for the preferred “Method A”;

— 12.1.2 has been updated to change “greater than 98%” to “not less than 95%”.

Any feedback or questions on this document should be directed to the user’s national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

© ISO 2018 – All rights reserved

Introduction

Fires are caused by a wide range of possible ignition sources. Statistical analysis of fires has identified the main primary and secondary sources, especially for fires in buildings. The most frequent sources of fires have been found to be as follows:

a) cooking appliances;

b) space-heating appliances;

c) electric wiring, connectors and terminations;

d) other electrical appliances (such as washing machines, bedwarmers, televisions, water heaters);

e) cigarettes;

f) matches and smokers' gas lighters;

g) blow-lamps, blow-torches and welding torches;

h) rubbish burning; and

i) candles.

The above list covers the major primary ignition sources for accidental fires. Other sources can be involved in fires raised maliciously. Research into causes of fires has shown that primary ignition sources (e.g. glowing cigarettes or dropped flaming matches) can set fire to waste paper, which then acts as a secondary ignition source of greater intensity.

When analysing and evaluating the various ignition sources for applications involving plastics materials, it is important to answer the following questions on the basis of detailed fire statistics.

1) What is the significance of the individual ignition sources in various fire risk situations?

2) What proportion is attributable to secondary ignition sources?

3) Where does particular attention have to be paid to secondary ignition sources?

4) To what extent are different ignition sources responsible for fatal fire accidents?

The following laboratory ignition sources are intended to simulate actual ignition sources that have been shown to be the cause of real fires involving plastics. Laboratory ignition sources are preferred over actual ignition sources due to their consistency, which results in greater data repeatability within a laboratory and greater reproducibility between laboratories.

These laboratory ignition sources can be used to develop new test procedures.

© ISO 2018 – All rights reserved

Plastics — Fire tests — Standard ignition sources

1 Scope

This document describes and classifies a range of laboratory ignition sources for use in fire tests on plastics and products consisting substantially of plastics. These sources vary in intensity and area of impingement. They are suitable for use to simulate the initial thermal abuse to which plastics are potentially exposed in certain actual fire risk scenarios.

Different standards developing organizations have issued many standard test methods, specifications and regulations to assess fire properties of plastics or of products containing plastic materials. Many of those standards contain ignition sources associated with flaming and non-flaming ignition. This document describes the ignition sources and references the associated standard.

This compilation of ignition sources does not discuss the application of the standard where the ignition source is described and is likely not to be a fully comprehensive list of ignition sources.

This document does not address detailed test procedures.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 13943, *Fire safety — Vocabulary*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 13943 and the following apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at https://www.iso.org/obp

— IEC Electropedia: available at http://www.electropedia.org/

3.1
afterflame
flame (3.8) that persists after the ignition source has been removed

[SOURCE: ISO 13943:2017, 3.11]

3.2
afterflame time
length of time for which an *afterflame* (3.1) persists under specified conditions

[SOURCE: ISO 13943:2017, 3.12]

3.3
afterglow
persistence of glowing combustion after both removal of the ignition source and the cessation of any flaming combustion

[SOURCE: ISO 13943:2017, 3.13]

© ISO 2018 – All rights reserved

3.4
afterglow time
length of time for which an *afterglow* (3.3) persists under specified conditions

[SOURCE: ISO 13943:2017, 3.14]

3.5
combustion
exothermic reaction of a substance with an oxidizing agent

[SOURCE: ISO 13943:2017, 3.55, modified — note has been ommited.]

3.6
ease of ignition
measure of the ease with which a test specimen can be ignited, under specified conditions

[SOURCE: ISO 13943:2017, 3.212]

3.7
exposed surface
surface of a test specimen subjected to the heating conditions of a fire test

[SOURCE: ISO 13943:2017, 3.106]

3.8
flame, noun
rapid, self-sustaining, sub-sonic propagation of *combustion* (3.5) in a gaseous medium, usually with emission of light

[SOURCE: ISO 13943:2017, 3.159]

3.9
flame, verb
produce *flame* (3.8)

[SOURCE: ISO 13943:2017, 3.160]

3.10
flaming debris
burning material separating from a burning item and continuing to *flame* (3.9) on the floor, during a fire or fire test

Note 1 to entry: Alternatively, flaming debris can be burning material, other than drops, which has detached from a test specimen during a fire or fire test and continues to burn.

Note 2 to entry: Compare with the terms *flaming droplets* (3.11).

[SOURCE: ISO 13943:2017, 3.176]

3.11
flaming droplets
flaming molten or flaming liquefied drops which fall from the test specimen during the fire test and continue to burn on the floor

Note 1 to entry: Compare with the term *flaming debris* (3.10).

[SOURCE: ISO 13943:2017, 3.177]

© ISO 2018 – All rights reserved

3.12
glowing combustion
combustion (3.5) of a material in the solid phase without *flame* (3.8) but with emission of light from the combustion zone

[SOURCE: ISO 13943:2017, 3.197]

3.13
ignitability
measure of the ease with which a specimen can be *ignited* (3.14), under specified conditions

[SOURCE: ISO 13943:2017, 3.212]

3.14
ignite, transitive verb
initiate *combustion* (3.5)

[SOURCE: ISO 13943:2017, 3.215]

3.15
ignite, intransitive verb
catch fire with or without the application of an external heat source

[SOURCE: ISO 13943:2017, 3.214]

3.16
ignition
initiation of *combustion* (3.5)

[SOURCE: ISO 13943:2017, 3.217]

3.17
ignition source
source of energy that initiates *combustion* (3.5)

[SOURCE: ISO 13943:2017, 3.219]

3.18
ignition time
duration of exposure of a test specimen to a defined *ignition source* (3.17) required for the initiation of sustained *combustion* (3.5) under specified conditions

[SOURCE: ISO 13943:2017, 3.220]

3.19
irradiance
ratio of the radiant flux incident on a small but measurable element of surface containing the point, by the area of that element

[SOURCE: ISO 13943:2017, 3.236]

3.20
minimum ignition temperature
minimum temperature of a material at which sustained *combustion* (3.5) can be initiated under specified test conditions

[SOURCE: ISO 13943:2017, 3.327]

3.21
primary ignition source
first applied *ignition source* (3.17)

© ISO 2018 – All rights reserved

3.22
punking
propagation of a smouldering *combustion* (3.5) front after removal of the *ignition source* (3.17)

3.23
secondary ignition source
heat source which is activated following *ignition* (3.16) from a primary source

3.24
sustained flaming
flame (3.8), on or over the surface of a test specimen, which persists for longer than a defined period of time

Note 1 to entry: Compare with the term *transitory flaming* (3.25).

[SOURCE: ISO 13943:2017, 3.380]

3.25
transitory flaming
flame (3.8), on or over the surface of a test specimen, which persists for a defined short period of time

Note 1 to entry: Compare with the term *sustained flaming* (3.24).

[SOURCE: ISO 13943:2017, 3.408]

4 Ignition processes

4.1 When plastics are exposed to thermal energy, flammable vapours are often generated from their surface. Under suitable conditions (especially high temperatures), it is possible that a critical concentration of flammable vapour will form and spontaneous ignition will result. If a flame is present as the sole energy source, or as a supplementary source, the ignition process will be assisted; this mechanism is sometimes known as piloted ignition.

4.2 A specimen of plastic is regarded as ignited when flames appear on the surface of the plastic or when glowing combustion is evident.

4.3 After ignition has occurred, some burning plastics create additional fire hazards by forming flaming debris or drips. If this flaming debris falls on to combustible material, it is possible that secondary ignition will occur and the fire will spread more rapidly.

4.4 The localized application of a heat source to some plastics results in glowing combustion. With some thermoplastic foams and foams from thermosetting materials, the localized application of a heat source results in punking which produces a carbonaceous char.

5 Characteristics of ignition sources

5.1 The following factors are the main characteristics describing ignition sources and their relation to the test specimen:

a) intensity of the ignition source, which is a measure of the thermal load on the specimen resulting from the combined conduction, convection and radiation effects caused by the ignition source;

b) area of impingement of the ignition source on the specimen;

c) duration of exposure of the specimen and whether it is continuous or intermittent;

d) presentation of the ignition source to the specimen and whether or not it impinges;

© ISO 2018 – All rights reserved