TECHNICAL REPORT

ISO/TR 21414

First edition
2016-02-15

Hydrometry — Groundwater — Surface geophysical surveys for hydrogeological purposes

Hydrométrie — Eaux souterraines — Relevés géophysiques de surface pour des besoins hydrogéologiques

Reference number
ISO/TR 21414:2016(E)

© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

 © ISO 2016 – All rights reserved

Contents

Page

Foreword ..... **vi**
Introduction ..... **vii**
1 Scope **1**
2 Terms and definitions **1**
3 Units of measurement **5**
4 Purpose of geophysical survey **5**
5 Planning **6**
5.1 General considerations 6
5.2 Access to the area 6
5.3 Equipment 6
5.4 Safety and precautions in operation 6
5.5 Planning of survey 7
5.6 Quality control in field data collection 7
5.7 Site/area details 7
6 Electrical resistivity **7**
6.1 Purpose 7
6.2 Principles of measurement 8
6.3 Instruments 13
6.4 Field procedures 13
6.5 Processing of data 15
6.6 Interpretation 15
6.7 Advantages 17
6.8 Disadvantages 17
6.9 Limitations 17
7 Self-potential **18**
7.1 Purpose 18
7.2 Principles of measurement 18
7.3 Instrument 18
7.4 Field procedures 18
7.5 Processing of data 19
7.6 Interpretation 19
7.7 Advantages 19
7.8 Disadvantages 19
7.9 Limitations 19
8 Frequency domain electromagnetic (horizontal loop) **20**
8.1 Purpose 20
8.2 Principles of measurement 20
8.3 Instrument 21
8.4 Field procedures 21
8.5 Processing of data 22
8.6 Interpretations 22
8.7 Advantages 22
8.8 Disadvantages 23
8.9 Limitations 23
9 Transient (time domain) electromagnetic **23**
9.1 Purpose 23
9.2 Principles of measurement 23
9.3 Instrument 23
9.4 Field procedures 24
9.5 Processing of data 24
9.6 Interpretation 24

© ISO 2016 – All rights reserved

9.7 Advantages 24
9.8 Disadvantages 24
9.9 Limitations 25

10 Very low frequency (VLF) electromagnetic 25
10.1 Purpose 25
10.2 Principles of measurement 25
10.3 Instrument 25
10.4 Field procedures 26
10.5 Processing of data 26
10.6 Interpretation 26
10.7 Advantages 27
10.8 Disadvantages 27
10.9 Limitations 27

11 Seismic refraction 27
11.1 Purpose 27
11.2 Principles of measurement 27
11.3 Instruments 31
11.4 Field procedure 31
11.5 Processing of data 32
11.6 Interpretation 32
11.7 Advantages 32
11.8 Disadvantages 32
11.9 Limitations 32

12 Seismic reflection 32
12.1 Purpose 32
12.2 Principles of measurement 33
12.3 Instrument 33
12.4 Field procedures 33
12.5 Acquisition and processing of data 34
12.6 Interpretation 34
12.7 Advantages 34
12.8 Disadvantages 34
12.9 Limitations 35
12.10 Comparison of seismic refraction and reflection methods 35

13 Magnetic 35
13.1 Purpose 35
13.2 Principles of measurement 35
13.3 Instrument 36
13.4 Field procedures 36
13.5 Processing of data 37
13.6 Interpretation 38
13.7 Advantages 38
13.8 Disadvantages 38
13.9 Limitations 38

14 Gravity 38
14.1 Purpose 38
14.2 Principles of measurement 38
14.3 Instrument 39
14.4 Field procedure 39
14.5 Processing of data 39
14.6 Micro-gravity measurements 39
14.7 Interpretation 40
14.8 Advantages 40
14.9 Disadvantages 40
14.10 Limitations 40

 © ISO 2016 – All rights reserved

15 Other techniques **40**
15.1 Induced polarization 40
15.1.1 Purpose 40
15.1.2 Principles of measurement 41
15.1.3 Instrument 41
15.1.4 Field procedures 41
15.1.5 Processing of data 42
15.1.6 Interpretation 42
15.1.7 Advantages 42
15.1.8 Disadvantages 42
15.1.9 Limitations 42
15.2 Mise-a-la-masse 42
15.2.1 Purpose 42
15.2.2 Principles of measurement 42
15.2.3 Instrument 43
15.2.4 Field procedures 43
15.2.5 Processing of data 43
15.2.6 Interpretation 43
15.2.7 Advantages 44
15.2.8 Disadvantages 44
15.2.9 Limitations 44
15.3 Ground-Penetrating Radar (GPR) 44
15.3.1 Purpose 44
15.3.2 Principles of measurements 44
15.3.3 Field procedures and data acquisition 45
15.3.4 Interpretation 47
15.3.5 Advantages 49
15.3.6 Disadvantages 49
16 Report writing and presentation of results **50**
Bibliography **52**

© ISO 2016 – All rights reserved

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: Foreword - Supplementary information.

The committee responsible for this document is ISO/TC 113, *Hydrometry*, Subcommittee SC 8, *Ground water*.

© ISO 2016 – All rights reserved

Introduction

Groundwater is available almost everywhere. Access to clean water is a human right and a basic requirement for economic development. The safest kind of water supply is the use of groundwater. However, its distribution is not uniform due to varying hydrogeological, topographical and climatic conditions. As a result, groundwater is not always available in the required quantity and/or quality, particularly in hard rock terrains where fractures and weathered zones are the primary conduits for groundwater storage and flow. Detailed knowledge on the extent, hydraulic properties, and vulnerability of groundwater reservoirs is necessary to enable a sustainable use of the resources. Therefore, collection of information on prospective groundwater zones, although costly, is essential. Geophysical methods are currently recognized as cost-effective techniques useful for collecting groundwater information. Measuring physical properties of the earth and their variation and then associating these properties with hydrogeological characteristics is the objective of groundwater geophysics.

Of the various geophysical techniques available today, the electrical resistivity method is probably most commonly used due to its relatively simple and economical field operation, its effective response to groundwater conditions and the relative ease with which interpretations can be made. This type of survey is occasionally supplemented by other techniques such as induced polarization, spontaneous potential, and Mise-a-la-Masse galvanic electrical techniques. Other geophysical methods in order of preference used for hydrogeological purpose are electromagnetic, seismic refraction, magnetic, gravity and seismic reflection surveys. More recently developed geophysical techniques include ground probing radar and nuclear magnetic resonance. Because surface geophysical surveys are carried out at the surface of the earth, the responses received from different precisional demarcations. Ambiguity exists in interpreted results and the effective application of these methods often depends on the skill and experience of the investigator, knowledge of local hydrogeological conditions, and the utility (and limitations) of the technique(s) themselves. The application of two or more geophysical techniques is a useful approach to reduce ambiguity. Integration of information from other disciplines, such as remote sensing, geologic mapping, hydrogeological characterization, chemical analysis of well water samples, etc., is also useful for interpreting geophysical field data.

Modern geophysical techniques are highly advanced in terms of instrumentation, field data acquisition, and interpretation. Field data are digitized to enhance the signal-to-noise ratio and computers are used to more accurately analyse and interpret the data. However, the present-day potential of geophysical techniques has probably not been fully realized, not only because such surveys can be expensive, but also because of the inadequate understanding of the application of relevant techniques in diverse hydrogeological conditions.

© ISO 2016 – All rights reserved

Hydrometry — Groundwater — Surface geophysical surveys for hydrogeological purposes

1 Scope

The application of geophysical methods is an evolving science that can address a variety of objectives in groundwater investigations. However, because the successful application of geophysical methods depends on the available technology, logistics, and expertise of the investigator, there can be no single set of field procedures or approaches prescribed for all cases. This Technical Report provides guidelines that are useful for conducting geophysical surveys for a variety of objectives (including environmental aspects), within the limits of modern-day instrumentation and interpretive techniques, are provided. The more commonly used field techniques and practices are described, with an emphasis on electrical resistivity, electromagnetic, and seismic refraction techniques as these are widely used in groundwater exploration. Theoretical aspects and details of interpretational procedures are referred to only in a general way. For full details, reference is intended to be made to specialized texts listed in the Bibliography.

2 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

2.1
acoustic impedance
product of seismic velocity and density of a layer

2.2
anisotropy
variation in physical property with direction of measurement

2.3
apparent resistivity
ratio of measured voltage to input current multiplied by the *geometric factor* (2.16) for the electrode configuration

2.4
blind zone
layer having seismic velocity less than that in the layer overlying it

2.5
Bouguer correction
correction made in observed gravity data to account for the attraction (gravitational) of the rock between the datum and the plane of measurement

2.6
Bouguer anomaly
anomaly obtained after applying latitude, terrain, and elevation (free air and Bouguer) corrections to the observed gravity value and finally subtracting it from measured value at some particular station in the survey area

2.7
contact resistance
electrical resistance developed between an electrode planted in the ground and the ground material immediately surrounding it

© ISO 2016 – All rights reserved

2.8
Dar Zarrouk parameters
longitudinal unit conductance and transverse unit resistance of a geoelectrical layer

2.9
deconvolution
process of inverse filtering to nullify the undesired effect of an earlier filter operation

2.10
dipole-dipole electrode configuration
configuration in which the spacing between the current electrode pair and that between the potential electrode pair is considerably small in comparison with the distance between these two pairs

2.11
diurnal correction
correction applied to magnetic data to compensate for daily fluctuations of the geomagnetic field

2.12
drift correction
quantitative adjustment to account for a uniform change in the reference value with time

2.13
eddy current
current induced in a conductive body by the primary electromagnetic (EM) field

2.14
equivalence
function of product or ratio of two parameters (e.g. bed thickness and resistivity) where variation in the parameters keeping the ratio or product constant can yield almost the same response

2.15
geoelectrical layer
subsurface layer having characteristic of uniform electrical resistivity

2.16
geometric factor
numerical value dependent upon the arrangement of electrodes which, when multiplied by the measured voltage-to-current ratio, gives the *apparent resistivity* (2.3)

2.17
geophone
instrument which detects seismic energy and converts it into electrical voltage

2.18
gradient configuration
variation of the *Schlumberger configuration* (2.38) where the current electrodes are kept at a great distance from one another and central space is scanned by a small potential dipole

2.19
half–Schlumberger configuration
configuration in which one of the current electrodes is kept at infinity (large distance) and need not be collinear with the other three electrodes

2.20
homogeneity
characteristic of a formation with uniform physical property or properties

2.21
in-phase
component of a secondary electromagnetic (EM) field with the same phase angle as that of the exciting primary EM field

© ISO 2016 – All rights reserved

2.22
Lee-partitioning configuration
variation of the Wenner array where one additional electrode is placed at the centre between the potential electrodes

2.23
longitudinal conductance
ratio of the thickness of a geoelectrical layer (2.15) to its resistivity

2.24
magnetic permeability
ratio of magnetic induction (flux density) in a body to the strength of the inducing magnetic field

2.25
magnetic susceptibility
ratio of the intensity of magnetization produced in a body to the strength of the magnetic field

2.26
migration
part of processing of seismic reflection data required to plot the dipping reflections at their correct position

2.27
non-polarizing electrode
electrode which is not affected by electrochemical potential generated between the electrode and ground material in which it is planted

2.28
normal moveout
effect of variation of shot-geophone distance on time of arrival of seismic reflection

2.29
off-set Wenner configuration
modification in *Wenner configuration* (2.48) to remove or minimize the effect of lateral inhomogeneities

2.30
overburden
part of the host medium which lies above the target and is usually of no interest in exploration, but has physical properties that affect the measurements

2.31
phasor diagram
graph obtained by plotting *in-phase* (2.21) and *quadrature* (2.35) components of secondary electromagnetic (EM) field for different frequencies of primary EM field

2.32
polar diagram
method of plotting resistivity sounding data

2.33
porosity
ratio of the volume of pore space in a sample to the bulk volume of that sample

2.34
proton precession magnetometer
instrument to measure the magnetic field normal to the earth's magnetic field

2.35
quadrature
out-of-phase or imaginary component of secondary electromagnetic (EM) field

© ISO 2016 – All rights reserved

2.36
reflector
interface which separates two layers of contrasting *acoustic impedance* (2.1) giving rise to reflection

2.37
refractor
layer along which the refracted or head wave travels at a velocity that is higher than that in the overlying layer

2.38
Schlumberger configuration
collinear four-electrode configuration of current and potential electrodes in which potential electrodes are kept close to the centre of the configuration

2.39
skin depth
depth of penetration of electromagnetic (EM) field in a medium where the intensity of the EM reduces to about 37 % of its original value at the surface of the earth

2.40
Snell's law
laws applied when a seismic wave encounters a boundary between two media having different velocities

2.41
stacking
process of compositing data, for the same parameter, from various data sets for the purpose of eliminating noise

2.42
suppressed layer
layer lacking a response because of its small thickness and/or contrast in physical property with the surrounding environment

2.43
terrain correction
correction applied to measured gravity data to nullify the effect of irregular topographic relief in the immediate vicinity of the station of measurement

2.44
transition
linear or exponential variation of a physical property with depth

2.45
transverse resistance
product of the thickness and resistivity of a *geoelectrical layer* (2.15)

2.46
two-electrode (pole-pole) configuration
one current and one potential electrode are kept at infinity (more than ten times the distance between active electrodes) and perpendicular to the profile along which the other two active electrodes are moved

2.47
vibroseis
seismic survey in which a vibrator is used as a non-destructive source, instead of an explosive, to generate controlled frequency seismic waves in the ground

2.48
Wenner configuration
collinear four-electrode configuration of potential and current electrodes in which all the electrodes are equidistant

© ISO 2016 – All rights reserved