RTCA, Inc.
1150 18th Street, NW, Suite 910
Washington D.C. 20036

Minimum Operational Performance Standards (MOPS) for the Aeronautical Mobile Airport Communication System (AeroMACS)

RTCA DO-346A
June 23, 2022

Prepared by: SC-223
© 2022 RTCA, Inc.

Copies of this document may be obtained from
RTCA, Inc.
Telephone: 202-833-9339
Facsimile: 202-833-9434
Internet: www.rtca.org
Please visit the RTCA Online Store for document pricing and ordering information.

FOREWORD

This document was prepared by Special Committee 223 (SC-223) jointly with EUROCAE WG-82 and approved by the RTCA Program Management Committee (PMC) and the EUROCAE Council on June 23, 2022.

RTCA, Incorporated is a not-for-profit corporation formed to advance the art and science of aviation and aviation electronic systems for the benefit of the public. The organization functions as a Standards Development Organization and develops consensus-based recommendations on contemporary aviation issues. RTCA's objectives include but are not limited to:

- coalescing aviation system user and provider technical requirements in a manner that helps government and industry meet their mutual objectives and responsibilities;
- analyzing and recommending solutions to the system technical issues that aviation faces as it continues to pursue increased safety, system capacity and efficiency;
- developing consensus on the application of pertinent technology to fulfill user and provider requirements, including development of minimum operational performance standards for electronic systems and equipment that support aviation; and
- assisting in developing the appropriate technical material upon which positions for the International Civil Aviation Organization and the International Telecommunication Union and other appropriate international organizations can be based.

The organization's recommendations are often used as the basis for government and private sector decisions as well as the foundation for many Federal Aviation Administration Technical Standard Orders and advisory circulars.

Since RTCA is not an official agency of the United States Government, its recommendations may not be regarded as statements of official government policy unless so enunciated by the U.S. government organization or agency having statutory jurisdiction over any matters to which the recommendations relate.

DISCLAIMER

This publication is based on material submitted by various participants during the SC approval process. Neither the SC nor RTCA has made any determination whether these materials could be subject to valid claims of patent, copyright or other proprietary rights by third parties, and no representation or warranty, expressed or implied is made in this regard. Any use of or reliance on this document shall constitute an acceptance thereof "as is" and be subject to this disclaimer.

This Page Intentionally Left Blank

TABLE OF CONTENTS

1 Purpose and Scope 1
1.1 Introduction 1
1.2 System Overview – AeroMACS 2
1.2.1 Document Hierarchy 3
1.3 Operational Application(s) 5
1.3.1 Mobile Applications Examples 6
1.4 Intended Function 6
1.5 Operational Goals 6
1.6 Assumptions 6
1.7 Test Procedures 6
1.8 Definition of Terms 7
1.9 Anticipated Future Growth 9
1.10 Reference Documents 9

2 Minimum Performance Standards 11
2.1 General Design Requirements 11
2.1.1 Effect of Test 11
2.1.2 Intended Function 11
2.1.3 ITU Regulations and Federal Communications Commission Rules 11
2.1.4 Equipment Classes 11
2.1.5 Airborne - General Design Requirements 11
2.1.5.1 Software Management 11
2.1.5.2 Airworthiness 11
2.1.5.3 Fire Protection 11
2.1.5.4 Operation of Controls 11
2.1.5.5 Design Assurance 12
2.1.5.5.1 Accessibility of Controls 12
2.1.5.5.2 Display of Navigation Facility Identification 12
2.1.6 Ground – General Design Requirements 12
2.1.6.1 Controls and indicators 12
2.2 Equipment Performance – Standard Conditions 12
2.2.1 AeroMACS Operating Frequency Band 12
2.2.2 Supported Channel Bandwidth 12
2.2.3 Reserved 13
2.2.4 Reserved 13
2.2.5 Service-specific CS 13
2.2.5.1 ATM CS 13
2.2.5.2 Packet CS 13
2.2.5.2.1 MAC SDU format 13
2.2.5.2.2 Classification 13
2.2.5.2.3 Payload header suppression (PHS) 13
2.2.5.2.3.1 PHS operation 13
2.2.5.2.3.2 PHS signaling 13
2.2.5.2.4 IEEE 802.3/Ethernet-specific part 13
2.2.5.2.4.1 IEEE 802.3/Ethernet CS PDU format 13

2.2.5.2.4.2 IEEE 802.3/Ethernet CS classification rules 13
2.2.5.2.5 IP specific part 13
2.2.5.2.5.1 IP CS PDU format 14
2.2.5.2.5.2 IP classification rules 14
2.2.5.3 Generic Packet Convergence Sublayer (GPCS) 14
2.2.6 MAC common part sub-layer 14
2.2.6.1 Point to multipoint (PMP) operation overview 14
2.2.6.2 Reserved 14
2.2.6.3 Data and Control Plane 14
2.2.6.3.1 Addressing and connections 14
2.2.6.3.1.1 Point-to-multipoint (PMP) 14
2.2.6.3.2 MAC PDU formats 14
2.2.6.3.2.1 MAC header formats 14
2.2.6.3.2.1.1 Generic MAC header 14
2.2.6.3.2.1.2 MAC header without payload 14
2.2.6.3.2.1.2.1 MAC signaling header type I 14
2.2.6.3.2.1.2.1.1 Bandwidth request (BR) header 14
2.2.6.3.2.1.2.1.2 Bandwidth request and UL Tx power report header 14
2.2.6.3.2.1.2.1.3 BR and CINR report header 14
2.2.6.3.2.1.2.1.4 CQICH allocation request header 14
2.2.6.3.2.1.2.1.5 PHY channel report header 15
2.2.6.3.2.1.2.1.6 BR and UL sleep control header 15
2.2.6.3.2.1.2.1.7 SN report header 15
2.2.6.3.2.1.2.2 MAC signaling header type II 15
2.2.6.3.2.1.2.2.1 Feedback header 15
2.2.6.3.2.1.2.2.2 MIMO channel feedback header 15
2.2.6.3.2.2 MAC subheaders and special payloads 15
2.2.6.3.2.2.1 Fragmentation subheader (FSH) 15
2.2.6.3.2.2.2 Grant management subheader (GMSH) 15
2.2.6.3.2.2.3 Packing subheader (PSH) 15
2.2.6.3.2.2.4 ARQ/Feedback 15
2.2.6.3.2.2.5 Reserved 15
2.2.6.3.2.2.6 Fast-feedback allocation subheader (FFSH) 15
2.2.6.3.2.2.7 Extended subheader format 15
2.2.6.3.2.2.7.1 SDU SN extended subheader 15
2.2.6.3.2.2.7.2 DL sleep control extended subheader 15
2.2.6.3.2.2.7.3 Feedback request extended subheader 15
2.2.6.3.2.2.7.4 MIMO mode feedback extended subheader 16
2.2.6.3.2.2.7.5 UL Tx power report extended subheader 16
2.2.6.3.2.2.7.6 Mini-feedback extended subheader 16
2.2.6.3.2.2.7.7 SN request extended subheader 16
2.2.6.3.2.2.7.8 PDU SN extended subheader 16
2.2.6.3.2.2.7.9 ertPS resumption bitmap extended subheader 16
2.2.6.3.2.2.7.10 Persistent Allocation Error Event 16
2.2.6.3.2.3 MAC management messages 16
2.2.6.3.2.3.1 DCD (DL channel descriptor) message 16
2.2.6.3.2.3.2 DL-MAP (Downlink map) message 16

2.2.6.3.2.3.3 UCD (UL channel descriptor) message....16
2.2.6.3.2.3.4 UL-MAP (UL map) message....16
2.2.6.3.2.3.5 RNG-REQ (ranging request) message....16
2.2.6.3.2.3.6 RNG-RSP (ranging response) message....16
2.2.6.3.2.3.7 REG-REQ (registration request) message....16
2.2.6.3.2.3.8 REG-RSP (registration response) message....16
2.2.6.3.2.3.9 Privacy key management (PKM) messages (PKM-REQ/PKM-RSP)....16
2.2.6.3.2.3.10 DSA-REQ message....17
2.2.6.3.2.3.10.1 MS-Initiated DSA....17
2.2.6.3.2.3.10.2 BS-Initiated DSA....17
2.2.6.3.2.3.11 DSA-RSP message....17
2.2.6.3.2.3.11.1 MS-Initiated DSA....17
2.2.6.3.2.3.11.2 BS-Initiated DSA....17
2.2.6.3.2.3.12 DSA-ACK message....17
2.2.6.3.2.3.13 DSC-REQ (DSC request) message....17
2.2.6.3.2.3.14 DSC-RSP (DSC response) message....17
2.2.6.3.2.3.15 DSC-ACK (DSC acknowledge) message....17
2.2.6.3.2.3.16 DSD-REQ message....17
2.2.6.3.2.3.17 DSD-RSP message....17
2.2.6.3.2.3.18 MCA-REQ (multicast polling assignment request) message....17
2.2.6.3.2.3.19 MCA-RSP (multicast polling assignment response) message....17
2.2.6.3.2.3.20 DBPC-REQ (DL burst profile change request) message....17
2.2.6.3.2.3.21 DBPC-RSP (DL burst profile change response) message....18
2.2.6.3.2.3.22 RES-CMD (reset command) message....18
2.2.6.3.2.3.23 SBC-REQ (SS basic capability request) message....18
2.2.6.3.2.3.24 SBC-RSP (SS basic capability response) message....18
2.2.6.3.2.3.25 CLK-CMP (clock comparison) message....18
2.2.6.3.2.3.26 DREG-CMD (de/reregister command) message....18
2.2.6.3.2.3.27 DSX-RVD (DSx received) message....18
2.2.6.3.2.3.28 TFTP-CPLT (Config File TFTP complete) message....18
2.2.6.3.2.3.29 TFTP-RSP (Config File TFTP complete response) message....18
2.2.6.3.2.3.30 ARQ-Feedback message....18
2.2.6.3.2.3.31 ARQ-Discard message....18
2.2.6.3.2.3.32 ARQ-Reset message....18
2.2.6.3.2.3.33 Channel Measurement REP-REQ/RSP (report request/response)....18
2.2.6.3.2.3.34 FPC (fast power control) message....18
2.2.6.3.2.3.35 AAS-FBCK-REQ/RSP (AAS channel feedback request/response) messages....18
2.2.6.3.2.3.36 AAS_Beam_Select message....18
2.2.6.3.2.3.37 DREG-REQ (SS deregistration request) message....18
2.2.6.3.2.3.38 HARQ MAP message....18
2.2.6.3.2.3.39 MOB_SLP-REQ (sleep request) message....19
2.2.6.3.2.3.40 MOB_SLP-RSP (sleep response) message....19
2.2.6.3.2.3.41 MOB_TRF-IND (traffic indication) message....19
2.2.6.3.2.3.42 MOB_NBR-ADV (neighbor advertisement) message....19
2.2.6.3.2.3.43 MOB_SCN-REQ (scanning interval allocation request) message....19
2.2.6.3.2.3.44 MOB_SCN-RSP (scanning interval allocation response) message....19
2.2.6.3.2.3.45 MOB_SCN-REP (scanning result report) message....19

2.2.6.3.2.3.46 MOB_ASC-REP (association result report) message....19
2.2.6.3.2.3.47 MOB_BSHO-REQ (BS HO request) message....19
2.2.6.3.2.3.48 MOB_MSHO-REQ (MS HO request) message....19
2.2.6.3.2.3.49 MOB_BSHO-RSP (BS HO response) message....19
2.2.6.3.2.3.50 MOB_HO-IND (HO indication) message....19
2.2.6.3.2.3.51 MOB_PAG-ADV (BS broadcast paging) message....19
2.2.6.3.2.3.52 MBS_MAP (multicast and broadcast service map) message....19
2.2.6.3.2.3.53 PMC_REQ (power control mode change request) message....20
2.2.6.3.2.3.54 PMC_RSP (power control mode change response) message....20
2.2.6.3.2.3.55 OFDMA SUB-DL-UL-MAP message....20
2.2.6.3.2.3.56 MIMO precoding setup/tear-down messages....20
2.2.6.3.2.3.57 MIH Payload Transfer (MOB_MIH-MSG) message....20
2.2.6.3.2.3.58 Service Identity Information (SII-ADV) message....20
2.2.6.3.2.3.59 Location Based Services (LBS-ADV) message....20
2.2.6.3.3 Construction and transmission of MAC PDUs....20
2.2.6.3.3.1 Conventions....20
2.2.6.3.3.2 Concatenation....20
2.2.6.3.3.3 Fragmentation....20
2.2.6.3.3.3.1 Non-ARQ connections....20
2.2.6.3.3.3.2 ARQ-enabled connections....20
2.2.6.3.3.4 Packing....20
2.2.6.3.3.4.1 Packing for non-ARQ connections....20
2.2.6.3.3.4.1.1 Packing fixed-length MAC SDUs....20
2.2.6.3.3.4.1.2 Packing variable-length MAC SDUs....21
2.2.6.3.3.4.2 Packing for ARQ-enabled connections....21
2.2.6.3.3.4.3 Packing ARQ Feedback IEs....21
2.2.6.3.3.5 CRC calculation....21
2.2.6.3.3.5.1 CRC32 calculation for SC and OFDM mode....21
2.2.6.3.3.5.2 CRC32 calculation for OFDMA mode....21
2.2.6.3.3.5.2.1 CRC32 test vectors for OFDMA mode....21
2.2.6.3.3.6 Encryption of MAC PDUs....21
2.2.6.3.3.7 Padding....21
2.2.6.3.4 ARQ mechanisms....21
2.2.6.3.4.1 ARQ block usage....21
2.2.6.3.4.2 ARQ Feedback IE format....21
2.2.6.3.4.2.1 ARQ Feedback IE format with extended capability....22
2.2.6.3.4.3 ARQ parameters....22
2.2.6.3.4.3.1 ARQ_BSN_MODULUS....22
2.2.6.3.4.3.2 ARQ_WINDOW_SIZE....22
2.2.6.3.4.3.3 ARQ_BLOCK_LIFETIME....22
2.2.6.3.4.3.4 ARQ_RETRY_TIMEOUT....22
2.2.6.3.4.3.5 ARQ_SYNC_LOSS_TIMEOUT....22
2.2.6.3.4.3.6 ARQ_RX_PURGE_TIMEOUT....22
2.2.6.3.4.3.7 ARQ_BLOCK_SIZE....22
2.2.6.3.4.4 ARQ procedures....22
2.2.6.3.4.4.1 ARQ state machine variables....22
2.2.6.3.4.4.1.1 Transmitter variables....22

2.2.6.3.4.4.1.2 Receiver variables....22
2.2.6.3.4.5 ARQ-enabled connection setup and negotiation....22
2.2.6.3.4.6 ARQ operation....22
2.2.6.3.4.6.1 Sequence number comparison....22
2.2.6.3.4.6.2 Transmitter state machine....22
2.2.6.3.4.6.3 Receiver state machine....23
2.2.6.3.5 Scheduling services....23
2.2.6.3.5.1 Outbound transmission scheduling....23
2.2.6.3.5.2 UL request/grant scheduling....23
2.2.6.3.5.2.1 Unsolicited grant service (UGS)....23
2.2.6.3.5.2.2 Real-time polling service (rtPS)....23
2.2.6.3.5.2.2.1 Extended rtPS....23
2.2.6.3.5.2.3 Non-real-time polling service (nrtPS)....23
2.2.6.3.5.2.4 Best effort (BE) service....23
2.2.6.3.6 Bandwidth allocation and request mechanisms....23
2.2.6.3.6.1 Requests....23
2.2.6.3.6.2 Grants....23
2.2.6.3.6.3 Polling....23
2.2.6.3.6.3.1 Unicast polling....23
2.2.6.3.6.3.2 Multicast and broadcast polling....24
2.2.6.3.6.3.3 PM bit....24
2.2.6.3.6.4 Contention-based focused BRs for WirelessMAN-OFDM....24
2.2.6.3.6.5 Contention-based CDMA BRs for WirelessMAN-OFDMA....24
2.2.6.3.7 MAC support of PHY....24
2.2.6.3.7.1 Frequency division duplexing (FDD)....24
2.2.6.3.7.2 Time division duplexing (TDD)....24
2.2.6.3.7.3 DL-MAP message....24
2.2.6.3.7.4 UL-MAP message....24
2.2.6.3.7.4.1 UL timing....24
2.2.6.3.7.4.2 UL allocations....24
2.2.6.3.7.4.3 UL interval definition....24
2.2.6.3.7.4.3.1 Request IE....24
2.2.6.3.7.4.3.2 Initial ranging IE....24
2.2.6.3.7.4.3.3 Data Grant Burst Type IEs....24
2.2.6.3.7.4.3.4 End of Map IE....24
2.2.6.3.7.4.3.5 Gap IE....24
2.2.6.3.7.5 Map relevance and synchronization....25
2.2.6.3.7.5.1 WirelessMAN-SC PHY....25
2.2.6.3.7.5.2 WirelessMAN-OFDM PHY....25
2.2.6.3.7.5.3 WirelessMAN-OFDMA PHY....25
2.2.6.3.7.6 Optional MAC AAS support of OFDM and OFDMA....25
2.2.6.3.7.6.1 AAS MAC services....25
2.2.6.3.7.6.2 MAC control functions....25
2.2.6.3.7.6.3 AAS DL synchronization....25
2.2.6.3.7.6.4 Alerting the BS about presence of a new SS in an AAS system....25
2.2.6.3.7.6.5 FDD/TDD support....25
2.2.6.3.7.6.6 Requesting bandwidth....25

2.2.6.3.8 Contention resolution....25
2.2.6.3.8.1 Transmission opportunities....25
2.2.6.3.9 Network entry and initialization....25
2.2.6.3.9.1 Scanning and synchronization to the DL....25
2.2.6.3.9.2 Obtain DL parameters....25
2.2.6.3.9.3 Obtain UL parameters....25
2.2.6.3.9.4 Message flows during scanning and UL parameter acquisition....26
2.2.6.3.9.5 Initial ranging and automatic adjustments....26
2.2.6.3.9.5.1 Contention-based initial ranging and automatic adjustments....26
2.2.6.3.9.6 Ranging parameter adjustment....26
2.2.6.3.9.7 Negotiate basic capabilities....26
2.2.6.3.9.8 SS authorization and key exchange....26
2.2.6.3.9.9 Registration....26
2.2.6.3.9.9.1 IP version negotiation....26
2.2.6.3.9.10 Establishing IP connectivity....26
2.2.6.3.9.11 Establishing time of day....26
2.2.6.3.9.12 Transferring operational parameters....26
2.2.6.3.9.13 Establishing provisioned connections....26
2.2.6.3.9.14 Forcing MSs to perform network entry at once....27
2.2.6.3.10 Ranging....27
2.2.6.3.10.1 DL burst profile management....27
2.2.6.3.10.2 UL periodic ranging....27
2.2.6.3.10.3 OFDMA-based ranging....27
2.2.6.3.10.3.1 Contention-based initial ranging and automatic adjustments....27
2.2.6.3.10.3.2 Periodic ranging and automatic adjustments....27
2.2.6.3.10.4 CDMA HO ranging and automatic adjustment....27
2.2.6.3.10.4.1 Dedicated ranging and automatic adjustments....27
2.2.6.3.11 Update of channel descriptors....27
2.2.6.3.12 Assigning SSs to multicast groups....27
2.2.6.3.13 Establishment of multicast connections....27
2.2.6.3.14 Quality of Service....27
2.2.6.3.14.1 Theory of operation....27
2.2.6.3.14.2 Service flows....27
2.2.6.3.14.3 Object models....27
2.2.6.3.14.4 Service classes....28
2.2.6.3.14.4.1 Global service classes....28
2.2.6.3.14.5 Authorization....28
2.2.6.3.14.6 Types of service flows....28
2.2.6.3.14.6.1 Provisioned service flows....28
2.2.6.3.14.6.2 Admitted service flows....28
2.2.6.3.14.6.3 Active service flows....28
2.2.6.3.14.7 Service flow creation....28
2.2.6.3.14.7.1 Dynamic service flow creation....28
2.2.6.3.14.7.1.1 Dynamic service flow creation – SS-initiated....28
2.2.6.3.14.7.1.2 Dynamic service flow creation – BS-initiated....28
2.2.6.3.14.8 Dynamic service flow modification and deletion....28
2.2.6.3.14.9 Service flow management....28

2.2.6.3.14.9.1 Overview 28
2.2.6.3.14.9.2 Dynamic service flow state transitions 28
2.2.6.3.14.9.3 Dynamic service addition (DSA) 28
2.2.6.3.14.9.3.1 SS-initiated DSA 28
2.2.6.3.14.9.3.2 BS-initiated DSA 28
2.2.6.3.14.9.3.3 DSA state transition diagrams 28
2.2.6.3.14.9.4 Dynamic service change (DSC) 29
2.2.6.3.14.9.4.1 SS-initiated DSC 29
2.2.6.3.14.9.4.2 BS-initiated DSC 29
2.2.6.3.14.9.4.3 DSC state transition diagrams 29
2.2.6.3.14.9.5 Connection release 29
2.2.6.3.14.9.5.1 SS-initiated DSD 29
2.2.6.3.14.9.5.2 BS-initiated DSD 29
2.2.6.3.14.9.5.3 DSD state transition diagrams 29
2.2.6.3.15 Procedures for shared frequency band usage 29
2.2.6.3.16 MAC support for HARQ 29
2.2.6.3.16.1 Subpacket generation 29
2.2.6.3.16.2 DL/UL ACK/NAK signaling 29
2.2.6.3.16.3 HARQ parameter signaling 29
2.2.6.3.17 DL CINR report operation 29
2.2.6.3.17.1 DL CINR report with REP-RSP MAC message 29
2.2.6.3.17.2 Periodic CINR report with fast-feedback (CQICH) channel 29
2.2.6.3.17.2.1 Conditions of transition triggering 30
2.2.6.3.18 Optional band AMC operations using 6-bit CQICH encoding 30
2.2.6.3.19 Data delivery services for mobile network 30
2.2.6.3.19.1 Types of data delivery services 30
2.2.6.3.19.1.1 Unsolicited grant service (UGS) 30
2.2.6.3.19.1.2 Real-time variable-rate (RT-VR) service 30
2.2.6.3.19.1.3 Non-real time variable-rate (NRT-VR) service 30
2.2.6.3.19.1.4 Best effort (BE) service 30
2.2.6.3.19.1.5 Extended real-time variable-rate (ERT-VR) service 30
2.2.6.3.20 Sleep mode for mobility-supporting MS 30
2.2.6.3.21 MAC HO procedures 30
2.2.6.3.21.1 Network topology acquisition 30
2.2.6.3.21.1.1 Network topology advertisement 30
2.2.6.3.21.1.2 MS scanning of neighbor BSs 30
2.2.6.3.21.1.3 Association procedure 30
2.2.6.3.21.2 HO process 30
2.2.6.3.21.2.1 Cell reselection 31
2.2.6.3.21.2.2 HO decision and initiation 31
2.2.6.3.21.2.3 HO cancellation 31
2.2.6.3.21.2.4 Fast ranging 31
2.2.6.3.21.2.5 Termination with the serving BS 31
2.2.6.3.21.2.6 Drops during HO 31
2.2.6.3.21.2.7 Network entry/reentry 31
2.2.6.3.21.2.8 MS-assisted coordination of DL transmission at target BS for HO 31
2.2.6.3.21.2.8.1 Context management during optimized HO 31

2.2.6.3.21.2.8.1.1 BS PHY settings 31
2.2.6.3.21.2.8.1.2 BS Channel descriptor settings 31
2.2.6.3.21.2.8.1.3 Ranging settings 31
2.2.6.3.21.2.8.1.4 Basic capabilities settings 31
2.2.6.3.21.2.8.1.5 Registration settings 31
2.2.6.3.21.2.8.1.6 Service flows settings 31
2.2.6.3.21.2.8.1.7 Scanning-dynamic and static context 31
2.2.6.3.21.2.9 HO process 31
2.2.6.3.21.2.10 HO optimization rules and scenarios 32
2.2.6.3.21.2.11 Seamless HO 32
2.2.6.3.21.3 Macro diversity handover (MDHO) and fast BS switching 32
2.2.6.3.21.3.1 MDHO decision and initiation 32
2.2.6.3.21.3.2 FBSS decision and initiation 32
2.2.6.3.21.3.3 Diversity set update for MDHO/FBSS 32
2.2.6.3.21.3.4 Anchor BS update for MDHO/FBSS 32
2.2.6.3.21.3.5 MS-assisted coordination of DL transmission at new anchor BS 32
2.2.6.3.22 Multicast and broadcast service (MBS) 32
2.2.6.3.22.1 Establishment and maintenance of MBSs 32
2.2.6.3.22.1.1 Inter-MBS Zone transition 32
2.2.6.3.22.2 Performance enhancement with macro diversity 32
2.2.6.3.22.3 Power saving operation 32
2.2.6.3.22.4 Multicast and broadcast zone (MBS_Zone) 32
2.2.6.3.23 MS idle mode (optional) 32
2.2.6.3.23.1 MS idle mode initiation 32
2.2.6.3.23.2 Cell selection 32
2.2.6.3.23.3 MS Broadcast paging message time synchronization 32
2.2.6.3.23.4 MS paging unavailable interval 33
2.2.6.3.23.5 MS paging listening interval 33
2.2.6.3.23.6 BS Broadcast paging message 33
2.2.6.3.23.7 Paging availability mode termination 33
2.2.6.3.23.7.1 MS side 33
2.2.6.3.23.7.2 BS side 33
2.2.6.3.23.8 Location update 33
2.2.6.3.23.8.1 Location update conditions 33
2.2.6.3.23.8.2 Location update process 33
2.2.6.3.23.9 Network reentry from idle mode 33
2.2.6.3.24 MIHF support 33
2.2.6.3.25 Location Based Services 33
2.2.6.3.25.1 Time Difference of Arrival (TDOA) 33
2.2.6.3.26 Persistent Scheduling 33
2.2.6.3.26.1 Persistent Region ID 33
2.2.6.3.26.1.1 Downlink operation 33
2.2.6.3.26.1.2 Uplink operation 33
2.2.6.3.26.2 Resource shifting 33
2.2.6.3.26.3 HARQ retransmission 34
2.2.6.3.26.4 Error handling procedures 34
2.2.6.3.26.4.1 Maximum Number of Persistent Allocations 34

2.2.6.3.26.4.2 MAP ACK channel....34
2.2.6.3.26.4.3 MAP NACK channel....34
2.2.6.3.26.4.4 Error Correction Information....34
2.2.6.3.26.4.5 Change indicator....34
2.2.6.3.26.4.6 Retransmission flag....34
2.2.6.3.26.4.7 Error recovery....34
2.2.6.3.27 Emergency Service....34
2.2.7 Security sublayer....34
2.2.7.1 Architecture....34
2.2.7.1.1 Secure encapsulation of MAC PDUs....34
2.2.7.1.2 Key Management Protocol....34
2.2.7.1.3 Authentication Protocol....34
2.2.7.1.3.1 PKM RSA Authentication....34
2.2.7.1.3.2 PKM EAP Authentication....34
2.2.7.1.4 Mapping of connections to SAs....35
2.2.7.1.5 Cryptographic suite....35
2.2.7.2 PKM protocol....35
2.2.7.2.1 PKM Version1....35
2.2.7.2.1.1 Security Associations....35
2.2.7.2.1.2 SS authorization and AK exchange overview....35
2.2.7.2.1.2.1 Authorization via RSA protocol....35
2.2.7.2.1.3 TEK exchange overview....35
2.2.7.2.1.3.1 TEK exchange overview for PMP topology....35
2.2.7.2.1.4 Security Capability Selection....35
2.2.7.2.1.5 Authorization State Machine....35
2.2.7.2.1.5.1 States....35
2.2.7.2.1.5.2 Messages....35
2.2.7.2.1.5.3 Events....36
2.2.7.2.1.5.4 Parameters....36
2.2.7.2.1.5.5 Action....36
2.2.7.2.1.6 TEK State Machine....36
2.2.7.2.1.6.1 States....36
2.2.7.2.1.6.2 Messages....36
2.2.7.2.1.6.3 Events....36
2.2.7.2.1.6.4 Parameters....36
2.2.7.2.1.6.5 Action....36
2.2.7.2.2 PKM Version 2....36
2.2.7.2.2.1 TEK exchange overview for PMP topology....36
2.2.7.2.2.2 Key Derivation....36
2.2.7.2.2.2.1 RSA Based Authorization....36
2.2.7.2.2.2.2 EAP Authentication....36
2.2.7.2.2.2.3 AK derivation....36
2.2.7.2.2.2.4 KEK derivation....36
2.2.7.2.2.2.5 Group Key Encryption Key (GKEK)....36
2.2.7.2.2.2.6 Traffic Encryption Key (TEK)....37
2.2.7.2.2.2.6.1 Counter-based TEK Generation for HO....37
2.2.7.2.2.2.7 Group Traffic Encryption Key (GTEK)....37

2.2.7.2.2.2.8 MBS Traffic Encryption Key (MTK) 37
2.2.7.2.2.2.9 Message authentication keys (HMAC/CMAC) and KEK derivation 37
2.2.7.2.2.2.9.1 CMAC_KEY_COUNT_ management 37
2.2.7.2.2.2.9.1.1 Maintenance of CMAC_KEY_COUNTM by the MS 37
2.2.7.2.2.2.9.1.1.1 CMAC_KEY_LOCK state 37
2.2.7.2.2.2.9.1.2 Processing of CMAC_KEY_COUNTB by the BS 37
2.2.7.2.2.2.9.2 Derivation of message authentication codes 37
2.2.7.2.2.2.10 Key Hierarchy 37
2.2.7.2.2.2.11 Maintenance of PMK and AK 37
2.2.7.2.2.2.12 PKMv2 PMK and AK switching methods 38
2.2.7.2.2.3 Associations 38
2.2.7.2.2.3.1 Security associations (SAs) 38
2.2.7.2.2.3.2 Group security associations (GSAs) 38
2.2.7.2.2.3.3 Multicast and broadcast service group security associations (MBSGSAs) 38
2.2.7.2.2.4 Security context 38
2.2.7.2.2.4.1 AK context 38
2.2.7.2.2.4.2 GKEK context 38
2.2.7.2.2.4.3 PMK context 38
2.2.7.2.2.4.4 PAK context 38
2.2.7.2.2.5 Authentication state machine 38
2.2.7.2.2.5.1 States 38
2.2.7.2.2.5.2 Messages 38
2.2.7.2.2.5.3 Events 38
2.2.7.2.2.5.4 Parameters 38
2.2.7.2.2.5.5 Actions 38
2.2.7.2.2.6 TEK state machine 38
2.2.7.2.2.6.1 States 39
2.2.7.2.2.6.2 Messages 39
2.2.7.2.2.6.3 Events 39
2.2.7.2.2.6.4 Parameters 39
2.2.7.2.2.6.5 Actions 39
2.2.7.3 Dynamic SA creation and mapping 39
2.2.7.3.1 Dynamic SA creation 39
2.2.7.3.2 Dynamic SA mapping 39
2.2.7.4 Key usage 39
2.2.7.4.1 BS key usage 39
2.2.7.4.1.1 AK key lifetime 39
2.2.7.4.1.2 AK transition period on BS side 39
2.2.7.4.1.3 BS usage of AK 39
2.2.7.4.1.4 TEK lifetime 39
2.2.7.4.1.5 BS usage of TEK 39
2.2.7.4.2 SS key usage 40
2.2.7.4.2.1 SS reauthorization 40
2.2.7.4.2.2 SS usage of AK 40
2.2.7.4.2.3 SS usage of TEK 40
2.2.7.5 Cryptographic methods 40
2.2.7.5.1 Data Encryption methods 40

2.2.7.5.1.1 Data encryption with DES in CBC mode 40
2.2.7.5.1.2 Data encryption with AES in CCM mode 40
2.2.7.5.1.2.1 PDU payload format 40
2.2.7.5.1.2.2 Packet number (PN) 40
2.2.7.5.1.2.3 CCM algorithm 40
2.2.7.5.1.2.4 Receive processing rules 40
2.2.7.5.1.2.5 AES-CCM mode example encrypted MAC PDUs 40
2.2.7.5.1.3 Data encryption with AES in CTR mode 40
2.2.7.5.1.3.1 Encrypted MBS PDU payload format 40
2.2.7.5.1.4 Data encryption with AES in CBC mode 41
2.2.7.5.1.4.1 CBC IV generation 41
2.2.7.5.2 Encryption of TEK 41
2.2.7.5.2.1 Encryption of TEK with 3-DES 41
2.2.7.5.2.2 Encryption of TEK with RSA 41
2.2.7.5.2.3 Encryption of TEK-128 with AES 41
2.2.7.5.2.4 Encryption of TEK-128 with AES key wrap 41
2.2.7.5.3 Calculation of HMAC-Digests 41
2.2.7.5.4 Derivation of TEKs, KEKs, and message authentication keys 41
2.2.7.5.4.1 DES keys 41
2.2.7.5.4.2 Key encryption keys (KEKs) 41
2.2.7.5.4.3 HMAC authentication keys 41
2.2.7.5.4.4 Cipher-based message authentication code (CMAC) 41
2.2.7.5.4.4.1 Calculation of CMAC value 41
2.2.7.5.4.5 Derivation of TEKs, KEKs, message authentication keys and GKEKs in PKMv2 41
2.2.7.5.4.5.1 AES KEKs in PKMv2 41
2.2.7.5.4.5.2 Encryption of GKEK in PKMv2 42
2.2.7.5.4.5.2.1 Encryption of GKEK with 3-DES in PKMv2 42
2.2.7.5.4.5.2.2 Encryption of GKEK with RSA in PKMv2 42
2.2.7.5.4.5.2.3 Encryption of GKEK with ECB mode AES in PKMv2 42
2.2.7.5.4.5.2.4 Encryption of GKEK with AES key wrap in PKMv2 42
2.2.7.5.4.6 Key derivation functions for PKMv2 42
2.2.7.5.4.6.1 Dot16KDF for PKMv2 42
2.2.7.5.5 Public-key encryption of of AK 42
2.2.7.5.6 Digital signatures 42
2.2.7.6 Certificate profile 42
2.2.7.6.1 Certificate format 42
2.2.7.6.1.1 tbsCertificate.validity.notBefore and tbsCertificate.validity.notAfter 42
2.2.7.6.1.2 tbsCertificate.SerialNumber 42
2.2.7.6.1.3 tbsCertificate.signature and signature Algorithm 42
2.2.7.6.1.4 tbsCertificate.Issuer and tbsCertificate.subject 42
2.2.7.6.1.4.1 Manufacturer Certificate 42
2.2.7.6.1.4.2 SS certificate 42
2.2.7.6.1.4.3 BS Certificate 42
2.2.7.6.1.5 tbsCertificate.subjectPublicKeyInfo 42
2.2.7.6.1.6 tbsCertificate.issuerUniqueID and tbsCertificate.subjectUniqueID 43
2.2.7.6.1.7 tbsCertificate.extensions 43
2.2.7.6.1.7.1 SS certificate 43

2.2.7.6.1.7.2 Manufacturer certificate 43
2.2.7.6.1.8 Signature Value 43
2.2.7.6.2 Certificate storage and management in the SS 43
2.2.7.6.3 Certificate processing and management in the BS 43
2.2.7.7 Preauthentication 43
2.2.7.8 PKMv2 43
2.2.7.8.1 PKMv2 SA-TEK 3-way handshake 43
2.2.7.8.2 BS and SS RSA mutual authentication and AK exchange overview 43
2.2.7.8.3 Multicast and broadcast service (MBS) support 43
2.2.7.8.3.1 MBS security associations 43
2.2.7.8.3.2 MBS key management 43
2.2.7.8.3.2.1 MAK establishment 43
2.2.7.8.3.2.2 MGTEK establishment 43
2.2.7.8.3.2.3 MTK establishment 43
2.2.7.9 Multicast and broadcast rekeying algorithm (MBRA) 44
2.2.7.9.1 MBRA flow 44
2.2.7.9.1.1 BS usage of GTEK 44
2.2.7.9.1.2 SS usage of GTEK 44
2.2.7.9.2 Messages 44
2.2.7.9.3 Encryption of GKEK 44
2.2.7.9.4 Message authentication keys for the Key Update Command message 44
2.2.8 Physical layer 44
2.2.8.1 Wireless MAN-SC PHY specification 44
2.2.8.2 Reserved 44
2.2.8.3 WirelessMAN-OFDM PHY 44
2.2.8.4 WirelessMAN-OFDMA PHY 44
2.2.8.4.1 Introduction 44
2.2.8.4.2 OFDMA symbol description, symbol parameters and transmitted signal 44
2.2.8.4.2.1 Time domain description 44
2.2.8.4.2.2 Frequency domain description 44
2.2.8.4.2.3 Primitive parameters 44
2.2.8.4.2.4 Derived parameters 44
2.2.8.4.2.5 Transmitted signal 45
2.2.8.4.3 OFDMA basic terms definition 45
2.2.8.4.3.1 Slot and data region 45
2.2.8.4.3.2 Segment 45
2.2.8.4.3.3 Permutation zone 45
2.2.8.4.3.4 OFDMA data mapping 45
2.2.8.4.4 Frame structure 45
2.2.8.4.4.1 TDD frame structure 45
2.2.8.4.4.2 FDD Frame Structure 45
2.2.8.4.4.3 OFDMA Frame Parameters and Operations 45
2.2.8.4.4.4 DL frame prefix 45
2.2.8.4.4.5 Allocation of subchannels for FCH and DL-MAP and logical subchannel numbering 45
2.2.8.4.4.6 UL transmission allocations 45
2.2.8.4.4.7 Optional AAS Support 45
2.2.8.4.5 Map message fields and IEs 45

2.2.8.4.5.1 DL-MAP PHY Synchronization field....45
2.2.8.4.5.2 Frame duration codes....45
2.2.8.4.5.3 DL-MAP IE format....46
2.2.8.4.5.3.1 DIUC allocation....46
2.2.8.4.5.3.2 DL-MAP Extended IE format....46
2.2.8.4.5.3.2.1 DL-MAP Extended IE encoding format....46
2.2.8.4.5.3.2.2 DL-MAP Extended-2 IE encoding format....46
2.2.8.4.5.3.2.3 DL-MAP Extended-3 IE encoding format....46
2.2.8.4.5.3.3 AAS DL IE format....46
2.2.8.4.5.3.4 STC DL Zone IE format....46
2.2.8.4.5.3.5 Channel Measurement IE....46
2.2.8.4.5.3.6 Data Location In Another BS IE....46
2.2.8.4.5.3.7 CID Switch IE....46
2.2.8.4.5.3.8 MIMO DL Basic IE format....46
2.2.8.4.5.3.9 MIMO DL Enhanced IE....46
2.2.8.4.5.3.10 HARQ and Sub-MAP Pointer IE....46
2.2.8.4.5.3.11 DL-MAP Physical Modifier IE....46
2.2.8.4.5.3.12 MBS MAP IE....47
2.2.8.4.5.3.13 DL PUSC Burst Allocation in Other Segment IE....47
2.2.8.4.5.3.14 HO Anchor Active DL MAP....47
2.2.8.4.5.3.15 HO Active Anchor DL MAP....47
2.2.8.4.5.3.16 HO CID Translation MAP IE....47
2.2.8.4.5.3.17 MIMO in Another BS IE....47
2.2.8.4.5.3.18 Macro-MIMO DL Basic IE....47
2.2.8.4.5.3.19 UL Noise and Interference Level IE format....47
2.2.8.4.5.3.20 Dedicated DL Control IE....47
2.2.8.4.5.3.21 HARQ DL MAP IE....47
2.2.8.4.5.3.21.1 Dedicated MIMO DL Control IE format....47
2.2.8.4.5.3.22 DL HARQ ACK IE....47
2.2.8.4.5.3.23 Enhanced DL MAP IE....47
2.2.8.4.5.3.24 Closed-loop MIMO DL enhanced IE....47
2.2.8.4.5.3.25 Broadcast Control Pointer IE....47
2.2.8.4.5.3.26 AAS SDMA DL IE format....47
2.2.8.4.5.3.27 PUSC ASCA Allocation IE....47
2.2.8.4.5.3.28 H-FDD Group Switch IE....47
2.2.8.4.5.3.29 Persistent HARQ DL MAP Allocation IE....48
2.2.8.4.5.3.30 Power Boosting IE....48
2.2.8.4.5.3.31 Extended Broadcast Control Pointer IE....48
2.2.8.4.5.4 UL-MAP IE format....48
2.2.8.4.5.4.1 UIUC allocation....48
2.2.8.4.5.4.2 PAPR Reduction/Safety Zone/Sounding Zone Allocation IE....48
2.2.8.4.5.4.3 CDMA Allocation UL-MAP IE format....48
2.2.8.4.5.4.4 UL-MAP Extended IE....48
2.2.8.4.5.4.4.1 UL-MAP Extended IE....48
2.2.8.4.5.4.4.2 UL-MAP Extended-2 IE....48
2.2.8.4.5.4.4.3 UL-MAP Extended-3 IE....48
2.2.8.4.5.4.5 Power Control IE format....48

2.2.8.4.5.4.6 AAS UL IE format....48
2.2.8.4.5.4.7 UL Zone Switch IE....48
2.2.8.4.5.4.8 Mini-Subchannel Allocation IE....48
2.2.8.4.5.4.9 Fast-Feedback Allocation IE....48
2.2.8.4.5.4.10 MIMO UL Basic IE format....48
2.2.8.4.5.4.11 CQICH Allocation IE Format....48
2.2.8.4.5.4.12 UL-MAP Physical Modifier IE....49
2.2.8.4.5.4.13 UL Allocation Start IE....49
2.2.8.4.5.4.14 CQICH Enhanced Allocation IE....49
2.2.8.4.5.4.15 UL PUSC Burst Allocation in Other Segment IE....49
2.2.8.4.5.4.16 HO Anchor Active UL-MAP IE....49
2.2.8.4.5.4.17 HO Active Anchor UL MAP IE....49
2.2.8.4.5.4.18 MIMO UL Enhanced IE format....49
2.2.8.4.5.4.19 OFDMA Fast Ranging IE....49
2.2.8.4.5.4.20 UL-MAP Fast Tracking IE....49
2.2.8.4.5.4.21 Anchor BS Switch IE....49
2.2.8.4.5.4.22 HARQ UL-MAP IE....49
2.2.8.4.5.4.22.1 Dedicated UL Control IE....49
2.2.8.4.5.4.22.2 Dedicated MIMO UL Control IE format....49
2.2.8.4.5.4.23 HARQ ACK Region Allocation IE....49
2.2.8.4.5.4.24 UL Sounding Command IE....49
2.2.8.4.5.4.25 AAS SDMA UL IE format....49
2.2.8.4.5.4.26 Feedback Polling IE feedback header not supported....49
2.2.8.4.5.4.27 Uplink Power Control Bitmap IE....49
2.2.8.4.5.4.28 Persistent HARQ UL MAP Allocation IE....50
2.2.8.4.5.4.29 FDD Paired Allocation IE....50
2.2.8.4.5.5 Burst profile format....50
2.2.8.4.5.6 Compressed maps....50
2.2.8.4.5.6.1 Compressed DL-MAP....50
2.2.8.4.5.6.2 Compressed UL-MAP....50
2.2.8.4.5.7 AAS-FBCK-REQ/RSP message bodies....50
2.2.8.4.5.8 Optional reduced AAS private maps....50
2.2.8.4.5.9 Reduced AAS private maps....50
2.2.8.4.5.9.1 Reduced AAS private DL-MAP....50
2.2.8.4.5.9.2 Reduced AAS private UL-MAP....50
2.2.8.4.6 OFDMA subcarrier allocations....50
2.2.8.4.6.1 Downlink (DL)....50
2.2.8.4.6.1.1 Preamble....51
2.2.8.4.6.1.1.1 Common SYNC symbol (optional)....51
2.2.8.4.6.1.1.2 Common SYNC symbol sequence....51
2.2.8.4.6.1.2 Symbol structure....51
2.2.8.4.6.1.2.1 Symbol Structure for PUSC....51
2.2.8.4.6.1.2.1.1 DL subchannels subcarrier allocation in PUSC....51
2.2.8.4.6.1.2.2 Symbol Structure for FUSC....51
2.2.8.4.6.1.2.3 Additional optional symbol structure for FUSC....51
2.2.8.4.6.1.2.4 Optional DL tile usage of subchannels – TUSC1....51
2.2.8.4.6.1.2.5 Optional DL tile usage of subchannels – TUSC2....51

2.2.8.4.6.1.2.6 TUSC1/TUSC2 Support for SDMA....51
2.2.8.4.6.2 Uplink (UL)....51
2.2.8.4.6.2.1 Symbol structure for subchannel (PUSC)....51
2.2.8.4.6.2.2 Partitioning of subcarriers into subchannels in the UL....51
2.2.8.4.6.2.3 UL permutation example....51
2.2.8.4.6.2.4 Partition a slot to mini-subchannels....51
2.2.8.4.6.2.5 Additional optional symbol structure for PUSC....52
2.2.8.4.6.2.6 Data subchannel rotation scheme....52
2.2.8.4.6.2.7 Optional UL channel sounding in TDD systems....52
2.2.8.4.6.3 Optional adjacent subcarrier permutations for AMC....52
2.2.8.4.6.4 Optional permutations for PUSC....52
2.2.8.4.7 OFDMA ranging....52
2.2.8.4.7.1 Initial ranging and HO ranging transmissions....52
2.2.8.4.7.2 Periodic ranging and BR transmissions....52
2.2.8.4.7.3 Ranging codes....52
2.2.8.4.7.4 Ranging and BR opportunity size....52
2.2.8.4.8 Space-time coding (STC)....52
2.2.8.4.8.1 STC using two antennas....52
2.2.8.4.8.1.1 Multiple-input, single-output channel estimation and synchronization....52
2.2.8.4.8.1.2 STC using two antennas....53
2.2.8.4.8.1.2.1 STC encoding....53
2.2.8.4.8.1.2.1.1 STC using 2 antennas in PUSC....53
2.2.8.4.8.1.2.1.2 STC using 2 antennas in FUSC....53
2.2.8.4.8.1.2.1.3 Data mapping....53
2.2.8.4.8.1.2.2 STC decoding....53
2.2.8.4.8.1.3 Frequency hopping diversity coding (FHDC)....53
2.2.8.4.8.1.4 STC/FHDC configurations....53
2.2.8.4.8.1.5 UL using STC....53
2.2.8.4.8.1.6 STC of two antennas using directivity through four antennas....53
2.2.8.4.8.2 STC for four antennas....53
2.2.8.4.8.2.1 STC for four antennas using PUSC....53
2.2.8.4.8.2.2 STC for four antennas using FUSC....53
2.2.8.4.8.2.3 STC configurations....53
2.2.8.4.8.2.4 MIMO MDHO-based macro-diversity transmission....53
2.2.8.4.8.3 STC for the optional zones in the DL....53
2.2.8.4.8.3.1 Symbol structure for optional AMC and optional FUSC....54
2.2.8.4.8.3.2 Symbol structure for the optional PUSC-ASCA....54
2.2.8.4.8.3.3 Transmission schemes for 2-antenna BS in DL....54
2.2.8.4.8.3.4 Transmission schemes for 3-antenna BS in DL....54
2.2.8.4.8.3.5 Transmission schemes for 4-antenna BS....54
2.2.8.4.8.3.6 MIMO precoding....54
2.2.8.4.8.4 STC for the optional zones in the UL....54
2.2.8.4.8.4.1 Allocation of pilot subcarriers....54
2.2.8.4.8.4.2 Allocation of data subchannels....54
2.2.8.4.8.4.3 Transmission schemes for 2-antenna MS in UL....54
2.2.8.4.8.5 MIMO Midamble....54
2.2.8.4.8.5.1 Midamble sequence....54

2.2.8.4.8.5.1.1 PAPR reduction sequence for BS with two antennas 54
2.2.8.4.8.5.1.2 PAPR reduction sequence for BS with three or four antennas 54
2.2.8.4.8.6 STC subpacket combining 54
2.2.8.4.8.7 Cyclic delay diversity (CDD) 54
2.2.8.4.9 Channel coding 54
2.2.8.4.9.1 Randomization 54
2.2.8.4.9.2 Encoding 55
2.2.8.4.9.2.1 Convolutional coding (CC) 55
2.2.8.4.9.2.1.1 Incremental redundancy HARQ support (optional) 55
2.2.8.4.9.2.2 Block turbo coding (BTC) (optional) 55
2.2.8.4.9.2.3 Convolutional turbo codes (CTCs) (optional) 55
2.2.8.4.9.2.3.1 CTC encoder (Basic functionality) 55
2.2.8.4.9.2.3.2 CTC interleaver 55
2.2.8.4.9.2.3.3 Determination of CTC circulation states 55
2.2.8.4.9.2.3.4 Subpacket generation 55
2.2.8.4.9.2.3.4.1 Bit separation 55
2.2.8.4.9.2.3.4.2 Subblock interleaving 55
2.2.8.4.9.2.3.4.3 Bit grouping 55
2.2.8.4.9.2.3.4.4 Bit selection 55
2.2.8.4.9.2.3.5 Optional IR HARQ support 56
2.2.8.4.9.2.4 Zero tailed convolutional coding (optional) 56
2.2.8.4.9.2.5 Low density parity check (LDPC) code (optional) 56
2.2.8.4.9.3 Interleaving 56
2.2.8.4.9.3.1 Optional interleaver for convolutional coding 56
2.2.8.4.9.4 Modulation 56
2.2.8.4.9.4.1 Subcarrier randomization 56
2.2.8.4.9.4.2 Data modulation 56
2.2.8.4.9.4.3 Pilot modulation 56
2.2.8.4.9.4.4 Example of OFDMA UL CC encoding is just an example 56
2.2.8.4.9.5 Repetition 56
2.2.8.4.9.6 Zone boosting 56
2.2.8.4.9.7 Multiple HARQ (optional) 56
2.2.8.4.9.7.1 Generic chase HARQ 56
2.2.8.4.9.7.2 CC-IR HARQ 56
2.2.8.4.10 Control mechanisms 57
2.2.8.4.10.1 Synchronization 57
2.2.8.4.10.1.1 Network synchronization 57
2.2.8.4.10.1.2 SS synchronization 57
2.2.8.4.10.2 Ranging 57
2.2.8.4.10.3 Power control 57
2.2.8.4.10.3.1 Closed-loop power control 57
2.2.8.4.10.3.2 Optional open-loop power control 57
2.2.8.4.11 Fast-feedback channels 57
2.2.8.4.11.1 Fast DL measurement feedback 57
2.2.8.4.11.2 Fast MIMO feedback 57
2.2.8.4.11.3 Mode selection feedback 57
2.2.8.4.11.4 Effective CINR feedback for fast-feedback channel 57

2.2.8.4.11.5 Enhanced fast-feedback channels....57
2.2.8.4.11.6 Fast DL measurement feedback for enhanced fast-feedback channel....57
2.2.8.4.11.7 Fast MIMO feedback of quantized precoding weight for enhanced fast-feedback channel 57
2.2.8.4.11.8 MIMO mode feedback for enhanced fast-feedback channel....58
2.2.8.4.11.9 Anchor BS report....58
2.2.8.4.11.10 UEP fast-feedback....58
2.2.8.4.11.11 Band AMC differential CINR feedback for enhanced fast-feedback channel....58
2.2.8.4.11.12 Indication flag feedback....58
2.2.8.4.11.13 Primary and secondary fast-feedback channels....58
2.2.8.4.11.14 Extended rtPS BR....58
2.2.8.4.11.15 MIMO feedback for Tx beamforming....58
2.2.8.4.11.16 MAP ACK Channel....58
2.2.8.4.11.17 MAP NACK Channel....58
2.2.8.4.12 Channel quality measurements....58
2.2.8.4.12.1 Introduction....58
2.2.8.4.12.2 RSSI mean and standard deviation....58
2.2.8.4.12.3 CINR mean and standard deviation....58
2.2.8.4.12.4 Optional frequency selectivity characterization....58
2.2.8.4.13 Transmitter requirements....58
2.2.8.4.13.1 Tx power level control....58
2.2.8.4.13.2 Transmitter spectral flatness....59
2.2.8.4.13.3 Transmitter constellation error and test method....59
2.2.8.4.13.3.1 RMS constellation error measurement for BS (DL)....59
2.2.8.4.13.3.2 RMS constellation error measurement for SS....59
2.2.8.4.13.3.3 Calculation of RMS constellation error....59
2.2.8.4.13.3.4 Unmodulated subcarrier errors for SS....59
2.2.8.4.13.4 Transmitter reference timing accuracy....59
2.2.8.4.14 Receiver requirements....59
2.2.8.4.14.1 OFDMA PHY requirements for enhanced HO performance....59
2.2.8.4.14.1.1 Receiver sensitivity....59
2.2.8.4.14.1.2 MS UL Tx time tracking accuracy....59
2.2.8.4.14.1.3 MS autonomous neighbor cell scanning....59
2.2.8.4.14.2 Receiver adjacent and nonadjacent channel rejection....59
2.2.8.4.14.3 Receiver maximum input signal....60
2.2.8.4.14.3.1 SS receiver maximum input signal....60
2.2.8.4.14.3.2 BS receiver maximum input signal....60
2.2.8.4.14.4 Receiver maximum tolerable signal....60
2.2.8.4.14.4.1 SS receiver maximum tolerable signal....60
2.2.8.4.14.4.2 BS receiver maximum tolerable signal....60
2.2.8.4.15 Frequency control requirements....60
2.2.8.4.15.1 Center frequency and symbol clock frequency tolerance....60
2.2.8.4.16 Optional HARQ support....60
2.2.8.4.16.1 Optional Chase HARQ support....60
2.2.8.4.16.1.1 HARQ retransmission process....60
2.2.8.4.16.1.2 CRC....60
2.2.8.4.16.1.3 Concurrent transmission of UL HARQ bursts....60

2.2.8.4.16.1.4 Encoding....61
2.2.8.4.16.2 Optional IR HARQ for convolutional code....61
2.2.8.4.16.3 UL ACK channel....61
2.2.9 AeroMACS Transmitter Output power....61
2.2.9.1 Downlink Output Power....61
2.2.9.2 Uplink Output Power....61
2.2.10 AeroMACS Transmitter characteristics....62
2.2.10.1 Transmitter Spurious Emissions....62
2.2.10.2 AeroMACS Transmitted Spectral Mask....62
2.2.11 Receiver Spurious Emissions....63
2.2.12 Transceiver Requirements....63
2.2.12.1 Doppler Velocity....63
2.2.12.2 Time Standard....63
2.3 Equipment Performance – Environmental Conditions....63
2.3.1 Airborne (MS) Environmental Conditions....63
2.3.2 Ground Base Station Environmental Conditions....66
2.3.2.1 Test conditions, power sources and ambient temperatures....66
2.3.2.1.1 Test power source....66
2.3.2.1.2 Test channels....67
2.3.2.1.3 General conditions of measurement....67
2.3.2.1.3.1 Receiver test signal arrangement....67
2.3.2.1.3.2 Performance check....67
2.3.2.1.4 Normal and extreme test conditions....67
2.3.2.1.4.1 Normal test conditions....67
2.3.2.1.4.1.1 Normal temperature and humidity....67
2.3.2.1.4.1.2 Normal power sources....67
2.3.2.1.4.1.2.1 Mains voltage and frequency....67
2.3.2.1.4.1.2.2 Other power sources....67
2.3.2.1.4.2 Extreme test conditions....68
2.3.2.1.4.2.1 Extreme temperatures....68
2.3.2.1.4.2.2 Procedure for tests at extreme temperatures....68
2.3.2.1.4.2.2.1 General....68
2.3.2.1.4.2.2.2 High temperature....68
2.3.2.1.4.2.2.3 Low temperature....68
2.3.2.1.4.2.3 Extreme values of test power sources....68
2.3.2.1.4.2.4 Other power sources....69
2.3.2.1.4.2.5 Performance check....69
2.4 Equipment Test Procedures....69
2.4.1 Definition of Terms and Conditions of Test....69
2.4.2 Test Procedures....70

3 Installed Equipment Performance....71
3.1 Equipment Installation....71
3.1.1 Dynamic Range....71
3.1.2 Interference Effects....71
3.1.3 Aircraft Power Source....71
3.1.4 Frame Duration and Uplink/Downlink Ratio Configuration....71

3.2 Installed Equipment Performance Requirements (MS) 71
3.2.1 Antenna Cables (MS) 71
3.2.1.1 Antenna Cable VSWR (MS) 71
3.2.2 Antenna Characteristics (MS) 72
3.2.3 Mobile Station Equivalent Isotropic Radiated Power (EIRP) 72
3.3 Conditions of Test 73
3.3.1 Ground Test Procedures 73
3.3.2 Verification of Dynamic Range 73
3.3.3 Interference Effects 73
3.3.4 Verification of Power Fluctuation 73
3.3.5 Antenna Cables 73
3.3.5.1 Verification of Antenna Cable VSWR 73
3.3.6 Antenna Characteristics 73

4 Equipment Operational Performance Characteristics 75
4.1 Required Operational Performance Requirements 75
4.1.1 Power Inputs 75
4.1.2 Displays 75
4.1.3 Communication Controls 75
4.1.4 Equipment Operating Functions 75
4.1.5 System Operational Indication 75
4.1.6 Equipment Operating Limitations 75
4.2 Test Procedures for Operational Performance Requirements 75
4.2.1 Power Input 75
4.2.2 Communication Displays 75
4.2.3 Communication Controls 76
4.2.4 Functional Operating Tests 76
4.2.5 System Operational Indication 76
4.2.6 Equipment Operating Limitations 76

5 Membership 77

Appendix A List of Abbreviations and Acronyms 1

Appendix B Requirement Applicability 1

Appendix C Example Receiver Sensitivity Calculation 1

TABLE OF TABLES

Table 1-1: Features of IEEE 802.16 Desirable for Implementation of AeroMACS Networks 2
Table 2-1: ARQ Ack Definitions 21
Table 2-2: Transmitter Spurious Emissions 62
Table 2-3: General Receiver Spurious Emission Requirements 63
Table 2-4: Airborne MS Environmental Conditions 64

Table 3-1: Transmitter Spurious EIRP Emissions.....72
Table B-1: Requirements Applicability.....B-1
Table C-1: Receiver Sensitivity.....C-1
Table C-2: Receiver SNR Assumptions.....C-2

This Page Intentionally Left Blank

1 PURPOSE AND SCOPE

1.1 Introduction

This document contains Minimum Operational Performance Standards for both the Airborne Component and Ground Based base station of the Aeronautical Mobile Airport Communication System (AeroMACS).

Compliance with these standards is recommended as one means of assuring that the equipment will perform its intended function(s) satisfactorily under all conditions normally encountered in routine aeronautical operation. Any regulatory application of this document is the sole responsibility of appropriate governmental agencies. These standards specify system characteristics that should be useful to designers, manufacturers, installers and users of the equipment.

Section 1 of this document provides information needed to understand the rationale for equipment characteristics and requirements stated in the remaining sections. It describes typical equipment operations and operational goals, as envisioned by the members of Special Committee 223 and Working Group 82, and establishes the basis for the standards stated in Sections 2 through 3. Definitions and assumptions essential to proper understanding of this document are also provided in this section.

Section 2 contains the Minimum Performance Standards for the equipment. These standards specify the required performance under standard environmental conditions. Also included are recommended bench test procedures necessary to demonstrate equipment compliance with the stated minimum requirements.

Section 3 describes the performance required for installed equipment. Tests for the installed equipment are included when performance cannot be adequately determined through bench testing.

Section 4 describes the operational performance characteristics for equipment installations and defines conditions that will assure the equipment user that operations can be conducted safely and reliably in the expected operational environment.

Appendix A - List of abbreviations and acronyms

Appendix B – Requirement Applicability

Appendix C – Example receiver sensitivity calculation

This document considers an equipment configuration consisting of AeroMACS radio and modem from antenna interface to the network interface. This MOPS addresses both Airborne Mobile Station and Ground Base Station components of the AeroMACS system.

PROPRIETARY DISCLAMER

This publication makes references to written material or systems that are protected by copyrights and/or patents. RTCA offers no opinion on the validity of the proprietary claims of the specified holder(s) of copyrights and/or patents. Neither does RTCA endorse or warrant the product of specific manufacturers or holders of copyrights and/or patents. RTCA has no economic stake in the use of any proprietary product.

 © 2022, RTCA, Inc.