UL 60947-7-2:2026

(IEC 60947-7-2:2002, MOD)

STANDARD FOR SAFETY

Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER
REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

UL Standard for Safety for Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors, UL 60947-7-2

Fourth Edition, Dated January 27, 2017

Summary of Topics

This revision of UL 60947-7-2 dated April 17, 2026 is issued to remove the ANSI logo and approval from the title page, and includes an update to remove the ANCE logo from the title page and ANCE references from the Preface. No technical changes have been made.

UL 60947-7-2 is an adoption of IEC 60947-7-2, Second Edition, issued by the IEC (2002). Please note that the National Difference document incorporates all of the U.S. national differences for UL 60947-7-2.

As noted in the Commitment for Amendments statement located on the back side of the title page, ULSE and CSA are committed to updating this harmonized standard jointly. However, the revisions dated April 17, 2026 will not be jointly issued by ULSE and CSA as these revision pages address removal of ANSI logo and approval, and also includes removing the ANCE logo from the title page and Preface. While ANCE continues to participate in the technical development of this trinational standard, the ANCE logo has been removed from the title page and Preface as standards cannot be formally published in Mexico at this time.

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

CSA Group
CAN/CSA-C22.2 No. 60947-7-2:17
First Edition
(IEC 60947-7-2:2002, MOD)

ULSE Inc.
UL 60947-7-2
Fourth Edition
(IEC 60947-7-2:2002, MOD)

Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors

January 27, 2017

(Title Page Reprinted: April 17, 2026)

This national standard is based on publication IEC 60947-7-2, second edition (2002).

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

Commitment for Amendments

This standard is issued jointly by the Canadian Standards Association (operating as "CSA Group"), and ULSE Inc. (ULSE). Comments or proposals for revisions on any part of the standard may be submitted to CSA Group or ULSE at anytime. Revisions to this standard will be made only after processing according to the standards development procedures of CSA Group and ULSE. CSA Group and ULSE will issue revisions to this standard by means of a new edition or revised or additional pages bearing their date of issue.

ISBN 978-1-4883-0020-2 © 2017 Canadian Standards Association

All rights reserved. No part of this publication may be reproduced in any form whatsoever without the prior permission of the publisher.

This Standard is subject to review within five years from the date of publication, and suggestions for its improvement will be referred to the appropriate committee. The technical content of the IEC and ISO publications is kept under constant review by IEC and ISO. To submit a proposal for change, please send the following information to inquiries@csagroup.org and include "Proposal for change" in the subject line: Standard designation (number); relevant clause, table, and/or figure number; wording of the proposed change; and rationale for the change.

To purchase CSA Group Standards and related publications, visit CSA Group's Online Store at www.csagroup.org/store/ or call toll-free 1-800-463-6727 or 416-747-4044.

© 2026 ULSE Inc. All rights reserved.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

This UL Standard for Safety consists of the Fourth Edition including revisions through April 17, 2026.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in the Collaborative Standards Development System (CSDS) at https://csds.ul.com.

For information on ULSE Standards, visit https://www.shopulstandards.com, call toll free 1-888-853-3503 or email us at ClientService@shopULStandards.com.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

CONTENTS

Preface **5**

NATIONAL DIFFERENCES **7**

FOREWORD **9**

1 General 11
1.1 Scope 11
1.1DV.1 Modification of Clause 1.1: 11
1.1DV.2 Modification by adding the following: 11
1.1DV.3 Modification by adding the following: 11
1.1DV.4 Modification by adding the following: 12
1.1DV.5 Modification by adding the following: 12
1.2 Normative references 12
1.2DV Modification by adding the following 12
2 Definitions 13
2.2DV Modification by adding the following: 13
2.3DV Delete Clause 2.3: 13
3 Classification 13
3DV.1 Modification by adding the following dashed item to the list: 13
3DV.2 Modification by replacing the seventh dashed item in the list with the following: 14
3DV.3 Modification by adding the following: 14
4 Characteristics 14
4.1 Summary of characteristics 14
4.2 Type of protective conductor terminal block 14
4.3 Rated and limiting values 14
5 Product information 15
5.1 Marking 15
5.1DV Add the following to Clause 5.1: 16
Figure 6DV Addition of the following figure: 16
5.2 Additional information 16
5.2DV.1 Deletion of item a). 16
5.2DV.2 Modification by replacing item c) with the following: 16
5.2DV.3 Modification by replacing the Note with the following: 17
5.2DV.4 Modification by adding the following: 17
6 Normal service, mounting and transport conditions 17
7 Constructional and performance requirements 17
7.1 Constructional and performance requirements 17
7.2 Performance requirements 19
7.3 Electromagnetic compatibility (EMC) 20
8 Tests 20
8.1 Kinds of test 20
8.2 General 20
Table 8.2DV Addition of the following table: 20
8.3 Verification of mechanical characteristics 21
8.4 Verification of electrical characteristics 22
8.5 Verification of thermal characteristics 29
8.6 Verification of EMC characteristics 29
8.7DV Addition of the following subclause: 29

Annex A (normative) Maximum short-time withstand currents allocated to the rail profile and thermal rated current of a PEN busbar

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

Annex B (normative) Tightening torques for the verification of the mechanical strength of screw-type clamping units

Annex DVA (normative) Standards references

DVA Addition: Add Annex DVA to the Part 2: 32

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

Preface

This is the harmonized CSA Group and ULSE standard for Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors. It is the first edition of CAN/CSA No. 60947-7-2, and the fourth edition of UL 60947-7-2. This edition of UL 60947-7-2 supersedes the previous edition(s) published on May 6, 2011.

This harmonized standard is based on IEC Publication 60947-7-2: Edition 2 (2002), Low-voltage switchgear and controlgear – Part 7-2: Ancillary equipment – Protective conductor terminal blocks for copper conductors. IEC 60947-7-2 is copyrighted by the IEC.

This harmonized standard was prepared by CSA Group and ULSE. The efforts and support of the Technical Harmonization Committee for Industrial Control Equipment, of the Council on the Harmonization of Electrotechnical Standards of the Nations of the Americas (CANENA), are gratefully acknowledged.

This Standard is considered suitable for use for conformity assessment within the stated scope of the Standard.

While ANCE continues to participate in the technical development of this trinational standard, the ANCE logo has been removed from the title page as standards cannot be formally published in Mexico at this time.

This standard was reviewed by the CSA Subcommittee on Terminal Assemblies, under the jurisdiction of the CSA Technical Committee on Industrial Products and the CSA Strategic Steering Committee on Requirements for Electrical Safety, and has been formally approved by the CSA Technical Committee. This standard has been developed in compliance with Standards Council of Canada requirements for National Standards of Canada. It has been published as a National Standard of Canada by CSA Group.

Application of Standard

Where reference is made to a specific number of samples to be tested, the specified number is to be considered a minimum quantity.

Note: Although the intended primary application of this standard is stated in its scope, it is important to note that it remains the responsibility of the users of the standard to judge its suitability for their particular purpose.

This CAN/CSA-C22.2 No. 60947-7-2, Standard for Safety for Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors, is to be used in conjunction with the first edition of CAN/CSA-C22.2 No. 60947-7-1. The requirements for Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors are contained in this Part 2 Standard and CAN/CSA-C22.2 No. 60947-7-1. Requirements of this Part 2 Standard, where stated, amend the requirements of CAN/CSA C22.2 No. 60947-7-1. Where a particular subclause of CAN/CSA-C22.2 No. 60947-7-1 is not mentioned in CAN/CSA-C22.2 No. 60947-7-2, the CAN/CSA-C22.2 No. 60947-7-1 subclause applies.

This UL 60947-7-2, Standard for Safety for Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductor, is to be used in conjunction with the fourth edition of UL 60947-7-1. The requirements for Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductor are contained in this Part 2 Standard and UL 60947-7-1. Requirements of this Part 2 Standard, where stated, amend the requirements of UL 60947-7-1. Where a particular subclause of UL 60947-7-1 is not mentioned in UL 60947-7-2, the UL 60947-7-1 subclause applies.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

Level of harmonization

This standard adopts the IEC text with national differences.

This standard is published as an equivalent standard for CSA Group and ULSE.

An equivalent standard is a standard that is substantially the same in technical content, except as follows: Technical national differences are allowed for codes and governmental regulations as well as those recognized as being in accordance with NAFTA Article 905, for example, because of fundamental climatic, geographical, technological, or infrastructural factors, scientific justification, or the level of protection that the country considers appropriate. Presentation is word for word except for editorial changes.

All national differences from the IEC text are included in the CSA Group and ULSE versions of the standard. While the technical content is the same in each organization's version, the format and presentation may differ.

Reasons for differences from IEC

National differences from the IEC are being added in order to address safety and regulatory situations present in the US, Canada and Mexico.

Interpretations

The interpretation by the standards development organization of an identical or equivalent standard is based on the literal text to determine compliance with the standard in accordance with the procedural rules of the standards development organization. If more than one interpretation of the literal text has been identified, a revision is to be proposed as soon as possible to each of the standards development organizations to more accurately reflect the intent.

IEC Copyright

For CSA Group, the text, figures, and tables of International Electrotechnical Commission Publication 60947-7-2, Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductor, copyright 2002, are used in this standard with the consent of the International Electrotechnical Commission. The IEC Foreword is not a part of the requirements of this standard but is included for information purposes only.

These materials are subject to copyright claims of IEC and ULSE. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ULSE. All requests pertaining to the Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors UL 60947-7-2 Standard should be submitted to ULSE.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

NATIONAL DIFFERENCES

National Differences from the text of International Electrotechnical Commission (IEC) Publication 60947-7-2, Low-Voltage Switchgear and Controlgear – Part 7-2: Ancillary Equipment – Protective Conductor Terminal Blocks for Copper Conductors, second edition (2002), are indicated by notations (differences) and are presented in bold text. The national difference type is included in the body.

There are five types of National Differences as noted below. The difference type is noted on the first line of the National Difference in the standard. The standard may not include all types of these National Differences.

DR – These are National Differences based on the **national regulatory requirements**.

D1 – These are National Differences which are based on **basic safety principles and requirements**, elimination of which would compromise safety for consumers and users of products.

D2 – These are National Differences from IEC requirements based on existing **safety practices**. These requirements reflect national safety practices, where empirical substantiation (for the IEC or national requirement) is not available or the text has not been included in the IEC standard.

DC – These are National Differences based on the **component standards** and will not be deleted until a particular component standard is harmonized with the IEC component standard.

DE – These are National Differences based on **editorial comments or corrections**.

Each national difference contains a description of what the national difference entails. Typically one of the following words is used to explain how the text of the national difference is to be applied to the base IEC text:

Addition / Add - An addition entails adding a complete new numbered clause, subclause, table, figure, or annex. Addition is not meant to include adding select words to the base IEC text.

Modification / Modify - A modification is an altering of the existing base IEC text such as the addition, replacement or deletion of certain words or the replacement of an entire clause, subclause, table, figure, or annex of the base IEC text.

Deletion / Delete - A deletion entails complete deletion of an entire numbered clause, subclause, table, figure, or annex without any replacement text.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.