UL 991

STANDARD FOR SAFETY

Tests for Safety-Related Controls
Employing Solid-State Devices

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER
REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

UL Standard for Safety for Tests for Safety-Related Controls Employing Solid-State Devices, UL 991

Third Edition, Dated October 22, 2004

Summary of Topics

This revision of UL 991 dated December 27, 2024 includes the following changes in requirements:

– Clarification of requirements if no critical components are found in a failure mode and effects analysis: Figure 6.1, 6.3, and 23.4.

– Alternate test methods for the environmental stress tests: 11.1.1, 12.1, 13.1, 14.1.1, 15.1.1 – 15.1.4, 15.1.1A, 15.2.1A, 15.2.2A, 15.2.3A, 15.2.4A.

Text that has been changed in any manner or impacted by ULSE's electronic publishing system is marked with a vertical line in the margin.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated February 16, 2024

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

OCTOBER 22, 2004
(Title Page Reprinted: December 27, 2024)

UL 991

Standard for Tests for Safety-Related Controls Employing Solid-State Devices

First Edition – January, 1989
Second Edition – June, 1995

Third Edition

October 22, 2004

This UL Standard for Safety consists of the Third Edition including revisions through December 27, 2024.

Comments or proposals for revisions on any part of the Standard may be submitted to ULSE at any time. Proposals should be submitted via a Proposal Request in the Collaborative Standards Development System (CSDS) at https://csds.ul.com.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

The text included in paragraphs 11.2.1, 11.3.1, 11.4.1, 11.4.2, and 11.4.3 is based on material in Electromagnetic compatibility (EMC) – Part 4: Testing and measuring techniques – Section 11: Voltage dips, short interruptions and voltage variations immunity tests, IEC 61000-4-11, First edition copyright 1994-06. This material is used in this Standard with the consent of the IEC and the American National Standards Institute (ANSI). The IEC copyrighted material has been reproduced with permission from ANSI. ANSI should be contacted regarding the reproduction of any portion of the IEC material. Copies of the IEC Publication 61000-4-11 may be purchased from ANSI, 11 West 42nd Street, New York, New York, 10036, (212)642-4900.

© 2024 ULSE Inc. All rights reserved.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

CONTENTS

INTRODUCTION

1 Scope 5
2 Components 5
3 Units of Measurement 5
4 Undated References 6
5 Glossary 6

INVESTIGATION

6 General 7
7 Failure-Mode and Effect Analysis (FMEA) 9
8 Electrical Supervision 10

ENVIRONMENTAL STRESS TESTS

9 General 11
10 Overvoltage and Undervoltage Tests 12
11 Power Supply Voltage Dips and Short Interruption Test 12
11.1 General 12
11.2 Test voltage levels 13
11.3 Test Conditions 13
11.4 Test procedure 13
12 Transient Overvoltage Test 13
13 Voltage Variation Test 20
13.1 General 20
13.2 Test duration and procedure 20
14 Electromagnetic Susceptibility Tests 21
14.1 General 21
14.2 Electrical fast transient/burst test 21
14.3 Electrical fast transient/burst generator 23
14.4 Test levels 27
14.5 Test procedure 28
14.6 Test conditions 28
14.7 Signal circuit fast transient test 29
14.8 Radiated EMI test 29
14.9 Digital equipment modulation interference test 31
14.10 Keying interference test 31
15 Electrostatic Discharge Test 31
15.1 General 31
15.2 Test methods 31
15.3 Electrostatic discharge probe 32
15.4 Discharge test 33
15.5 Electric field test 33
15.6 Magnetic field test 34
16 Composite Operational and Thermal Cycling Test 35
17 Test for Effects of Shipping and Storage 36
18 Thermal Cycling Test 36
19 Humidity Test 36
20 Dust Test 37
21 Vibration Test 38
21.1 General 38
21.2 Mounting 39

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

21.3 Vibration characteristics 39
22 Jarring Test 41

COMPUTATIONAL INVESTIGATION AND DEMONSTRATED METHOD

23 General 41
24 Computational Investigation 42
24.1 General 42
24.2 Preliminary procedure 42
24.3 Parts stress method 42
24.4 Operational test 44
25 Demonstrated Method 44
25.1 General 44
25.2 Test method 46

POWER CYCLING TESTS

26 General 47
27 Overload Test 47
28 Endurance Test 47

FOLLOW-UP PROGRAM

29 General 47

RATING

30 General 47

MARKING

31 General 48

SUPPLEMENT SA – FOLLOW-UP PROGRAM

INTRODUCTION

SA1 Scope 49
SA2 Glossary 49
SA3 Responsibilities of the Manufacturer 50
SA3.1 General 50
SA3.2 Records 51
SA3.3 Equipment 51
SA3.4 Follow-up program 52
SA4 Responsibilities of the Field Representative 60

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

INTRODUCTION

1 Scope

1.1 These requirements apply to controls that employ solid-state devices and are intended for specified safety-related protective functions.

1.2 These requirements address the potential risks unique to the electronic nature of a control. Equipment or components employing an electronic feature shall also comply with the basic construction and performance requirements contained in the applicable end-product or component standard. These requirements are intended to supplement applicable end-product or component standards and are not intended to serve as the sole basis for investigating the risks of fire, electric shock, or injury to persons associated with a control.

1.3 These requirements do not cover controls covered by end-product standards in which an electronic control investigation is specified.

1.4 Sections 9 – 22 contain standardized test methods for investigating the performance of an electronic control when subjected to particular environmental stresses. The suitability of each test to a given control shall be determined by the end-product standard(s). Determination shall include an assessment of:

a) Whether the control will be exposed to a particular environmental stress in its application, and

b) Whether the response of the control to a particular environmental stress is relevant to its intended safety-related protective function in its application.

2 Components

2.1 Except as noted in 2.2, a component of a product covered by this standard shall comply with the requirements for that component.

2.2 A component is not required to comply with a specific requirement that:

a) Involves a feature or characteristic not required in the application of the component in the product covered by this standard, or

b) Is superseded by a requirement in this standard.

2.3 A component shall be used in accordance with its rating established for the intended conditions of use.

2.4 Specific components are incomplete in construction features or restricted in performance capabilities. Such components are intended for use only under limited conditions, such as certain temperatures not exceeding specified limits, and shall be used only under those specific conditions.

3 Units of Measurement

3.1 Values stated without parentheses are the requirement. Values in parentheses are explanatory or approximate information.

3.2 In addition to being stated in the inch/pound units that are customary in the USA, each of the requirements in this standard is also stated in units that make the requirement conveniently usable in countries employing the various metric systems (practical SI and customary).

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

4 Undated References

4.1 Any undated reference to a code or standard appearing in the requirements of this standard shall be interpreted as referring to the latest edition of that code or standard.

5 Glossary

5.1 For the purpose of this standard, the following definitions apply.

5.2 CONTROL – For the purpose of this standard, a control shall be considered a complete control, a subassembly, a circuit, or an individual component.

5.3 CRITICAL CIRCUIT – A circuit that performs one or more safety related functions and has been identified as critical in accordance with General, Section 6, and Failure Mode and Effect Analysis, Section 7.

5.4 CRITICAL COMPONENT – A component that performs one or more safety-related functions and that has been identified as critical in accordance with General, Section 6, and Failure Mode and Effect Analysis, Section 7.

5.5 CRITICAL FAILURE – A failure of a component or circuit that results in a condition, such as the risk of fire, electric shock, or injury to persons, in the end product application.

5.6 CRITICAL FUNCTION – The failure of a specific action of a control that results in a condition, such as the risk of fire, electric shock, or injury to persons in the end product application.

5.7 DECADE – 3.32 octaves.

5.8 DISTINCTIVE AUDIBLE SIGNAL – A signal obtained from various devices such as bells, horns, sirens, and buzzers, or a variance in the nature of the signal such as a continuous signal obtained under one condition and a pulsing signal under another.

5.9 ELECTROMAGNETIC INTERFERENCE (EMI) – The impairment of a desired electromagnetic signal by an electromagnetic disturbance.

5.10 ELECTROMAGNETIC SUSCEPTIBILITY – The characteristic of electronic equipment that results in undesirable responses when subjected to an electromagnetic disturbance.

5.11 OCTAVE – A range of signals having a frequency ratio of 2:1.

5.12 SUPERVISION – The monitoring of a circuit so that a fault condition will result in a trouble indication or other acceptable action.

5.13 TEST ACCELERATION FACTOR – A number, that varies with the test temperature, chosen to conduct the Demonstrated Method, Section 25. It is used to calculate the required test unit-hours.

5.14 TEST UNIT-HOURS – The mathematical product of the number of samples under test and the time of the test.

5.15 TROUBLE INDICATION – A visible or audible signal intended to indicate a fault or trouble condition, such as an open or shorted condition of a component in the device or an open or ground in the connected wiring.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.