ULC Standards
Normes ULC

JOINT CANADA – UNITED STATES NATIONAL STANDARD

ANSI/CAN/UL/ULC 842A:2026

STANDARD FOR SAFETY

Valves for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 98 Percent (E0 – E98)

Approved American National Standard
ANSI

ANSI/UL 842A-2026

scc ccn

SCC FOREWORD

National Standard of Canada

A National Standard of Canada is a standard developed by a Standards Council of Canada (SCC) accredited Standards Development Organization, in compliance with requirements and guidance set out by SCC. More information on National Standards of Canada can be found at www.scc.ca.

SCC is a Crown corporation within the portfolio of Innovation, Science and Economic Development (ISED) Canada. With the goal of enhancing Canada's economic competitiveness and social well-being, SCC leads and facilitates the development and use of national and international standards. SCC also coordinates Canadian participation in standards development, and identifies strategies to advance Canadian standardization efforts.

Accreditation services are provided by SCC to various customers, including product certifiers, testing laboratories, and standards development organizations. A list of SCC programs and accredited bodies is publicly available at www.scc.ca.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

UL Standard for Safety for Valves for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 98 Percent (E0 – E98), ANSI/CAN/UL/ULC 842A

Third Edition, Dated July 29, 2026

Summary of Topics

This new Third Edition of ANSI/CAN/UL/ULC 842A dated July 29, 2026 includes changes to revise the title and scope of UL/ULC 842A to increase ethanol concentration from 85 % to 98 % for fuel handling equipment and a correction/clarification of weak section strength test and external leakage test limits.

The new and revised requirements are substantially in accordance with Proposal(s) on this subject dated December 5, 2025 and May 8, 2026.

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form by any means, electronic, mechanical photocopying, recording, or otherwise without prior permission of ULSE Inc. (ULSE).

ULSE provides this Standard "as is" without warranty of any kind, either expressed or implied, including but not limited to, the implied warranties of merchantability or fitness for any purpose.

In no event will ULSE be liable for any special, incidental, consequential, indirect or similar damages, including loss of profits, lost savings, loss of data, or any other damages arising out of the use of or the inability to use this Standard, even if ULSE or an authorized ULSE representative has been advised of the possibility of such damage. In no event shall ULSE's liability for any damage ever exceed the price paid for this Standard, regardless of the form of the claim.

Users of the electronic versions of UL's Standards for Safety agree to defend, indemnify, and hold ULSE harmless from and against any loss, expense, liability, damage, claim, or judgment (including reasonable attorney's fees) resulting from any error or deviation introduced while purchaser is storing an electronic Standard on the purchaser's computer system.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

ANSI/UL 842A-2026

JULY 29, 2026

ANSI/CAN/UL/ULC 842A:2026

Standard for Valves for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 98 Percent (E0 – E98)

First Edition – February, 2015
Second Edition – May, 2024

Third Edition

July 29, 2026

This ANSI/CAN/UL/ULC Safety Standard consists of the Third Edition.

The most recent designation of ANSI/UL 842A as an American National Standard (ANSI) occurred on July 29, 2026. ANSI approval for a standard does not include the Cover Page, Transmittal Pages, Title Page, Preface or SCC Foreword.

This Standard has been designated as a National Standard of Canada (NSC) on July 29, 2026.

© 2026 ULSE Inc. All rights reserved.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

No Text on This Page

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

CONTENTS

Preface 5

INTRODUCTION

1 Scope 7
2 Components 8
3 Units of Measurement 9
4 Referenced Publications 9
5 Glossary 10

CONSTRUCTION

6 Assembly 11
6.1 All valves 11
6.2 Shutoff valves 11
7 Materials 12
7.1 Metallic materials 12
7.2 Nonmetallic materials 15
7.3 Casting impregnation materials 17
7.4 Internal parts 17
7.5 Blending options 17
8 Bodies and Covers 17
9 Seals and Stuffing Boxes 18
10 Diaphragms 19
11 Springs 19
12 Operating Mechanisms 19

PERFORMANCE

13 General 19
14 Long Term Exposure Test 20
14.1 General 20
14.2 Samples 20
14.3 Method 21
14.4 Results 21
15 Deformation Test 22
16 External Leakage Test 23
17 Seat Leakage Test 23
18 Fire Test 23
19 Weak Section Strength Test 25
20 Endurance Test 26
21 Endurance Test – Mechanical Line Leak Detectors 26
22 Hydrostatic Strength Test 27
23 Moist Ammonia-Air Stress Cracking Test 27
24 Marking Adhesion Test 27
25 Blending Cycling Test 28

MANUFACTURING AND PRODUCTION

26 General 28

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

INSTALLATION INSTRUCTIONS

27 General 29

MARKING

28 General 29

ANNEX A (Normative) – TEST FLUIDS

A.1 Details 31

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

Preface

This is the Third Edition of ANSI/CAN/UL/ULC 842A, Standard for Valves for Gasoline and Gasoline/Ethanol Blends with Nominal Ethanol Concentrations up to 98 Percent (E0 – E98).

ULSE is accredited by the American National Standards Institute (ANSI) and the Standards Council of Canada (SCC) as a Standards Development Organization (SDO).

This Standard has been developed in compliance with the requirements of ANSI and SCC for accreditation of a Standards Development Organization.

This ANSI/CAN/UL/ULC 842A Standard is under continuous maintenance, whereby each revision is approved in compliance with the requirements of ANSI and SCC for accreditation of a Standards Development Organization. In the event that no revisions are issued for a period of four years from the date of publication, action to revise, reaffirm, or withdraw the standard shall be initiated.

Annex A is identified as Normative, as such, form mandatory parts of this Standard.

In Canada, there are two official languages, English and French. All safety warnings must be in French and English. Attention is drawn to the possibility that some Canadian authorities may require additional markings and/or installation instructions to be in both official languages.

This Third Edition joint American National Standard and National Standard of Canada is based on, and now supersedes, the Second Edition of UL 842A.

Comments or proposals for revisions on any part of the Standard may be submitted at any time. Proposals should be submitted via a Proposal Request in the Collaborative Standards Development System (CSDS) at https://csds.ul.com.

Our Standards for Safety are copyrighted by ULSE Inc. Neither a printed nor electronic copy of a Standard should be altered in any way. All of our Standards and all copyrights, ownerships, and rights regarding those Standards shall remain the sole and exclusive property of ULSE Inc.

This Edition of the Standard has been formally approved by the Technical Committee (TC) on Valves for Flammable Fluids, TC 842.

This list represents the TC 842 membership when the final text in this Standard was balloted. Since that time, changes in the membership may have occurred.

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

TC 842 Membership

Name	Representing	Interest Category	Region
Paras Bhattal	UL Solutions	Testing & Standards Org.	USA
Mark Bishoff	Lorax Systems Inc.	Producer	Canada
Dennis Boyd	BP America Inc.	Commercial /Industrial User	USA
Claude Deschamps	Regie du Batiment du Quebec	Authorities Having Jurisdiction	Quebec
John Dutton	J Dutton	General Interest	Canada
Tom Henderson	State Water Resources Control Board	Authorities Having Jurisdiction	USA
Michelle Hilger	Mongoose Power Solutions	General Interest	USA
Wolf Koch	Technology Resources International	General Interest	USA
Matt Lauber	OPW Fueling Components Inc.	Producer	USA
Pierre Legault	Integrated Review Services – Consulting	General Interest	Canada
Jeanne Murphy Meyer	Core Engineered Solutions Inc.	Commercial / Industrial User	USA
Lokeswar Panchala	NCI Canada Inc.	Producer	Canada
James Petersen	Petersen Engineering	General Interest	USA
Jeffrey Prusko	UL Standards & Engagement	TC Project Manager – Non-voting	USA
Adam Stowers	Hercules OEM	Supply Chain	USA
Vivek Vijay	Emirates Safety Laboratory	Testing & Standards Org.	United Arab Emirates
Laura Werner	UL Standards & Engagement	TC Chair – Non-voting	Canada
Brian Wiegert	PMMIC	Commercial / Industrial User	USA
Jeremy Yager	Morrison Bros. Co.	Producer	USA

International Classification for Standards (ICS): 23.060.01; 75.180.99; 75.160.20

For information on ULSE Standards, visit https://www.shopulstandards.com, call toll free 1-888-853-3503 or email us at ClientService@shopULStandards.com.

This Standard is intended to be used for conformity assessment.

The intended primary application of this Standard is stated in its scope. It is important to note that it remains the responsibility of the user of the standard to judge its suitability for this particular application.

CETTE NORME NATIONALE DU CANADA EST DISPONIBLE EN VERSIONS FRANÇAISE ET ANGLAISE

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.

INTRODUCTION

1 Scope

1.1 These requirements cover valves that are intended to be used for the control of fluids and their vapors for the fluids indicated in 1.3. They are of the type commonly used in piping systems and in the assembly of motor fuel dispensing equipment. Valves covered by this Standard are for use with flammable fluids which are handled at temperatures normally within the range of minus 20 °F (minus 29 °C) – 125 °F (52 °C).

1.2 Valves for gasoline/ethanol blends with nominal ethanol concentrations up to 98 % (E0 – E98) shall be constructed to comply with the following:

a) The requirements defined in the Standard for Valves for Flammable and Combustible Liquids, UL/ULC 842; and

b) The requirements in this Standard.

1.3 Valves covered by these requirements are intended for use with one or more of the following, as applicable:

a) Gasoline formulated in accordance with the Standard Specification for Automotive Spark-Ignition Fuel, ASTM D4814;

b) Gasoline/ethanol blends with nominal ethanol concentrations up to 25 % ethanol (E25), consisting of gasoline formulated in accordance with the Standard Specification for Automotive Spark-Ignition Fuel, ASTM D4814, when blended with denatured fuel ethanol formulated to be consistent with the Standard Specification for Denatured Fuel Ethanol, ASTM D4806; or

c) Gasoline/ethanol blends with nominal ethanol concentrations above 25 % formulated in accordance with the following:

1) Standard Specifications in (b);

2) Standard Specification for Ethanol Fuel Blends for Flexible-Fuel Automotive Spark-Ignition Engines, ASTM D5798; or

3) Standard Specification for Denatured Fuel Ethanol, ASTM D4806.

1.4 These requirements cover valves of the manually operated, pressure operated, or temperature operated types, or combinations of such to the exclusion of types operated wholly or partially by electricity. When they form a part of an assembly which provides for additional functions or service, the requirements are outside the scope of these requirements.

1.5 Products covered by this Standard are intended to be installed and used in accordance with the applicable Codes and Regulations as determined by the Authority Having Jurisdiction (AHJ), such as, but not limited to:

a) In the United States:

1) Flammable and Combustible Liquids Code, NFPA 30;

2) Code for Motor Fuel Dispensing Facilities and Repair Garages, NFPA 30A.

b) In Canada:

1) The National Fire Code of Canada; or

ULSE INC. COPYRIGHTED MATERIAL – NOT AUTHORIZED FOR FURTHER REPRODUCTION OR DISTRIBUTION WITHOUT PERMISSION FROM ULSE INC.